



7		8	
REV.	ECN NO.	REVISED	DATE

NOTE:

1.MATERIAL:

- a.HOUSING: LCP UL94V-0
b.CONTACT: PHOSPHOR BRONZE
(SURFACE PLATING: Au1u")

SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
b.INSULATION RESISTANCE: 100 MEGA OHMS MIN
c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
d.OPERATING TEMPERATURE: -25° C ~ +85° C

ORDERING INFORMATION

BS-24-B***016

电池座系列

BS-24系列

SMT 180° TYPE


PLATING:
A-Au1U"
J-Ni100U"~120U"
K-Sn100U"~120U"

MATERIAL:
1A-PBT BLACK
1B-PA66 BLACK
2A-PPA BROWN
2B-PPA BLACK
3A-PPS BROWN
3B-PPS BLACK
4A-LCP WHITE
4B-LCP BLACK

工程部

2018-05-30

LQ. HUANG



PCB Layout Diagram
Top View

3	TERMINAL(-)	1	PHOSPHOR BRONZE, T=0.15mm	Gold Plating and Ni Under-Plating
2	TERMINAL(+)	1	PHOSPHOR BRONZE, T=0.15mm	Gold Plating and Ni Under-Plating
1	HOUSE	1	LCP UL94 V-0	WHITE
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES		MYOUNG 美用 www.meiyangdz.com					
DECIMALS:	ANGLES:	DSND	YangFeng	DATE	2018-05-30	TITLE:	
X : ±0.30	X : ±1°	CHKD	ZhouRuicai	DATE	2018-05-30	BS-2450-2 Au SMT	
X.X : ±0.25	X.X : ±0.5°	APVD	XueShunYong	DATE	2018-05-30	PART NO.:	
X.XX : ±0.20		WEIGHT:	SCALE:	SIZE:	A4	VIEW:	BS-24-B4AA016
X.XXX : ±0.10		SHEET 1 OF 1	UNIT: mm	REV.:	A/0	OBJECT: MY	DRAW NO.:MY-CP-0138