SATATYA RIDR80FL28CWP P2

8MP IR Ruggedized Camera with 2.8mm Lens

MATRIX TELECOM | SECURITY

SATATYA RIDR80FL28CWP P2

8MP IR Ruggedized Camera with 2.8mm Lens

Matrix Ruggedized Series IP Cameras are specifically designed for the demanding Transportation industry i.e. Railways and Roadways. Powered by Low light Sensitivity and High quantum efficiency Sensor it offers superior Video Quality and performance necessary to capture the events happening at a zap speed in/from a moving vehicle.

The Ruggedized IP Cameras are cameras which are best suited for mobile applications. Loaded with versatile functions and a range of features, Matrix Ruggedized IP Cameras are an ideal Solution for Railways and Roadways to monitor the assets and provide superior customer service.

USP

- SONY STARVIS SENSOR
- H.265 COMPRESSION
- IVA
- HIGHER FIELD OF VIEW
- SMART STREAMING
- ADAPTIVE STREAMING
- TRUE WDR
- NAS

CERTIFICATION

STQC Certification | NDAA Compliant | ONVIF | EN 50155 | IP68 | IK10 | CE CERTIFIED | FC

Customer Care: (+91) 265 613 7222

E-mail: Inquiry@MatrixComSec.com

www.MatrixComSec.com

Make in India

SATATYA RIDR80FL28CWP P2

8MP IR Ruggedized Camera with 2.8mm Lens

MATRIX TELECOM | SECURITY

TECHNICAL SPECIFICATIONS	
IMAGE SENSOR	
Resolution	8 MP (3840 × 2160)
Sensor Type and Size	1/2.8" SONY - CMOS 8 MP Active Pixel Progressive Scan, Back Illuminated Image sensor (STARVIS Series)
LENS	
Minimum Illumination	Color - 0.01 Lux @ F1.2 (AGC ON) Monochrome - 0 Lux
Focal Length	2.8mm
Focus Range	0.5m to infinity
Field of View (FOV)	HFOV - 106.9° VFOV - 56.9° DFOV - 127.62°
Focus	Fixed focus
Aperture (F#)	F 1.6
Iris Type	Fixed
IR Range	Up to 30m
IR Led Wavelength	850nm
IR Switching	Auto/ Manual
DORI AS PER IEC 62676 - IV	D: 82 m, O: 32 m, R: 17m, I: 9 m
AUDIO INTERFACE	
Built-in Microphone	Yes
Audio IN	1
Audio OUT	1
Two-way Audio	Supported
Audio Compression	G.726 and G.711µ
Alarm In	1
Alarm Out	1
HARDWARE SPECIFICATIONS	
SD Card	Up to 512GB
Camera Adjustment Angle	Pan: -30° to 30° Tilt: 10° to 90° Rotate: -175° to 175°
IMAGE AND VIDEO	
No of Stream Profiles	4
Stream Profiles	Profile 1: 4k @30 FPS H.264, H.265 Profile 2: D1 @30 FPS H.264, H.265 Profile 3: 3MP @10 FPS H.264, H.265,MJPEG Profile 4: 2MP @15 FPS H.264, H.265, MJPEG

SATATYA RIDR80FL28CWP P2

8MP IR Ruggedized Camera with 2.8mm Lens

MATRIX TELECOM | SECURITY

Available Resolutions	3840 × 2160, 3200 x 1800, 2592 x 1944, 2592 x 1520, 2048 x 1536, 1920 x 1080,720p, D1, 2CIF, VGA, CIF
Max Resolution	3840 × 2160
Bitrate	128kbps-16Mbps
Bitrate Type	CBR, VBR
Video Compression	H.265, H.264, MJPEG
Frame Rate	1-30fps
Shutter Speed	1/15s-1/100000s
Adaptive Streaming	Yes
ONVIF Profiles	Profile S, G & T
Edge Recording	Yes
Alarm Recording	Pre and Post
Motion Recording	Yes
Video Parameters	Snapshot, Region of Interest (ROI), BLC, HLC, Day/Night Settings (Auto/Manual)
Privacy Masks	8
WDR	True WDR (120dB)
SNR	>70dB
Image Enhancement	Rotate mode/Saturation/Brightness/Contrast and Sharpness Adjustable by Client Software or Web Browser
DNR	2D &3D
Digital Zoom	16x
Video Analytics	Motion/No Motion Detection, View Tamper Detection, Trip/No Trip Detection,Object Intrusion/Zone Intrusion, Audio Exception
ALERTS	
IP Conflict	Yes
Network Disconnect	Yes
Storage Full	Yes
Time Triggered	Yes
EVENTS AND ACTIONS	
Upload Image	SD, NAS, SFTP
Upload Clip	SD, NAS, SFTP
Notifications	E-mail, SMS, TCP
PROTOCOLS SUPPORTED	
Supported protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, DNS, DynDNS, DDNS, RTP, RTCP, RTSP, PPPOE, SMTP, NTP, SNMP, FTP, TLS/SSL, SFTP, ICMP, IGMPv2 & v3, ARP, 802.1x, IPv4, IPv6, QoS Layer 3, DSCP, CIFS, SSH, UPnP, Bonjour
Web Viewer	Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0, Safari, Edge
Browser	IE, Chrome, Mozilla, Edge, Safari

SATATYA RIDR80FL28CWP P2

8MP IR Ruggedized Camera with 2.8mm Lens

CYBER SECURITY as per ISO/IEC 27402	
Secure boot	Yes
Signed firmware	Yes
Data Encryption	All data, including sensitive data, is encrypted with AES 256 and RSA 2048
IP Address Filtering	Yes
HTTPS Streaming	Yes, using TLS 1.2
Edge Data Encryption	Yes
Network Authentication	Yes, 802.1x Network authentication
Secure Firmware Upgrade	Yes
Anti-roll back firmware	Yes
Web login Password Protection	Yes
Unused Debug Interface Protection	Yes
OPERATING PARAMETERS	
Power Supply	12V (DC); 802.3af (PoE)
Power Consumption	6.5W
Operating Humidity	≤95% RH (non-condensing)
Operating Temperature	-30°C to 70°C
PHYSICAL PARAMETERS	
Communication Interface	10Base-T/100Base-TX Ethernet (M12, Female, 4-pin D-coded)
Weight	700g
Color	Infinity White
Storage	SD Card, NAS
Dimensions	120.5x118.6x63.3 mm (L*W*H)
Certifications	BIS, CE, FCC Part-15 Subpart – B, IK10, IP68, ONVIF S, G & T, NEMA 4X** EN50155, Essential Requirement (ER) by STQC, Delhi, NDAA Compliant

Specifications are subject to change without prior noticeMTO*

SATATYA RIDR80FL28CWP P2

8MP IR Ruggedized Camera with 2.8mm Lens

ABOUT MATRIX

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 4000 channel partners, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.

MATRIX COMSEC
Head Office
394-GIDC, Makarpura,
Vadodara – 390 010, India.
Ph: +91 265 613 7222
E-mail: Inquiry@MatrixComSec.com

Factory
19 – GIDC, Waghodia,
Dist. Vadodara – 391 760, India.
Ph: +91 265 613 7222

MATRIX COMSEC – North America
2 Wickstead Crt,
Brampton,
Ontario, L6R
1N8.

Ph: (+1) 408-643-0581 (USA)
Ph: (+1) 437-266-1005 (Canada)

www.MatrixComSec.com