

Living Documentation

Version 1.0.0-SNAPSHOT

Table of Contents

1. Introduction	1
2. Summary	2
3. Features	3
3.1. Manage database with DBUnit Rules Core	3
3.1.1. Scenario: Seed database using yml dataset	3
3.2. Manage database with DBUnit Rules CDI	5
3.2.1. Scenario: Seed database using yml dataset	6
3.3. Manage database with DBUnit Rules Cucumber	8
3.3.1. Scenario: Seed database using DBUnit rules in Cucumber tests	11
3.4. Dynamic data using scribable datasets	15
3.4.1. Scenario: Seed database with groovy script in dataset	16
3.4.2. Scenario: Seed database with javascript in dataset	17
3.5. Database assertion using expected datasets	18
3.5.1. Scenario: Database assertion with yml dataset	19
3.5.2. Scenario: Database assertion with regular expression in expected dataset	20
3.5.3. Scenario: Database assertion with seeding before test execution	21
3.5.4. Scenario: Failling database assertion	23
3.5.5. Scenario: Database assertion using automatic transaction	24

Chapter 1. Introduction

DBUnit Rules aims for bringing [DBUnit](#) closer to your JUnit tests. Here are the main features:

- [JUnit rule](#) to integrate with DBUnit via annotations:

```
@Rule
public DBUnitRule dbUnitRule = DBUnitRule.instance(jdbcConnection);①

@Test
@DataSet(value = "datasets/yml/users.yml")
public void shouldSeedDataSet(){
    //database is seed with users.yml dataset
}
```

① The rule depends on a JDBC connection.

- CDI interceptor to seed database without rule instantiation;
- Json, Yaml, xml and flat xml support;
- Cucumber integration;
- JPA integration;
- Multiple database support;
- Date/time support in datasets;

The project is composed by 5 modules:

- [Core](#): Contains the dataset executor and JUnit rule;
- [CDI](#): provides the DBUnit interceptor
- [Cucumber](#): a CDI aware cucumber runner;
- [JPA](#): Comes with a dataset executor based on JPA entity manager
- [Examples module](#).

Chapter 2. Summary

Scenarios			Steps							Features: 5	
Passed	Failed	Total	Passed	Failed	Skipped	Pending	Undefined	Missing	Total	Duration	Status
Manage database with DBUnit Rules Core											
1	0	1	4	0	0	0	0	0	4	002ms	passed
Manage database with DBUnit Rules CDI											
1	0	1	4	0	0	0	0	0	4	04s 310ms	passed
Manage database with DBUnit Rules Cucumber											
1	0	1	5	0	0	0	0	0	5	002ms	passed
Dynamic data using scribable datasets											
2	0	2	7	0	0	0	0	0	7	002ms	passed
Database assertion using expected datasets											
5	0	5	16	0	0	0	0	0	16	009ms	passed
Totals											
10	0	10	36	0	0	0	0	0	36	04s 327ms	

Chapter 3. Features

3.1. Manage database with DBUnit Rules Core

In order to manage database state in JUnit tests
As a developer
I want to use DBUnit in my tests.

DBUnit Rules Core module brings [DBunit](#) to your unit tests via [JUnit rules](#).

3.1.1. Scenario: Seed database using yml dataset

Given

The following junit rules 👍 (002ms)

```
@RunWith(JUnit4.class)
public class DBUnitRulesIt {
    @Rule
    public EntityManagerProvider emProvider =
        EntityManagerProvider.instance("rules-it"); ①

    @Rule
    public DBUnitRule dbUnitRule =
        DBUnitRule.instance(emProvider.connection()); ②
}
```

- ① [EntityManagerProvider](#) is a simple Junit rule that creates a JPA entityManager for each test. DBunit rule don't depend on EntityManagerProvider, it only needs a JDBC connection.
- ② DBUnit rule responsible for reading [@DataSet](#) annotation and prepare the database for each test.

And

The following dataset 🍌 (000ms)

src/test/resources/dataset/yml/users.yml

```
user:
  - id: 1
    name: "@realpestano"
  - id: 2
    name: "@dbunit"
tweet:
  - id: abcdef12345
    content: "dbunit rules!"
    user_id: 1
  - id: abcdef12233
    content: "dbunit rules!"
    user_id: 2
  - id: abcdef1343
    content: "CDI for the win!"
    user_id: 2
follower:
  - id: 1
    user_id: 1
    follower_id: 2
```

When

The following test is executed: 📌 (000ms)

```
@Test
@DataSet(value = "datasets/yml/users.yml", useSequenceFiltering =
true)
public void shouldSeedUserDataSet() {
    User user = (User) em().createQuery("select u from User u join
fetch u.tweets join fetch u.followers where u.id =
1").getSingleResult();
    assertNotNull(user);
    assertEquals(1, user.getId());
    assertNotNull(user.getTweets().hasSize(1));
    Tweet tweet = user.getTweets().get(0);
    assertNotNull(tweet);
    Calendar date = tweet.getDate();
    Calendar now = Calendar.getInstance();

    assertEquals(date.get(Calendar.DAY_OF_MONTH), now.get(Calendar.
DAY_OF_MONTH));
}
```

Then

The database should be seeded with the dataset content before test execution 📌 (000ms)

3.2. Manage database with DBUnit Rules CDI

In order to manage database state in **CDI** based tests
As a developer
I want to use DBUnit in a CDI test environment.

DBUnit CDI integration is done through a [CDI interceptor](#).

CDI must be enabled in your test, see the following example:



```
@RunWith(CdiTestRunner.class) ①  
public class DBUnitCDITest {  
  
}
```

① [CdiTestRunner](#) is provided by [Apache Deltaspike](#) but you should be able to use other CDI test runners.

3.2.1. Scenario: Seed database using yml dataset

Given

DBUnit interceptor is enabled in your test beans.xml: 🍻 (04s 310ms)

src/test/resources/META-INF/beans.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://java.sun.com/xml/ns/javaee"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/beans_1_0.xsd">
  <interceptors>

  <class>com.github.dbunit.rules.cdi.DBUnitInterceptor</class>
  </interceptors>
</beans>
```



Your test itself must be a CDI bean to be intercepted. if you're using [Deltaspike test control](#) just enable the following property in `test/resources/META-INF/apache-deltaspike.properties`:

```
deltaspike.testcontrol.use_test_class_as_cdi_bean=true
```

And

The following dataset 🍌 (000ms)

src/test/resources/dataset/yml/users.yml

```
user:
  - id: 1
    name: "@realpestano"
  - id: 2
    name: "@dbunit"
tweet:
  - id: abcdef12345
    content: "dbunit rules!"
    user_id: 1
  - id: abcdef12233
    content: "dbunit rules!"
    user_id: 2
  - id: abcdef1343
    content: "CDI for the win!"
    user_id: 2
follower:
  - id: 1
    user_id: 1
    follower_id: 2
```

When

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -
include:../../../src/test/java/com/github/dbunit/rules/DBUnitCDITest.java
[tags=seedDatabase]
```

Then

The database should be seeded with the dataset content before test execution 🍌 (000ms)

3.3. Manage database with DBUnit Rules Cucumber

In order to manage database state in **BDD** tests
As a BDD developer
I want to use DBUnit along side my BDD tests.

DBUnit enters the BDD world through a dedicated JUnit runner which is based on [Cucumber](#) and [Apache DeltaSpike](#).

This runner just starts CDI within your BDD tests so you just have to use [DBUnit rules CDI interceptor](#) on Cucumber steps, here is the so called Cucumber CDI runner declaration:

```
package com.github.dbunit.rules.bdd;

import com.github.dbunit.rules.cucumber.CdiCucumberTestRunner;
import cucumber.api.CucumberOptions;
import org.junit.runner.RunWith;

/**
 * Created by rmpestano on 4/17/16.
 */
@RunWith(CdiCucumberTestRunner.class)
@CucumberOptions(features = {
    "src/test/resources/features/core/core-seed-database.feature",
    "src/test/resources/features/cdi/cdi-seed-database.feature",
    "src/test/resources/features/cucumber/cucumber-seed-database.feature",
    "src/test/resources/features/general/dataset-replacements.feature",
    "src/test/resources/features/general/expected-dataset.feature"
},
    plugin = "json:target/dbunit-rules.json")
public class DBUnitRulesBdd {
}
```



As cucumber doesn't work with JUnit Rules, see [this issue](#), you won't be able to use Cucumber runner with *DBUnit Rules Core* because its based on JUnit rules.

Dependencies

Here is a set of maven dependencies needed by DBUnit rules Cucumber:



Most of the dependencies, except CDI container implementation, are bring by DBUnit Rules Cucumber module transitively.

Cucumber dependencies

```
<dependency>
  <groupId>com.github.dbunit-rules</groupId>
  <artifactId>cucumber</artifactId>
  <version>${project.parent.version}</version>
  <scope>test</scope>
</dependency>
<dependency> ❶
  <groupId>info.cukes</groupId>
  <artifactId>cucumber-junit</artifactId>
  <version>1.2.4</version>
  <scope>test</scope>
</dependency>
<dependency> ❶
  <groupId>info.cukes</groupId>
  <artifactId>cucumber-java</artifactId>
  <version>1.2.4</version>
  <scope>test</scope>
</dependency>
```

- ❶ You don't need to declare because it comes with DBUnit Rules Cucumber module dependency.

```
<dependency> ①
  <groupId>org.apache.deltaspike.modules</groupId>
  <artifactId>deltaspike-test-control-module-api</artifactId>
  <version>${ds.version}</version>
  <scope>test</scope>
</dependency>

<dependency> ①
  <groupId>org.apache.deltaspike.core</groupId>
  <artifactId>deltaspike-core-impl</artifactId>
  <version>${ds.version}</version>
  <scope>test</scope>
</dependency>

<dependency> ①
  <groupId>org.apache.deltaspike.modules</groupId>
  <artifactId>deltaspike-test-control-module-impl</artifactId>
  <version>${ds.version}</version>
  <scope>test</scope>
</dependency>

<dependency> ②
  <groupId>org.apache.deltaspike.cdictrl</groupId>
  <artifactId>deltaspike-cdictrl-owb</artifactId>
  <version>${ds.version}</version>
  <scope>test</scope>
</dependency>

<dependency> ②
  <groupId>org.apache.openwebbeans</groupId>
  <artifactId>openwebbeans-impl</artifactId>
  <version>1.6.2</version>
  <scope>test</scope>
</dependency>
```

① Also comes with DBUnit Rules Cucumber.

② You can use CDI implementation of your choice.

3.3.1. Scenario: Seed database using DBUnit rules in Cucumber tests

Given

The following feature 👍 (000ms)

Feature: Contacts test

As a user of contacts repository

I want to crud contacts

So that I can expose contacts service

Scenario Outline: search contacts

Given we have a list of contacts

When we search contacts by name "<name>"

Then we should find <result> contacts

Examples: examples1

name	result
delta	1
sp	2
querydsl	1
abcd	0

Scenario: delete a contact

Given we have a list of contacts

When we delete contact by id 1

Then we should not find contact 1

And

The following dataset 🍌 (001ms)

```
contact:
- id: 1
  name: "deltaspike"
  email: "users@deltaspike.apache.org"
  company_id: 1
- id: 2
  name: "querydsl"
  email: "info@mysema.com"
  company_id: 2
- id: 3
  name: "Spring"
  email: "spring@pivotal.io"
  company_id: 3

company:
- id: 1
  name: "Apache"
- id: 2
  name: "Mysema"
- id: 3
  name: "Pivotal"
- id: 4
  name: "Google"
```

And

The following Cucumber test 🍌 (000ms)

```
package com.github.dbunit.rules.examples.cucumber;

import com.github.dbunit.rules.cucumber.CdiCucumberTestRunner;
import cucumber.api.CucumberOptions;
import org.junit.runner.RunWith;

@RunWith(CdiCucumberTestRunner.class)
@CucumberOptions(
    features = {"src/test/resources/features/contacts.feature"},
    plugin = {"json:target/cucumber.json"}
    //glue = "com.github.dbunit.rules.examples.glues"
)
public class ContactFeature {
}
```

When

The following cucumber steps are executed 🍌 (000ms)

```
package com.github.dbunit.rules.examples.cucumber; ①

import com.github.dbunit.rules.cdi.api.UsingDataSet;
import cucumber.api.java.en.Given;
import cucumber.api.java.en.Then;
import cucumber.api.java.en.When;
import org.example.jpdomain.Contact;
import org.example.jpdomain.Contact_;
import org.example.service.deltaspike.ContactRepository;

import javax.inject.Inject;

import static org.junit.Assert.assertEquals;
import static org.junit.Assert.assertNull;

public class ContactSteps {

    @Inject
    ContactRepository contactRepository; ①

    Long count;

    @When("^we search contacts by name \"([^\"]*)\"$")
```



```

    public void we_search_contacts_by_name_(String name) throws
    Throwable {
        Contact contact = new Contact();
        contact.setName(name);
        count = contactRepository.countLike(contact, Contact_.name);
    }

    @Then("^we should find (\\d+) contacts$")
    public void we_should_find_result_contacts(Long result) throws
    Throwable {
        assertEquals(result, count);
    }

    @Given("^we have a list of contacts$")
    @UsingDataSet("datasets/contacts.yml") ②
    public void given() {
        assertEquals(contactRepository.count(), new Long(3));
    }

    @When("^we delete contact by id (\\d+)$")
    public void we_delete_contact_by_id(long id) throws Throwable {
        contactRepository.remove(contactRepository.findById(id));
    }

    @Then("^we should not find contact (\\d+)$")
    public void we_should_not_find_contacts_in_database(long id) throws
    Throwable {
        assertNull(contactRepository.findById(id));
    }
}

```

- ① As the Cucumber cdi runner enables CDI, you can use injection into your Cucumber steps.
- ② Here we use the DBUnit Rules CDI interceptor to seed the database before step execution.

Then

The database should be seeded with the dataset content before step execution 👍 (000ms)

3.4. Dynamic data using scribable datasets

In order to have dynamic data in datasets
As a developer
I want to use scripts in DBUnit datasets.

Scritable datasets are backed by JSR 223. [2: Scripting for the Java Platform, for more information access the official [docs here](#)].

3.4.1. Scenario: Seed database with groovy script in dataset

Given

Groovy script engine is on test classpath 🍌 (001ms)

```
<dependency>
  <groupId>org.codehaus.groovy</groupId>
  <artifactId>groovy-all</artifactId>
  <version>2.4.6</version>
  <scope>test</scope>
</dependency>
```

And

The following dataset 🍌 (000ms)

```
tweet:
- id: "1"
  content: "dbunit rules!"
  date: "groovy:new Date()" ①
  user_id: 1
```

① Groovy scripting is enabled by **groovy:** string.

When

The following test is executed: 🍷 (000ms)

```
@Test
@DataSet(value = "datasets/yml/groovy-with-date-
replacements.yml",cleanBefore = true, disableConstraints = true,
executorId = "rules-it")
public void shouldReplaceDateUsingGroovyInDataset() {
    Tweet tweet = (Tweet) emProvider.em().createQuery("select t from
    Tweet t where t.id = '1'").getSingleResult();
    assertThat(tweet).isNotNull();

    assertThat(tweet.getDate().get(Calendar.DAY_OF_MONTH)).isEqualTo(now.ge
    t(Calendar.DAY_OF_MONTH));

    assertThat(tweet.getDate().get(Calendar.HOUR_OF_DAY)).isEqualTo(now.get
    (Calendar.HOUR_OF_DAY));
}
```

Then

Dataset script should be interpreted while seeding the database 🍷 (000ms)

3.4.2. Scenario: Seed database with javascript in dataset



Javascript engine comes within JDK so no additional classpath dependency is necessary.

Given

The following dataset 🍌 (000ms)

```
tweet:
  - id: "1"
    content: "dbunit rules!"
    likes: "js:(5+5)*10/2" ①
    user_id: 1
```

① Javascript scripting is enabled by `js:` string.

When

The following test is executed: 🍌 (000ms)

```
@Test
@DataSet(value = "datasets/yml/js-with-calc-
replacements.yml",cleanBefore = true ,disableConstraints = true,
executorId = "rules-it")
public void shouldReplaceLikesUsingJavaScriptInDataset() {
    Tweet tweet = (Tweet) emProvider.em().createQuery("select t from
Tweet t where t.id = '1']").getSingleResult();
    assertThat(tweet).isNotNull();
    assertThat(tweet.getLikes()).isEqualTo(50);
}
```

Then

Dataset script should be interpreted while seeding the database 🍌 (000ms)

3.5. Database assertion using expected datasets

In order to verify database state after test execution

As a developer

I want to assert database state with datasets.

3.5.1. Scenario: Database assertion with yml dataset

Given

The following dataset 🍌 (001ms)

expectedUsers.yml

```
user:
  - id: 1
    name: "expected user1"
  - id: 2
    name: "expected user2"
```

When

The following test is executed: 📌 (000ms)

```
@RunWith(JUnit4.class)
public class ExpectedDataSetIt {

    @Rule
    public EntityManagerProvider emProvider =
        EntityManagerProvider.instance("rules-it");

    @Rule
    public DBUnitRule dbUnitRule =
        DBUnitRule.instance(emProvider.connection());

    @Test
    @DataSet(cleanBefore = true)①
    @ExpectedDataSet(value = "yaml/expectedUsers.yaml", ignoreCols = "id")
    public void shouldMatchExpectedDataSet() {
        EntityManagerProvider instance =
            EntityManagerProvider.newInstance("rules-it");
        User u = new User();
        u.setName("expected user1");
        User u2 = new User();
        u2.setName("expected user2");
        instance.tx().begin();
        instance.em().persist(u);
        instance.em().persist(u2);
        instance.tx().commit();
    }
}
```

① Clear database before to avoid conflict with other tests.

Then

Test must pass because database state is as in expected dataset. 📌 (000ms)

3.5.2. Scenario: Database assertion with regular expression in expected dataset

Given

The following dataset 🍌 (000ms)

expectedUsersRegex.yml

```
user:
  - id: "regex:\\d+"
    name: regex:^expected user.* #expected user1
  - id: "regex:\\d+"
    name: regex:.*user2$ #expected user2
```

When

The following test is executed: 🍌 (000ms)

```
@Test
@DataSet(cleanBefore = true)
@ExpectedDataSet(value = "yaml/expectedUsersRegex.yml")
public void shouldMatchExpectedDataSetUsingRegex() {
    User u = new User();
    u.setName("expected user1");
    User u2 = new User();
    u2.setName("expected user2");
    tx().begin();
    em().persist(u);
    em().persist(u2);
    tx().commit();
}
```

Then

Test must pass because database state is as in expected dataset. 🍌 (000ms)

3.5.3. Scenario: Database assertion with seeding before test execution

Given

The following dataset 🍌 (000ms)

user.yml

```
user:
  - id: 1
    name: "@realpestano"
  - id: 2
    name: "@dbunit"
```

And

The following dataset 🍌 (000ms)

expectedUser.yml

```
user:
  - id: 2
    name: "@dbunit"
```

When

The following test is executed: 🍌 (000ms)

```
@Test
@DataSet(value = "yaml/user.yml", disableConstraints = true)
@ExpectedDataSet(value = "yaml/expectedUser.yml", ignoreCols = "id")
public void shouldMatchExpectedDataSetAfterSeedingDataBase() {
    tx().begin();
    em().remove(em().find(User.class, 1L));
    tx().commit();
}
```

Then

Test must pass because database state is as in expected dataset. 🍌 (000ms)

3.5.4. Scenario: Failing database assertion

Given

The following dataset 🍌 (000ms)

expectedUsers.yml

```
user:
  - id: 1
    name: "expected user1"
  - id: 2
    name: "expected user2"
```

When

The following test is executed: 🍌 (000ms)

```
@Test
@ExpectedDataSet(value = "yaml/expectedUsers.yml", ignoreCols = "id")
public void shouldNotMatchExpectedDataSet() {
    User u = new User();
    u.setName("non expected user1");
    User u2 = new User();
    u2.setName("non expected user2");
    tx().begin();
    em().persist(u);
    em().persist(u2);
    tx().commit();
}
```

Then

Test must fail with following error: 🍷 (005ms)



```
junit.framework.ComparisonFailure: value (table=USER, row=0,
col=name) expected:<[]expected user1> but was:<[non ]expected
user1>                                     at
org.dbunit.assertion.JUnitFailureFactory.createFailure(JUnitFailur
eFactory.java:39)                         at
org.dbunit.assertion.DefaultFailureHandler.createFailure(Default
FailureHandler.java:97)                   at
org.dbunit.assertion.DefaultFailureHandler.handle(DefaultFailure
Handler.java:223) at ...
```

3.5.5. Scenario: Database assertion using automatic transaction

Given

The following dataset 🍌 (000ms)

expectedUsersRegex.yml

```
user:
  - id: "regex:\\d+"
    name: regex:^expected user.* #expected user1
  - id: "regex:\\d+"
    name: regex:.user2$ #expected user2
```

When

The following test is executed: 🍌 (000ms)

```
@Test
@DataSet(cleanBefore = true, transactional = true)
@ExpectedDataSet(value = "yaml/expectedUsersRegex.yml")
public void shouldManageTransactionAutomatically() {
    User u = new User();
    u.setName("expected user1");
    User u2 = new User();
    u2.setName("expected user2");
    em().persist(u);
    em().persist(u2);
}
```



Transactional attribute will make DBUnit Rules start a transaction before test and commit the transaction **after** test execution but **before** expected dataset comparison.

Then

Test must pass because inserted users are committed to database and database state matches expected dataset. 🍌 (000ms)