

# Living Documentation

# Table of Contents

1. Introduction.....	1
2. Summary.....	2
3. Features.....	3
3.1. Seeding database .....	3
3.1.1. Scenario: Seed database using dbunit CDI .....	3

# Chapter 1. Introduction

**DBUnit Rules** aims for bringing [DBUnit](#) closer to your JUnit tests. Here are the main features:

- [JUnit rule](#) to integrate with DBUnit via annotations:

```
@Rule
public DBUnitRule dbUnitRule = DBUnitRule.instance(jdbcConnection);①

@Test
@DataSet(value = "datasets/yml/users.yml")
public void shouldSeedDataSet(){
    //database is seed with users.yml dataset
}
```

① The rule depends on a JDBC connection.

- CDI interceptor to seed database without rule instantiation;
- Json, Yaml, xml and flat xml support;
- Cucumber integration;
- JPA integration;
- Multiple database support;
- Date/time support in datasets;

The project is composed by 5 modules:

- [Core](#): Contains the dataset executor and JUnit rule;
- [CDI](#): provides the DBUnit interceptor
- [Cucumber](#): a CDI aware cucumber runner;
- [JPA](#): Comes with a dataset executor based on JPA entity manager
- [Examples module](#).

# Chapter 2. Summary

Scenarios			Steps							Features: 1	
Passed	Failed	Total	Passed	Failed	Skipped	Pending	Undefined	Missing	Total	Duration	Status
Seeding database											
1	0	1	4	0	0	0	0	0	4	775ms	passed
Totals											
1	0	1	4	0	0	0	0	0	4	775ms	

# Chapter 3. Features

## 3.1. Seeding database

### 3.1.1. Scenario: Seed database using dbunit CDI

DBUnit CDI integration is done through a [CDI interceptor](#).



CDI must be enabled in your test, see the following example:

```
@RunWith(CdiTestRunner.class) ①
public class DBUnitCDITest {

}
```

① [CdiTestRunner](#) is provided by [Apache Deltaspike](#) but you should be able to use other CDI test runners.

*Given*

DBUnit interceptor is enabled in your test beans.xml: 👍 (486ms)

*src/test/resources/META-INF/beans.xml*

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://java.sun.com/xml/ns/javaee"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/beans_1_0.xsd">
  <interceptors>

  <class>com.github.dbunit.rules.cdi.DBUnitInterceptor</class>
  </interceptors>
</beans>
```

*And*

The following dataset located at `src/test/resources/datasets/users.yml`: 🍌 (000ms)

```
user:
- id: 1
  name: "@realpestano"
- id: 2
  name: "@dbunit"
tweet:
- id: abcdef12345
  content: "dbunit rules!"
  user_id: 1
- id: abcdef12233
  content: "dbunit rules!"
  user_id: 2
- id: abcdef1343
  content: "CDI for the win!"
  user_id: 2
follower:
- id: 1
  user_id: 1
  follower_id: 2
```

### When

The following test is executed: 🍌 (000ms)

```
@Test
@UsingDataSet("yml/users.yml")
public void shouldSeedUserDataSetUsingCdiInterceptor() {
    List<User> users = em.createQuery("select u from User u order
by u.id asc").getResultList();
    User user1 = new User(1);
    User user2 = new User(2);
    Tweet tweetUser1 = new Tweet();
    tweetUser1.setId("abcdef12345");
    Tweet tweetUser2 = new Tweet();
    tweetUser2.setId("abcdef12233");
    assertThat(users).isNotNull().hasSize(2).contains(user1,
user2);
    List<Tweet> tweetsUser1 = users.get(0).getTweets();

    assertThat(tweetsUser1).isNotNull().hasSize(1).contains(tweetUser1);
}
```

*Then*

The database should be seeded with the dataset content 🍷 (288ms)