

Identity Blockchain - Proof of Identity

Albert Vučinović, University North
Miroslav Jerković, University of Zagreb

July 23, 2022

Abstract

Identity Blockchain uses state-certified electronic identities (eIDs) to create blockchain identities and a consensus protocol called Proof of Identity (PoI). PoI is "green" and enables many applications that are impossible to implement without verified identity on the blockchain, e.g., direct democracy and universal basic income, encrypted messaging, etc. *Identity Blockchain* preserves identity anonymity by using zk-SNARKs and an anonymization protocol for identity onboarding.

1 Introduction

TODO

2 Notation

(K, K^{-1})	Pair of public key K and the corresponding private key K^{-1}
$K(value)$	String $value$ encrypted with a public key K
$K^{-1}(value)$	String $value$ encrypted with a private key K^{-1}
H	zk-SNARK-friendly hash function
Nin	Unique state-issued personal <i>National Identification Number</i>
CA	Certificate Authority
eID	Electronic identification document
K_{ID}	CA-certified public key of eID
K_P	Person key, unique public key used to access <i>Identity Blockchain</i>

Sometimes we write K for (K, K^{-1}) .

3 Registering K_{ID}

Register K_{ID} on *Identity Blockchain* by calling

$$\text{register}K_{ID}(H(Nin), K_{ID}^{-1}(\text{"register}K_{ID}\text{"}), \text{proof}NinOwnsKid).$$

Pseudo-solidity code

```
1  mapping(uint => uint) public ninKidUsed;
2  mapping(uint => bool) public kidInvalid;
3
4  function registerKid(
5      uint hNin, // hNin = H(Nin)
6      uint vKid, // vKid = KidPrivate("registerKid")
7      uint[2] memory proofPointA,
8      uint[2][2] memory proofPointB,
9      uint[2] memory proofPointC,
10     bool invalidate
11 ) public {
12     //Setting public arguments
13     uint[] memory inputValues = new uint[](2)
14     inputValues[0] = hNin;
15     inputValues[1] = vKid;
16
17     require(
18         verifyProof(
19             proofPointA,
20             proofPointB,
21             proofPointC,
22             inputValues
23         )
24     );
25
26
27     uint previousKey = ninKidUsed[hNin];
28     if (previousKey == vKid) return; // already registered
29
30
31     uint previousVKid = ninKidUsed[hNin];
32     if (previousVKid != vKid and invalidate == true) {
33         //If they are different, we need to invalidate old Kid
34         kidInvalid[previousVKid] = true;
35     }
36     require(!kidInvalid[vKid]);
37
38     ninKidUsed[hNin] = vKid;
39 }
```

Pseudo-circom code

Using <https://github.com/zkp-application/circom-rsa-verify> for now, MIT license. Which probably doesn't work, we should check (sha256?).

The next line is used on a file of shape:

—BEGIN PUBLIC KEY—

...

```

—END PUBLIC KEY—
—BEGIN CERTIFICATE—
...
—END CERTIFICATE—

```

We assume:

```

modulus = Subject Modulus
exp = Subject Exponent
openssl x509 -in Identification.pem -text -noout

```

Statements we need to check:

- CA is an accepted CA by *Identity Blockchain*
 - A set representation exists on blockchain which contains CA public keys (CA-public-keys).
 - Verify inclusion of the CA in cert in CA-public-keys.
 - A set representation exists on blockchain which has all the revoked CA public keys (Revoked-CA-public-keys).
 - Verify exclusion of the CA in cert from Revoked-CA-public-keys.
 - Verify CA validity with respect to time (maybe blockchain)
- Cert CA signed
 - the Kid
 - x509 Subject that contains Nin in the right place in the subject
 - verify Validity of x509 cert with respect to time
- Kid is not on revoked certs list by CA (blockchain hosted list)
- Kid decrypts vKid into clear text "registerKid".

```

1  pragma circom 2.0.0;
2
3  include "../utils/rsa_verify.circom"
4  include "../circomlib/circuits/sha256/sha256.circom"
5  include "../circomlib/bitify.circom"
6
7  //hashNumberOfWords = 4 for sha256
8  //rsaNumberOfWords = 32 for 2048 rsa
9  //we use words of 64 bits
10 template NinOwnsKid(
11     rsaNumberOfWords,
12     hashNumberOfWords,
13     lengthInBitsOfSignedMessage,
14     lengthOfNinInBits,
15     bitsInAWord
16 ){
17     //TODO: What happens to uint256 when converted to signal
18
19     //public:
20     signal input hNin;
21     signal input vKid;
22

```

```

23 //private:
24 signal input Nin;
25 //Kid, CA signature
26 singal input exp[rsaNumberOfWords];
27 signal input sign[rsaNumberOfWords];
28 signal input modulus[rsaNumberOfWords];
29
30 //we need some inputs to verify what is signed
31 //and that Nin in the right place in the signed message
32 signal input messageToBeSigned[lengthInBitsOfSignedMessage];
33 signal input Nin[lengthOfNinInBits];
34
35 //TODO: Insert Nin into messageToBeSigned in the right place
36 //or create constraint on the corresponding bits
37
38
39 component sha = Sha256(lengthInBitsOfSignedMessage);
40 for (int i = 0; i<lengthInBitsOfSignedMessage; i++) {
41     sha.in[i] <== messageToBeSigned[i]
42 }
43
44 var hashed[hashNumberOfWords]; //4x64 bit
45 var hashedBits[hashNumberOfWords*bitsInAWord];
46 for (int i=0; i<hashNumberOfWords*bitsInAWord; i++){
47     hashedBits[i] <== sha.out[i];
48 }
49 component b2n = Bits2Num(64);
50 //TODO: Can we use a component multiple times?
51 //Will all the constraints be generated
52 for (int i=0; i<hashNumberOfWords; i++){
53     for (int j=0; j<bitsInAWord; j++){
54         b2n.in[j] <== hashedBits[i*64+j];
55     }
56     hashed[i] <== b2n.out;
57 }
58
59
60 //lets assume sha256WithRSAEncryption
61 //verify CA signature of Kid
62 component rsa = RsaVerifyPkcs1v15(bitsInAWord, rsaNumberOfWords,
63     17, 4);
64 for (var i = 0; i < rsaNumberOfWords; i++){
65     rsa.exp[i] <== exp[i];
66     rsa.sign[i] <== sign[i];
67     rsa.modulus[i] <== modulus[i];
68 }
69 for (var i = 0; i<hashNumberOfWords; i++){
70     rsa.hashed[i] <== hashed[i];
71 }
72 //TODO: verify Kid(vKid)=="registerKid"
73
74 //Check CA on CA approved list
75 //On blockchain mapping (uint256 => bool) public CValid
76
77
78 //Take Kid

```

```

79 //Take CA
80
81
82
83 }
84 component main { public [hNin,vKid]] = NinOwnsKid();

```

Features

Sybil resistance

A Person is prevented from registering more than one K_P , e.g. by using different identification documents issued for the same Nin .

Fix for the loss of eID

A Person who has lost a previously registered K_{ID} , e.g. due to loss of eID, can overwrite it by registering a new K_{ID} .

Identity theft damage control

If a Person overwrites the previous K_{ID} with a new one, the identity Thief loses access to services that verify the entire identity chain.

Remarks

- i) An entity that knows K_{ID} , e.g. the CA who certified the corresponding eID, can know that the Person has registered K_{ID} on *Identity Blockchain*.
- ii) Reasoning for the choice of arguments: if $H(Nin, K_{ID}^{-1}(\text{"register } K_{ID}"))$ was used as an argument, then if someone tried to register with two different ids, we couldn't tell if Nin was already used. On the other hand, the choice of arguments Nin and $K_{ID}^{-1}(\text{"register } K_{ID}"))$ would be almost the same as $hNin$ and $K_{ID}^{-1}(\text{"register } K_{ID}"))$, because you can brute force all the possible $Nins$ and find the corresponding $hNins$.

4 Registering K_P

Register K_P on *Identity Blockchain* by calling

$$\text{registerK}_P(\text{NinK}_{ID}, \text{NinK}_{ID}K_P, \text{proof}),$$

where:

$$\text{NinK}_{ID} = H(\text{Nin}, K_{ID}^{-1}(\text{"registerK}_P\text{"}))$$

$$\text{NinK}_{ID}K_P = H(\text{Nin}, K_{ID}^{-1}(\text{"registerK}_P\text{"}), K_P^{-1}(\text{"registerK}_P\text{"})).$$

Pseudo-solidity code

```
1  mapping(uint => uint) public ninKidKpUsed;
2
3  function registerKp(
4      uint hNinKid,
5      uint hNinKidKp,
6      uint[2] memory proofPointA,
7      uint[2][2] memory proofPointsB,
8      uint[2] memory proofPointC
9  ) public {
10
11      //Setting public arguments
12      uint[] memory inputValues = new uint[](2)
13      inputValues[0] = hNinKid;
14      inputValues[1] = hNinKidKp;
15
16
17      require(
18          verifyProof(
19              proofPointA,
20              proofPointsB,
21              proofPointC,
22              inputValues
23          )
24      );
25
26      ninKidKpUsed[hNinKid] = hNinKidKp;
27  }
```

Features

Sybil resistance

K_P is a unique public key bound to the Person on the *Identity Blockchain*. By design, the Person cannot have two valid K_P keys at the same time.

TODO: Explanation/proof.

Anonymity

No one who has a database with all public keys K_{ID} or/and public keys K_P can tell, from the function call, which Nin , K_{ID} or K_P was used. This is true under the assumption that CA, which certified the eID, does not have access to K_{ID}^{-1} , i.e. that K_{ID} was securely generated on the eID.

TODO: Explanation/proof.

Remarks

- i) Reasoning behind the choice of arguments: We want to connect Nin with K_P in a unique, but untraceable way. If we only used $NinK_{ID}K_P$ then if someone used multiple K_P s we wouldn't be able to prove the connection to Nin (i.e. they could register a lot of K_P s). Hashing connects arguments, and makes them opaque without the knowledge of arguments (which in this case include private keys), so the arguments are opaque without the knowledge of private keys.

Pseudo-circom code Statements we need to check:

- CA

5 Problems

- P1** The rate of addition of identities, the problems of frequent changes of Merkle Tree Roots, and how long it takes to generate zkp proof, and block generation time.
- P2** The Thief stole K_{ID}^{-1} before we registered on *Identity Blockchain* and then registered K_{ID} and K_P .
- P3** The Thief stole K_{ID}^{-1} after we registered on *Identity Blockchain*.
- P4** Trying to use unregistered Key.
- P5** Trying to register the same *Nin* with multiple Keys (e.g. two physical ids).
- P6** Using K_P without checking the whole $CA \rightarrow K_{ID} \rightarrow K_P$ chain.
- i) Using K_P to register as a mining key.
 - ii) Invalidating K_P .
 - iii) Using new K_P as a mining key.

Solution

Look at the solution to **P7**.

The Mining Registry can accept new K_P after an expiration period (which can be e.g. one day).

- P7** A combination of **P2** and **P6**. The Thief steals K_{ID} , registers K_P and registers K_P for mining. The problem is bigger, because we can't invalidate K_P if we don't know which K_P it is.

Solution

We make K_P renewable. We write the last block number it was renewed on to the *Identity Blockchain*. Mining Registry can choose to accept K_P that is not older than some time period (for the Registry a good period would seem to be one day). When paying the miners, the Registry also requires proof of K_P .

- P8** Only K_P is compromised.