

Empirical Proof Record: INCONCLUSIVE

2026-05-24T00:59:27.196828+00:00

Empirical Proof Record — **INCONCLUSIVE**

Proof ID: cc005bda452d1f584a1cc340d51b84bd...

Created: 2026-05-24T00:59:27.196828+00:00

1. Claim

Kimera's representation-distance (relative divergence of the manifold state: coupling / order_parameter / knowledge_mass) between same-multiset return histories GRADES their real $|\Delta \text{ max-drawdown}|$ (Spearman fidelity) better than a standard order-aware retriever, by a margin: $\text{graded_fidelity_advantage} = \text{fidelity}(\text{kimera_state}) - \text{fidelity}(\text{order_aware}) \geq 0.2$. The prime set-distance is scored alongside as a saturation control.

- **Operationalisation:** For 2 real return multisets, generate 8+2 orderings spanning drawdowns; score each representation by Spearman(pairwise distance, $|\Delta \text{ max-drawdown}|$). Headline = mean over windows of $\text{fidelity}(\text{kimera_state}) - \text{fidelity}(\text{order_aware shingle})$; the prime set-distance fidelity (saturation control) and the order-blind mean-pool ~ 0 floor are reported alongside.
- **Threshold:** $\text{graded_fidelity_advantage} \geq 0.2$ spearman_rho
- **H0:** H0: $\text{advantage} < \text{margin}$ — Kimera's manifold-state divergence does not grade drawdown better than generic order-aware retrieval.
- **H1:** H1: $\text{advantage} \geq \text{margin}$ — Kimera's manifold-state divergence carries graded path-magnitude that generic order-aware retrieval does not.

2. Verdict

INCONCLUSIVE — observed 0.0

only 2/2 windows yielded manifold state for all orderings (need 4).

3. Evidence

Pillar	Statistic	Value	95% CI	Library
graded-fidelity	graded_fidelity_advantage	0.0	—	scipy spearmanr

4. Pre-registration

- Registered at: 2026-05-24T00:59:26.933514+00:00
- Config hash: 5c54f11dc61f758ff9f76a2c69f7c578...
- Data hash: daefbdeac7a7e6b95e7144bd2a4d5e8c...

5. Signature

ee0c662bb35a803d737e05db627081e1a26b16243e79840a4bcd90944fe1824b