

# Statistics of Natural Stochastic Textures with application in Image Processing

Ido Zachevsky

Joint work with Prof. Y. Y. Zeevi





June 2016

# Natural stochastic textures (NST) in natural images



Natural stochastic textures are abundant in natural images.





# Statistics of *natural stochastic textures* (NST) (I)



Natural image



Stochastic texture



Synthetic texture (fBm)

★ Wavelet domain statistics

# Statistics of *natural stochastic textures* (NST) (II)

Properties of NSTs include:

- NSTs are considered as realizations of 2D random processes.
- *Gaussian* statistics in marginal and joint distributions, unlike general natural images. [Zachevsky and Zeevi, 2014a, 2016]
  - In image space.
  - In wavelet domain.
- Self similarity – scale invariance [Srivastava et al., 2003].

## Main conclusion from current study

Natural stochastic textures have *Gaussian* statistics.

A suitable model should be *Gaussian and self-similar*.

# Fractional Brownian motion (fBm)

[Mandelbrot and Van Ness, 1968, Kolmogorov, 1940]

fBm  $\Rightarrow$  Gaussianity and self-similarity [Samorodnitsky, 2006]:


①  $B(\{t_1, t_2, \dots, t_k\}) \sim \mathcal{N}(0, \Sigma(\{t_i\}))$

②  $B(ct) \stackrel{d}{=} c^H B(t), c > 0$


③ Stationary increments.

$\Rightarrow B(t)$  is fBm with a self-similarity parameter  $H \in (0, 1)$  and autocorrelation:


$$E[B_H(t)B_H(s)] = \frac{\sigma_H^2}{2} (|t|^{2H} + |s|^{2H} - |t - s|^{2H})$$




$H = 0.1$



$H = 0.3$



$H = 0.5$



$H = 0.7$



$H = 0.9$

# Is fBm sufficient as a prior?

## Relevance as a model for NST


- + Gaussian.
- + Statistically self-similar.
- *Random phase – no edges* in the usual sense.



Isotropic texture

## NSTs are of a broader class

- Anisotropic/Asotropic.
- *Phase*-based properties.




Asotropic texture

## Conclusion

A suitable model for NST should consist of a generalization of fBm to a more elaborate model.


# The importance of the phase in natural images




Einstein

- ★ Phase is important for the visual appearance of images [Oppenheim and Lim, 1981].


- ★ Global v. Localized phase [Behar et al., 1992]



Mandrill




$$\mathcal{F}^{-1}\{|Mandrill| \exp(j\angle Einstein)\}$$




$$\mathcal{F}^{-1}\{|Einstein| \exp(j\angle Mandrill)\}$$

# The importance of the phase in natural textures

## "Unlocking the phase"



*Isotropic* texture




Phase with  $\sigma = 1$  normal distributed i.i.d  
noise (14.9dB PSNR)


- \* *Little* visual change in the case of isotropic textures.
- \* Isotropic textures – Random phase.
- \* Anisotropic textures – Phase info required.

# The importance of the phase in natural textures

## "Unlocking the phase"



*Asotropic* texture



Phase with  $\sigma = 1$  normal distributed i.i.d  
noise (18.1dB PSNR)

- \* *Significant* contribution of phase info in the case of anisotropic textures.
- \* Isotropic textures – Random phase.
- \* Asotropic textures – Phase info required.

## Some examples

# Super-resolution from a single image [Zachevsky and Zeevi, 2014b]

Problem formulation:

$$\hat{X}(\eta_1, \eta_2) = \arg \min_X \|Y - \mathcal{D}(B * X)\|_2^2 + \lambda \phi(X)$$

Solution method:

- Use the fBm averaged spectrum and *retain* phase.
- *Self-similarity*: Use the autocorrelation of the low-resolution image for reconstruction of the high-resolution image.
- Implementation via anisotropic PDE (tensor diffusion), modified to promote recovery of small details:

$$\begin{aligned} X'_t &= 2(DB)^T(DBX' - Y) - 2\bar{H}_{HP}(\hat{X}_{HP} - \bar{H}_{HP}X') + \\ &\quad + \beta \nabla \cdot (\Psi'(|\nabla X'| + \gamma |\nabla Y_\phi|^2) \nabla (X' + \gamma Y_\phi)) \end{aligned}$$

# Super-resolution from a single image

[Zachevsky and Zeevi, 2014b]




LR image



Sparseness-based SR [Yang et al., 2008]



Proposed method



Ground truth


# Retaining the phase for anisotropic textures

[Zachevsky and Zeevi, 2016 (submitted)]


- ★ Reconstruction of severely degraded anisotropic textures
- ★ Estimation of *magnitudes* while retaining the *phase*
- ★ Example: degradation by Gaussian blur, width  $\sigma_f = 1$  and AWGN  $\sigma_N = 0.1$




Ground truth



Blur+noise (17.47dB, 0.567)



BM3D (20.43dB, 0.713) [Danielyan et al., 2012]



Proposed alg. (20.33dB, 0.841)

# Further research: towards a texture manifold

A texture manifold should include:

- Stochastic characteristics (fBm, mBm): Self similarity ( $\{H_i\}$ ), LRD,
- Phase dependency:
  - Local phase.
  - Orientation –  $\theta$
  - Coherence –  $\mu$

Representation via a manifold [Peyré, 2009]:

$$(\eta_1, \eta_2) \rightarrow (\eta_1, \eta_2, H_i, \theta, \mu, \dots).$$

Desired properties:

- Natural representation for color textures including depth information.
- A measure of similarity between two textures via the intrinsic metric.

# Bibliography I

- Ido Zachevsky and Yehoshua Y Zeevi. On the statistics of natural stochastic textures and their application in image processing. In *IEEE Int. Conf. Acoust. Speech Signal Process.*, pages 5829–5833, Florence, Italy, may 2014a.
- Ido Zachevsky and Yehoshua Y Zeevi. On the phase of natural stochastic structured textures and its application in deconvolution and image decomposition. *CCIT Report, Tech.*, 1855(898):1–65, 2016.
- A Srivastava, A B Lee, and E P Simoncelli. On Advances in Statistical Modeling of Natural Images. *J. Math. Imaging Vis.*, 18:17–33, 2003.
- Gennady Samorodnitsky. Long memory and self-similar processes. *Ann. - Fac. des Sci. Toulouse Math.*, 15(1):107–129, 2006. URL [#0](http://scholar.google.com/scholar?hl=en&btnG=Search&q=intitle:Long+memory+and+self-similar+processes).
- Benoit B Mandelbrot and John W Van Ness. Fractional Brownian motions, fractional noises and applications. *SIAM Rev.*, 10(4):422–437, 1968.
- Andrei N Kolmogorov. Wienersche Spiralen und einige andere interessante Kurven im Hilbertschen Raum. In *CR Acad. Sci. URSS*, volume 26, pages 115–118, 1940.
- Alan V. Oppenheim and Jae S. Lim. Importance of Phase in Signals. *Proc. IEEE*, 69(5):529–541, 1981.
- Jacques Behar, Moshe Porat, and Yehoshua Y Zeevi. Image Reconstruction from Localized Phase. *IEEE Trans. Signal Process.*, 40(4):736–743, 1992.
- I Zachevsky and Y Y Zeevi. Single-Image Superresolution of Natural Stochastic Textures Based on Fractional Brownian Motion. *IEEE Trans. Image Process.*, 23(5):2096–2108, 2014b. ISSN 1057-7149. doi: 10.1109/TIP.2014.2312284.
- Jianchao Yang, John Wright, Yi Ma, and Thomas Huang. Image super-resolution as sparse representation of raw image patches. In *IEEE Conf. Comput. Vis. Pattern Recognit*, pages 1–8, jun 2008. ISBN 978-1-4244-2242-5. doi: 10.1109/CVPR.2008.4587647. URL <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=4587647>.
- Aram Danielyan, Vladimir Katkovnik, and Karen Egiazarian. BM3D frames and variational image deblurring. *IEEE Trans. Image Process.*, 21(4):1715–1728, apr 2012. ISSN 1941-0042. doi: 10.1109/TIP.2011.2176954. URL <http://www.ncbi.nlm.nih.gov/pubmed/22128008>.
- Gabriel Peyré. Manifold models for signals and images. *Comput. Vis. Image Underst.*, 113(2):249–260, feb 2009. ISSN 10773142. doi: 10.1016/j.cviu.2008.09.003. URL <http://linkinghub.elsevier.com/retrieve/pii/S1077314208001550>.