

Inheritance

Course: CSL304

Prof. Juhi Ganwani

CONTENT


1. Types of inheritance
2. Method overriding
3. super keyword
4. Abstract class and method
5. final keyword
6. Multiple inheritance using interface
7. extends keyword

Inheritance




- Concept of reusability
- Mechanism of deriving a new class from an old one
- New class derive properties from base class
- Old class: base class or super class or parent class
- New class: derived class or sub class or child class
- To inherit from a class, use the extends keyword.

class derived-class extends base-class

```
{  
    //methods and fields  
}
```




Types of Inheritance



Multiple inheritance (through interfaces)

- Java does not support multiple inheritance using classes
- Class C is inherited from interface A and B



Single Inheritance

```
class Rectangle
{
    int length, breadth;
    Rectangle(int x,int y)
    {length=x;          breadth=y;}
    int area(){
        return length*breadth;}
}
class RectangularPrism extends Rectangle
{
    int height;
    RectangularPrism(int x,int y,int z){
        super(x,y);
        height=z;}
    int volume(){
        return length*breadth*height;}}
```

```
class SingleInheritance
{
    public static void main(String args[])
    {
        RectangularPrism prism=new RectangularPrism(2,3,10);
        int area1=prism.area();
        int vol1=prism.volume();
        System.out.println("Area="+area1);
        System.out.println("Volume="+vol1);
    }
}
```

Note:

Subclass constructor uses the keyword super to invoke the constructor method of the superclass

Call to superclass constructor must appear as the first statement within the subclass constructor

super keyword

- It is similar to this keyword
- It is used to differentiate members of superclass from subclass, if they have same names
- It is used to invoke superclass constructor from subclass

```
class Super_class
{
int num = 20;
public void display()
{
System.out.println("This is the display method
of superclass");
}
}
```

```
public class Sub_class extends Super_class
{
int num = 10;
public void display()
{System.out.println("This is the display method
of subclass");}
```

```
public void my_method()
{
Sub_class sub = new Sub_class();
sub.display();
super.display();
System.out.println("value of the variable named num
in sub class:"+ sub.num);
System.out.println("value of the variable named num
in super class:"+ super.num);
}
```

```
public static void main(String args[])
{
    Sub_class obj = new Sub_class();
    obj.my_method();
}
}
```


Multilevel Inheritance

```
class Shape {  
    public void display() {  
        System.out.println("Inside display");  
    }  
}  
  
class Rectangle extends Shape {  
    public void area() {  
        System.out.println("Inside area");  
    }  
}
```

```
class Cube extends Rectangle {  
    public void volume() {  
        System.out.println("Inside volume");  
    }  
}  
  
public class CubeMain {  
    public static void main(String[] arguments) {  
        Cube cube = new Cube();  
        cube.display();  
        cube.area();  
        cube.volume();  
    }  
}
```

Hierarchical Inheritance

```
class Animal{  
void eat()  
{System.out.println("eating...");}  
}  
class Dog extends Animal{  
void bark()  
{System.out.println("barking...");}  
}
```

```
class Cat extends Animal{  
void meow()  
{System.out.println("meowing...");}  
}  
Class AnimalMain{  
public static void main(String args[]){  
Cat c=new Cat();  
c.meow();  
c.eat();  
//c.bark();      //C.T.Error  
}}
```

Why Multiple Inheritance is not allowed?

- To reduce the complexity and simplify the language
- Consider a scenario where A, B, and C are three classes. The C class inherits A and B classes.
- If A and B classes have the same method and you call it from child class object, there will be ambiguity to call the method of A or B class.

Example

```
class A{
void msg(){System.out.println("Hello");}
}
class B{
void msg(){System.out.println("Welcome");}
}
class C extends A,B{//suppose if it were

public static void main(String args[]){
    C obj=new C();
    obj.msg(); //Now which msg() method would be invoked?
}
}
```

Method overriding

- Methods having same name & argument list of which one is in superclass & other is in subclass.
- Child class can give its own implementation to a method which is already provided by the parent class.
- Method in parent class is called overridden method and the method in child class is called overriding method.
- If a call is made from subclass, then it will refer to subclass method thereby hiding the method of the superclass.
- If a method call is outside the superclass & subclass then the method invoked will be based on object invoking it.

```
class Super
{
void display(){
System.out.println("Super class");
}
}
class Sub extends Super
{
void display(){
System.out.println("Sub class");
super.display();
}
}
```

```
class OverrideTest
{
public static void main(String args[])
{
    Super s1=new Super();
    s1.display();
    Sub s2=new Sub();
    s2.display();
}
}
```

final keyword

Final Variable → To create constant variables

Final Methods → Prevent Method Overriding

Final Classes → Prevent Inheritance

final variable

- When a variable is declared with *final* keyword, its value cannot be modified.

class Bike

```
{
    final int speedlimit=90;
    void run(){
        speedlimit=400;
    }
    public static void main(String args[]){
        Bike obj=new Bike();
        obj.run();
    }
}
```


final method

- We cannot override any final method

```
class Bike{
    final void run(){
        System.out.println("running");}
}
class Honda extends Bike
{
    void run(){
        System.out.println("Running safely with 100kmph");}

    public static void main(String args[]){
        Honda h=new Honda();
        h.run();
    }
}
```

final class

- Final class cannot be extended

```
final class Bike
```

```
{}
```

```
class HondaClass extends Bike
```

```
{
```

```
    void run(){
```

```
        System.out.println("Running safely with 100kmph");}
```

```
    public static void main(String args[])
```

```
    {
```

```
        HondaClass h=new HondaClass();
```

```
        h.run();
```

```
    }
```

```
}
```

Abstraction

- Data **abstraction** is the process of hiding certain details and showing only essential information to the user.
- **Abstraction** - hiding the implementation details and showing only functionality to the user.
- Example: email, sms, etc
- It can be achieved using abstract classes or interfaces
- **Abstract class:** is a restricted class that cannot be used to create objects
- **Abstract method:** can only be used in an abstract class, and it does not have a body. The body is provided by the subclass

Rules of abstract class

- It may or may not contain *abstract methods*, i.e., methods without body
- If a class has at least one abstract method, then the class **must** be declared abstract.
- To use an abstract class, you have to inherit it from another class, provide implementations to the abstract methods in it.
- If you inherit an abstract class, you have to provide implementations to all the abstract methods in it.

Abstract class

```
abstract class Animal {  
    public abstract void animalSound();  
    public void sleep() {  
        System.out.println("Zzz");  
    }  
}
```

Example

```
abstract class Animal {  
    public abstract void animalSound();  
    public void sleep() {  
        System.out.println("Zzz");  
    }  
    class Dog extends Animal {  
        public void animalSound() {  
            // The body of animalSound() is provided here  
            System.out.println("The Dog says: woof woof");  
        }  
    }  
}
```

```
class MyMainClass {  
    public static void main(String[] args) {  
        Dog mydog = new Dog();  
        mydog.animalSound();  
        mydog.sleep();  
    }  
}
```

Interface

- It is similar to a class
- Methods declared in an interface is by default abstract and variables are public, static & final
- Interfaces define only abstract methods & final fields.
- Class has to implement interface to define the code for implementation of these methods

Syntax:

```
interface InterfaceName
{
    variables declaration;
    methods declaration;
}
```

Interface

Example:

```
interface Area
```

```
{
```

```
    final static float pi=3.142;
```

```
    float compute(float x, float y);
```

```
    void show();
```

```
}
```


Implementing interface

- Class can implement more than one interface
- Interface can extends another interfaces
- A class that implements interface must implement all the methods in interface otherwise that class should be declared as abstract class

Example

interface Area

```
{  
    final static double pi = 3.14;  
    double calc(double x,double y);  
}
```

class Rectangle implements Area

```
{  
    public double calc(double x,double y)  
    {  
        return(x*y);  
    }  
}
```

class Circle implements Area

```
{    public double calc(double x,double y)    {  
        return(pi*x*y);  
    }  
}
```

class InterfaceTest

```
{  
    public static void main(String arg[])    {  
        Rectangle r = new Rectangle();  
        Circle c = new Circle();  
        System.out.println("\nArea of Rectangle is : " +r.calc(10,20));  
        System.out.println("\nArea of Circle is : " +c.calc(15,15));    }  
}
```

Partial implementation of an interface

```
interface Area
{
    double pi=3.14;
    double compute(double x,double y);
}
abstract class Circle implements Area
{
    public void display()
    {
        System.out.println("Circle Class");
    }
}
```

Extending interfaces (multiple inheritance)

```
interface One {  
    public void methodOne();  
}  
interface Two {  
    public void methodTwo();  
}  
class Three implements One, Two {  
    public void methodOne()  
    {}  
    public void methodTwo()  
    {}  
}
```

Note: A class can extend a class and can implement any number of interfaces simultaneously.

Interface Examples

- Write a class Rectangle which implements interface Polygon having method getArea with parameters length and breadth. (Rectangle Main)
- Write a class Bird which implements two interfaces BirdEat & BirdFly having method eating & flying respectively. (BirdMain)
- Write a class College which inherits class Name and implements two interfaces Teacher & Student having method teach and study respectively. (CollegeTest.java)