```
'!'=0
'#'=0
'$'=1703
'*'=(   )
-=569XZilms
0=-zsh
'?'=0
@=(   )
ARGC=0
CDPATH=''
COLUMNS=80
CPUTYPE=arm64
EGID=20
EUID=502
FIGNORE=''
FPATH=/usr/local/share/
zsh/site-functions:/usr/
share/zsh/site-
functions:/usr/share/zsh/
5.9/functions
FUNCNEST=700
GID=20
HISTCHARS='!^#'
HISTCMD=73
HISTFILE=/Users/
demouser/.zsh_sessions/
EAD2055F-48DC-4AC3-85F3-
A1B1BE48F7C7.historynew
HISTSIZE=2000
HOME=/Users/demouser
HOST=QTD26P4556-MacBook-
Pro.local
IFS=$' \t\n\C-@'
KEYBOARD_HACK=''
KEYTIMEOUT=40
LANG=en_US.UTF-8
LINENO=20
LINES=24
LISTMAX=100
```

```
LOGNAME=demouser
MACHTYPE=x86_64
MAILCHECK=60
MAILPATH=''
MANPATH=''
MATCH=T
MBEGIN=1
MEND=1
MODULE_PATH=/usr/lib/zsh/
5.9
NULLCMD=cat
OLDPWD=/private/var/
folders/pm/
1z2qd7mj2s3_nfmwc2pdcn0r0
000gp
OPTARG=''
OPTIND=1
OSTYPE=darwin22.0
PATH=/usr/local/bin:/
System/Cryptexes/App/usr/
bin:/usr/bin:/bin:/usr/
sbin:/sbin:/var/run/
com.apple.security.crypte
xd/codex.system/
bootstrap/usr/local/bin:/
var/run/
com.apple.security.crypte
xd/codex.system/
bootstrap/usr/bin:/var/
run/
com.apple.security.crypte
xd/codex.system/
bootstrap/usr/
appleinternal/bin
PPID=1702
PROMPT='%n@%m %1~ %# '
PROMPT2='%_> '
PROMPT3='?# '
PROMPT4='+%N:%i> '
```

```
PS1='%n@%m %1~ %# '
PS2='%_> '
PS3='?# '
PS4='+%N:%i> '
PSVAR=''
PWD=/private/var/folders/
pm/
1z2qd7mj2s3_nfmwc2pdcn0r0
000gp/T
RANDOM=27810
READNULLCMD=more
SAVEHIST=1000
SECONDS=56
SHELL=/bin/zsh
SHELL_SESSION_DID_HISTORY
_CHECK=1
SHELL_SESSION_DID_INIT=1
SHELL_SESSION_DIR=/Users/
demouser/.zsh_sessions
SHELL_SESSION_FILE=/
Users/
demouser/.zsh_sessions/
EAD2055F-48DC-4AC3-85F3-
A1B1BE48F7C7.session
SHELL_SESSION_HISTFILE=/
Users/
demouser/.zsh_sessions/
EAD2055F-48DC-4AC3-85F3-
A1B1BE48F7C7.history
SHELL_SESSION_HISTFILE_NE
W=/Users/
demouser/.zsh_sessions/
EAD2055F-48DC-4AC3-85F3-
A1B1BE48F7C7.historynew
SHELL_SESSION_HISTFILE_SH
ARED=/Users/
demouser/.zsh_history
SHELL_SESSION_HISTORY=1
SHELL_SESSION_TIMESTAMP_F
```

```
ILE=/Users/
demouser/.zsh_sessions/
_expiration_check_timesta
mp
SHLVL=1
SPROMPT='zsh: correct
'\''%R'\'' to
'\''%r'\'' [nyae]? '
SSH_AUTH_SOCK=/private/
tmp/
com.apple.launchd.VJ1BlvM
0kw/Listeners
TERM=xterm-256color
TERM_PROGRAM=Apple_Termin
al
TERM_PROGRAM_VERSION=447
TERM_SESSION_ID=EAD2055F-
48DC-4AC3-85F3-
A1B1BE48F7C7
TIMEFMT='%J   %U user %S
system %P cpu %*E total'
TMPDIR=/var/folders/pm/
1z2qd7mj2s3_nfmwc2pdcn0r0
000gp/T/
TMPPREFIX=/tmp/zsh
TRY_BLOCK_ERROR=-1
TRY_BLOCK_INTERRUPT=-1
TTY=/dev/ttys000
TTYIDLE=0
UID=502
USER=demouser
USERNAME=demouser
VENDOR=apple
WATCH
WORDCHARS='*?_-.[]~=/&;!
#$%^(){}<>'
XPC_FLAGS=0x0
XPC_SERVICE_NAME=0
ZSH_ARGZERO=-zsh
```

```
ZSH_EVAL_CONTEXT=toplevel
ZSH_NAME=zsh
ZSH_PATCHLEVEL=zsh-5.9-0-
g73d3173
ZSH_SUBSHELL=0
ZSH_VERSION=5.9
_=set
__CFBundleIdentifier=com.
apple.Terminal
aliases
argv=(  )
builtins
cdpath=(  )
commands
dirstack
dis_aliases
dis_builtins
dis_functions
dis_functions_source
dis_galiases
dis_patchars
dis_reswords
dis_saliases
fignore=(  )
fpath=( /usr/local/share/
zsh/site-functions /usr/
share/zsh/site-
functions /usr/share/zsh/
5.9/functions )
funcfiletrace
funcsourcetrace
funcstack
functions
functions_source
functrace
galiases
histchars='!^#'
history
historywords
```

```
jobdirs
jobstates
jobtexts
key=( [Backspace]=$'\C-
H' [Delete]=$'\C-
[[3~' [Down]=$'\C-
[OB' [End]=$'\C-
[OF' [F1]=$'\C-
[OP' [F10]=$'\C-
[[21~' [F11]=$'\C-
[[23~' [F12]=$'\C-
[[24~' [F13]=$'\C-
[[1;2P' [F14]=$'\C-
[[1;2Q' [F15]=$'\C-
[[1;2R' [F16]=$'\C-
[[1;2S' [F17]=$'\C-
[[15;2~' [F18]=$'\C-
[[17;2~' [F19]=$'\C-
[[18;2~' [F2]=$'\C-
[OQ' [F20]=$'\C-
[[19;2~' [F3]=$'\C-
[OR' [F4]=$'\C-
[OS' [F5]=$'\C-
[[15~' [F6]=$'\C-
[[17~' [F7]=$'\C-
[[18~' [F8]=$'\C-
[[19~' [F9]=$'\C-
[[20~' [Home]=$'\C-
[OH' [Insert]=$'\C-
[[2~' [Left]=$'\C-
[OD' [PageDown]=$'\C-
[[6~' [PageUp]=$'\C-
[[5~' [Right]=$'\C-
[OC' [Up]=$'\C-[OA' )
keymaps
mailpath=(  )
manpath=(  )
module_path=( /usr/lib/
zsh/5.9 )
```

```
modules
nameddirs
options
parameters
patchars
path=( /usr/local/bin /
System/Cryptexes/App/usr/
bin /usr/bin /bin /usr/
sbin /sbin /var/run/
com.apple.security.crypte
xd/codex.system/
bootstrap/usr/local/bin /
var/run/
com.apple.security.crypte
xd/codex.system/
bootstrap/usr/bin /var/
run/
com.apple.security.crypte
xd/codex.system/
bootstrap/usr/
appleinternal/bin )
pipestatus=( 0 )
precmd_functions=( update
_terminal_cwd )
prompt='%n@%m %1~ %# '
psvar=(   )
reswords
saliases
signals=( EXIT HUP INT
QUIT ILL TRAP ABRT EMT
FPE KILL BUS SEGV SYS
PIPE ALRM TERM URG STOP
TSTP CONT CHLD TTIN TTOU
IO XCPU XFSZ VTALRM PROF
WINCH INFO USR1 USR2 ZERR
DEBUG )
status=0
termcap
terminfo
```

```
userdirs
usergroups
watch
widgets
zle_bracketed_paste=( $'\
C-[[?2004h' $'\C-[[?
2004l' )
zsh_eval_context=( toplev
el )
zsh_scheduled_events
zshexit_functions=( shell
_session_update )

T
-L$o-
t
```