PERK PALOOZA

PRODUCT REQUIREMENTS DOCUMENT

Developer handoff • Version 1.0 • 19 October 2026

Product promise: Give money with a clear purpose. The recipient can use the card only at an approved business or category, and the giver receives confirmation when it is redeemed.

Document Control

Product name	Perk Palooza
Document	Product Requirements Document (PRD)
Version / date	1.0 / 19 October 2026
Primary audience	Product, UI/UX, frontend, backend, QA, operations and business teams
Product type	Purpose-restricted digital and physical spending card platform
Payment provider	Paystack (giver checkout/funding)
Status	Draft for developer review; unresolved policy decisions are listed at the end

1. Executive Summary

Perk Palooza helps a person send money for a specific errand without handing over unrestricted cash. A giver creates and funds a purpose-restricted card, chooses its value and where it can be used, then sends it to a recipient by WhatsApp, email or physical delivery. The recipient does not need a Perk Palooza account in Version 1. An approved business validates the card before completing the purchase. On successful redemption, the card is marked used, the giver's committed wallet value is debited, the business's float ledger is updated, and the giver is notified.

The platform is built around purpose, control and transparency. It is not a general-purpose payment card and must not be redeemable at unapproved businesses or outside its configured restriction.

2. Problem Statement

Cash and bank transfers make it difficult for a giver to confirm that money sent for an errand was spent as intended. This creates uncertainty, extra follow-up, requests for receipts and friction between the giver and recipient. Businesses also need a fast way to distinguish valid cards from expired, already-used or fraudulent codes, with a clear route for disputes.

3. Product Goals

- Let givers create a card for a specific amount and purpose with a clear business or category restriction.
- Make card delivery and redemption simple enough for a recipient who has no account or app.
- Ensure a card can be redeemed only once, within its validity period and approved restriction.
- Give givers a clear view of available, committed, redeemed, cancelled and expired/locked value.
- Give onboarded businesses a fast validation flow, float visibility and redemption history.
- Give operations a traceable way to vet businesses, monitor float levels, handle disputes and manage exceptions.

4. Non-Goals for Version 1

- Self-service business registration or onboarding.
- Recipient accounts or a dedicated recipient app.
- Reloading or topping up an already-issued card; a new errand requires a new card.

- Using one card across multiple businesses or multiple categories. A card is restricted to one selected business OR one selected category.
- Unrestricted cash withdrawal from a card.
- Real-time individual settlement to a business for every redemption; the operating model uses a business float that is replenished periodically.

5. Users and Roles

Role	Responsibilities
Giver	Creates an account, funds a card, chooses amount/purpose/restriction/delivery, monitors the wallet and cards, and receives redemption notifications.
Recipient	Receives a digital or physical card and presents it at the approved business. No account is required. Physical cards must be activated by the recipient before use.
Business operator	A company-vetted business user who signs in to the business dashboard, validates cards, redeems eligible cards, reviews float/history and reports issues.
Platform operations/admin	Internal operational role implied by the onboarding and float model. Vets businesses, configures business accounts, manages float, reviews reports/disputes, and pauses or removes businesses. Detailed admin permissions require confirmation.

6. Core Product Concepts

6.1 Purpose-restricted card

Each card has a unique code, face value, purpose/description, restriction type, allowed business or category, issue time, expiry time, delivery method and lifecycle status. The restriction is enforced by the backend during redemption; displaying it on screen is not sufficient.

6.2 Giver wallet and committed value

The giver pays one combined checkout amount consisting of card face value, Paystack processing fee and platform fee. The card face value is represented in the giver's wallet as committed/unspent value until redemption. On redemption, the corresponding value leaves the giver's wallet. The interface and ledger must distinguish spendable wallet balance from value committed to issued cards.

6.3 Business float

The platform/company maintains a working float for each onboarded business. Redemptions draw down the business float ledger. Operations monitors balances and replenishes the float periodically. The business receives the full face value of a valid redemption; no platform fee is deducted from the business. If a valid card is presented when the float is depleted, the stated product rule is to allow the sale and record a temporary float overdraft for settlement at the next top-up.

6.4 Cashback

The source concept includes a small cashback for the recipient on redemption. The amount/rate, funding source, payout destination, eligibility, and whether a recipient needs to provide contact/payment details are not yet specified. Treat cashback as a configurable rule that must not be enabled in production until these decisions are approved.

7. Primary User Journeys

7.1 Giver: create and fund a digital card

1. Giver signs in or creates an account.
2. Giver opens Create Card and enters the card value and purpose/description.
3. Giver chooses exactly one restriction: a specific approved business OR an approved business category.
4. Giver selects delivery method: WhatsApp or email, and provides the recipient destination. Physical delivery is handled through the separate physical-card flow.
5. System calculates and displays the face value, Paystack processing fee, platform fee and total payable before confirmation.
6. Giver completes checkout through Paystack. Backend verifies payment status through a trusted server-side confirmation/webhook; the client redirect alone must not be treated as proof of payment.
7. After confirmed payment, the system creates the card, records the committed value and generates a unique code.
8. System sends the card details and usage restriction through the selected channel and shows the card in the giver dashboard.

7.2 Recipient: use a digital card

9. Recipient receives the card and its purpose, face value, expiry and allowed business/category details.
10. Recipient visits an eligible onboarded business and presents the code or digital card.
11. Business operator signs in and enters or scans the code.
12. System validates the card's existence, status, expiry, restriction, and whether it has already been redeemed.
13. If valid, business confirms redemption before handing over goods/services.
14. System atomically marks the card redeemed, posts the ledger entries, updates business float and sends a redemption notification to the giver.
15. The business sees the redemption confirmation and updated float/history.

7.3 Giver: cancel a card before redemption

16. Giver opens an issued card that has not been redeemed and selects Cancel.
17. System confirms the card is eligible for cancellation and asks the giver to confirm.
18. System invalidates the code and returns the card face value to the giver's available wallet balance. The original source rule says cancellation before redemption is refunded to the wallet, not locked.
19. System records the cancellation and notifies the giver. Any platform or payment processing fee refund treatment remains a policy decision.

7.4 Physical card: delivery and activation

20. Giver chooses physical delivery and supplies the recipient and shipping details.
21. System creates the physical card in an inactive state; it must not be redeemable during shipping.
22. Recipient receives the card and completes the activation flow using the activation method defined by the product team.
23. System marks the card active only after successful activation, then makes it eligible for normal redemption checks.
24. If the physical card is lost before activation, the giver can report it lost; system permanently cancels the original code and issues a replacement with the same amount and restrictions.

The exact activation method, shipping integrations, replacement limits and proof-of-possession checks are open implementation decisions.

8. Functional Requirements

ID	Requirement	Priority / Notes
FR-01	Giver authentication The system shall support giver account creation, login, logout and account recovery.	Must
FR-02	Wallet balance The dashboard shall distinguish available balance, value committed to active cards, redeemed value and locked expired value.	Must
FR-03	Card creation The giver shall set amount, purpose/description, restriction type, restriction target, expiry and delivery method.	Must
FR-04	Single restriction Each card shall be restricted to one approved business or one approved category, never both or multiple targets in Version 1.	Must
FR-05	Checkout breakdown Before payment, show face value, Paystack fee, platform fee and total charge.	Must
FR-06	Paystack payment Create cards only after verified payment success; handle pending, failed, cancelled and duplicate webhook events safely.	Must
FR-07	Card code Generate a unique, sufficiently unpredictable code; never expose internal database IDs as redeemable codes.	Must
FR-08	Card delivery Send digital card details via WhatsApp or email and show delivery status where supported.	Must
FR-09	Card dashboard Show cards with value, restriction, created/expiry dates, delivery and lifecycle status.	Must
FR-10	Redemption notification Notify giver after successful redemption and include card, business, amount and timestamp.	Must
FR-11	Expiry Expire cards at the configured expiry time. An unused expired card becomes visible as locked value and is not withdrawable or reusable.	Must
FR-12	Pre-redemption cancellation Allow eligible unredeemed cards to be cancelled and face value returned to available wallet balance.	Must
FR-13	Physical-card activation Keep physical cards inactive until recipient activation is confirmed.	Must for physical-card launch
FR-14	Business authentication Provide separate business login and	Must

	secure redemption authorization.	
FR-15	Code validation Allow code entry and, where supported, scanning; return a clear valid/invalid reason without exposing sensitive data.	Must
FR-16	Atomic redemption A valid card must be redeemed only once, even if two requests arrive concurrently.	Must
FR-17	Business float dashboard Show current float, initial/total float provided, total redeemed, adjustments/overdrafts and transaction history.	Must
FR-18	Float alerts/top-up request Warn operations/business when float approaches a configured threshold and allow a business to request a top-up.	Must
FR-19	Failed validation report Allow business operators to submit a failed-card report with code/reference, timestamp and reason.	Must
FR-20	Business onboarding Only internal operations can create/approve business accounts; record vetting and go-live status.	Must
FR-21	Business pause/removal Allow operations to pause/remove a business, stop new redemptions there and resolve affected outstanding cards according to an approved policy.	Must
FR-22	Audit trail Record payment events, card state changes, activation, redemptions, cancellations, expiry, float changes, top-ups and dispute actions.	Must
FR-23	Cashback Support cashback only after rate, funding, eligibility and payout mechanism are approved.	Pending policy
FR-24	Admin operations Provide controlled internal tools for business management, float oversight and dispute review.	Required capability; scope to be finalized

9. Card Lifecycle and Statuses

The backend must be the source of truth for card state. A suggested lifecycle is below; developers should implement explicit transition rules rather than allowing arbitrary status changes.

- Pending payment: checkout started but payment has not been verified.
- Inactive: physical card created but not activated.
- Active: eligible for validation until expiry or another terminal event.
- Redeeming: optional short-lived internal lock while a redemption request is being processed.
- Redeemed: successfully used; terminal state.
- Cancelled: cancelled by the giver before redemption; code permanently invalid.
- Expired/locked: expiry passed without redemption; face value remains visible but is not withdrawable or reusable under the source rules.

- Lost/replaced: original physical card invalidated and replacement linked for audit purposes.

10. Business Rules

25. A card can only be redeemed at the exact approved business or within the selected approved category.
26. A card can only be redeemed once.
27. A card must be active, unexpired and unpaid/unused state must be verified server-side before redemption.
28. Digital cards become usable after successful payment confirmation and creation.
29. Physical cards remain inactive until recipient activation.
30. The giver pays the face value plus Paystack processing fee plus platform fee in one checkout.
31. The business receives the full card face value; fees are not deducted from the business.
32. The giver's wallet value is debited at redemption, not at card issuance. Issuance commits the value.
33. Unused cards that expire become locked and cannot be withdrawn or reused under the current product concept.
34. A card cancelled by the giver before redemption returns its face value to available wallet balance.
35. A redemption already in progress at the exact expiry boundary should receive a short grace window. The duration and locking semantics must be configured and approved.
36. If a valid card is presented while a business float is depleted, the source concept requires the sale to proceed and the gap to be recorded as a temporary overdraft, settled at the next top-up.
37. Businesses are vetted and onboarded by the platform; self-service business signup is excluded from Version 1.
38. If a business is paused or removed, new redemptions must stop. Existing cards must follow an approved redirect/cancel/refund policy; never silently redirect a restricted card to a different business.

11. Edge Cases and Expected Handling

Scenario	Expected handling
Payment succeeds but browser/app does not return	Use server-side payment verification/webhook and idempotency; allow the giver to refresh status without paying twice.
Duplicate Paystack webhook	Process idempotently; do not create duplicate cards or ledger entries.
Payment pending or failed	Do not issue a usable card until payment is confirmed. Show the payment state and recovery path.
Two redemption attempts at once	Use an atomic state transition/transaction so only one request succeeds; the other receives "already redeemed/in progress."
Card expired during checkout at the business	Apply the configured short grace window only if redemption began before expiry; define exact start/end rules before launch.
Business float is zero or insufficient	Allow valid sale per the source concept and record a controlled overdraft; alert operations immediately.
Physical card lost before activation	Invalidate original code permanently and allow authorized replacement with same amount/restrictions.
Card code invalid or already used	Do not debit giver or float; show safe reason and allow business to report issue.
Dispute after redemption	Preserve code/reference, business, timestamp, status transition and notification audit trail for operations review.
Business suspended/removed with active cards	Stop new redemption at that business and use approved resolution policy; do not redirect without respecting original restriction and giver consent/policy.
Notification provider fails	Persist the event and retry delivery; dashboard state and ledger must remain correct even if notification delivery is delayed.
Partial purchase / spending less than face value	The source document does not define partial redemption,

	change, or remaining value; block or support only after this policy is decided.

12. Wallet, Ledger and Float Accounting

Because this product moves value between ledgers, balances should be derived from auditable ledger entries rather than editable balance fields alone. Every financial event should have a unique reference, timestamp, amount, currency, source, destination, status and link to the related card/payment/business.

- Giver ledger concepts: wallet funding, available balance, card-value commitment, redemption debit, cancellation release, locked expired value, fees and any approved cashback entry.
- Business float ledger concepts: opening float, redemption drawdown, top-up, approved adjustment, temporary overdraft and settlement of overdraft.
- Do not treat a card code as money itself; it is a reference that authorizes a constrained redemption.
- Ledger entries should be immutable. Corrections should be represented by reversing/adjustment entries with an audit reason.
- Currency is assumed to be NGN based on the source examples; confirm whether multiple currencies are ever required.
- The source describes a wallet but does not fully specify whether it is a regulated stored-value wallet, an internal accounting balance or a bank-held safeguarded balance. The implementation and operational model must be confirmed before production.

13. Notifications and Messaging

Event	Recipient	Minimum content
Card issued	Recipient by WhatsApp/email; giver dashboard	Purpose, value, restriction, expiry, code/card link and redemption instructions.
Card redeemed	Giver	Card reference, business, amount, timestamp and status.
Card expired unused	Giver	Card reference, value now locked, expiry date and explanation.
Card cancelled	Giver	Confirmation that code is invalid and face value returned to available balance.
Physical card activation	Giver and/or recipient as defined	Activation confirmation and current status.
Business float low	Business and operations	Current float, threshold and top-up/request action.
Redemption failed	Business; operations if reported	Safe failure reason and report/reference path.
Payment status	Giver	Pending, successful or failed status; never expose payment secrets.

14. Security, Privacy and Reliability Requirements

- Use role-based access control: giver data, business data and internal operations tools must be separated.
- Protect card codes as bearer credentials: use high-entropy codes, rate-limit attempts, avoid logging full codes unnecessarily, and provide revocation for eligible states.
- Store passwords securely using an industry-standard password hashing mechanism; never store plaintext passwords. Prefer stronger authentication controls for business operators and administrators.

- Verify payment notifications server-side and validate webhook signatures; use idempotency for payments and redemption requests.
- Enforce redemption rules on the backend; never rely on UI-only checks.
- Use HTTPS for all network traffic and protect sensitive personal and payment data in storage and logs.
- Record audit events for administrative actions, business float adjustments, card lifecycle changes and dispute resolution.
- Use consistent timestamps and an agreed timezone strategy; display local times clearly.
- Design notifications and payment/redemption actions for retries and temporary network failure without duplicate financial effects.
- Define backup, recovery, monitoring, alerting and incident response procedures before production launch.

15. Analytics and Operational Reporting

- Cards created, delivered, activated, redeemed, cancelled and expired.
- Redemption success/failure rates and common validation failure reasons.
- Total card value issued, committed, redeemed and locked.
- Giver wallet funding and fee totals.
- Business float balance, redemption drawdown, top-up history, overdraft exposure and low-float incidents.
- Delivery and notification success/failure rates.
- Dispute count, resolution time and outcomes.

These are proposed operational metrics derived from the product workflows; metric definitions, retention periods and reporting permissions should be confirmed.

16. Acceptance Criteria for Key Flows

Flow	Acceptance condition
Card issuance	A card cannot become usable until payment is verified; it has a unique code, correct amount/restriction/expiry and an audit record.
Restriction enforcement	A card restricted to Business A is rejected at Business B. A category-restricted card is accepted only at a vetted business in that category.
Successful redemption	One valid redemption produces exactly one redeemed state, one giver wallet debit, one business float drawdown, one audit event and a notification event.
Duplicate redemption	Repeated or concurrent redemption requests cannot cause a second debit or second float drawdown.
Expired card	An expired unused card cannot be redeemed and its value is visible as locked, not available for withdrawal or reuse.
Cancellation	An eligible unredeemed card is invalidated and its face value is released to the giver's available wallet balance.
Physical activation	A physical card cannot pass validation before successful activation.
Float shortage	A valid redemption is handled according to the approved overdraft rule and the overdraft is visible to operations.
Business dispute	A business can submit a failed validation report and operations can retrieve the related audit trail.
Payment retry	A duplicated payment webhook or client retry cannot create duplicate cards or duplicate wallet credits.

17. Brand and UI Direction

Use the selected Option 1 palette as the starting point for the product UI. The palette is a design direction, not a substitute for contrast testing.

Token	HEX	Use
Primary deep teal	#0F766E	Primary actions, key brand moments
Mint accent	#14B8A6	Highlights and secondary emphasis
Pale mint	#DDF7F0	Soft backgrounds and selected states
Off-white	#F8FAFC	Main app background
Charcoal	#172B2A	Primary text

- Use clear labels and icons alongside status colours; never communicate status through colour alone.
- Target WCAG AA contrast for text and controls.
- The UI should prioritize trust, control, transparency and a quick redemption process.
- The stylized “P” logo concept should work in app-icon, horizontal, stacked and single-colour formats.

18. Suggested Technical Components (Implementation-Neutral)

- Authentication and role/permission service.
- Giver profile and wallet ledger service.
- Card creation, code generation, lifecycle and expiry service.
- Paystack payment initiation and verified webhook handler.
- Delivery and notification service for WhatsApp/email and in-app notifications.
- Business account, vetting status and approved category/business registry.
- Redemption validation and atomic redemption processor.
- Business float ledger and low-balance/top-up request workflow.
- Operations/admin console for onboarding, float oversight, business pause/removal and dispute review.
- Audit logging, monitoring and reporting.

These are logical components, not a mandated architecture or technology stack. Developers should propose the deployment architecture, data model, API contracts and integration choices.

19. Open Decisions Before Development Is Finalized

Decision	Question to resolve
Decision	**Question to resolve**
OD-01 — Partial redemption	Can a card be used for a purchase below its face value? What happens to the remainder? Can multiple partial purchases be made?
OD-02 — Card expiry	What is the default validity period, who can choose it, and what exact grace window applies to redemption already in progress?
OD-03 — Locked expired value	How long does it remain locked? Can operations unlock it under an approved exception? Are there any legal/accounting rules for eventual treatment?
OD-04 — Cashback	Rate/amount, who funds it, when it is credited, whether it is wallet credit or cash, and recipient data requirements.
OD-05 — Fees	Platform fee amount/formula, Paystack fee calculation, fee refund treatment for cancellation, and whether fees vary by card value.

OD-06 — Wallet funding/withdrawal	Can givers add funds separately to a wallet? Can they withdraw available wallet balance? What exactly happens to wallet funds before redemption?
OD-07 — Payment and safeguarding model	Where funds are held, who legally holds them, reconciliation process, and compliance requirements for a Nigerian launch.
OD-08 — Physical card scope	Is physical-card issuance included in the first release? Shipping provider, cost, delivery tracking, activation verification and replacement limits.
OD-09 — Recipient delivery	WhatsApp/email provider, recipient contact validation, retry behavior, and whether a card can be resent or its code rotated.
OD-10 — Redemption amount	Does the business redeem the full card face value or enter an actual purchase amount? How is change handled?
OD-11 — Business float	How are initial float sizes determined, who approves top-ups, what are thresholds, and what are the limits/approval rules for overdraft?
OD-12 — Business settlement	The source says the business receives full face value and uses a platform float; define the actual accounting, settlement and reconciliation process.
OD-13 — Business/category changes	What happens to active cards when a business changes category, is paused, or is removed? Should affected cards be cancelled/refunded or handled by another policy?
OD-14 — Admin roles	Define internal roles, approval limits, separation of duties and audit requirements for float adjustments and disputes.
OD-15 — Currency and launch geography	NGN is assumed from the source example; confirm currency, supported geography and any future multi-currency need.
OD-16 — Notifications	Which channels are mandatory for launch (email, WhatsApp, SMS, in-app), and which events require immediate delivery?

20. Version 1 Release Recommendation

For a controlled first release, prioritize giver account and wallet visibility, card creation, verified Paystack checkout, digital delivery, restriction enforcement, business login, code validation, atomic redemption, giver notifications, business float/history, and internal business onboarding. Physical cards, cashback and advanced admin workflows should only be included in the launch scope once their open decisions are resolved and tested.

21. Definition of Done

- Requirements and open decisions relevant to the release have an approved owner and documented answer.
- Core user journeys work in test and production-like environments.
- Payment and redemption flows are idempotent and covered by automated tests.
- Access control, expiry, cancellation, restriction and duplicate-redemption tests pass.
- Wallet and float ledgers reconcile for successful, failed, cancelled and reversed scenarios.
- Notification failure does not corrupt card, wallet or float state.
- Operations can investigate a reported issue using the audit trail.
- UI states include loading, empty, success, failure, pending and unavailable cases.
- Product, engineering, QA and operations approve the release checklist.

Appendix A. Example Scenario

A giver creates a ₦50,000 card for school books and restricts it to one approved bookshop. The checkout shows ₦50,000 face value plus the Paystack fee and platform fee, then the giver completes payment. Once payment is verified, the card is created and sent by WhatsApp or email. The ₦50,000 is shown as committed in the giver's

wallet. At the bookshop, the operator validates the code. If valid and unexpired, the system marks it redeemed once, debits the committed value, records the redemption against the bookshop's float, and notifies the giver. If the card expires unused, the value becomes locked according to the product's stated rule.

Appendix B. Glossary

Giver: The person who funds and configures a card.

Recipient: The person who receives and presents the card.

Business: A vetted participating merchant that accepts cards.

Face value: The amount available to be redeemed on a card.

Committed value: Giver wallet value reserved for an issued, not-yet-redeemed card.

Float: Working balance the platform maintains for a participating business.

Redemption: The successful validation and use of a card at an approved business.

Locked value: Value from a card that expired unused; visible but not withdrawable or reusable under the current rules.