

Parallel Python

Home ▸ Documents

8+1

Home

Forums

Documents

Examples

FAQ

Downloads

Links

Blogs

Contact Us

Shell calculator for developers.

Parallel Python documentation



Module API

[Quick start guide, SMP](#)

[Quick start guide, clusters](#)

[Quick start guide, clusters with auto-discovery](#)

[Advanced guide, clusters](#)

[Command line arguments, ppserver.py](#)

[Security and secret key](#)

[ppserver.py stats and PID file example](#)

[PP FAQ](#)

pp 1.6.3 module API

class **Server**

Parallel Python SMP execution server class

Methods defined here:

__init__(self, ncpus='autodetect', ppservers=(), secret=None, restart=False, proto=2, socket_timeout=3600)
Creates **Server** instance

ncpus - the number of worker processes to start on the local computer, if parameter is omitted it will be set to the number of processors in the system
ppservers - list of active parallel python execution servers to connect with
secret - passphrase for network connections, if omitted a default passphrase will be used. It's highly recommended to use a custom passphrase for all network connections.
restart - whether to restart worker process after each task completion
proto - protocol number for pickle module
socket_timeout - socket timeout in seconds which is also the maximum time a remote job could be executed. Increase this value if you have long running jobs or decrease if connectivity to remote ppservers is often lost.

With ncpus = 1 all tasks are executed consequently
For the best performance either use the default "autodetect" value or set ncpus to the total number of processors in the system

destroy(self)
Kills ppworkers and closes open files

get_active_nodes(self)
Returns active nodes as a dictionary
[keys - nodes, values - ncpus]

get_ncpus(self)

Returns the number of local worker processes (ppworkers)

get_stats(self)

Returns job execution statistics as a dictionary

print_stats(self)

Prints job execution statistics. Useful for benchmarking on clusters

set_ncpus(self, ncpus='autodetect')

Sets the number of local worker processes (ppworkers)

ncpus - the number of worker processes, if parameter is omitted it will be set to the number of processors in the system

submit(self, func, args=(), depfuncs=(), modules=(), callback=None, callbackargs=(), group='default', globals=None)

Submits function to the execution queue

func - function to be executed

args - tuple with arguments of the 'func'

depfuncs - tuple with functions which might be called from 'func'

modules - tuple with module names to import

callback - callback function which will be called with argument

list equal to callbackargs+(result,)

as soon as calculation is done

callbackargs - additional arguments for callback function

group - job group, is used when **wait**(group) is called to wait for

jobs in a given group to finish

globals - dictionary from which all modules, functions and classes

will be imported, for instance: globals=globals()

wait(self, group=None)

Waits for all jobs in a given group to finish.

If group is omitted waits for all jobs to finish

default_port = 60000**default_secret = 'epo20pdosl;dksldkmm'**class **Template****Template** class

Methods defined here:

__init__(self, job_server, func, depfuncs=(), modules=(), callback=None, callbackargs=(), group='default', globals=None)Creates **Template** instance

jobs_server - pp server for submitting jobs

func - function to be executed

depfuncs - tuple with functions which might be called from 'func'

modules - tuple with module names to import

callback - callback function which will be called with argument

list equal to callbackargs+(result,)

as soon as calculation is done

callbackargs - additional arguments for callback function

group - job group, is used when wait(group) is called to wait for

jobs in a given group to finish

globals - dictionary from which all modules, functions and classes

will be imported, for instance: globals=globals()

submit(self, *args)

Submits function with *arg arguments to the execution queue

Data

copyright = 'Copyright (c) 2005-2012 Vitalii Vanovschi. All rights reserved'
version = '1.6.3'

Quick start guide, SMP

1) Import pp module:

```
import pp
```

2) Start pp execution server with the number of workers set to the number of processors in the system

```
job_server = pp.Server()
```

3) Submit all the tasks for parallel execution:

```
f1 = job_server.submit(func1, args1, depfuncs1, modules1)
```

```
f2 = job_server.submit(func1, args2, depfuncs1, modules1)
```

```
f3 = job_server.submit(func2, args3, depfuncs2, modules2)
```

...etc...

4) Retrieve the results as needed:

```
r1 = f1()
```

```
r2 = f2()
```

```
r3 = f3()
```

...etc...

To find out how to achieve efficient parallelization with pp please take a look at [examples](#)

Quick start guide, clusters

On the nodes

1) Start parallel python execution server on all your remote computational nodes:

```
node-1> ./ppserver.py
```

```
node-2> ./ppserver.py
```

```
node-3> ./ppserver.py
```

On the client

2) Import pp module:

```
import pp
```

3) Create a list of all the nodes in your cluster (computers where you've run ppserver.py)

```
ppservers=("node-1", "node-2", "node-3")
```

4) Start pp execution server with the number of workers set to the number of processors in the system and list of pp servers to connect with :

```
job_server = pp.Server(ppservers=ppservers)
```

5) Submit all the tasks for parallel execution:

```
f1 = job_server.submit(func1, args1, depfuncs1, modules1)
```

```
f2 = job_server.submit(func1, args2, depfuncs1, modules1)
f3 = job_server.submit(func2, args3, depfuncs2, modules2)
...etc...
```

6) Retrieve the results as needed:

```
r1 = f1()
r2 = f2()
r3 = f3()
...etc...
```

To find out how to achieve efficient parallelization with pp please take a look at [examples](#)

Quick start guide, clusters with autodiscovery

On the nodes

1) Start parallel python execution server on all your remote computational nodes:

```
node-1> ./ppserver.py -a
node-2> ./ppserver.py -a
node-3> ./ppserver.py -a
```

On the client

2) Import pp module:

```
import pp
```

3) Set ppservers list to auto-discovery:

```
ppservers=("",)
```

4) Start pp execution server with the number of workers set to the number of processors in the system and list of ppservers to connect with :

```
job_server = pp.Server(ppservers=ppservers)
```

5) Submit all the tasks for parallel execution:

```
f1 = job_server.submit(func1, args1, depfuncs1, modules1)
f2 = job_server.submit(func1, args2, depfuncs1, modules1)
f3 = job_server.submit(func2, args3, depfuncs2, modules2)
...etc...
```

6) Retrieve the results as needed:

```
r1 = f1()
r2 = f2()
r3 = f3()
...etc...
```

To find out how to achieve efficient parallelization with pp please take a look at [examples](#)

Advanced guide, clusters

On the nodes

1) Start parallel python execution server on all your remote computational nodes (listen to a given port 35000, and local network interface only, accept only connections which know correct secret):

```
node-1> ./ppserver.py -p 35000 -i 192.168.0.101 -s "mysecret"
```

```
node-2> ./ppserver.py -p 35000 -i 192.168.0.102 -s "mysecret"
```

```
node-3> ./ppserver.py -p 35000 -i 192.168.0.103 -s "mysecret"
```

On the client

2) Import pp module:

```
import pp
```

3) Create a list of all the nodes in your cluster (computers where you've run ppserver.py)

```
ppservers=("node-1:35000", "node-2:35000", "node-3:35000")
```

4) Start pp execution server with the number of workers set to the number of processors in the system, list of ppservers to connect with and secret key to authorize the connection:

```
job_server = pp.Server(ppservers=ppservers, secret="mysecret")
```

5) Submit all the tasks for parallel execution:

```
f1 = job_server.submit(func1, args1, depfuncs1, modules1)
```

```
f2 = job_server.submit(func1, args2, depfuncs1, modules1)
```

```
f3 = job_server.submit(func2, args3, depfuncs2, modules2)
```

```
...etc...
```

6) Retrieve the results as needed:

```
r1 = f1()
```

```
r2 = f2()
```

```
r3 = f3()
```

```
...etc...
```

7) Print the execution statistics:

```
job_server.print_stats()
```

To find out how to achieve efficient parallelization with pp please take a look at [examples](#)

Command line options, ppserver.py

Usage: ppserver.py [-hda] [-i interface] [-b broadcast] [-p port] [-w nworkers] [-s secret] [-t seconds]

Options:

```
-h          : this help message
-d          : debug
-a          : enable auto-discovery service
-i interface: interface to listen
-b broadcast: broadcast address for auto-discovery service
-p port     : port to listen
-w nworkers : number of workers to start
-s secret   : secret for authentication
-t seconds  : timeout to exit if no connections with clients exist
-k seconds  : socket timeout in seconds
-P pid_file : file to write PID to
```

Security and secret key

Due to the security concerns it is highly recommended to run `ppserver.py` with a non-trivial secret key (`-s` command line argument) which should be paired with the matching `secret` keyword of PP Server class constructor. Since PP 1.5.3 it is possible to set secret key by assigning `pp_secret` variable in the configuration file `.pythonrc.py` which should be located in the user home directory (please make this file readable and writable only by user). The key set in `.pythonrc.py` could be overridden by command line argument (for `ppserver.py`) and `secret` keyword (for PP Server class constructor).

ppserver.py stats and PID file example

To print job execution statistics for `ppserver.py` send a `SIGUSR1` signal to its main process.

For instance on UNIX platform following commands will start a server and print its stats:

```
ppserver.py -P /tmp/ppserver.pid
```

```
kill -s SIGUSR1 `cat /tmp/ppserver.pid`
```



By using this website, you signify your acceptance of [Terms and Conditions](#) and [Privacy Policy](#).

Parallel Python Solutions | Parallel Python Forums | Parallel Python Community

Parallel Python © 2005 - 2014 Vitalii Vanovschi. All rights reserved