COMP4097 Mobile Computing Assignment 2

Jonatan Juhas (19502966)

November 20, 2019

1. a) As the hamming code (7 4) requires a message length of 4, we split it into 2 parts: 1000 and 1010.

The first part (assuming the pattern M7 M6 M5 P4 M3 P2 P1) is:

The second part is:

So the message transmitted to Station B will be 1001011 1010010

1.b) We receive 2 messages: 1011011 and 1011010. For the first message we check all parity bits:

P1:
$$1011 \rightarrow 1 + 0 + 1 + 1 = 3$$
 X
P2: $1001 \rightarrow 1 + 0 + 0 + 1 = 2$ \(\sqrt{}

P4:
$$1101 \rightarrow 1 + 1 + 0 + 1 = 3$$
 X

Correcting the message with P1 + P4 = 5 to 1001011.

We check the parity bits in the second message:

P1: $0011 \rightarrow 0 + 0 + 1 + 1 = 2$

P2: $1001 \rightarrow 1 + 0 + 0 + 1 = 2$

P4: $1101 \rightarrow 1 + 1 + 0 + 1 = 3$ X

Correcting the message with P4 = 4 to 1010010.

1.c) We again receive 2 messages after the spike: 1100111 and 1011010. The first message check results in:

P1: $1101 \rightarrow 1 + 1 + 0 + 1 = 3$

P2: $1111 \rightarrow 1 + 1 + 1 + 1 = 4$

P4: $0011 \rightarrow 0 + 0 + 1 + 1 = 2$

Correcting the message with P1 = 1 to 1100110.

The second message check:

P1: $0011 \rightarrow 0 + 0 + 1 + 1 = 2$

P2: $1001 \rightarrow 1 + 0 + 0 + 1 = 2$

P4: $1101 \rightarrow 1 + 1 + 0 + 1 = 3$ X

Correcting the message with P4 = 4 to 1010010.

The channel seems to be quite unreliable but we manage to fix all errors thanks to the hamming code encoding.

2. a) The equation for calculating the rate can be summarized as:

$$\frac{\text{payload bytes} * 8 * 1000}{\# \text{ slots} * 0.625 * 1000}$$

An ACL Link (Asynchronous Connection-Less) using DM5 and maximum number of bytes can achieve a rate of $\frac{224*8*1000}{5*0.625*1000} \approx 477.8kb/s$ as indicated in the table under asymmetric rate.

The reverse connection rate uses DM1 so we adjust the number of payload bytes to 17 and and number of slots to 1 so we get $\frac{17*8*1000}{1*0.625*1000} \approx 108.8 kb/s$.

2. b) 2Mb = 2000kb so with a transfer speed of 477.8kbps we can transfer the image in $\approx 4.1s$.

2.c) Since the high quality stream requires a minimum transfer speed of 256kbps, which is below our theoretical maximum of 477.8kbps, the connection will be stable.

The "professional" grade mp3 transfer requires 512kbps transfer rate, which exceeds our limits. Certain packets will therefore come delayed or not at all which will result in stuttering in the audio.

- **2. d)** An SCO HV3 link only supports a maximum connection speed of 64kbps, which is way below our limit. Most packets will not arrive at the slave on time or at all and will be dropped. The listening experience will be drastically diminished.
- **3. a)** Given the frequency reuse of 7 and a semi-random distribution of the initial cell frequencies (2-4-6-3-5-7) we construct a hexagonal latice as shown in figure 1.




Figure 1: Suggested cell layout using frequency reuse of 7

The cell area can be calculated as $1.5\sqrt{3}R^2$. Since our radius is 1km for each cell, one cell covers the surface of $\approx 2.6km^2$. Our are consists of 23

segments which totals an area of $\approx 59.8 km^2$.

3. b)