

ICPC Lib

September 7, 2025

Contents

1 Strategy

1.1	Início (primeira 1h30)	1
1.2	Meio	2
1.3	Final (última 1h30)	2

2 binary_lifting.cpp

3 count_inversions_merge_sort.cpp

4 dsu.cpp

5 fft.cpp

6 Geometry

6.1	convex_hull.hpp	4
6.2	point.hpp	4
6.3	polygon.hpp	6
6.4	triangle.hpp	7

7 Graphs

7.1	2sat.cpp	7
7.2	bellman_ford.cpp	8
7.3	cycle_detection.cpp	9
7.4	dfs_toposort.cpp	9
7.5	dijkstra.cpp	9
7.6	dinic.cpp	10
7.7	floyd_warshall.cpp	12

7.8	kosaraju.cpp	12
7.9	lexicographical_minimal_toposort.cpp	13
7.10	tarjan.cpp	13

8 Number Theory

8.1	fastexp.cpp	14
8.2	spf.cpp	14

9 Range Queries

9.1	bit.cpp	14
9.2	segtree.cpp	15

10 Strings

10.1	rabin_karp.cpp	15
10.2	suffix_array.cpp	16
10.3	trie.cpp	17

11 template.cpp

12 Trees

12.1	centroid.cpp	18
12.2	hld.cpp	19
12.3	lca.cpp	20
12.4	path_queries.cpp	21

1 Strategy

1.1 Início (primeira 1h30)

- Ler questões

- Passar no máximo 10-15 min por questão
- Implementar apenas as fáceis
 - Priorizar primeiro aquelas que são simples e rápidas de implementar (em detrimento por ex. de uma aplicação trivial de um algoritmo longo, como uma SegTree ou fluxo)
- Fase mais individual
- Priorizar para implementação aquela pessoa que tem a ideia mais clara da solução

1.2 Meio

- Ler o restante da prova
- Olhar os standings para selecionar a próxima questão
- Analisar mais profundamente no papel para conseguir passar as médias/difíceis
- Evitar ficar três pessoas em uma mesma questão

1.3 Final (última 1h30)

- Foco do time todo em uma ou duas questões mais prováveis de passarem

2 binary_lifting.cpp

```
#include <bits/stdc++.h>
using namespace std;
```

```
const int N = 2e5, LOGN = 20;
int lift[LOGN + 1][N];
```

```
void binary_lifting(const vector<vector<int>> &forest){
    const int n = forest.size();
    vector<int> parent(n, -1);
    for (int u = 0; u < n; u++){
        for (int v: forest[u]){
            parent[v] = u;
        }
    }
}
```

```
for (int u = 0; u < n; u++){
    lift[0][u] = parent[u];
}
for (int k = 1; k <= LOGN; k++){
    for (int u = 0; u < n; u++){
        lift[k][u] = lift[k - 1][lift[k - 1][u]];
    }
}

int jump(int u, int k){
    for (int i = 0; i <= LOGN; i++){
        if ((k >> i) & 1){
            u = lift[i][u];
        }
    }
    return u;
}
```

3 count_inversions_merge_sort.cpp

```
#include <bits/stdc++.h>
using namespace std;
```

```
// sorts and returns count of inversions. Modifies original array!
int inversions(vector<int>& a, int l, int r){
    if (l == r) return 0;
    const int m = l + (r - l) / 2;
    int total = inversions(a, l, m) + inversions(a, m + 1, r);
    vector<int> left, right;
    for (int i = l; i <= m; i++) left.emplace_back(a[i]);
    for (int i = m + 1; i <= r; i++) right.emplace_back(a[i]);

    int idx = l;
    int pl = 0, pr = 0;
    while (pl < left.size() || pr < right.size()){
        // we only count the inversion pairs from the perspective of
        // the smaller
        // element on the right
        // 1 3 5 | 2 4
        // if right[pr] < left[pl] then it is smaller than
        // [left[pl]..left[|left|-1]]
        // so contributes for left-pl cross-inversions
        if (pr == right.size())
            a[idx++] = left[pl++];
        else if (pl == left.size())
            a[idx++] = right[pr++];
    }
}
```

```

        else {
            if (left[pl] < right[pr])
                a[idx++] = left[pl++];
            else {
                a[idx++] = right[pr++];
                total += left.size() - pl;
            }
        }
    }
    return total;
}

```

4 dsu.cpp

```

#include <bits/stdc++.h>
using namespace std;

struct DSU {
    vector<int> parent, sz;
    vector<vector<int>> elements;

    DSU(int n){
        parent.resize(n);
        iota(parent.begin(), parent.end(), 0);
        sz.assign(n, 1);
        elements.resize(n);
        for (int i = 0; i < n; i++){
            elements[i].emplace_back(i);
        }
    }

    int find(int x){
        if (parent[x] != x){
            parent[x] = find(parent[x]); // path-compression
        }
        return parent[x];
    }

    void unite(int x, int y){
        x = find(x);
        y = find(y);
        if (x == y){
            return;
        } else if (sz[x] > sz[y]) {
            swap(x, y);
        }
        sz[y] += sz[x];
    }
}

```

```

        for (int z: elements[x]){
            elements[y].emplace_back(z);
        }
        parent[x] = y;
    }
};

```

5 fft.cpp

```

// CODE TAKEN FROM CP-ALGORITHMS
#include <bits/stdc++.h>
using namespace std;

using cd = complex<double>;
const double PI = acos(-1);

void fft(vector<cd> & a, bool invert) {
    int n = a.size();

    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;

        if (i < j)
            swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            cd w(1);
            for (int j = 0; j < len / 2; j++) {
                cd u = a[i+j], v = a[i+j+len/2] * w;
                a[i+j] = u + v;
                a[i+j+len/2] = u - v;
                w *= wlen;
            }
        }
    }

    if (invert) {
        for (cd & x : a)
            x /= n;
    }
}

```

```

}

vector<int> multiply(vector<int> const& a, vector<int> const& b) {
    vector<cd> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    int n = 1;
    while (n < a.size() + b.size())
        n <= 1;
    fa.resize(n);
    fb.resize(n);

    fft(fa, false);
    fft(fb, false);
    for (int i = 0; i < n; i++)
        fa[i] *= fb[i];
    fft(fa, true);

    vector<int> result(n);
    for (int i = 0; i < n; i++)
        result[i] = round(fa[i].real());
    return result;
}

```

6 Geometry

6.1 convex_hull.hpp

```

#include "../point.hpp"
#include "../polygon.hpp"
#define i64 int64_t

// counterclockwise convex hull, can include collinear points or not
vector<pt> convex_hull(vector<pt> poly, bool INCLUDE_COLLINEAR){
    // choose bottommost point as pivot
    pt pivot = poly[0];
    const i64 n = poly.size();
    for (i64 i = 1; i < n; i++){
        if (poly[i].y < pivot.y || (poly[i].y == pivot.y && poly[i].x
            < pivot.x)){
            pivot = poly[i];
        }
    }
    sort(poly.begin(), poly.end(),
        [&pivot](pt p, pt q){return polarComp(pivot, p, q);});
    // since including collinear points, we want to privilege the
    // farthest collinear points
    // when coming back (e.g (0,0), (1,0), (2,0), (2,1), (2,2), (1,1))

```

```

if (INCLUDE_COLLINEAR){
    i64 i = n - 1;
    while (i > 0 && orientation(pivot, poly[i], poly.back()) == 0){
        i--;
    }
    reverse(poly.begin() + i + 1, poly.end());
}
vector<pt> hull = {pivot};
for (i64 i = 1; i < n; i++){
    while (
        hull.size() >= 2
        && (
            orientation(hull[hull.size() - 2], hull[hull.size() -
                1], poly[i]) == 1
            || (!INCLUDE_COLLINEAR && orientation(hull[hull.size()
                - 2], hull[hull.size() - 1], poly[i]) == 0)
        )
    ){
        // goes clockwise, break orientation
        hull.pop_back();
    }
    hull.emplace_back(poly[i]);
}
return hull;
}

```

6.2 point.hpp

```

#include <bits/stdc++.h>
using namespace std;

#define i64 int64_t

struct pt {
    i64 x, y;

    pt(i64 x, i64 y) : x(x), y(y) {}
    pt(const pt& p) : x(p.x), y(p.y) {}

    i64 cross(pt p){
        return x * p.y - y * p.x;
    }
    i64 dot(pt p){
        return x * p.x + y * p.y;
    }
    void operator=(const pt q){
        x = q.x;
        y = q.y;
    }
}

```

```

    }
};

pt operator-(pt p1, pt p2){
    return pt(p1.x - p2.x, p1.y - p2.y);
}
pt operator+(pt p1, pt p2){
    return pt(p1.x + p2.x, p1.y + p2.y);
}
pt operator*(pt p1, i64 k){
    return pt(k * p1.x, k * p1.y);
}
pt operator*(i64 k, pt p1){
    return pt(k * p1.x, k * p1.y);
}

i64 orientation(pt p, pt q, pt r){
    i64 o = (q - p).cross(r - p);
    if (o > 0){
        return -1; // counterclockwise
    } else if (o < 0){
        return 1; // clockwise
    } else {
        return 0; // collinear
    }
}

i64 ccw(pt p, pt q, pt r) { return orientation(p, q, r) < 0; }

bool is_collinear(pt p, pt q, pt r){
    return (q - p).cross(r - p) == 0;
}

// is p on segment q,r?
bool on_segment(pt p, pt q, pt r){
    // pqr is collinear
    // qp and pr have the same sign/orientation (as p in between q and r)
    return (
        is_collinear(p, q, r)
        && ((p - q).dot(r - p) >= 0)
    );
}

// counterclockwise polar sort
bool polarComp(pt pivot, pt p, pt q){

```

```

    auto d2 = [](pt a){
        return a.x * a.x + a.y * a.y;
    };
    i64 o = orientation(pivot, p, q);
    if (o == -1) return true;
    else if (o == 1) return false;
    else {
        // collinear => return closest point
        return d2(p - pivot) < d2(q - pivot);
    }
}

// line intersection
bool line_line_intersect(pt a, pt b, pt c, pt d){
    return (
        (b - a).cross(d - c) != 0
        || (b - a).cross(c - a) == 0
    ); // not parallel, or equal lines (ab||cd and abc collinear)
}

// line ab, segment cd
bool line_segment_intersect(pt a, pt b, pt c, pt d){
    // c and d are in different half-planes
    // ==> different orientations
    // OR any triple abc, abd is collinear
    return orientation(c, a, b) * orientation(d, a, b) != 1;
}

// https://cp-algorithms.com/geometry/check-segments-intersection.html
bool segment_segment_intersect(pt a, pt b, pt c, pt d){
    auto inter1d = [](i64 l1, i64 r1, i64 l2, i64 r2){
        if (l1 < r1) swap(l1, r1);
        if (l2 < r2) swap(l2, r2);
        return max(l1, l2) <= min(r1, r2);
    };
    if (orientation(a, b, c) == 0 && orientation(a, b, d) == 0){
        // all four are collinear
        // reduces to 1d interval intersection
        return inter1d(a.x, b.x, c.x, d.x) && inter1d(a.y, b.y, c.y, d.y);
    }
    return
        // different half-planes: line ab intersects segment cd
        (orientation(a, b, c) != orientation(a, b, d))
        // different half-planes: line cd intersects segment ab
        && (orientation(c, d, a) != orientation(c, d, b))
    ;
}

```

```

}

// horizontal ray from a, direction +-1, intersects segment cd?
// DOES include intersection at endpoints (cd) by default,
// verified by CSES "Point in Polygon"
bool horizontal_ray_segment_intersect(pt a, pt c, pt d, i64 direction
= 1){
    if (c.y <= a.y && a.y < d.y){ // different half-planes from ray,
        c below or at line, d above
        // now we need d in the same half-plane as the ray
        (considering line ac)
        // so the intersection happens on the ray and not on the other
        side
        if (direction == 1){
            return orientation(c, a, d) > 0;
        } else {
            return orientation(c, a, d) < 0;
        }
    } else if (d.y <= a.y && a.y < c.y){
        return horizontal_ray_segment_intersect(a, d, c, direction);
    }
    return false;
}

```

6.3 polygon.hpp

```

#include "../point.hpp"
#include "../triangle.hpp"

// shoelace formula
double area(vector<pt>& p){
    i64 a = 0;
    i64 n = p.size();
    for (i64 i = 0; i < n; i++){
        a += p[i].cross(p[(i + 1) % n]); // area of OP[i]P[i+1]
    }
    return (double)a / 2.0f;
}

// O(log n) check for boundary/inside convex polygon
// take the first pt (lexicographically) as reference (P0), and sort
// by polar order
// since polygon is convex, then P = U P[0]P[i]P[i+1] for i=1..n-2
// do binary search to find i, and then check for being inside triangle
// check for boundaries separately
const i64 INSIDE = 1;
const i64 BOUNDARY = 0;
const i64 OUTSIDE = -1;

```

```

i64 inside_polygon_convex(pt q, vector<pt> p){
    const i64 n = p.size();
    pt pivot = p[0];
    for (pt a: p){
        if (make_pair(a.x, a.y) < make_pair(pivot.x, pivot.y)){
            pivot = a;
        }
    }
    sort(p.begin(), p.end(), [&pivot](pt a, pt b){return
        polarComp(pivot, a, b);});

    i64 l = 1, r = n - 2, i = -1;
    while (l <= r){
        i64 m = l + (r - l) / 2;
        // is in P[0]P[m]P[m+1] iff P[m]P[0]Q is ccw but P[m+1]P[0]Q
        is cw
        if (ccw(p[m], p[0], q)){
            if (!ccw(p[m + 1], p[0], q)){
                i = m;
                break;
            } else {
                l = m + 1;
            }
        } else {
            r = m - 1;
        }
    }

    // inside_triangle includes boundaries
    if (i == -1 || !inside_triangle(q, p[0], p[i], p[i + 1])) return
        OUTSIDE;
    else if (
        on_segment(q, p[i], p[i + 1])
        || (i == 1 && on_segment(q, p[0], p[1]))
        || (i == n - 2 && on_segment(q, p[0], p[n - 1]))
    ){
        return BOUNDARY;
    } else return INSIDE;
}

// Raycasting algorithm, works on all polygons, convex or not.
// Complexity: O(N)
// if the ray intersects a vertex, then it only counts if orientation
// changes
// (so it does not hit "tangentially", but cuts through)
i64 inside_polygon(pt q, vector<pt>& p){
    const i64 n = p.size();
    // draw horizontal ray

```

```

i64 ray_intersections = 0;
for (i64 i = 0; i < n; i++){
    // p[i]p[i+1]
    if (on_segment(q, p[i], p[(i + 1) % n])){
        return BOUNDARY;
    }
    ray_intersections += horizontal_ray_segment_intersect(q, p[i],
        p[(i + 1) % n]);
}
// to be inside: odd exits
if (ray_intersections % 2 == 1){
    return INSIDE;
} else {
    return OUTSIDE;
}
}

```

6.4 triangle.hpp

```

#include "../point.hpp"

// pqr oriented area
// can also be calculated by shoelace
double area(pt p, pt q, pt r){
    return (double)((q - p).cross(r - p)) / 2.0f;
}

bool inside_triangle(pt q, pt p1, pt p2, pt p3){
    i64 abs_area = 0;
    pt p[3] = {p1, p2, p3};
    for (i64 i = 0; i < 3; i++){
        abs_area += abs((p[i] - q).cross(p[(i + 1) % 3] - q));
    }
    i64 total = abs((p[1] - p[0]).cross(p[2] - p[0]));
    return abs_area == total;
}

```

7 Graphs

7.1 2sat.cpp

```

#include <bits/stdc++.h>
using namespace std;

namespace SAT2 {

```

```

vector<vector<int>> build_graph(const vector<pair<int, int>>
    &clauses, int n){
    vector<vector<int>> g(2 * n);
    for (auto[x, y]: clauses){
        // (x or y) clause = (~x => y) clause and (~y => x) clause
        g[(x + n) % (2 * n)].emplace_back(y);
        g[(y + n) % (2 * n)].emplace_back(x);
    }
    return g;
}

vector<vector<int>> transpose(vector<vector<int>> &g){
    vector<vector<int>> gt(g.size());
    for (int u = 0; u < g.size(); u++){
        for (int v: g[u]){
            gt[v].emplace_back(u);
        }
    }
    return gt;
}

void forward_dfs(
    const int u, vector<vector<int>> &g, vector<bool> &vis,
    vector<int> &stack
){
    vis[u] = true;
    for (int v: g[u]){
        if (!vis[v]){
            forward_dfs(v, g, vis, stack);
        }
    }
    stack.emplace_back(u);
}

void backward_dfs(
    const int u, vector<vector<int>> &g, vector<bool> &vis,
    vector<int> &comp, int c = 0
){
    vis[u] = true;
    comp[u] = c;
    for (int v: g[u]){
        if (!vis[v]){
            backward_dfs(v, g, vis, comp, c);
        }
    }
}

pair<vector<int>, int> scc(const vector<pair<int, int>> &clauses,

```

```

int n){
    vector<vector<int>> g = build_graph(clauses, n);
    vector<vector<int>> gt = transpose(g);

    const int s = g.size();
    vector<int> stack, comp(s);
    vector<bool> vis(s, false);
    for (int u = 0; u < s; u++){
        if (!vis[u]){
            forward_dfs(u, g, vis, stack);
        }
    }
    reverse(stack.begin(), stack.end());
    fill(vis.begin(), vis.end(), false);
    int c = 0;
    for (int u: stack){
        if (!vis[u]){
            backward_dfs(u, gt, vis, comp, c);
            ++c;
        }
    }
    return {comp, c};
}

pair<vector<bool>, bool> solve(const vector<pair<int, int>>&
    clauses, int n){
    // run scc (Kosaraju)
    auto[comp, num_comps] = scc(clauses, n);

    // build quotient graph
    vector<vector<int>> g_scc(num_comps);
    for (auto[x, y]: clauses){
        // (x or y) = (~x => y) = (~y => x)
        g_scc[comp[(x + n) % (2 * n)]] .emplace_back(comp[y]);
        g_scc[comp[(y + n) % (2 * n)]] .emplace_back(comp[x]);
    }

    // build valuation: mark as true the first one that appears
    vector<bool> valuation(n);
    for (int u = 0; u < n; u++){
        if (comp[u] < comp[u + n]){
            valuation[u] = false;
        } else {
            valuation[u] = true;
        }
    }
}

```

```

// check valuation
bool ok = true;
for (auto[x, y]: clauses){
    bool left = ((x < n) ? valuation[x] : !valuation[x - n]);
    bool right = ((y < n) ? valuation[y] : !valuation[y - n]);
    ok &= left | right;
}
return {valuation, ok};
};

```

7.2 bellman_ford.cpp

```

#include <bits/stdc++.h>
using namespace std;

// edges: (a, b, c) = directed edge from a to b with weight c
vector<int> negative_cycle(const vector<tuple<int, int, int>> edges,
    int n){
    // virtual vertex connects to all others with weight 0
    // so ALL negative cycles are reachable!
    // for that effect we just need to set d[u] = 0 for all u
    // (we don't need an actual new vertex)
    vector<int> d(n, 0);
    vector<int> source_list;
    vector<int> prev(n, -1);
    // all paths of size s
    for (int s = 0; s <= n; s++){
        bool any = false;
        for (auto[a, b, c]: edges){
            if (d[a] + c < d[b]){
                any = true;
                prev[b] = a;
                d[b] = d[a] + c;
            }
        }
        if (!any) break;
    }

    // run a (single) new iteration of relaxation
    int target = -1;
    for (auto[a, b, c]: edges){
        if (d[a] + c < d[b]){
            target = b;
            break;
        }
    }
    if (target != -1){

```



```

vector<int> cyc;
// might be a cycle end or a vertex reachable from a negative
// cycle
int curr = target;
vector<bool> vis(n);
while (!vis[curr]) {
    cyc.emplace_back(curr);
    vis[curr] = true;
    // we might have prev[curr] == curr
    // (in case of self negative edges!)
    curr = prev[curr];
}
// now curr is a visited vertex (closed the cycle!)
cyc.emplace_back(curr);
reverse(cyc.begin(), cyc.end());
while (cyc.back() != cyc[0]){
    cyc.pop_back(); // remove vertices reachable from the
                    // cycle but not in it
}
return cyc;
} else {
    return vector<int>();
}
}

```

7.3 cycle_detection.cpp

```

#include <bits/stdc++.h>
using namespace std;

#define WHITE 0
#define GRAY 1
#define BLACK 2
bool has_cycle = false;

void dfs(vector<vector<int>> &g, int u, vector<int> &color){
    if (color[u] != WHITE){
        return;
    }
    color[u] = GRAY;
    for (int v: g[u]){
        if (color[v] == GRAY){
            has_cycle = true;
        } else if (color[v] == WHITE){
            dfs(g, u, color);
        }
    }
    color[u] = BLACK;
}

```

```

}

```

7.4 dfs_toposort.cpp

```

#include <bits/stdc++.h>
using namespace std;

namespace Graph {
    int c;

    void dfs(
        int u, vector<vector<int>> &G, vector<bool> &vis, vector<int>
        &order
    ){
        vis[u] = true;
        for (int v: G[u]){
            if (!vis[v]){
                dfs(v, G, vis, order);
            }
        }
        order[u] = c;
        --c;
    }

    vector<int> toposort(vector<vector<int>> &G){
        c = G.size() - 1;
        const int n = G.size();
        vector<bool> vis(n, false);
        vector<int> order(n);
        for (int u = 0; u < n; u++){
            if (!vis[u]){
                dfs(u, G, vis, order);
            }
        }
        // validate order
        for (int u = 0; u < n; u++){
            for (int v: G[u]){
                if (order[u] >= order[v]) {
                    return vector<int>();
                }
            }
        }
        return order;
    }
}

```

7.5 dijkstra.cpp

```

#include <bits/stdc++.h>
using namespace std;

const int INF = (int)2e9;

// directed edges are pairs (weight, endpoint)
void dijkstra(vector<vector<pair<int, int>>> &adj, int dis[], int s)
{
    for (int i = 0; i < (int)adj.size(); i++) dis[i] = INF;

    priority_queue<pair<int, int>, vector<pair<int, int>>,
        greater<pair<int, int>> > pq;
    pq.emplace(0, s);
    dis[s] = 0;
    while (!pq.empty())
    {
        auto [dis_u, u] = pq.top();
        pq.pop();
        if (dis_u > dis[u])
            continue; // skip suboptimal
        // since dis[u] is always updated when better path is found,
        // dis[u] <= d for each [d, u] state on the priority queue

        for (auto [w, v] : adj[u])
        {
            if (dis[u] + w < dis[v])
            {
                dis[v] = dis[u] + w;
                pq.emplace(dis[v], v);
                // sorting by dis[v] is the same as sorting by the
                // weights w[u, v]
                // since dis[v] - w(u, v) = dis[u] for all v (constant
                // difference)
            }
        }
    }
}

```

7.6 dinic.cpp

```

// Tested on CSES - Police Chases
#include <bits/stdc++.h>
using namespace std;
#define i64 int64_t

/*
Dinic (overview):
// make residual graph (edges and backedges)

```

```

// then on each iteration
// do bfs to make layer graph
// do dfs to find blocking flow
*/

const i64 INF = (i64)2e18;
struct Edge {
    i64 u, v;
    i64 c, f;
    i64 other(i64 x){
        return (x == u ? v : u);
    }
    i64 cap_from(i64 x){
        if (x == u){
            return c - f;
        } else {
            return f;
        }
    }
};

void add_flow(i64 from, i64 dF){
    if (from == u) { // consume flow
        f += dF;
    } else { // undo flow
        f -= dF;
    }
}

Edge(i64 from, i64 to, i64 cap) : u(from), v(to), c(cap), f(0) {}

};

struct Dinic {
    i64 n, s, t;
    vector<vector<Edge*>> adj; // [cap, to] pairs

    void add_edge(i64 u, i64 v, i64 c){
        // must be heap-allocated, or else will disappear when leaving
        // function
        Edge* e = new Edge(u, v, c);
        adj[u].emplace_back(e);
        adj[v].emplace_back(e);
    }

    Dinic(const vector<vector<pair<i64, i64>>> g, i64 s, i64 t)
        : n(g.size()), s(s), t(t) {
        adj.resize(n);
        for (i64 u = 0; u < n; u++){
            for (auto [c, v] : g[u]){

```

```

        add_edge(u, v, c);
    }
}

// dag adj list, level vector
pair<vector<vector<Edge*>>, vector<i64>> make_dag(){
    vector<vector<Edge*>> dag(n);
    vector<i64> level(n, INF);
    queue<i64> q;
    q.emplace(s);
    level[s] = 0;
    vector<i64> vis(n, false);
    while (!q.empty()){
        i64 u = q.front();
        q.pop();
        if (vis[u]) continue;
        vis[u] = true;
        for (Edge* e: adj[u]){
            if (e->cap_from(u) == 0) continue; // edge does not
            exist
            i64 v = e->other(u);
            if (!vis[v]){
                level[v] = level[u] + 1;
                dag[u].emplace_back(e);
                q.emplace(v);
            }
        }
    }
    return {dag, level};
}

// push_flow on layer dag of residual graph
i64 push_flow(i64 u, vector<i64>& blocked, vector<i64>& level, i64
dF = INF){
    if (u == t){
        return dF; // already at sink
    }
    bool all_neighbors_blocked = true;
    i64 pushedF = 0;
    for (Edge* e: adj[u]){
        if (dF == 0) break;
        i64 v = e->other(u);
        if (level[v] != level[u] + 1) continue; // not dag edge
        if (e->cap_from(u) == 0 || blocked[v]) continue;

        // NOTE: this push_flow might block v!

```

```

        i64 delta = push_flow(v, blocked, level,
            min(e->cap_from(u), dF));
        e->add_flow(u, delta);
        dF -= delta;
        pushedF += delta;

        if (e->cap_from(u) > 0 && !blocked[v]){ // still valid
            after pushing
            all_neighbors_blocked = false;
        }
    }
    if (all_neighbors_blocked) blocked[u] = true;
    return pushedF;
}

i64 maxflow(){
    while (true){
        auto[dag, level] = make_dag();
        if (level[t] == INF) break; // no more augmenting paths
        // can't assume anyone is blocked (reuse block vector),
        // since we might try to unblock by undoing flow
        vector<i64> blocked(n, false); // indicates that vertex
        is blocked: can't push flow from it
        push_flow(s, blocked, level);
    }
    i64 maxFlow = 0;
    for (Edge* e: adj[s]){
        if (s == e->u){ // is origin vertex: forward edge
            maxFlow += e->f;
        } else { // backward edge
            maxFlow -= e->f;
        }
    }
    return maxFlow;
}

// assumes dinic was called first
vector<i64> mincut(){
    auto[, level] = make_dag();
    vector<i64> partition_num(n);
    for (i64 u = 0; u < n; u++){
        if (level[u] < INF){
            partition_num[u] = 0;
        } else {
            partition_num[u] = 1;
        }
    }
}

```

```

        return partition_num;
    }
};

```

7.7 floyd_warshall.cpp

```

#include <bits/stdc++.h>
using namespace std;

const int INF = (int)2e9; // might change depending on the problem

vector<vector<int>> floydWarshall(const vector<tuple<int, int, int>>&
    edges, int n){
    vector<vector<int>> d(n, vector<int>(n, INF));
    for (int i = 0; i < n; i++){
        d[i][i] = 0;
    }
    for (auto [a, b, w]: edges){
        d[a][b] = min(d[a][b], w);
    }
    for (int k = 0; k < n; ++k) {
        for (int i = 0; i < n; ++i) {
            for (int j = 0; j < n; ++j) {
                if (d[i][k] < INF && d[k][j] < INF)
                    d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
            }
        }
    }
    return d;
}

```

7.8 kosaraju.cpp

```

#include <bits/stdc++.h>
using namespace std;

vector<vector<int>> transpose(const vector<vector<int>> &g){
    vector<vector<int>> gt(g.size());
    for (int u = 0; u < g.size(); u++){
        for (int v: g[u]){
            gt[v].emplace_back(u);
        }
    }
    return gt;
}

void forward_dfs(

```

```

    const int u, const vector<vector<int>> &g, vector<bool> &vis,
        vector<int> &stack
){
    vis[u] = true;
    for (int v: g[u]){
        if (!vis[v]){
            forward_dfs(v, g, vis, stack);
        }
    }
    stack.emplace_back(u);
}

void backward_dfs(
    const int u, const vector<vector<int>> &g, vector<bool> &vis,
    vector<int> &comp, int c = 0
){
    vis[u] = true;
    comp[u] = c;
    for (int v: g[u]){
        if (!vis[v]){
            backward_dfs(v, g, vis, comp, c);
        }
    }
}

pair<vector<int>, int> scc(const vector<vector<int>> &g, int n){
    vector<vector<int>> gt = transpose(g);

    const int s = g.size();
    vector<int> stack, comp(s);
    vector<bool> vis(s, false);
    for (int u = 0; u < s; u++){
        if (!vis[u]){
            forward_dfs(u, g, vis, stack);
        }
    }
    reverse(stack.begin(), stack.end());
    fill(vis.begin(), vis.end(), false);
    int c = 0;
    for (int u: stack){
        if (!vis[u]){
            backward_dfs(u, gt, vis, comp, c);
            ++c;
        }
    }
    return {comp, c};
}

```

7.9 lexicographical_minimal_toposort.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define i64 int64_t

// toposort with bfs, returns the lexicographically smallest
// topological order
// Runs in O(n log n) because of sorting
// Returns boolean indicating if topo order exists, and the order in
// case it does
pair<bool, vector<i64>> lexicographical_toposort(const
vector<vector<i64>>& dag){
    const i64 n = dag.size();
    // dependencies_met[i]: how many j such that j->i
    // have received their order number
    vector<i64> dependencies_met(n, 0),
                in_degree(n, 0),
                order(n, -1);
    for (i64 u = 0; u < n; u++){
        for (i64 v: dag[u]){
            ++in_degree[v];
        }
    }
    priority_queue<i64, vector<i64>, greater<i64>> q;
    // min pq guarantees lexicographical order and topo order
    // by only pushing when all dependencies are met
    for (i64 u = 0; u < n; u++){
        if (!in_degree[u]) q.emplace(u);
    }
    i64 c = 0;
    while (!q.empty()){
        i64 u = q.top();
        order[u] = c++;
        q.pop();
        for (i64 v: dag[u]){
            ++dependencies_met[v];
            if (dependencies_met[v] == in_degree[v]){
                q.emplace(v);
            }
        }
    }
    for (i64 u = 0; u < n; u++){
        // circular dependencies exist
        if (order[u] == -1) return {false, {}};
    }
    return {true, order};
}
```

```
}
```

7.10 tarjan.cpp

```
#include <bits/stdc++.h>
using namespace std;

const int INF = (int)2e9;

namespace Tarjan {
    vector<int> lowlink, t_in;
    vector<pair<int, int>> dfs_tree_edges;
    int timer;

    void dfs(int u, const vector<vector<int>> &g, vector<bool> &vis,
            int parent = -1){
        vis[u] = true;
        t_in[u] = lowlink[u] = timer++;
        for (int to: g[u]){
            if (to == parent) continue;
            else if (vis[to]){
                // back edge on DFS tree
                lowlink[u] = min(t_in[to], lowlink[u]);
            } else {
                dfs(to, g, vis, u);
                dfs_tree_edges.emplace_back(u, to);
                lowlink[u] = min(lowlink[to], lowlink[u]);
            }
        }
    }

    // lowlink(u) = min(t_in(u), min_{p->u} t_in(u), min_{u->to em
    // tree} lowlink(to))
    vector<vector<pair<int, int>>> dfs_tree_bridges(const
    vector<vector<int>> &g) {
        const int n = g.size();
        vector<bool> vis(n, false);
        lowlink = vector<int>(n, INF);
        t_in = vector<int>(n, INF);
        dfs_tree_edges.clear();
        timer = 0;

        for (int u = 0; u < n; u++){
            if (!vis[u]){
                dfs(u, g, vis);
            }
        }
    }
}
```

```

        vector<vector<pair<int, int>>> h(n);
        for (auto[v, to]: dfs_tree_edges){
            if (lowlink[to] > t_in[v]){
                h[v].emplace_back(to, 1);
            } else {
                h[v].emplace_back(to, 0);
            }
        }
        return h;
    }
}

```

8 Number Theory

8.1 fastexp.cpp

```

#include <bits/stdc++.h>
using namespace std;

const int MOD = (int)1e9 + 7; // NOTE: MIGHT CHANGE

int bexp(int a, int p){
    if (p == 0){
        return 1;
    } else {
        int m = bexp(a, p / 2);
        if (p % 2 == 1){
            return ((m * m) % MOD) * a % MOD;
        } else {
            return (m * m) % MOD;
        }
    }
}

int inv(int a){
    return bexp(a, MOD - 2);
}

```

8.2 spf.cpp

```

/*
Given N, calculates the smallest prime factor (spf) that divides K for
each 1 <= K <= N
If K is prime, that prime factor will be K itself
*/

#include <bits/stdc++.h>

```

```

using namespace std;

void spf(int N, int ans[]){
    // ans is a N+1 sized array
    for (int i = 0; i <= N; i++){
        ans[i] = i;
    }

    int is_prime[N+1]; // 0 means is prime, 1 means is composite
    memset(is_prime, N + 1, 0);
    is_prime[0] = 1; is_prime[1] = 1;
    for (int i = 2; i <= N; i++){
        if (is_prime[i] == 0){
            for (int mul = i; mul <= N; mul += i){
                ans[mul] = min(ans[mul], i);
                // last value will be the smallest divisor of mul greater than
                // 1 (which is the spf)
            }
        }
    }
}

```

9 Range Queries

9.1 bit.cpp

```

#include <bits/stdc++.h>
using namespace std;

vector<int> BIT(const vector<int> &a){
    int n = a.size();
    vector<int> B(n + 1, 0);

    for (int i = 0; i < n; i++){
        update(B, i, a[i]); // sum a[i] to position i+1 of the BIT
    }
    return B;
}

int get(const vector<int> &BIT, int i){
    int s = 0;
    while (i >= 0){
        s += BIT[i];
        // i & -i == 2^lsb(i)
        i = i ^ (i & (-i));
    }
}

```

```

    }
    return s;
}

void update(vector<int> &BIT, int i, int x){
    const int n = BIT.size() - 1;
    while (i <= n){
        BIT[i] += x;
        i += i & (-i);
    }
}

```

9.2 segtree.cpp

```

#include <bits/stdc++.h>
using namespace std;

const int INF = (int)2e9;

// default seg tree (in this example, a Max Seg)
struct MaxSegTree {
    vector<int> seg;
    vector<int> a;
    int n;

    MaxSegTree(int n, int val = -INF) : n(n) {
        seg.assign(4 * n, val);
        a.assign(n, val);
    }

    int query(int l, int r){
        return _query(l, r, 0, n - 1, 0);
    }

    void update(int p, int x){
        _update(p, x, 0, n - 1, 0);
    }

private:
    int _query(int l, int r, int tl, int tr, int node){
        if (l == tl && r == tr){
            return seg[node];
        } else {
            int tm = tl + (tr - tl) / 2;
            if (r <= tm){
                return _query(l, r, tl, tm, 2 * node + 1);
            } else if (l > tm){
                return _query(l, r, tm + 1, tr, 2 * node + 2);
            }
        }
    }
}

```

```

    } else {
        return max(
            _query(l, tm, tl, tm, 2 * node + 1),
            _query(tm + 1, r, tm + 1, tr, 2 * node + 2)
        );
    }
}

void _update(int p, int x, int tl, int tr, int node){
    if (tl == p && tr == p){
        seg[node] = x;
        a[p] = x;
    } else {
        int tm = tl + (tr - tl) / 2;
        if (p <= tm){
            _update(p, x, tl, tm, 2 * node + 1);
        } else {
            _update(p, x, tm + 1, tr, 2 * node + 2);
        }
        seg[node] = max(seg[2 * node + 1], seg[2 * node + 2]);
    }
}
};

```

10 Strings

10.1 rabin_karp.cpp

```

#include <bits/stdc++.h>
using namespace std;

#define i64 int64_t

vector<i64> rollingHash(const vector<int>& v, i64 p, i64 m){
    const i64 n = v.size();
    vector<i64> prefH(n);
    vector<i64> p_pow(n);
    // prefH = hash(v[0...i]) = sum(j<=i) v[j] * p^j mod m
    p_pow[0] = 1;
    prefH[0] = v[0] % m;
    for (i64 i = 1; i < n; i++){
        p_pow[i] = (p_pow[i - 1] * p) % m;
        prefH[i] = (v[i] * p_pow[i] + prefH[i - 1]) % m;
    }
    return prefH;
}

```

```

// lowercase
vector<i64> rollingHash(const string& s){
    vector<int> s_repr(s.size());
    for (i64 i = 0; i < s.size(); i++){
        s_repr[i] = s[i] - 'a';
    }
    return rollingHash(s_repr, 31, (i64)1e9 + 7);
}

i64 bexp(const i64 a, const i64 p, const i64 mod){
    if (p == 0){
        return 1;
    } else {
        const i64 b = bexp(a, p / 2, mod);
        if (p % 2 == 0){
            return (b * b) % mod;
        } else {
            return (a * ((b * b) % mod)) % mod;
        }
    }
}

vector<i64> prime_powers(const i64 n, const i64 p = 31, const i64 m =
(i64)1e9 + 7){
    vector<i64> p_pow(2 * n + 1);
    p_pow[n] = 1;
    p_pow[n - 1] = bexp(p, m - 2, m);    // fermat little theorem
    for (i64 i = 1; i <= n; i++){
        p_pow[n + i] = (p_pow[n + i - 1] * p) % m;
    }
    for (i64 i = 2; i <= n; i++){
        p_pow[n - i] = (p_pow[n - i + 1] * p_pow[n - 1]) % m;
    }
    return p_pow;
}

vector<i64> rabinKarpMatch(const string& s, const string& t){
    vector<i64> prefix_s = rollingHash(s), prefix_t = rollingHash(t);

    const i64 mod = (i64)1e9 + 7, p = 31;
    const i64 HS = prefix_s.back();    // complete hash of s
    // precompute prime powers mod M
    const vector<i64> p_pow = prime_powers(t.size(), p, mod);

    vector<i64> matches;    // starting points of matches

```

```

const i64 offset = t.size();
for (i64 i = 0; i + s.size() <= t.size(); i++){
    // hash of t[i...i + |s| - 1] == (hash(t[0...i + |s| - 1]) -
    hash(t[0...i - 1])) * p-i
    const i64 h = ((prefix_t[i + s.size() - 1] - (i > 0 ?
    prefix_t[i - 1] : 0) + mod) * p_pow[offset - i]) % mod;
    if (h != HS){
        continue;
    }
    // compare
    bool ok = true;
    for (i64 j = 0; (j < s.size()) && ok; j++){
        ok = ok && (s[j] == t[i + j]);
    }
    if (ok) matches.emplace_back(i);
}
return matches;
}

```

10.2 suffix_array.cpp

```

#include <bits/stdc++.h>
using namespace std;

#define ALPHABET 256

void csort(vector<int>& p, const vector<int>& classes, int offset){
    const int n = p.size();
    vector<int> cnt(max(ALPHABET, n), 0), ptemp(n);
    for (int i = 0; i < n; i++){
        ++cnt[classes[i]];
    }
    for (int i = 1; i < max(ALPHABET, n); i++){
        cnt[i] += cnt[i - 1];
    }
    // distribute on blocks in reverse order to make sorting stable
    // distribute according to order of k-th element (k=offset)
    for (int i = n - 1; i >= 0; i--){
        int offseted_pos = (p[i] + offset) % n;
        ptemp[--cnt[classes[offseted_pos]]] = p[i];
    }
    swap(ptemp, p);
}

pair<vector<int>, vector<vector<int>>> suffix_array(const string& s){
    int lg = 0;
    string t = s;
    t.push_back('$');

```



```

int n = t.size();
while ((1ll << lg) < n) ++lg; // now 2^lg >= n
vector<int> p(n);
vector<vector<int>> c(lg + 1, vector<int>(n));
for (int i = 0; i < n; i++){
    p[i] = i;
    c[0][i] = (int)t[i];
}
csort(p, c[0], 0);
// check offset of size 2^k
for (int k = 0; k <= lg; k++){
    csort(p, c[k], (1ll << k)); // sort by second, stably
    csort(p, c[k], 0); // sort by first, stably
    if (k == lg) break;
    // redo equivalence classes
    c[k + 1][p[0]] = 0; // first element receives class=0
    int cls = 0;
    for (int i = 1; i < n; i++){
        if (
            (c[k][p[i - 1]] < c[k][p[i]])
            || (c[k][(p[i - 1] + (1ll << k)) % n] < c[k][(p[i] +
                (1ll << k)) % n])
        ){
            ++cls;
        }
        c[k + 1][p[i]] = cls;
    }
}
return {p, c};
}

int lcp(int i, int j, const vector<vector<int>>& cls){
    const int n = cls[0].size();
    int lg = 0;
    while ((1ll << lg) < n) ++lg; // now 2^lg >= n
    int ans = 0;
    for (int k = lg; k >= 0; k--){
        if (cls[k][i] == cls[k][j]){
            i = (i + (1ll << k)) % n;
            j = (j + (1ll << k)) % n;
            ans += (1ll << k);
        }
    }
    return ans;
}

```

10.3 trie.cpp

```

#include <bits/stdc++.h>
using namespace std;

template<int K> // sum of characters in the set
struct Trie {
    int children[K][26];
    int cnt[K]; // cnt of each word
    int ptr = 1;

    Trie(){
        for (int i = 0; i < K; i++){
            for (int j = 0; j < 26; j++){
                children[i][j] = -1;
            }
            cnt[i] = 0;
        }
    }

    void insert(string& u, int i=0, int node=0){
        int idx = u[i] - 'a';
        if (children[node][idx] == -1){
            // create node
            children[node][idx] = ptr++;
        }
        if (i + 1 < u.size()){
            insert(u, i + 1, children[node][idx]);
        } else {
            ++cnt[children[node][idx]];
        }
    }

    int search(string &u, int i=0, int node=0){
        if (i == u.size()){
            return cnt[node];
        } else {
            int idx = u[i] - 'a';
            if (children[node][idx] == -1){
                return 0;
            } else {
                return search(u, i + 1, children[node][idx]);
            }
        }
    }

    bool isleaf(int node){
        bool ok = true;
        for (int i = 0; i < 26; i++){

```

```

        ok = ok && children[node][i] == -1;
    }
    return ok;
}

void remove(string &u, int i=0, int node=0){
    int idx = u[i] - 'a';
    if (children[node][idx] != -1){
        remove(u, i + 1, children[node][idx]);
        if (isleaf(children[node][idx]) &&
            cnt[children[node][idx]] == 0){
            children[node][idx] = -1;
        }
    } else {
        // reached leaf
        cnt[node] = max(cnt[node] - 1, 0);
    }
}
};

```

11 template.cpp

```

#define TESTCASES
#define debug cerr

#include <bits/stdc++.h>
using namespace std;
#define fastio
    ios_base::sync_with_stdio(false); cin.tie(NULL); cout.tie(NULL)
#define endl '\n'

#define i64 int64_t
#define u64 uint64_t
#define i128 __int128
#define all(x) begin(x), end(x)
#define printmsg(msg, first, last) debug << msg; for(auto it = first;
    it != last; it++){debug << *it << " ";} debug << endl;
#define printgraph(msg, G) debug << msg << endl; \
    for (u64 u = 0; u < G.size(); u++) { \
        debug << "G[" << u << "]="; \
        for (u64 v: G[u]) { \
            debug << v << " "; \
        } \
        debug << endl; \
    }

template <typename T, typename U>

```

```

ostream& operator<< (ostream& out, pair<T, U> x)
{
    out << x.first << " " << x.second;
    return out;
}

template <typename T>
ostream& operator<< (ostream& out, vector<T> v)
{
    for (const auto& x: v){
        out << x << " ";
    }
    return out;
}

template <typename T>
using min_pq = priority_queue<T, vector<T>, greater<T>>;
template <typename T>
using max_pq = priority_queue<T>;

void solve(){

}

signed main(){
    fastio;
    int t;
#ifdef TESTCASES
    cin >> t;
#else
    t = 1;
#endif
    while (t--){
        solve();
    }
}

```

12 Trees

12.1 centroid.cpp

```

#include <bits/stdc++.h>
using namespace std;

namespace CentroidDecomposition {
    int subtree_size(int u, const vector<vector<int>>& adj,
        vector<int>& s, vector<int>& blocked, int p = -1){
        s[u] = 1;
    }
}

```

```

    for (int v: adj[u]){
        if (v == p) continue;
        if (blocked[v]) continue;
        s[u] += subtree_size(v, adj, s, blocked, u);
    }
    return s[u];
}

// find centroid of subtree
int find_centroid(int u, const vector<vector<int>>& adj,
    vector<int>& s, vector<int>& blocked, int total_size, int p =
-1){
    for (int v: adj[u]){
        if (v == p) continue;
        if (blocked[v]) continue;
        if (2 * s[v] >= total_size){
            return find_centroid(v, adj, s, blocked, total_size,
                u); // there can be only one such vertex
        }
    }
    return u;
}

// total_size = size of subtree rooted at root (considering
    deletions)
// @return centroid subtree root
int _build_centroid_tree(
    const vector<vector<int>>& adj,
    vector<int>& blocked,
    vector<vector<int>>& centroid_adj,
    vector<int>& sz,
    int total_size,
    int root = 0
){
    subtree_size(root, adj, sz, blocked);
    int c = find_centroid(root, adj, sz, blocked, total_size);
    blocked[c] = true;
    for (int v: adj[c]){
        if (blocked[v]) continue;
        // build centroid subtree on partition and get its root
        int c2 = _build_centroid_tree(adj, blocked, centroid_adj,
            sz, sz[v], v);
        centroid_adj[c].emplace_back(c2);
    }
    return c;
}

```

```

// @return pair (centroid tree root, directed centroid tree)
pair<int, vector<vector<int>>> centroid_tree(const
    vector<vector<int>>& adj){
    const int n = adj.size();
    vector<int> blocked(n, false), sz(n);
    vector<vector<int>> centroid_adj(n);
    int master_centroid = _build_centroid_tree(
        adj, blocked, centroid_adj, sz, n
    );
    return {master_centroid, centroid_adj};
}

```

12.2 hld.cpp

```

// HLD implementation
// Tested on CSES Path Queries (https://cses.fi/problemset/task/1138)
// Query: sum of vertices from root to v
// Update: set value of v to x

// Implementation note: there is an implementation where
// you use a single seg-tree and the node positions are their
// time of visit in the DFS, where you **visit heavy edges first**
// (so heavy paths make contiguous ranges)
// However, this leads to a larger segtree and can be slower!

#include <bits/stdc++.h>
using namespace std;
#define i64 int64_t

// uses some modifications: now the heavy edge is the edge with the
    largest subtree
// instead of the restriction s(c) >= s(v) / 2
// Still, going through light (i.e not heavy) edge reduces size by half
// Heavy path goes up to just the vertex before light edge
using tree = vector<vector<i64>>
struct HLD {
    vector<i64> heavy;    // heavy[u] = v <==> uv is heavy edge
    vector<i64> sz;
    vector<i64> head;    // head[u] = start of heavy path that goes
        through u
    vector<i64> pos;    // depth of vertex in path. Head has depth 0
    vector<i64> parent;
    // NOTE: SegTree is the segment tree implementation
    // NOTE: SegTree needs default constructor
    vector<SegTree> segs;
    vector<i64> a;
    vector<i64> depth;
}

```

```

HLD(const tree& adj, const vector<i64>& _a, i64 root = 0) : a(a) {
    const i64 n = adj.size();
    heavy.resize(n);
    sz.resize(n);
    head.resize(n);
    pos.resize(n);
    parent.resize(n);
    segs.resize(n);

    subtree(root, adj);
    dfs(root, adj);

    // build segment trees
    for (i64 h = 0; h < n; h++){
        if (h == head[h]){
            vector<i64> path;
            i64 cur = h;
            while (cur != -1 && head[cur] == h){
                path.emplace_back(a[cur]); // add value
                cur = heavy[cur];
            }
            segs[h] = SegTree(path);
        }
    }
}

void subtree(i64 u, const tree& adj, i64 p = -1, i64 d = 0){
    sz[u] = 1;
    depth[u] = d;
    for (i64 v: adj[u]){
        if (v == p) continue;
        subtree(v, adj, u, d + 1);
        sz[u] += sz[v];
    }
}

void dfs(i64 u, const tree& adj, i64 p = -1, i64 h = 0, i64 d = 0){
    i64 cur_sz = 0;
    pos[u] = d;
    head[u] = h;
    parent[u] = p;
    heavy[u] = -1;
    for (i64 v: adj[u]){
        if (v == p) continue;
        if (sz[v] > cur_sz){
            cur_sz = sz[v];

```

```

            heavy[u] = v;
        }
    }
    for (i64 v: adj[u]){
        if (v == p) continue;
        if (v == heavy[u]){
            dfs(v, adj, u, h, d + 1);
        } else {
            dfs(v, adj, u, v, 0);
        }
    }
}

// query from u to p^min(k, depth[u])(u), inclusive
// NOTE: SUM QUERY HERE, other variations are possible
i64 query_up(i64 u, i64 k){
    i64 s = 0;
    while (u != -1 && k >= pos[u]){
        s += segs[head[u]].query(0, pos[u]);
        u = parent[head[u]];
    }
    if (u != -1){ // k < pos[u]
        s += segs[head[u]].query(pos[u] - k, pos[u]);
    }
    return s;
}

i64 query_path(i64 u, i64 v){
    // TODO implement LCA!
    i64 l = lca(u, v);
    return query_up(u, depth[u] - depth[l]) + query_up(v, depth[v]
        - depth[l]) - a[l];
}

void update(i64 u, i64 x){ // set value to x
    segs[head[u]].update(pos[u], x);
}
};

```

12.3 lca.cpp

```

#include <bits/stdc++.h>
using namespace std;

const int N = 2e5, LOGN = 20;
int lift[LOGN + 1][N];

void binary_lifting(const vector<vector<int>> &forest){

```

```

const int n = forest.size();
vector<int> parent(n, -1);
for (int u = 0; u < n; u++){
    for (int v: forest[u]){
        parent[v] = u;
    }
}

for (int u = 0; u < n; u++){
    lift[0][u] = parent[u];
}

for (int k = 1; k <= LOGN; k++){
    for (int u = 0; u < n; u++){
        lift[k][u] = lift[k - 1][lift[k - 1][u]];
    }
}

}

int jump(int u, int k){
    for (int i = 0; i <= LOGN; i++){
        if ((k >> i) & 1){
            u = lift[i][u];
        }
    }
    return u;
}

int LCA(
    int u, int v, const vector<int> &level,
    const vector<int> &parent
){
    // invariant: level[u] <= level[v]
    if (level[v] < level[u]) swap(u, v);
    v = jump(v, level[v] - level[u]);

    if (u == v){
        return u;
    }

    // loop invariant: u and v are distinct
    // (we have not reached a common ancestor yet)
    for (int i = LOGN; i >= 0; i--){
        if (lift[i][u] != lift[i][v]){
            // keeps loop invariant -> greedily take it!
            u = lift[i][u];
            v = lift[i][v];
        }
    }
}

```

```

// at the end of the invariant we must be just one level below the
// LCA
// otherwise we could have jumped more
return parent[u];
}

```

12.4 path_queries.cpp

```

// Tested on CSES Distance Queries
// sum queries on paths. Values are on vertices

```

```

#include <bits/stdc++.h>
using namespace std;

```

```

const int N = 2e5, LOGN = 20;
int lift[LOGN + 1][N];
int sums[LOGN + 1][N];

void binary_lifting(const vector<int>& parent, const vector<int>&
values){
    const int n = parent.size();
    for (int u = 0; u < n; u++){
        lift[0][u] = parent[u];
        sums[0][u] = values[u];
    }
    for (int k = 1; k <= LOGN; k++){
        for (int u = 0; u < n; u++){
            lift[k][u] = lift[k - 1][lift[k - 1][u]];
            //  $u \dots p^{(2^{k-1})}(u)$  and then  $p^{(2^{k-1}+1)}(u)$  to
            //  $p^{(2^k)}(u)$ 
            sums[k][u] = sums[k - 1][u] + sums[k - 1][lift[k - 1][u]];
        }
    }
}

int jump(int u, int k){
    for (int i = 0; i <= LOGN; i++){
        if ((k >> i) & 1){
            u = lift[i][u];
        }
    }
    return u;
}

//  $v[u] + v[p[u]] + \dots + v[p^{(2^k-1)}(u)]$ 
int query_sum(int u, int k){

```

```

int s = 0;
for (int i = 0; i <= LOGN; i++){
    if ((k >> i) & 1){
        s += sums[i][u];
        u = lift[i][u];
    }
}
return s;
}

int LCA(
    int u, int v, const vector<int> &level,
    const vector<int> &parent
){
    // invariant: level[u] <= level[v]
    if (level[v] < level[u]) swap(u, v);
    v = jump(v, level[v] - level[u]);

    if (u == v){
        return u;
    }

    // loop invariant: u and v are distinct
    // (we have not reached a common ancestor yet)
    for (int i = LOGN; i >= 0; i--){
        if (lift[i][u] != lift[i][v]){
            // keeps loop invariant -> greedily take it!
            u = lift[i][u];
            v = lift[i][v];
        }
    }

    // at the end of the invariant we must be just one level below the
    // LCA
    // otherwise we could have jumped more
    return parent[u];
}

int path_sum(int u, int v, const vector<int> &level, const vector<int>
&parent){
    int lca = LCA(u, v, level, parent);

    int left = query_sum(u, level[u] - level[lca]), right =
        query_sum(v, level[v] - level[lca]);
    return left + right + sums[0][lca];
}

```