

Software Requirements Specification for ESP32 Room Climate Station

Version 2

Prepared by Ihor Huz

Lodz University of Technology

May 8, 2026

Table of Contents

Software Requirements Specification	1
Revision History	3
1. Introduction	4
1.1. Purpose	4
1.2. Document Conventions	4
1.3. Intended Audience and Reading Suggestions	4
1.4. Product Scope	4
1.4.1. In Scope (Includes)	4
1.4.2. Out Scope (Excludes)	4
1.5. References	5
2. Overall Description	5
2.1. Product Perspective	5
2.2. Product Features	5
2.3. User Classes and Characteristics	6
2.4. Operating Environment	6
2.5. Design and Implementation Constraints	6
2.6. User Documentation	6
2.7. Assumptions and Dependencies	6
3. System Features	6
3.1. «Feature Name»	6
3.«N». «Additional feature blocks as needed»	6
4. External Interface Requirements	6
4.1. User Interfaces Overview	6
4.2. Hardware Interfaces	6
4.3. Software Interfaces	7
5. System Features/Modules	7
5.1. «System Feature Name»	7
5.1.1 Description and Priority	7
5.1.2 Stimulus/Response Sequences	7
5.1.3 Functional Requirements	7
6. Nonfunctional Requirements	8
6.1. Performance	8
6.2. Reliability	8
6.3. Maintainability	8

Revision History

Name	Date	Reason for Changes	Version
Ihor Huz	April 27, 2026	Initial draft for Lab 1: Requirement Analysis	1
Ihor Huz	May 8, 2026	Added the UML Use Case Diagram. Updated Product Perspective, Product Features, and External Interface Requirements	2

1. Introduction

1.1. Purpose

«Identify the product whose software requirements and design are specified in this document, including the revision or release number. Describe the scope of the product that is covered by this specification.»

1.2. Document Conventions

«Describe any standards or typographical conventions that were followed when writing this specification, such as fonts or highlighting that have special significance. For example, state whether priorities for higher-level requirements are assumed to be inherited by detailed requirements, or whether every requirement statement is to have its own priority.»

1.3. Intended Audience and Reading Suggestions

«Describe the different types of reader that the document is intended for, such as developers, project managers, marketing staff, users, testers, and documentation writers. Describe what the rest of this document contains and how it is organized. Suggest a sequence for reading the document, beginning with the overview sections and proceeding through the sections that are most pertinent to each reader type.»

1.4. Product Scope

The ESP32 Room Climate Station addresses this limitation by functioning as a centralized, persistently logging IoT environment monitor. It bridges the gap between local hardware and remote software by reading ambient conditions through a high-accuracy SHTC3 sensor and making that data available through three distinct interfaces: a local LCD, a web-based dashboard, and a Telegram bot. Furthermore, the system solves the common IoT problem of volatile memory loss by utilizing SPIFFS to store a 24-hour rolling buffer of environmental data. This ensures that in the event of a power failure, the user does not lose their historical trend data. The integration of mDNS and Over-The-Air (OTA) updates ensures the device remains a low-maintenance, headless appliance once deployed.

1.4.1. In Scope (Includes)

The following capabilities are explicitly included within the boundaries of this project:

- Continuous monitoring of ambient temperature and humidity via the SHTC3 sensor.
- Local data display via a hardware LCD and manual physical toggle button.
- Remote reporting and basic remote command execution via a Telegram Bot API.
- A local, mDNS-accessible web dashboard for visualizing 24-hour historical data trends.
- Persistent storage of the most recent 24 hours of data in the internal SPIFFS memory.
- Over-The-Air (OTA) firmware update capabilities via the local network.

1.4.2. Out Scope (Excludes)

The following capabilities are explicitly excluded from this system boundary to maintain project focus and hardware performance:

- Active Climate Control: The system acts strictly as an environmental monitor. It will not interface with or control external appliances (e.g., HVAC systems, humidifiers, or fans).
- Long-Term Cloud Storage: The system will not push data to external cloud databases (e.g., AWS, Firebase) for long-term retention beyond the rolling 24-hour local buffer.
- Complex Web Authentication: The local web dashboard assumes a trusted local network (climate.local) and will not feature multi-user login or complex role-based access control.
- Battery/Deep Sleep Optimization: Because the device must run a continuous web server and listen for Telegram commands, deep-sleep power saving states are excluded. The system assumes a continuous wall-power supply.

1.5. References

«List any other documents or Web addresses to which this document refers or was based on. These may include user interface style guides, contracts, standards, system requirements specifications, use case documents, or a vision and scope document. Provide enough information so that the reader could access a copy of each reference, including title, author, version number, date, and source or location. Include the assignment document in the references.»

2. Overall Description

2.1. Product Perspective

Maintaining optimal indoor climate conditions (temperature and humidity) is critical for personal health, equipment longevity, and general comfort. Traditional consumer thermometers provide only real-time snapshots of the environment, lacking historical context and remote accessibility. When users leave the room or building, they lose visibility into the environmental trends.

2.2. Product Features

The ESP32 Room Climate Station offers a wide range of environmental monitoring capabilities by balancing local hardware interactions with remote access. At its core, the system constantly monitors the local weather and displays real-time sensor data on a physical hardware screen. To assist remote users, it includes a Telegram Bot that handles periodic weather reports and conducts remote orders. The device in question also features a local web dashboard for visualising past data patterns and managing firmware through Over-The-Air (OTA) updates. Furthermore, the system encompasses proactive intelligence in the form of active threshold alerts, which send emergency notifications when conditions become dangerous, as well as a dynamic web configuration interface that allows users to securely update network and API credentials on the fly without reprogramming the device. The UML Use Case Diagram below shows how our primary actors (Home User and System Timer) and secondary actors (Telegram API) interact with these features across the system boundary:




Figure 1: The UML Use Case Diagram for the Project

2.3. User Classes and Characteristics

«Identify the various user classes (intended target for the product) that you anticipate will use this product. User classes may be differentiated based on frequency of use, subset of product functions used, technical expertise, security or privilege levels, educational level, or experience. Describe the pertinent characteristics of each user class. Certain requirements may pertain only to certain user classes. Distinguish the most important user classes for this product from those who are less important to satisfy.»

2.4. Operating Environment

«Describe the environment in which the software will operate, including the hardware platform, operating system and versions, and any other software components or applications with which it must peacefully coexist.»

2.5. Design and Implementation Constraints

«Describe any items or issues that will limit the options available to the developers. These might include: corporate or regulatory policies; hardware limitations (timing requirements, memory requirements); interfaces to other applications; specific technologies, tools, and databases to be used; parallel operations; language requirements; communications protocols; security considerations; design conventions or programming standards (for example, if the customer's organization will be responsible for maintaining the delivered software).»

2.6. User Documentation

«List the user documentation components (such as user manuals, on-line help, and tutorials) that will be delivered along with the software. Identify any known user documentation delivery formats or standards.»

2.7. Assumptions and Dependencies

«List any assumed factors (as opposed to known facts) that could affect the requirements stated in the specification. These could include third-party or commercial components that you plan to use, issues around the development or operating environment, or constraints. The project could be affected if these assumptions are incorrect, are not shared, or change. Also identify any dependencies the project has on external factors, such as software components that you intend to reuse from another project, unless they are already documented elsewhere (for example, in the vision and scope document or the project plan).»

3. System Features

«The purpose here is to give a brief introduction to the system features, so that §4 has something to reference. Then, the full explanation of the system features is given in §5, likely referencing §4. The numbering in §3 and §5 should match.»

3.1. «Feature Name»

«Brief description of the feature, generally 1-3 sentences»

3.«N». «Additional feature blocks as needed»

4. External Interface Requirements

4.1. User Interfaces Overview

The ESP32 Room Climate Station incorporates three separate user interfaces designed for various interaction scenarios. The major physical interface is a 16x2 I2C LCD panel that shows real-time temperature and humidity information, as well as a hardware push-button that allows you to manually control the screen's lighting. The system uses a Telegram Bot interface for remote interaction, allowing users to manage the device and get structured, periodic climatic data by sending specified textual instructions like /status or /restart. Finally, a local web dashboard may be accessed via a browser at climate.Local provides a graphical user interface. This dashboard uses Highcharts to visualise 24-hour historical data patterns and includes a secure settings panel for dynamically configuring network and API credentials.

4.2. Hardware Interfaces

The software directly interfaces with several specific hardware components connected to the ESP32 microcontroller. The system communicates with both the SHTC3 environmental sensor and the 16x2 LCD module utilizing the Inter-Integrated Circuit (I2C) communication protocol, which requires the software to manage the clock timing and specific device addresses. Additionally, the software monitors a digital input on GPIO pin 4, utilizing hardware debouncing techniques to detect state changes from a physical momentary push-button that triggers the LCD backlight control logic. The system assumes a continuous, stable power supply provided via the ESP32's onboard USB port, as deep-sleep battery optimizations are excluded from this architecture.

4.3. Software Interfaces

To complete its feature set, the system interacts with a number of external and internal software components. Externally, it needs a secure outbound HTTPS connection to communicate with the Telegram Bot API, which is required for both sending outward alert messages and polling the server for incoming user instructions. Internally, the software significantly relies on the ESP32's SPIFFS (Serial Peripheral Interface Flash File System) library to constantly read and write the rolling 24-hour environmental data buffer to the device's non-volatile flash memory. Furthermore, the firmware runs an asynchronous local web server on standard HTTP port 80 and uses the Multicast DNS (mDNS) protocol to broadcast its local hostname to the network router, guaranteeing that the dashboard is always available without the need for static IP setups.

5. System Features/Modules

«This template illustrates organizing the functional requirements for the product by system features, the major services provided by the product.»

5.1. «System Feature Name»

5.1.1 Description and Priority

«Provide a short description of the feature. Give its priority, too.»

5.1.2 Stimulus/Response Sequences

«"Stimulus" or "Condition": «Describe the stimulus or condition»

Response: «Describe the response»

«Additional Stimulus/Response pairs as needed»

5.1.3 Functional Requirements

Feature 1: Local Climate Monitoring and Display

- **REQ-1.1:** The system shall measure ambient temperature and humidity using the connected SHTC3 sensor.
- **REQ-1.2:** The system shall display the current temperature and humidity readings locally on the 16x2 I2C LCD.
- **REQ-1.3:** The system shall allow the user to manually toggle the LCD backlight state (on/off) using a physical hardware button connected to GPIO 4.

Feature 2: Telegram Bot Integration

- **REQ-2.1:** The system shall automatically transmit a formatted ambient climate report to the configured Telegram Bot every 15 minutes.
- **REQ-2.2:** The system shall parse and execute the following remote commands received via Telegram: `/light_on` (enables LCD), `/light_off` (disables LCD), `/status` (returns current readings), and `/restart` (initiates a soft reboot).

- **REQ-2.3:** The system shall clear the Telegram message queue immediately upon booting to prevent infinite restart loops triggered by stale commands.

Feature 3: Web Dashboard and Device Management

- **REQ-3.1:** The system shall serve a local web dashboard accessible via `http://climate.local` that displays a Highcharts-powered visualization of both live trends and 24-hour historical data.

Feature 4: Active Threshold Alerts

- **REQ-4.1:** The system shall store user-defined maximum and minimum threshold values for both temperature and humidity in non-volatile memory.
- **REQ-4.2:** The system shall immediately transmit an emergency alert message via the Telegram Bot if a polled sensor reading falls outside the defined threshold limits.

Feature 5: Dynamic Web Configuration

- **REQ-5.1:** The system shall provide a secure settings route on the web dashboard (`http://climate.local/settings`).
- **REQ-5.2:** The system shall allow the user to input and save new WiFi credentials, Telegram Bot tokens, and Telegram Chat IDs via the web interface.

6. Nonfunctional Requirements

6.1. Performance

- **NF-1.1:** The system shall utilize non-blocking timers for network operations to ensure that the physical hardware toggle (GPIO 4) and local LCD updates remain responsive, acting with less than a 500-millisecond delay.

6.2. Reliability

- **NF-2.1:** The system shall persist a rolling 24-hour history of sensor data to internal SPIFFS flash memory to ensure data is preserved and reloaded across unexpected device restarts.

6.3. Maintainability

- **NF-3.1:** The system shall support Over-The-Air (OTA) firmware updates via a local web browser interface, allowing deployment of new code without a physical USB connection.