

VDMTools

VDM++ Sorting Algorithms
ver.1.0



How to contact:

<http://fmvdm.org/>

<http://fmvdm.org/tools/vdmttools>

inq@fmvdm.org

VDM information web site(in Japanese)

VDMTools web site(in Japanese)

Mail

VDM++ Sorting Algorithms 1.0

— Revised for VDMTools v9.0.6

© COPYRIGHT 2016 by Kyushu University

The software described in this document is furnished under a license agreement.
The software may be used or copied only under the terms of the license agreement.

This document is subject to change without notice


Contents

1	Introduction	1
2	Sort Machine	2
3	Sorter class	4
4	MergeSort	5
5	DoSort	7
6	ImplSort	8
7	ExplSort	9

1 Introduction

This document contains a sorting example. The class diagram can be seen in Figure 1. The structure of the example is known as the *strategy* pattern. This pattern defines a family of algorithms, encapsulates each one and make them interchangeable. The *strategy* pattern lets the algorithm vary independently from clients that use it. The **SortMachine** class is the client that uses the different sorting algorithms. The **Sorter** class is an abstract class that defines a common interface to all supported algorithms.

Figure 1: Class diagram for the sort example



80028440attern "Strategy". This is the class that uses the 0ifferent sorting algorithms.

2 Sort Machine

```
class SortMachine
```

```
instance variables
```

```
    srt: Sorter := new MergeSort();
```

The instance variable "srt" is an object reference to the sorting algorithm currently in use. The initial sorting algorithm is MergeSort.

Setting/changing which sorting algorithm to use.

```
operations
```

```
    public SetSort: Sorter ==> ()
    SetSort(s) ==
        srt := s;
```

Sorting with the sorting algorithm currently in use.

```
    public GoSorting: seq of int ==> seq of int
    GoSorting(arr) ==
        return srt.Sort(arr);
```

Set/change first the sorting algorithm and sort afterwards.

```
public SetAndSort: Sorter * seq of int ==> seq of int
SetAndSort(s, arr) ==
( srt := s;
  return srt.Sort(arr)
)

end SortMachine
```

3 Sorter class

```
class Sorter
operations
  public
  Sort: seq of int ==> seq of int
  Sort(arg) ==
    is subclass responsibility
end Sorter
```

4 MergeSort

```
class MergeSort is subclass of Sorter
```

```
operations
```

```
public Sort: seq of int ==> seq of int
Sort(l) ==
  return MergeSorter(l)
```

```
functions
```

```
MergeSorter: seq of real -> seq of real
MergeSorter(l) ==
  cases l:
    []      -> l,
    [e]     -> l,
    others  -> let l1^l2 in set {l} be st abs (len l1 - len l2) < 2
               in
               let l_l = MergeSorter(l1),
                 l_r = MergeSorter(l2) in
                 Merge(l_l, l_r)
  end;
```

```
Merge: seq of int * seq of int -> seq of int
Merge(l1,l2) ==
  cases mk_(l1,l2):
    mk_([],l),mk_(l,[]) -> l,
    others              -> if hd l1 <= hd l2 then
                           [hd l1] ^ Merge(tl l1, l2)
                           else
                           [hd l2] ^ Merge(l1, tl l2)
    end
  pre forall i in set inds l1 & l1(i) >= 0 and
    forall i in set inds l2 & l2(i) >= 0
```

```
end MergeSort
```


5 DoSort

```
class DoSort is subclass of Sorter
```

```
operations
```

```
public Sort: seq of int ==> seq of int
Sort(l) ==
  return DoSorting(l)
```

```
functions
```

```
DoSorting: seq of int -> seq of int
DoSorting(l) ==
  if l = [] then
    []
  else
    let sorted = DoSorting (tl l) in
      InsertSorted (hd l, sorted);
```

```
InsertSorted: int * seq of int -> seq of int
InsertSorted(i,l) ==
  cases true :
    (l = [])    -> [i],
    (i <= hd l) -> [i] ^ l,
    others      -> [hd l] ^ InsertSorted(i,tl l)
  end
```

```
end DoSort
```

An overview of the test coverage information for the *DoSort* class is listed in the table below. The test coverage information is generated using the argument file *sort.arg*.

0X0P+0n implicit specification of a sorting algorithm

6 ImplSort

The class *ImplSort* is an example of an sorting algorithm defined by implicit functions.

class ImplSort is subclass of Sorter

operations

```
public Sort: seq of int ==> seq of int
Sort(l) ==
  return ImplSorter(l);
```

functions

```
public ImplSorter(l: seq of int) r: seq of int
post IsPermutation(r,l) and IsOrdered(r);
```

```
IsPermutation: seq of int * seq of int -> bool
IsPermutation(l1,l2) ==
  forall e in set (elems l1 union elems l2) &
    card {i | i in set inds l1 & l1(i) = e} =
    card {i | i in set inds l2 & l2(i) = e};
```

```
IsOrdered: seq of int -> bool
IsOrdered(l) ==
  forall i,j in set inds l & i > j => l(i) >= l(j)
```

```
end ImplSort
```

7 ExplSort

The class *ExplSort* is a refinement of the algorithm described in *ImplSort*.

```

class ExplSort is subclass of Sorter

operations

  public Sort: seq of int ==> seq of int
  Sort(l) ==
    let r in set Permutations(l) be st IsOrdered(r) in
    return r

functions

  Permutations: seq of int -> set of seq of int
  Permutations(l) ==
    cases l:
      [], [-] -> {l},
      others -> dunion {{[l(i)]^j |
                        j in set Permutations(RestSeq(l,i))} |
                        i in set inds l}
    end;

  RestSeq: seq of int * nat -> seq of int
  RestSeq(l,i) ==
    [l(j) | j in set (inds l \ {i})]
  pre i in set inds l
  post elems RESULT subset elems l and
       len RESULT = len l - 1;

  IsOrdered: seq of int -> bool
  IsOrdered(l) ==
    forall i,j in set inds l & i > j => l(i) >= l(j)

end ExplSort

```
