

- 1) Файлын гарчиг өгөх
- 2)

```

1 package lab6;
2
3 class HelloWorld {
4
5     public static void main(String[] args) {
6         // TODO Auto-generated method stub
7         System.out.print("Hello Ikhee");
8     }
9
10 }
11

```


Markers Properties Servers Data Source Explorer Sn

<terminated> HelloWorld [Java Application] C:\Program Files\Java\jre1.8.0

Hello Ikhee

- 3) /**
 - * HelloWorld class нь дэлгэцэнд
 - * "Hello Ikhee!" гаргалтыг хэвлэж харуулна.
 - */
 - class HelloWorld {
 - public static void main(String[] args) {
 - System.out.print("Hello Ikhee"); // Hello Ikhee String дэлгэцэнд харуулна.
- 4)
 - a) Abcd bacd cbad bcad cabd acbd
 - b)
 - i) Таны сонгосон програмын аргумент юу вэ?
4 hello
 - ii) Тус аргументыг оруулан ажиллуулахад гарсан үр дүн эсвэл алдааны зурвасыг оруулж хэрхэн ажилсан талаар тайлбарла?
N тоо нь string Уртаас бага байх ёстой. Учир нь хүснэгтэн төрлийн утганд хандахад string уртаас хэтэрсэн утганд хандаж чадахгүй учир зарим үед java.lang.ArrayIndexOutOfBoundsException алдаа өгч байсан. Оруулсан string хувьд түүний үсэгнүүдийн байрыг оруулсан n тооноос хамааруулан сольж байрлуулж байсан.
 - iii) Яагаад энэ аргументыг сонгосныг тайлбарла.
Аргументээр орж ирэх утгаа permute функлуу дамжуулах учир эхний параметр нь Integer, дараагийг нь string төрөлтэй байх ёстой.
- 5)

a) Эхний гаралт:




b) Дараагийн гаралт:

```
Enter the temperature in F:
65
The temperature in C is: 18.3
```

6)

```
/**
 * @author ikhbayar.o
 * @version 1.1
 */
public class TempConvGUI {
    public static void main(String[] args) {
        String fahrString;
        double fahr, cel;
        while(true) {
            fahrString = JOptionPane.showInputDialog("Enter the
            temperature in F");
            if(!fahrString.isEmpty()) {
                fahr = Double.parseDouble(fahrString);
                cel = (fahr - 32) * 5.0 / 9.0;
                JOptionPane.showMessageDialog(null, "The temperature in
                C is, " + cel);
            }
        }
    }
}
```



7)

10)

```
package hucklebuckle;
```

```

/**
 * <p>
 * Second optional command-line parameter: ngames, the number of games to be
 * played on this run of the program, an integer between 0 and 9 inclusive.
 * Note: if only one command-line parameter is supplied, it is interpreted as
 * gridsize rather than as ngames, as indicated by the nested bracketing 9 on
 * the usage comment below.
 * <p>
 * Usage: hbbv1.1 [gridsize [ngames]]
 */
public class HuckleBuckle {

    public static final String VERSION = "1.1";

    public static void main(String[] args) {

        int gridSize = 5; // gridSize == 5, if there are no command-line args
        int nGames = 1; // 2 дахь аргумент байхгүй үед нэг удаа тоглоно гэдгийг
зааж өгнө.

        if (args.length > 0) {
            try {
                gridSize = Integer.parseInt(args[0]);
            } catch (NumberFormatException e) {
                System.err.println("Error: first arg (gridSize) must be an
integer. ");
                System.exit(1);
            }
            if (gridSize < 1 || gridSize > 40) {
                System.err.println("Error: first arg (gridSize) must be in
the range 1..40. ");
                System.exit(1);
            }
        }
        if (args.length > 1) {
            try {
                nGames = Integer.parseInt(args[1]);
            } catch (NumberFormatException e) {
                System.err.println("Error: second arg (nGames) must be an
integer. ");
                System.exit(1);
            }
            if (nGames < 0 || nGames > 10) {
                System.err.println("0 - 9 хооронд тоглолтын тоо байх
ёстой.");
                System.exit(1);
            }
        }

        if (args.length > 2) {
            System.err.println("Warning: too many args. ");
        }
        Game myGame = new Game(gridSize);

        myGame.play(nGames);
    }
}

```

```

    }
}

```

```
11) package hucklebuckle;
```

```

class Seeker extends Player {

    private Hider myHider;
    private int distanceMoved; // updated after every change of position

    Seeker(String name, Game game) {
        super(name, game);
        distanceMoved = 0;
    }

    void sayHelloTo(Hider h) {
        myHider = h;
        System.out.println(getName() + " says, \"Hi, \" + h.getName() + ", I'm "
+ getName() + ". Glad to meet you!\");
    }

    private void reportLocation() {
        System.out.println(getName() + " says, \"I'm at \" + getX() + ", \" +
getY() + ".\");
    }

    /**
     * Moves this seeker to (px, py).
     *
     * 12
     *
     * @param px the x-coord of the next position of this seeker
     * @param py the y-coord of the next position of this seeker
     *
     * If the distance moved is non-zero, the seeker reports their new
     * location.
     *
     * Constraint: this method should use Player.distance()
     */
    void moveTo(int px, int py) {
        if (distance(px, py) > 0.0) {
            distanceMoved += (int) distance(px, py);
            // To do: confirm that truncation is appropriate here, e.g.
            // that a Seeker who moves diagonally should count "one step"
            // for distances in the range [1.0, 2.0).
            setX(px);
            setY(py);
            reportLocation();
        }
    }
}

```

```

    void seek() {
        reportLocation(); // I report my initial location
        boolean moveRight = true; // I move left-to-right on even-numbered rows
        for (int y = 0; y < getGame().getGridSize(); y++) {
            for (int cx = 0; cx < getGame().getGridSize(); cx++) {
                int x = (moveRight ? cx : getGame().getGridSize() - cx -
1);

                moveTo(x, y);
                if (myHider.revealTemperature(this) == 0) { // Did I find
it?
                    System.out.println(getName() + " says, \"That was
fun! I walked " + distanceMoved
                                + " steps before I found it.\");
                    return; // I stop when I find the hidden object
                }
            }
            moveRight = !moveRight;
        }
        System.out.println(getName() + " says, \"I'm giving up. I took " +
distanceMoved + "steps before quitting.\");
    }
}

```