

# 2D Recognition Using SIFT

Introduction to Computational Photography:


EECS 395/495

Northwestern University

# A Little Quiz

---

How would you recognize the following types of objects?



Objects on an assembly line

# A Little Quiz

---

How would you recognize the following types of objects?



License plates

# A Little Quiz

---

How would you recognize the following types of objects?



Template



Rich 2D Image

Match “Interesting Points or Features”

# 2D Recognition Using SIFT

---

Recognize **2D objects** in real-world cluttered scenes using the **Scale Invariant Feature Transform (SIFT)**.

## Topics:

- (1) Local Appearance and Interest Points
- (2) Blob Detection
- (3) Scale-Space
- (4) The SIFT interest point detector
- (5) Matching and Results

# Raw Images are Hard to Match


---



Different Size, Orientation, Lighting, Brightness, ...

# Removing Sources of Variation


---



Matching becomes easier if we can  
remove variations like size and orientation.

# Some Patches are not “Interesting”

---







# What is an Interesting Point/Feature?

---

- Has **rich image content** (color variations, gradient variations, ...) within the local window
- Has well defined **representation (signature)** for matching/comparing with other points
- Has a well defined **position** in the image
- Should be **invariable to image rotation and scaling**
- Should be relatively **invariable to lighting** changes

# Are Lines/Edges Interesting?


---



Cannot “**Localize**” an Edge

# Are Blobs Interesting?

---



Yes! Blobs have **fixed position** and definite **size**.


# Blobs as Interest Points

---


We will use **Blob-like Features** for 2D recognition.

We need to:

- **Locate** a blob
- Determine its **size**
- Determine its **orientation**
- Formulate a **description** or signature that is independent of size and orientation




# Review: Gaussian Filter



Gaussian Filter is used for removing noise by smoothing


# Review: Derivative of Gaussian




Extremum of Derivative of Gaussian denotes an Edge

# Review: 2<sup>nd</sup> Derivative of Gaussian

$f$




$\nabla^2(n_\sigma)$



2<sup>nd</sup> Derivative of  
Gaussian







$\nabla^2(n_\sigma) * f$



Zero Crossings in 2<sup>nd</sup> Derivative of Gaussian denotes an Edge

# 1D Blobs


---




Examples of 1D Blob-like structures




# 1D Blob and 2<sup>nd</sup> Derivative of Gaussian



# 1D Blob and 2<sup>nd</sup> Derivative of Gaussian



# Characteristic Scale and Blob Size



Characteristic Scale: The  $\sigma$  at which 2<sup>nd</sup> Derivative attains its extreme value.

Characteristic Scale  $\propto$  Size of Blob



$$\frac{\text{Size of Blob A}}{\text{Size of Blob B}} = \frac{\sigma_A^*}{\sigma_B^*} ; \quad \frac{\text{Size of Blob B}}{\text{Size of Blob C}} = \frac{\sigma_B^*}{\sigma_C^*}$$

# 1D Blob Detection Summary

---

Given a 1D signal  $f(x)$ .

Compute  $\frac{\partial^2 n_\sigma}{\partial x^2} * f(x)$  at many scales  $(\sigma_0, \sigma_1, \sigma_2, \dots, \sigma_k)$ .

Find:

$$(x^*, \sigma^*) = \arg \max_{(x, \sigma)} \left| \frac{\partial^2 n_\sigma}{\partial x^2} * f(x) \right|$$

$x^*$ : Blob Position

$\sigma^*$ : Characteristic Scale (Blob Size)


# 2D Blob Detector

Normalized Laplacian of Gaussian (NLoG) is used as the 2D equivalent for Blob Detection.

Laplacian


$$\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2}$$

Gaussian




$n_\sigma$

LoG



$\nabla^2 n_\sigma$

NLoG



$\sigma^2 \nabla^2 n_\sigma$

Location of Blobs given by **Local Extrema** after applying Normalized Laplacian of Gaussian at many scales.


# Scale-Space




$S(x, y, \sigma_0)$



$S(x, y, \sigma_1)$



$S(x, y, \sigma_2)$



$S(x, y, \sigma_3)$

Increasing  $\sigma$ , Higher Scale, Lower Resolution

**Scale Space:** Stack created by filtering an image with Gaussians of different sigma( $\sigma$ )

$$S(x, y, \sigma) = n(x, y, \sigma) * I(x, y)$$

# Creating Scale-Space


---




$S(x, y, \sigma_0)$



$S(x, y, \sigma_1)$



$S(x, y, \sigma_2)$



$S(x, y, \sigma_3)$

...

Increasing  $\sigma$ , Higher Scale, Lower Resolution

Selecting sigma's to generate the scale-space:

$$\sigma_k = \sigma_0 s^k \quad k = 0, 1, 2, 3, \dots$$


where,  $s$ : Constant multiplier

$\sigma_0$ : Initial Scale


# Blob Detection using Local Extrema




$S(x, y, \sigma_0)$



$S(x, y, \sigma_1)$



$S(x, y, \sigma_2)$




$S(x, y, \sigma_3)$

...


$$\sigma^2 \nabla^2 S(x, y, \sigma)$$

(NLoG \* I(x, y))







# Blob Detection using Local Extrema




$S(x, y, \sigma_0)$



$S(x, y, \sigma_1)$




$S(x, y, \sigma_2)$





$S(x, y, \sigma_3)$

$$\sigma^2 \nabla^2 S(x, y, \sigma)$$

(*NLoG* \*  $I(x, y)$ )



# Comparison of Characteristic Scales



$\frac{\sigma_1^*}{\sigma_2^*}$ : Ratio of Blob Sizes

# 2D Blob Detection Summary

---

Given an image  $I(x, y)$ .

Convolve the image using NLoG at many scales  $\sigma$ .

Find: {

$$(x^*, y^*, \sigma^*) = \arg \max_{(x, y, \sigma)} |\sigma^2 \nabla^2 n_\sigma * I(x, y)|$$

or

$$(x^*, y^*, \sigma^*) = \arg \max_{(x, y, \sigma)} |\sigma^2 \nabla^2 S(x, y, \sigma)|$$

$(x^*, y^*)$ : Position of the blob


$\sigma^*$ : Size of the blob

# The SIFT Detector

## An Efficient Implementation of Blob Detector

Uses **Difference of Gaussian (DoG)** as an approximation of NLoG

$$\text{Difference of Gaussian(DoG)} = (n_{s\sigma} - n_{\sigma}) \approx (s - 1)\sigma^2 \nabla^2 n_{\sigma}$$




$$\text{DoG} \approx \text{NLoG}$$

# Extracting SIFT Interest Points



Image  
 $I(x, y)$




Gaussian  
Scale-Space  
 $S(x, y, \sigma)$

Difference of  
Gaussians (DoG)  
 $\approx \sigma^2 \nabla^2 S(x, y, \sigma)$


# Extracting SIFT Interest Points



Image  
 $I(x, y)$




# Extracting SIFT Interest Points






# Extracting SIFT Interest Points





# Extracting SIFT Interest Points




Interest Point  
Candidates

(includes weak extrema,  
bad contrast, ...)

SIFT  
Interest Points  
(after removing  
weak points)

# Extracting SIFT Interest Points



Interest Point  
Candidates

(includes weak extrema,  
bad contrast, ...)

SIFT  
Interest Points  
(after removing  
weak points)



Interest Point  
Depiction

# SIFT Detection Examples

---





# SIFT Detection Examples

---



# SIFT Detection Examples

---



# SIFT Scale Invariance

---

Use the characteristic scales to match sizes



# Computing the Principal Orientation

Use the histogram of gradient directions





Image gradient directions

$$\theta = \tan^{-1} \left( \frac{\partial I}{\partial y} / \frac{\partial I}{\partial x} \right)$$

Principal Orientation




Choose the most prominent gradient direction



# SIFT Rotation Invariance

---

Use the principal orientations to match rotation






# The SIFT Descriptor




---

“Describe” points so they can be compared



# Computing the SIFT Descriptor

Histograms of gradient directions over spatial regions



Invariant to Scale, Lighting, Brightness

# SIFT Results: Scale Invariance


---



SIFT detects corresponding features in images at different resolutions




# SIFT Results: Rotation Invariance



SIFT detects corresponding features in rotated images



# SIFT Robustness to Clutter



# Panorama Stitching using SIFT


---



Image 1



Image 2



Match SIFT Interest Points



# Panorama Stitching using SIFT


---



Transform/Warp one or both images so that corresponding SIFT points in images are aligned.

# Auto Collage using SIFT

---






# Auto Collage using SIFT


---



# SIFT for 3D Objects?



No Change in Viewpoint



30° Change in Viewpoint



90° Change in Viewpoint

# References

---

[Autopano] Software to make panoramas using SIFT. <http://user.cs.tu-berlin.de/~nowozin/autopano-sift/>

[Brown and Lowe 2002] M. Brown and D. Lowe. "Invariant Features from Interest Point Groups". *BMVC*, 2002.

[Harris and Stephens 1988] C. Harris and M. Stephens. "A Combined Corner and Edge Detector". *4<sup>th</sup> Alvey Vision Conference*, 1988.

[Lowe 2004] D. Lowe. "Distinctive Image Features from Scale-Invariant Keypoints". *IJCV*, 2004.

[Lindeberg 1994] T. Lindeberg. "Scale-Space Theory: A Basic Tool for Analysing Structures at Different Scales." *J. of Applied Statistics*, 1994.

[Matas 2002] J. Matas, O. Chum, M. Urban, and T. Pajdla. "Robust Wide Baseline Stereo from Maximally Stable Extremal Regions. *BMVC*, 2002.

[Mikolajczyk 2002] K. Mikolajczyk. "Detection of Local Features Invariant to Affine Transformations." *Ph.D. Thesis*, 2002.

# References

---

[Mikolajczyk 2004] K. Mikolajczyk and C. Schmid. "Scale and Affine Invariant Interest Point Detectors." *IJCV*, 2004.

[Mikolajczyk 2005] K. Mikolajczyk and C. Schmid. "A Performance Evaluation of Local Descriptors." *PAMI*, 2005.

[SIFT] SIFT Binaries. <http://www.cs.ubc.ca/~lowe/keypoints/>

[Witkin 1983] A. Witkin. "Scale-Space Filtering". *IJCAI*, 1983.

