

CivicPulse — File Index

Every tracked file in the repository, what it is for, and why it exists. 76 files · ~9,000 lines of TypeScript · ~1,250 lines of SQL.

Line counts are exact as of this document. Use this to find your way around; use [SOURCE-CODE.md](#) to understand how the pieces fit together.

Database — `supabase/`

Run these in the Supabase SQL Editor **in numerical order**. Every one is idempotent and safe to re-run.

File	Lines	Purpose
<code>SETUP.md</code>	163	Step-by-step setup: project creation, running migrations, granting yourself the control desk, the Cloudinary and cron options
<code>migrations/0001_init.sql</code>	221	Foundation. <code>grievance_tickets</code> , <code>admin_users</code> , the <code>current_phone()</code> / <code>is_admin()</code> helpers, ticket numbering, the workflow-column guard, RLS policies, and the <code>ticket-photos</code> storage bucket
<code>migrations/0002_escalation_cron.sql</code>	31	Documents the hourly <code>pg_cron</code> job that emails a department about tickets unresolved for 24h. The Edge Function it calls is not yet deployed
<code>migrations/0003_feedback.sql</code>	36	<code>platform_feedback</code> — anyone may insert (including signed-out visitors), only admins may read
<code>migrations/0004_profiles.sql</code>	129	<code>profiles</code> , mirroring name and phone out of <code>auth.users</code> so joins and policies can see identity. Includes the sync trigger and a backfill. Explicitly not an auth table
<code>migrations/0005_grant_admin.sql</code>	63	Promotes an already-registered account to the ward desk. Aborts loudly if no account has that phone, so a typo fails visibly instead of leaving <code>/admin</code> silently redirecting
<code>migrations/0006_storage_no_listing.sql</code>	52	Security fix. The original policy let anyone with the publishable key <i>list</i> every photo in the bucket, not just fetch one they had a link to. Drops it and adds admin-only listing
<code>migrations/0007_reject_tickets.sql</code>	119	Adds the <code>Rejected</code> status and <code>rejection_reason</code> , extends the workflow guard to cover it, and forces every citizen-filed report to start at <code>Submitted</code>
<code>migrations/0008_pulse_points.sql</code>	328	The reward system: <code>campuses</code> , the <code>pulse_points</code> ledger, <code>rewards</code> , <code>reward_codes</code> , <code>redemptions</code> , the award trigger and the atomic <code>redeem_reward()</code> function
<code>migrations/0009_upvotes.sql</code>	274	<code>ticket_upvotes</code> , the denormalised count, the <code>public_tickets</code> view (the privacy boundary), and haversine duplicate detection

Core services — `src/app/core/`

Framework-free logic and every call to Supabase. No component talks to the database directly.

File	Lines	Purpose
<code>models.ts</code>	266	Every shared type and constant — statuses, categories, urgencies, rejection reasons, description templates, ticket / profile / feedback / points / reward shapes. The single source of truth the rest of the app imports
<code>auth.service.ts</code>	244	Registration, sign-in, password change, admin lookup, and <code>normalisePhone</code> — the function whose output is a user's identity across the whole system
<code>tickets.service.ts</code>	259	Filing reports, the citizen's own list, the public regional feed, duplicate lookup, upvoting, and the admin workflow actions (status, category, rejection, proof)
<code>admin.service.ts</code>	125	Everything the control desk reads that is not a ticket: feedback, the citizen roster, per-person report counts, and the cross-table overview numbers
<code>points.service.ts</code>	82	Pulse Points — balance, ledger, reward catalogue, redemption. Has no <code>award()</code> method and could not have one: the browser has no write access to the ledger
<code>places.ts</code>	192	The campus and city pickers, with search that matches on institution, city, state or pincode
<code>escalation.ts</code>	98	Client-side mirror of the server's 24-hour escalation rule, so the countdown on <code>/escalations</code> matches what the cron job will actually do
<code>media.service.ts</code>	63	Photo upload. Uses Cloudinary when configured (unsigned preset, so no secret reaches the browser) and falls back to Supabase Storage otherwise
<code>institutions.ts</code>	60	The 26 campuses with coordinates and pincodes. Must stay in sync with the <code>campuses</code> table in migration 0008
<code>feedback.service.ts</code>	40	Platform feedback. Attaches the signed-in identity automatically and works fine without one
<code>auth.guards.ts</code>	34	<code>authGuard</code> and <code>adminGuard</code> . Convenience only — RLS is the real boundary
<code>supabase.errors.ts</code>	33	Turns opaque Postgres codes into sentences that name the fix, e.g. <code>PGRST205</code> → <i>"Run 0001_init.sql"</i>
<code>lightbox.service.ts</code>	31	Holds whichever photo is currently open full screen
<code>supabase.client.ts</code>	14	The client singleton. Publishable key only; the service-role key must never be imported from anything under <code>src/</code>
<code>auth.service.spec.ts</code>	53	Tests for phone normalisation and formatting — a tripwire, since changing that output silently orphans users from their reports

Pages — `src/app/features/`

All standalone and lazy-loaded.

File	Lines	Route	Purpose
home/home-page.ts	1542	/	The hero, animated map backdrop, campus/city picker, category picker, live capture flow and draft composer. The fast path from "I see a problem" to a filed report
admin/admin-reports.ts	566	/admin	The ticket queue — filters, status changes, category correction, rejection with reason, resolution proof upload, CSV export
points/pulse-points-page.ts	491	/pulse-points	The wallet: coin, balance, progress to the next reward, reward grid, claimed codes, full ledger
report/report-page.ts	415	/report	The full report form — urgency, department routing, description templates, duplicate check
issues/issues-page.ts	338	/issues	Public regional feed by city or pincode, with upvoting. Readable signed out
profile/profile-page.ts	332	/profile	The citizen's reports with a status trail, before/after photos, and any rejection reason
admin/admin-page.ts	260	/admin	The desk shell — overview stat strip over the three tabs
escalations/escalations-page.ts	245	/escalations	Live 24-hour countdown per unresolved ticket
auth/auth-page.ts	243	/auth	Sign in and register, phone + password, no OTP
security/security-page.ts	242	/security	Change password. Re-checks the current one, which Supabase does not require
resolved/resolved-page.ts	239	/resolved	Before-and-after proof gallery for the citizen's own closed tickets
admin/admin-citizens.ts	206	/admin	The registered-citizen roster, searchable, with report counts
admin/admin-feedback.ts	190	/admin	Platform feedback, filterable by sentiment. Read-only by design
admin/csv.ts	41	—	Hand-written CSV export with RFC 4180 quoting and a UTF-8 BOM so Excel does not mangle accented names
admin/csv.spec.ts	31	—	Tests for quote escaping, embedded commas and newlines, and null handling

Shared components — `src/app/shared/`

File	Lines	Purpose
<code>map-backdrop.ts</code>	408	The animated SVG map behind the hero. Hand-built, so it costs no map-tile requests
<code>camera-capture.ts</code>	406	The live-camera wizard: <code>getUserMedia</code> , review, then location consent. No file input — a saved photo cannot be submitted
<code>feedback-launcher.ts</code>	335	The floating feedback button and its dialog
<code>map-canvas.ts</code>	228	MapLibre canvas that recentres on the selected campus or the GPS fix
<code>duplicate-prompt.ts</code>	174	" <i>Already reported?</i> " — shows the nearby report's photo and asks whether it is the same problem. A question, never a block
<code>photo-lightbox.ts</code>	153	Full-screen photo viewer, mounted once at the app root. Closes on ✕, backdrop click or Escape
<code>photo-zoom.ts</code>	52	The <code>cpZoom</code> attribute that makes any <code></code> openable full screen, keyboard included, without touching its styling

App shell — `src/app/`

File	Lines	Purpose
<code>app.scss</code>	507	Navigation bar, profile popover, region search styling
<code>app.html</code>	195	The shell template — nav, profile menu with live counts, and the lightbox mount
<code>app.ts</code>	119	Nav state, popovers, region search, sign-out
<code>app.routes.ts</code>	67	Every route, its title, its guard and its lazy import
<code>app.spec.ts</code>	19	Smoke test that the shell renders
<code>app.config.ts</code>	7	Router and zoneless change detection

Entry, styling, environment — `src/`

File	Lines	Purpose
<code>styles.scss</code>	507	Global design tokens — the slate/emerald/amber palette, typography, and primitives (<code>.card</code> , <code>.pill</code> , <code>.btn-*</code> , <code>.field</code> , <code>.alert</code>)
<code>index.html</code>	23	The HTML shell and font loading
<code>main.ts</code>	5	Bootstrap
<code>environments/environment.ts</code>	38	Production config — Supabase URL, publishable key, the synthetic auth email domain, optional Cloudinary
<code>environments/environment.development.ts</code>	18	Same values for <code>ng serve</code> . Both must agree on <code>authEmailDomain</code> , since changing it locks out every registered user

Both environment files are **browser-safe by design**. The publishable key is meant to be public; RLS is what protects the data.

Configuration and tooling

File	Lines	Purpose
<code>angular.json</code>	86	Build targets and the dev/prod environment file swap
<code>README.md</code>	59	Repository landing page (still Angular CLI boilerplate — worth replacing)
<code>.gitignore</code>	49	Keeps <code>node_modules</code> , <code>dist</code> , <code>.vercel</code> and <code>.env</code> out of the repository
<code>.vscode/tasks.json</code>	42	Editor tasks
<code>package.json</code>	37	Dependencies, scripts, and the Node <code>22.x</code> pin that keeps Vercel on a version Angular supports
<code>tsconfig.json</code>	31	Strict-ish compiler options shared by app and tests
<code>.env.example</code>	19	Template for local tooling. The real <code>.env</code> is git-ignored and holds the service-role key, which must never appear under <code>src/</code>
<code>.editorconfig</code>	17	Whitespace conventions
<code>.prettierrc</code>	12	Formatting
<code>tsconfig.app.json</code> / <code>tsconfig.spec.json</code>	10 / 9	App and test compilation scopes
<code>.claude/settings.json</code>	7	Assistant tool permissions
<code>vercel.json</code>	6	Build command, output directory, and the SPA rewrite that stops <code>/admin</code> 404-ing on refresh
<code>.vscode/extensions.json</code>	4	Recommended extensions
<code>claude/claude.md</code>	112	Working notes and conventions for AI-assisted development
<code>public/favicon.ico</code>	—	Site icon

Documentation — docs/

File	Purpose
<code>SOURCE-CODE.md</code>	Architecture, the security model, data model, feature walkthrough, database functions, known gaps
<code>FILE-INDEX.md</code>	This file
<code>SIH- PRESENTATION.md</code>	Slide-by-slide content for the Smart India Hackathon deck

Reading order for someone new

1. `SOURCE-CODE.md §3` — the security model. Nothing else makes sense until you accept that the browser is untrusted and the database holds every rule.
2. `0001_init.sql` — the tables, the policies and the guard trigger.
3. `core/models.ts` — every shape the app passes around.
4. `core/tickets.service.ts` — the full lifecycle of a report.
5. `0008` and `0009` — the two features with real adversarial pressure on them: points and upvotes.