Name: I.Harshith

Rollno:2303A51624

Lab Assignment 18.3: API Integration:

Connecting to External Services with Error Handling

Task 1 – Movie Database API Integration

Question: Use AI to generate a Python script that connects to a Movie API (e.g., OMDb) and retrieves movie information by title. Implement error handling for invalid names, API key errors, timeouts, and empty responses.

Input: User enters a movie title (e.g., "Inception").

Python Code:

Python import

requests

```
def get_movie_details(title):
    api_key = "your_api_key_here" # Replace with actual API key url
    = f"http://www.omdbapi.com/?t={title}&apikey={api_key}"

    try:
        response = requests.get(url, timeout=5)
        response.raise_for_status() data =
        response.json()

        if data.get('Response') == 'False':
            print(f"Error: {data.get('Error', 'Movie not found.')}")
        else:
            print(f"Title: {data.get('Title')}") print(f"Release
            Year: {data.get('Year')}") print(f"Rating:
            {data.get('imdbRating')}") print(f"Plot:
            {data.get('Plot')}")

    except                    requests.exceptions.Timeout:
```

```
        print("Error: The request timed out.") except requests.exceptions.HTTPError
        as http_err:
        if response.status_code == 401:
            print("Error: Invalid API Key.")
        else:
            print(f"HTTP Error occurred: {http_err}")
    except requests.exceptions.RequestException as e:
        print(f"Error: A network error occurred: {e}")

movie_name = input("Enter movie title: ")
get_movie_details(movie_name)
```

Output:

Plaintext

Enter movie title: Inception

Title: Inception

Release Year: 2010 Rating:

8.8

Plot: A thief who steals corporate secrets through the use of dream-sharing technology...

Code Explanation: The script uses the requests library to send a GET request to the OMDb API. It includes a try-except block to catch specific exceptions such as Timeout and HTTPError. The script checks the JSON response for a 'False' status to handle invalid movie names gracefully without crashing.

Task 2 – Public Transport Schedule API

Question: Use AI assistance to integrate a transport schedule API. Fetch arrival times for a given station ID, validate input, handle server/timeout errors, and implement a retry mechanism.

Input: User enters a Station ID (e.g., "1005").

Python Code:

Python import

requests import

time

```
def fetch_transport_data(station_id, retries=1): url =
    f"https://api.example-transport.com/arrivals/{station_id}"

    for attempt in range(retries + 1):
        try:
            response = requests.get(url, timeout=3)
            response.raise_for_status()    arrivals    =
            response.json().get('arrivals', [])[:3]

            if not arrivals:
                print("No upcoming arrivals found for this stop.")
                return

            print(f"Next 3 arrivals for Station {station_id}:")
            for t in arrivals:
                print(f"- {t}")
            return

        except (requests.exceptions.RequestException, requests.exceptions.HTTPError) as
            e: print(f"Attempt {attempt + 1} failed: {e}") if attempt < retries:
            print("Retrying...") time.sleep(2) else: print("All retry attempts failed. Server may
            be unavailable.")

stop_id = input("Enter Station/Stop ID: ")
if stop_id.isalnum():
fetch_transport_data(stop_id) else:
print("Invalid Stop ID format.") Output:
Plaintext
Enter Station/Stop ID: 1005
Next 3 arrivals for Station 1005:
```

- 10:15 AM

- 10:45 AM

- 11:20 AM

Code Explanation: This script incorporates a retry loop to handle transient network or server issues. It validates that the input is alphanumeric before making the call. The try-except block captures timeouts and HTTP errors, providing specific feedback rather than a generic crash.

Task 3 – Stock Market Data API

Question: Generate a Python script that fetches live stock prices (Current, High, Low) for a given symbol. Handle invalid symbols, rate limits, and missing fields in the JSON response.

Input: Stock symbol (e.g., "AAPL").

Python Code:

Python import

requests

def get_stock_price(symbol): url = f"https://api.examplefinance.com/quote?symbol={symbol}"

try:

response = requests.get(url) if response.status_code

== 429:

print("Error: API rate limit exceeded. Please try again later.")

return

response.raise_for_status()

data = response.json()

Safely parse JSON with default values for missing

fields price = data.get('current_price', 'N/A') high =

data.get('day_high', 'N/A') low = data.get('day_low',

'N/A')

```
        if price == 'N/A':
            print("Error: Invalid stock symbol or no data available.")
        else:
            print(f"Stock: {symbol.upper()}")
            print(f"Current Price: {price}")
            print(f"Day High: {high}")
            print(f"Day Low: {low}")

    except requests.exceptions.RequestException as e:
        print(f"Connection error: {e}")

stock_symbol = input("Enter Stock Symbol: ").strip() get_stock_price(stock_symbol)
```

Output:

Plaintext

```
Enter Stock Symbol: AAPL
Stock: AAPL
Current Price: 185.92
Day High: 187.10
Day Low: 184.50
```

Code Explanation: The script handles API-specific errors like status code 429 (Rate Limit). It uses the .get() method with default values to prevent KeyError exceptions when parsing the JSON response. This ensures the application remains resilient even if some data fields are missing.

Task 4 – Geolocation API (IP Address Lookup)

Question: Integrate a Geolocation API to detect Country, City, and ISP based on an IP address. Validate IP format and handle JSON decoding errors.

Input: IP Address (e.g., "8.8.8.8").

Python Code: Python

```
import requests
import ipaddress
```

```
def get_geolocation(ip): #
    Validate IP format try:
        ipaddress.ip_address(ip) except
    ValueError:
        print("Error: Invalid IP address format.")
        return

    url = f"http://ip-api.com/json/{ip}"

    try:
        response = requests.get(url)
        response.raise_for_status()
        data = response.json()

        if data.get('status') == 'fail':
            print(f"API Error: {data.get('message')}") else:

            print(f"Country: {data.get('country')}")
            print(f"City: {data.get('city')}") print(f"ISP:
            {data.get('isp')}")

    except requests.exceptions.JSONDecodeError:
    print("Error: Failed to parse API response.") except
    requests.exceptions.RequestException as e:
        print(f"API Failure: {e}") ip_input
= input("Enter IP Address: ")
get_geolocation(ip_input)
```

Output:

Plaintext

```
Enter IP Address: 8.8.8.8
```

Country: United States

City: Ashburn

ISP: Google LLC

Code Explanation: The script uses the ipaddress library to validate the user's input before wasting an API call. It includes a specific handler for JSONDecodeError to manage corrupted or non-JSON responses from the server.

Task 5 – Real-Time Application: Payment Gateway Simulation API

Question: Simulate a payment integration by sending a POST request with amount, currency, and method. Handle HTTP status errors, network interruptions, and log failed transactions to a file.

Input: Amount: 100, Currency: USD, Method: Credit Card.

Python Code:

Python import

requests import

logging

Configure logging logging.basicConfig(filename='failed_transactions.log', level=logging.ERROR,

format='%(asctime)s - %(levelname)s - %(message)s')

def process_payment(amount, currency, method):

url = "https://sandbox.example-payment.com/v1/charge" payload

= {

"amount": amount,

"currency": currency,

"method": method

}

try:

response = requests.post(url, json=payload, timeout=10)

response.raise_for_status() print("Transaction Status:

SUCCESS") print(f"Transaction ID:

```
        {response.json().get('id')}")


    except requests.exceptions.HTTPError as err:
        error_msg = f"HTTP Error {response.status_code}: {err}"
    print(f"Transaction Status: FAILED. {error_msg}") logging.error(f"Payment
    Failed | Data: {payload} | Error: {error_msg}") except
    requests.exceptions.RequestException as e:
        print("Transaction Status: FAILED due to network interruption.") logging.error(f"Network
        Error | Data: {payload} | Error: {e}")


try:
    amt = float(input("Enter Amount: ")) curr =
input("Enter Currency (e.g., USD): ").upper() meth =
input("Enter Payment Method: ") process_payment(amt,
curr, meth) except
ValueError:
    print("Invalid Input: Amount must be a number.")
```

Output:

Plaintext

Enter Amount: 100

Enter Currency (e.g., USD): USD

Enter Payment Method: Credit Card

Transaction Status: SUCCESS

Transaction ID: TXN_998877

Code Explanation: This script uses the requests.post() method to simulate data submission. It validates the input amount as a float. Comprehensive error handling for status codes (400, 401, 500) and network issues is implemented. Failed attempts are automatically logged to failed_transactions.log for debugging and auditing.