

Turtle-WoW / Tortoise-WoW Extended - Master Command Reference & Architecture Guide

This document is the canonical CLI operational reference and architecture guide for **Tortoise-WoW Extended** ([twow project/tortoise-wow](#)), unifying upstream VMaNGOS bugfix porting, native Turtle-WoW core restoration, deterministic bug proving, isolated worktree builds, multi-factor priority ranking, database safety auditing, and release lifecycle management.

TIP

Universal Terminal Invocation All commands can be executed from any PowerShell console or terminal without changing current directory: `""powershell & "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" <command> [arguments] [options] ""`

Master Table of Contents (Index)

- [1. Overview & Operational Principles](#)
- [2. Architecture & Pipeline Flow](#)
- [3. Workflow Lifecycle of a Candidate Fix](#)
- [4. Master Command Reference: Core Automation Commands](#)
- [5. Master Command Reference: Extended Engineering Commands](#)
- [6. Verification Modes: FAST vs NORMAL vs DEEP](#)
- [7. Automatic Mode Escalation Rules](#)
- [8. DryRun Mode & Safety Guarantees](#)
- [9. Auto-Pilot Mode & Autonomous Batch Processing](#)
- [The One-Command End-to-End Pipeline](#)
- [Staging-Only Mode vs Auto-Commit Mode](#)
- [Clean CLI Invocations \(From Default Location / Any Prompt\)](#)
- [Running Auto-Pilot: With Tier vs Without Tier](#)
- [How Candidates Are Selected Without a Tier](#)
- [10. Roadmap Research, Commit Auditing & Catching New Upstream Commits \(\[task roadmap-refresh\]\(#\) \)](#)
- [11. Build Profiles & Compiler Toolchain](#)
- [12. Baseline Health Check & SHA Pinning](#)
- [13. Bug-Existence Proving Engine](#)
- [14. Database Safety, Schema Catalog & Provenance](#)
- [15. DBC, Client & Core Parity Auditor](#)
- [16. Crash Dump & Server Log Triage](#)
- [17. Worktree Isolation & Cleanup Management](#)
- [18. Run IDs, Idempotency & Resumption](#)
- [19. Canonical 30-State Machine](#)
- [20. CI / GitHub Actions PR Workflows](#)
- [21. Release Checkpoints & Manifest Generation](#)
- [22. Critical Safety Warnings](#)
- [23. Troubleshooting & Common Failure States](#)
- [24. Expected Status & Verdict Reference Values](#)
- [25. Architectural Strengths & Engineering Guarantees](#)
- [26. Daily Cheat Sheet & Top Fast Commands](#)

1. Overview & Operational Principles


The Tortoise-WoW porting system bridges upstream vanilla bugfixes ([vmangos/core](#)) with the customized Turtle-WoW 1.12.1/1.18.1 server core ([Ildourol/tortoise-wow-extended](#)).

Fundamental Engineering Invariants:


1. **Deterministic-First Authority:** Heuristics classify; deterministic engines prove; AI assists on ambiguity but NEVER acts as the sole validation gate.
2. **Standardized Exit Codes:**
- 0 : PASS (Operation completed successfully and verified).
 - 1 : VALIDATION / COMPATIBILITY FAILURE (Invariant violated, collision, or check failed).
 - 2 : TOOL / ENVIRONMENT FAILURE (Missing binary, invalid repo, git error).
 - 3 : INTERNAL / SCHEMA FAILURE (Malformed contract, schema validation failure).
3. **Strict Worktree Isolation:** All candidate patches and build checks execute exclusively in dedicated Git worktrees (`.worktrees/PORT-XXXX/`). The user's primary working tree is never touched, reset, or dirtied.
4. **No Destructive Rollbacks:** `git checkout .`, `git reset --hard`, and `git clean -fd` are strictly prohibited on the target repository.
5. **No Production Database Direct Writes:** Audits analyze SQL migrations offline against cached catalog schemas (`config/schema_catalog.json`).
6. **Compile and Link Do Not Imply Startup:** Server health verifies compile, link, and startup/smoke milestones separately.
7. **Single-Writer Constraint:** Compilations through MSVC 2022 / Ninja acquire single-writer synchronization to prevent compiler file locking and git index corruption.

2. Architecture & Pipeline Flow

The orchestration architecture consists of three interconnected subsystems feeding through canonical state stores:



3. Workflow Lifecycle of a Candidate Fix



4. Master Command Reference: Core Automation Commands

Command	Full Syntax	Mode	Access	AI Usage	Build Usage	DB Usage	Description	Migration Audit	Unified porting pipeline for upstream donor commits.
task auto-pilot	task.ps1 auto-pilot [N] [-Tier 1-5] [-Mode M]	Variable	Write (Worktree)	Advisory	Full MSVC	Migration Audit	One-command autonomous batch port & commit for \$N\$ commits (default workflow).		
task auto-port	task.ps1 auto-port <sha> [-Mode M] [-DryRun]	Variable	Write (Worktree)	Advisory	Full MSVC	Migration Audit	One-command end-to-end port & commit for a single commit.		
task port	`task.ps1 port <sha> [-Mode Fast\`	Normal\`	Deep] [-DryRun] [-AutoCommit]`	Variable	Write (Worktree)	Advisory	Patch-Aware		
task port-batch	task.ps1 port-batch <N> [-Tier 1-5] [-Mode M] [-DryRun] [-AutoCommit]	Variable	Write (Worktree)	Advisory	Patch-Aware	Migration Audit	Batch executes porting pipeline on next \$N\$ curated candidate commits.		
task build	task.ps1 build <profile>	Fast/Deep	Execute	None	Full MSVC	None	Builds server profile (world , auth , sql-only , playerbots).		
task build-packages	task.ps1 build-packages	Normal	Write (Worktree)	None	Full MSVC	Offline Audit	Compiles, verifies, and commits all staged PORT-XXXX and CORE-XXXX packages in worktree.		
task 2	task.ps1 2 <sha/topic>	Fast	Read-only	None	None	None	Searches 22,155 indexed forum threads for bug discussions and mechanics lore.		

Command	Full Syntax	Mode	Access	AI Usage	Build Usage	DB Usage	Description
task 3	task.ps1 3 [tbl] [id]	Fast	Read-only	None	None	Offline Catalog	Audits pending database migration SQL or scalps table entity details.
task 4	task.ps1 4 <sha>	Normal	Read-only	Advisory	None	None	Generates bounded AI semantic dossier with touched code and context lines.
task 5	task.ps1 5 <topic>	Normal	Read-only	Advisory	None	Offline Catalog	Native Turtle core specification auditor for missing custom features.
task 6	task.ps1 6 <id/query>	Fast	Read-only	None	None	Online DB API	Queries official Turtle Online DB viewer for item, spell, and creature tooltips.
task scalp	task.ps1 scalp <tbl> <id> [-Diff] [-Export]	Fast	Read-only	None	None	Brotalnia/Base	Extracts entity definitions and generates side-by-side vanilla vs Turtle diffs.
task extract	task.ps1 extract <tbl> <id>	Fast	Read-only	None	None	Brotalnia/Base	Alias for task scalp .
task restore	task.ps1 restore <topic> [-StageTemplate]	Normal	Staging	Advisory	None	Offline Catalog	Audits official staff posts and stages native core restoration manifests.
task restore-batch	task.ps1 restore-batch <N>	Normal	Staging	Advisory	None	Offline Catalog	Batch audits next \$N\$ un-audited Turtle patch topics from roadmap queue.
task status	task.ps1 status	Fast	Read-only	None	None	None	Displays live system metrics, queue counts, HEAD SHAs, and active run IDs.
task pdf	task.ps1 pdf	Fast	Read-only	None	None	None	Compiles COMMAND_REFERENCE.md to HTML and exports high-quality PDF via Edge.

5. Master Command Reference: Extended Engineering Commands

Command	Full Syntax	Mode	Access	AI Usage	Build Usage	DB Usage	Description
task test	task.ps1 test	Fast	Read-only	None	None	None	Executes comprehensive 38-case Pester test suite covering all invariants.
task prove	task.ps1 prove <sha>	Fast	Read-only	None	None	None	Deterministic bug prover inspecting diff hunks and target AST existence.
task relations	task.ps1 relations <sha>	Fast	Read-only	None	None	None	Analyzes commit reverts, duplicate fixes, and file overlap relationships.
task dependencies	task.ps1 dependencies <sha>	Fast	Read-only	None	None	None	Inspects git commit DAG for missing parents and prerequisite commits.
task rank	task.ps1 rank	Fast	Read-only	None	None	None	Computes 12-factor priority scores (0.0–100.0) across all pending candidates.
task next	task.ps1 next	Fast	Read-only	None	None	None	Returns the single highest-priority eligible candidate commit to port.
task plan	task.ps1 plan <sha> [-Mode M]	Variable	Read-only	None	None	None	Generates a complete verification plan and dry-run report without disk writes.
task build-profile	task.ps1 build-profile <sha>	Fast	Read-only	None	None	None	Selects optimal build target (world , auth , sql-only , playerbots).
task smoke	task.ps1 smoke [-Mode M]	Fast/Deep	Execute	None	Binary Test	None	Disposable server startup smoke test evaluating mangosd.exe & realmd.exe .
task crash	task.ps1 crash <path>	Fast	Read-only	None	None	None	Parses server crash dump / log, categorizes failure, and extracts stack frames.

Command	Full Syntax	Mode	Access	AI Usage	Build Usage	DB Usage	Description
task triage	task.ps1 triage <logfile>	Fast	Read-only	None	None	None	Categorizes log errors across 17 structured failure categories.
task baseline	task.ps1 baseline [-Force]	Fast	Read-only	None	Binary Test	None	Checks and caches compile, link, and startup health of target repository HEAD.
task state	task.ps1 state	Fast	Read-only	None	None	None	Outputs canonical pipeline state store summary and active run statistics.
task config-check	task.ps1 config-check	Fast	Read-only	None	None	None	Validates repository paths, toolchain binaries, and schema configuration.
task state-check	task.ps1 state-check	Fast	Read-only	None	None	None	Verifies state store integrity, active runs, and candidate transition history.
task worktree	task.ps1 worktree	Fast	Read-only	None	None	None	Lists all currently active and managed isolated Git worktrees.
task worktree-cleanup	task.ps1 worktree-cleanup [-DryRun]	Fast	Write (Worktree)	None	None	None	Safely purges obsolete or completed worktrees inside <code>.worktrees/</code> .
task parity	task.ps1 parity	Fast	Read-only	None	None	Offline DBC	Audits binary client DBCs (<code>ChrRaces</code> , <code>Map</code> , <code>Spell</code>) against server code.
task release-check	task.ps1 release-check	Fast	Read-only	None	None	Offline Catalog	Evaluates all release readiness gates (tree clean, invariants pass, baseline).
task release-manifest	task.ps1 release-manifest [name]	Fast	Write (Docs)	None	None	None	Generates a signed machine-readable release manifest in <code>docs/releases/</code> .
task tag-release	task.ps1 tag-release <name>	Fast	Write (Git Tag)	None	None	None	Gated Git tag creation; rejects release if any readiness gates fail.
task roadmap-refresh	task.ps1 roadmap-refresh [-FetchLatest]	Fast	Read/Write (Roadmap)	None	None	None	Audits all 7,300+ upstream commits, refreshes queue, and fetches latest commits.

6. Verification Modes: FAST vs NORMAL vs DEEP

The system provides three strictly defined verification modes. Each mode enforces all safety invariants, but varies in compilation scope, runtime validation depth, and AI assistance:

Verification Mode	Code Analysis	Invariant Scan	DB Schema Audit	Build Execution	Startup Smoke Test	Runtime Test	AI Consultation	Typical Duration
Fast	Deterministic diff matching	Full manifest invariant scan	Full 413-table column audit	Skipped	Skipped	Skipped	Skipped (Deterministic only)	1 – 3 seconds
Normal	Diff + Nearby context AST	Full manifest invariant scan	Full 413-table column audit	Patch-Aware (<code>world</code> / <code>auth</code>)	Disposable startup check	Optional / Smoke	Advisory (On ambiguity only)	30 – 90 seconds
Deep	Full call-graph & packet trace	Full manifest invariant scan	Full 413-table column audit	Full MSVC Solution	Full disposable smoke test	Reproducer verification	Advisory + Contextual trace	2 – 5 minutes

Mandatory Common Checks (Enforced Across ALL Modes):

- Deterministic Bug-Existence Proof:** Verification that the defect exists in target and was not previously fixed or intentionally diverged.
- Compatibility Invariant Scan:** Verifies `MAX_RACES = 11` , `sTWDebuff` , `SCRIPT_COMMAND_TAKE_MONEY = 93` , and protected manager hooks.
- Database Migration Safety Check:** Forbidden progressive versioning columns (`patch` , `build`) and custom ID boundaries (`spell_template` >= 40000, world templates >= 300000).
- Target Working Tree Cleanliness:** Main checkout is verified clean before worktree creation.

7. Automatic Mode Escalation Rules

The mode engine (`ModeEngine.ps1`) evaluates candidate risk factors. It automatically escalates execution modes to protect server integrity:

Fast $\rightarrow$ Normal Escalation Triggers:

- Candidate introduces or modifies SQL database migration files (`sql/database_updates/`).
- Candidate possesses one or more unresolved predecessor commit dependencies.
- Bug-existence confidence score is below \$0.85\$.
- Candidate modifies core spell mechanics (`SpellMgr.cpp` , `SpellEffects.cpp`).

Normal $\rightarrow$ Deep Escalation Triggers:

- Commit subject or diff touches security keywords: `crash` , `packet` , `opcode` , `thread` , `mutex` , `deadlock` , `leak` , `exploit` , `auth` , `crypto` .
- Touched files reside in security or networking subsystems (`src/shared/Auth/` , `src/game/WorldSocket.cpp` , `src/game/Opcodes.cpp`).
- Concurrency constructs are modified (locks, atomic variables, threading queues).

IMPORTANT

No Automatic Downgrade Policy Under no circumstances will an explicitly requested mode be automatically downgraded (e.g., `-Mode Deep` will never execute as `Normal` or `Fast`).

8. DryRun Mode & Safety Guarantees

Running any porting or cleanup command with `-DryRun` guarantees that **zero modifications** are written to the target repository or filesystem:

```
# Plan candidate 448df9ba0 without touching repository
task.ps1 port 448df9ba0 -DryRun
```

DryRun Guarantees:

- No Git branches created (`port/PORT-XXXX` is not created).
- No Git worktrees spawned (`.worktrees/` remains unchanged).
- No compiler or linker invocations executed.
- No database files modified.
- Outputs complete execution plan: Bug verdict, priority score, resolved mode, required build profile, and dependency links.

9. Auto-Pilot Mode & Autonomous Batch Processing

Auto-Pilot Mode enables hands-free, continuous candidate evaluation, bug proving, worktree provisioning, patch normalization, compatibility auditing, and candidate staging across multiple commits without manual per-commit intervention.

The One-Command End-to-End Pipeline

When you want an autonomous, zero-friction pipeline that takes upstream commits all the way to candidate branch commits in a single pass, use **Auto-Pilot Mode**:

```
# Auto-Pilot a batch of 10 candidates with automatic compilation and git commit:
task.ps1 auto-pilot 10

# Auto-Pilot with tier filter:
task.ps1 auto-pilot 10 -Tier 1
task.ps1 auto-pilot 10 1

# Auto-Pilot a specific single commit:
task.ps1 auto-port 448df9ba0
```

How the Chained Pipeline Works:

1. Forum & Mechanics Intelligence Scout (`Search-ForumArchive.ps1`):

- Automatically mines 22,155 indexed Turtle-WoW forum threads using keywords extracted from the commit subject. Identifies any related mechanics discussions, player bug reports, or staff statements.
2. **Database & Migration Safety Audit (`Audit-DatabaseMigrations.ps1`):**
- Checks whether the upstream commit touches SQL migrations. Inspects table definitions against the 413-table schema catalog, verifies Turtle custom ID ranges (creature >= 300,000, spell >= 40,000), checks for forbidden progressive columns, and stages any required SQL files into `tools/queue/staging_sql/`.
3. **AI Context Assembly & Semantic Dossier (`Invoke-AiAudit.ps1`):**
- Performs bounded diff context extraction, checks surrounding code ASTs, evaluates Turtle custom divergences (`MAX_RACES=11` , `sTWDebuff`), generates an AI audit dossier in `tools/queue/ai_dossiers/<sha>.md` , and packages the candidate into `tools/queue/02_ready_to_build/PORT-XXXX.json` .
4. **Isolated Worktree Builder & Committer (`Build-ReadyPackages.ps1`):**
- Creates an isolated git worktree (`.worktrees/candidate-PORT-XXXX`), applies the patch safely, enforces build profiles (`world` , `auth` , `sql-only`), compiles via MSVC 2022, and commits to a candidate branch with full provenance recorded in `tools/state/state_store.json` .

FAQ: Staging Mode vs Auto-Pilot Mode

Execution Command	Staged to Queue?	Automatically Compiled?	Automatically Committed?	Need follow-up build?
<code>task.ps1 port-batch 10</code>	Yes (<code>02_ready_to_build/</code>)	No	No	YES (Review first, then compile via <code>task.ps1 build-packages</code>)
<code>task.ps1 auto-pilot 10</code>	Yes	Yes (in worktree)	Yes (candidate branch)	NO (Fully automated in 1 command)
<code>task.ps1 port-batch 10 -AutoCommit</code>	Yes	Yes (in worktree)	Yes (candidate branch)	NO (Fully automated in 1 command)
<code>task.ps1 auto-port <sha></code>	Yes	Yes (in worktree)	Yes (candidate branch)	NO (Fully automated in 1 command)

NOTE

- Use `task.ps1 port-batch 10` when you want a **review step** (inspecting AI dossiers and patches in `tools/queue/02_ready_to_build/` before compiling).

- Use `task.ps1 auto-pilot 10` (or `task.ps1 auto-port`) when you want a **hands-off single command** that finishes the entire process and commits verified candidate branches automatically.

Clean CLI Invocations (From Default Open Location / Any Directory)

You do **not** need to `cd` into the project repository. All modules dynamically resolve repository roots from `$PSScriptRoot` .

Direct Invocation from PowerShell (from `C:\Users\Admin>` or any path):

```
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" auto-pilot 10
```

3. Permanent Global Setup via PowerShell `$PROFILE` (Recommended):

Run this once in PowerShell to make `task` globally accessible from any terminal:

```
if (!(Test-Path $PROFILE)) { New-Item -ItemType File -Path $PROFILE -Force | Out-Null }
Add-Content $PROFILE "`nfunction task { & 'C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1'
```

Once added, open a new PowerShell prompt anywhere and simply type:

```
task auto-pilot 10
task status
task next
task roadmap-refresh
```

Running Auto-Pilot Mode: With Tier vs Without Tier

A. Running WITH Tier Specification:

When you want to focus exclusively on a specific severity or architectural domain:

```
# Port the next 10 Tier 1 candidates (Crashes, Leaks, Deadlocks, Exploits)
task.ps1 port-batch 10 -Tier 1 -Mode Normal

# Port the next 10 Tier 2 candidates (Combat Accuracy, Spells, Formulas)
task.ps1 port-batch 10 -Tier 2 -Mode Normal
```

B. Running WITHOUT Tier Specification:

When you omit the `-Tier` argument:

```
# Auto-Pilot without tier: ports the next 10 highest-value candidates
task.ps1 port-batch 10 -Mode Normal
```

How Does Auto-Pilot Choose Commits Without a Tier?

1. Natural Architectural Hierarchy in `CRUCIAL_COMMITS_QUEUE.csv`:

The master queue is pre-sorted by architectural urgency: **Tier 1 (Crashes/Exploits)** $\rightarrow$ **Tier 2 (Combat/Spells)** $\rightarrow$ **Tier 3 (NPC/AI)** $\rightarrow$ **Tier 4 (Movement/Maps)** $\rightarrow$ **Tier 5 (General)**. Without a tier filter, Auto-Pilot processes strictly down this natural hierarchy.

2. Dynamic 12-Factor Priority Scoring Engine (`task rank` / `task next`):

In addition to tier order, every candidate is scored dynamically from \$0.0\$ to \$100.0\$ by `PriorityEngine.ps1`:

- Crash Severity: \$+25\$ points
- High Player Impact: \$+20\$ points
- Security / Exploit Risk: \$+20\$ points
- Low Target File Churn: \$+15\$ points
- Dependency Satisfaction: \$+10\$ points
- Baseline Stability: \$+10\$ points
- Non-Applicable / Intentional Divergence: **\$0.0\$ score hard gate** (instantly skipped).

You can inspect this ranking at any time with `task rank` or retrieve the single best candidate with `task next`.

3. State Store & Git History Deduplication:

Auto-Pilot automatically cross-references `tools/state/state_store.json` and the target `tortoise-wow` git history. Any candidate that has already been evaluated (`ALREADY_FIXED` , `NOT_APPLICABLE` , `TURTLE_INTENTIONAL_DIVERGENCE` , `PACKAGE_READY` , or `RELEASED`) is **automatically bypassed**, ensuring zero redundant work.

The Recommended 3-Phase Auto-Pilot Runbook

To run Auto-Pilot with 100% safety and predictability:

```
# Phase 1: Pre-Flight DryRun (Evaluates bug prover and outputs plan without writing files)
task.ps1 port-batch 10 -DryRun

# Phase 2: Isolated Autonomous Porting (Runs in .worktrees/PORT-XXXX/ with safety checks)
task.ps1 port-batch 10 -Mode Normal

# Phase 3: Single-Writer Candidate Build & Branch Commit
task.ps1 1
```

Auto-Pilot Safety Guarantees:

- **Zero Working Tree Contamination:** All patch application and test compilation occur strictly in `.worktrees/PORT-XXXX/`. The main repository working tree remains 100% untouched.

- **Stale Package Auto-Invalidation:** If the target repository HEAD advances during a batch run, any staged package whose pinned base SHA does not match is automatically invalidated.
- **Non-Destructive Rollback:** If a patch fails compilation or invariant checks, the isolated worktree is safely deleted without ever executing `git reset --hard` or `git checkout .`

10. Roadmap Research, Commit Auditing & Catching New Upstream Commits (`task roadmap-refresh`)

The upstream VMaNGOS repository (`vmangos/core`) continuously accepts new bugfixes and accuracy patches. The orchestration framework includes an automated research and auditing engine to catch, classify, and queue these new commits:

```
# Audit all local upstream commits and regenerate the roadmap
task.ps1 roadmap-refresh

# Fetch new commits from GitHub upstream remote, merge development, and audit
task.ps1 roadmap-refresh -FetchLatest
```

How the Roadmap List Refreshes:

- Upstream Remote Fetch (`-FetchLatest`):** When `-FetchLatest` is passed, the engine runs `git fetch origin` and `git merge --ff-only origin/development` inside `reference-upstreams/vmangos-core`, pulling down all new upstream commits.
- Donor Commit Scanning:** Scans all 7,300+ upstream commits in repository history (newest to oldest).
- Cross-Referencing Port History:** Compares every upstream commit SHA against commits already merged into `tortoise-wow` and documented in `docs/BACKPORT_HISTORY.md`.
- Older Superseded Duplicate Elimination:** Detects intermediate or superseded fixes and removes older duplicates so only modern final fixes are queued.
- Architectural Tier Classification:** Automatically assigns each commit to Tier 1 through Tier 5 based on modified subsystems and commit subjects.
- Artifact Generation:**
 - Updates `tools/porting/CRUCIAL_COMMITS_QUEUE.csv` (the active queue of 5,092 deduplicated crucial candidates).
 - Updates `tools/porting/ALL_AVAILABLE_COMMITS_REFERENCE.csv` (complete 7,339-commit catalog).
 - Re-renders `docs/ROADMAP.md` with updated metrics and live backlog status.

11. Build Profiles & Compiler Toolchain

The build engine (`BuildEngine.ps1`) optimizes build times by targeting only the solution components touched by the candidate patch:

Build Profile	Affected Subsystems	MSVC Target Project	Typical Compile Time
<code>world</code>	<code>src/game/</code> , <code>src/scripts/</code>	<code>mangosd</code>	~45 seconds
<code>auth</code>	<code>src/realmd/</code> , <code>src/shared/Auth/</code>	<code>realmd</code>	~15 seconds
<code>sql-only</code>	<code>sql/</code> , documentation	None (Bypasses compilation)	Instant (0s)
<code>playerbots</code>	<code>src/game/playerbot/</code>	<code>mangosd</code> (PlayerBots profile)	~45 seconds
<code>docs-only</code>	<code>docs/</code> , <code>tools/</code>	None	Instant (0s)

12. Baseline Health Check & SHA Pinning

The baseline checker (`BaselineChecker.ps1`) verifies the compile, link, and startup state of the unchanged target repository before applying candidate patches:

```
task.ps1 baseline
```

- **Cached Baseline:** Once verified for a target HEAD SHA, baseline status is cached in `tools/state/state_store.json`.
- **Three-Tier Classification:**

- **COMPILE_FAIL** : Target source fails compilation prior to patch.
- **LINK_FAIL** : Compilation passes, but linker errors occur.
- **STARTUP_FAIL** : Binary links, but crashes on startup (e.g. missing DBC or DB config).
- **HEALTHY** : Compile, link, and startup all succeed.

13. Bug-Existence Proving Engine

The bug prover (**BugProver.ps1**) executes deterministic analysis before any candidate is ported:

```
task.ps1 prove 448df9ba0
```

Deterministic Verdicts:

- **BUG_PRESENT** : Target source file contains the exact unpatched code pattern or cleanly applicable bug signature.
- **ALREADY_FIXED** : Target source already contains the upstream fix or equivalent logic from previous commits.
- **NOT_APPLICABLE** : Commit modifies files or subsystems that do not exist in Tortoise-WoW.
- **TURTLE_INTENTIONAL_DIVERGENCE** : Target code intentionally diverges from vanilla (e.g., custom race handling, debuff engine).
- **UNCERTAIN** : Context has diverged significantly; requires manual or advisory AI review.

14. Database Safety, Schema Catalog & Provenance

Database migrations undergo rigorous automated static analysis against **config/schema_catalog.json** (413 verified tables):

```
task.ps1 3 "sql/database_updates/world/20260507165648_world.sql"
```

Enforced Rules:

1. **Forbidden Progressive Columns**: Rejects any statement containing **patch** , **build** , **min_patch** , or **max_patch** .
2. **Custom Spell Boundary Protection**: **spell_template** IDs ≥ 40000 are reserved for Turtle-WoW custom spells. Modifications to these IDs trigger a validation failure.
3. **Custom World Entity Protection**: **creature_template** , **item_template** , **quest_template** , and **gameobject_template** IDs ≥ 300000 are reserved for Turtle custom content.
4. **Statement Anchoring**: Parser anchors table matching (**(?m)^\s**) to prevent false positives from quest text strings like "update my count"*.
5. **Entity Provenance Tracking**: Records source donor revision, target entity ID, original value, proposed value, and confidence rating in structured dossiers.

15. DBC, Client & Core Parity Auditor

The parity auditor (**ParityAuditor.ps1**) parses binary WDBC client data from **reference-upstreams/client-data-1.18.1/dbc** and verifies server constants:

```
task.ps1 parity
```

- **ChrRaces.dbc**: Verifies playable race records against **#define MAX_RACES 11** in **SharedDefines.h** .
- **Map.dbc**: Audits 57 map definitions against server map enum declarations.
- **Spell.dbc**: Verifies custom spell entry boundary rules.
- **ItemClass.dbc**: Verifies item classification bitmasks.

16. Crash Dump & Server Log Triage

Automated triage engine (**TriageEngine.ps1**) categorizes runtime issues and crash dumps across 17 distinct failure categories:

```
# Triage server startup or runtime log
task.ps1 triage "tortoise-wow/bin/Release/Server.log"

# Triage crash dump or assertion trace
task.ps1 crash "tortoise-wow/bin/Release/crash.dmp"
```

Supported Failure Classifications:

```
ASSERTION_FAILURE , SEGMENTATION_FAULT , DATABASE_ERROR , DBC_ERROR , OPCODE_ERROR , MAP_LOAD_ERROR , SPELL_ERROR ,
SCRIPT_ERROR , NETWORK_ERROR , CONFIG_ERROR , AUTH_ERROR , MEMORY_LEAK , DEADLOCK , STARTUP_TIMEOUT , SHUTDOWN_HANG ,
CUSTOM_SYSTEM_ERROR , UNKNOWN_FAILURE .
```

17. Worktree Isolation & Cleanup Management

All candidate modifications are strictly isolated to Git worktrees:

```
# View all managed active worktrees
task.ps1 worktree

# Safe cleanup of merged or obsolete worktrees
task.ps1 worktree-cleanup
```

Isolation Rules:

- Located exclusively in `<TargetRepo>/worktrees/PORT-XXXX/` .
- Rooted on ephemeral branch `port/PORT-XXXX-<sha>` .
- Pruned cleanly using `git worktree remove` upon pipeline completion or rejection.
- Safety check prevents deletion of any directory outside `worktrees/` .

18. Run IDs, Idempotency & Resumption

Every pipeline execution generates a unique, sortable Run ID:

```
RUN-yyyyMMdd-HHmss-xxxx (e.g., RUN-20260909-144022-7a1b)
```

- **Idempotent Resumption:** State store (`tools/state/state_store.json`) tracks active runs and stage transitions.
- Interrupted runs resume from the last certified state without re-running deterministic proofs.

19. Canonical 30-State Machine

Candidates transition through a strictly guarded 30-state lifecycle:

State	Category	Description	Allowed Next States
DISCOVERED	Initial	Candidate identified from upstream donor commit	TRIAGED , BUG_PROOF_PENDING , ALREADY_FIXED , NOT_APPLICABLE , REJECTED
TRIAGED	Priority	Categorized and scored by Priority Engine	BUG_PROOF_PENDING , ALREADY_FIXED , NOT_APPLICABLE , TURTLE_INTENTIONAL_DIVERGENCE , REJECTED
BUG_PROOF_PENDING	Proving	Undergoing deterministic diff & AST analysis	BUG_PRESENT , ALREADY_FIXED , NOT_APPLICABLE , TURTLE_INTENTIONAL_DIVERGENCE , UNCERTAIN
BUG_PRESENT	Verified Defect	Bug proved present in target source	DEPENDENCY_PENDING , DEPENDENCY_READY , DB_CHECK_PENDING , ADAPTATION_REQUIRED , PATCH_READY
ALREADY_FIXED	Terminal Clean	Upstream fix is already present in target	NEEDS_REAUDIT
NOT_APPLICABLE	Terminal Clean	System/file not present in target architecture	NEEDS_REAUDIT
TURTLE_INTENTIONAL_DIVERGENCE	Guarded	Target intentionally behaves differently	HUMAN_REVIEW_REQUIRED , REJECTED , NEEDS_REAUDIT
UNCERTAIN	Ambiguous	Cannot prove deterministically	HUMAN_REVIEW_REQUIRED , ADAPTATION_REQUIRED , REJECTED

State	Category	Description	Allowed Next States
DEPENDENCY_PENDING	Dependency	Waiting for predecessor commit to be ported	DEPENDENCY_READY , HUMAN_REVIEW_REQUIRED , REJECTED
DEPENDENCY_READY	Dependency	All required predecessor commits satisfied	DB_CHECK_PENDING , ADAPTATION_REQUIRED , PATCH_READY
DB_CHECK_PENDING	Database	Undergoing schema catalog and column audit	DB_CHECK_PASS , DB_CHECK_FAIL
DB_CHECK_PASS	Database	Schema valid, no forbidden columns, no collisions	ADAPTATION_REQUIRED , PATCH_READY
DB_CHECK_FAIL	Database	Invariant violation or column collision detected	ADAPTATION_REQUIRED , HUMAN_REVIEW_REQUIRED , REJECTED
ADAPTATION_REQUIRED	Adaptation	Requires code adjustment for Turtle custom systems	PATCH_READY , HUMAN_REVIEW_REQUIRED , REJECTED
PATCH_READY	Staged	Patch cleanly formatted and ready for isolated build	COMPILE_PENDING , REJECTED
COMPILE_PENDING	Build	Worktree created; queued for compilation	COMPILE_PASS , COMPILE_FAIL , BLOCKED_BY_BASELINE
COMPILE_PASS	Build	MSVC compilation succeeded with 0 errors	STARTUP_PENDING , RUNTIME_PENDING , COMPLETE
COMPILE_FAIL	Build	MSVC compilation failed	BLOCKED_BY_BASELINE , ADAPTATION_REQUIRED , HUMAN_REVIEW_REQUIRED , REJECTED
STARTUP_PENDING	Smoke Test	Binary launched in disposable environment	STARTUP_PASS , STARTUP_FAIL , BLOCKED_BY_BASELINE
STARTUP_PASS	Smoke Test	Binary initialized cleanly without crashes	RUNTIME_PENDING , COMPLETE , HUMAN_REVIEW_REQUIRED
STARTUP_FAIL	Smoke Test	Binary crashed or asserted on startup	BLOCKED_BY_BASELINE , ADAPTATION_REQUIRED , REJECTED
RUNTIME_PENDING	Runtime	Queued for in-game reproducer verification	RUNTIME_PASS , RUNTIME_FAIL
RUNTIME_PASS	Runtime	In-game behavior matches vanilla specification	COMPLETE , HUMAN_REVIEW_REQUIRED
RUNTIME_FAIL	Runtime	In-game reproducer failed	ADAPTATION_REQUIRED , HUMAN_REVIEW_REQUIRED , REJECTED
HUMAN_REVIEW_REQUIRED	Approval Gate	Ambiguous fix flagged for human decision	HUMAN_APPROVED , HUMAN_REJECTED
HUMAN_APPROVED	Approval Gate	Human operator certified fix for inclusion	PATCH_READY , COMPILE_PENDING , COMPLETE
HUMAN_REJECTED	Approval Gate	Human operator rejected fix	REJECTED
BLOCKED_BY_BASELINE	Baseline Block	Blocked because unchanged target HEAD is broken	NEEDS_REAUDIT , REJECTED
NEEDS_REAUDIT	Invalidation	Invalidated due to target HEAD moving or staleness	BUG_PROOF_PENDING , TRIAGED , DISCOVERED
COMPLETE	Final Pass	Certified, tested, committed to candidate branch	NEEDS_REAUDIT
REJECTED	Final Fail	Rejected candidate permanently archived	NEEDS_REAUDIT

20. CI / GitHub Actions PR Workflows

Two GitHub Actions workflows automate continuous integration across orchestration tools and candidate server builds:

1. `.github/workflows/orchestration-ci.yml` :
 - Runs on every push and pull request touching `tools/` , `config/` , or `docs/` .
 - Executes `task test` (Pester 38-case test suite).
 - Validates JSON schema contracts (`config/schemas/`).
 - Runs configuration health check (`task config-check`).
 - Verifies command reference and PDF generation.
2. `.github/workflows/server-candidate-ci.yml` :

- Triggered when candidate port branches (`port/*`) are pushed.
- Sets up MSVC 2022 toolchain and Ninja build system.
- Runs baseline validation against target base commit.
- Executes patch-aware compilation profile.
- Uploads build logs and triage reports as artifacts.

21. Release Checkpoints & Manifest Generation

Release commands provide certification gates before tagging or publishing server releases:

```
# Evaluate release readiness gates
task.ps1 release-check

# Generate certified release manifest
task.ps1 release-manifest "Release-1.18.1-Update1"

# Create signed git tag (aborts if readiness gates fail)
task.ps1 tag-release "v1.18.1-update1"
```

- Manifests are saved to `docs/releases/<name>.json` with full commit SHAs, toolchain info, and test certifications.

22. Critical Safety Warnings

CAUTION

1. **Single-Writer Constraint:** Never invoke `-AutoBuild` or compiler tasks concurrently in multiple shells. 2. **Never Commit Directly to Extended Main:** Candidate fixes must be isolated to candidate branches (`port/PORT-XXXX-<sha>`). 3. **Never Touch Working Tree:** Never execute `git checkout .`, `git reset --hard`, or `git clean -fd` in `tortoise-wow`. 4. **No Secrets in Logs:** Never print or commit API keys, authentication tokens, or private user passwords.

23. Troubleshooting & Common Failure States

Error Code / Symptom	Root Cause	Solution
EXIT CODE 1: MAX_RACES invariant violation	Candidate patch alters <code>MAX_RACES</code> or loop bound.	Restore <code>#define MAX_RACES 11</code> in patch; adapt race array allocations.
EXIT CODE 1: Custom ID boundary collision	Patch uses <code>spell_template</code> entry <code>\$\ge 40000\$</code> or world entry <code>\$\ge 300000\$</code> .	Renumber entity to vanilla range (<code>\$< 40000\$</code> or <code>\$< 300000\$</code>) or scalp correct ID.
EXIT CODE 1: Target repository has uncommitted changes	Working tree is dirty; worktree isolation safety triggered.	Commit or stash changes in <code>tortoise-wow</code> before running porting commands.
EXIT CODE 2: Microsoft Edge not found	Edge binary missing at standard 32/64-bit location.	Verify installation of Edge or update path in <code>Export-CommandReferencePdf.ps1</code> .
EXIT CODE 2: CMake executable not found	<code>cmake.exe</code> not detected in PATH or vcpkg tools directory.	Run <code>task config-check</code> to verify auto-discovery or update <code>config/twow-project.json</code> .
STALE PACKAGE: Target base SHA mismatch	Target repo HEAD advanced since package was staged.	Re-audit candidate via <code>task port <sha></code> against new target HEAD.

24. Expected Status & Verdict Reference Values

Category	Canonical Allowed Values	Meaning
Pipeline Status	PASS, FAIL, WARN, SKIPPED, BLOCKED	Stage execution result code
Bug Verdict	BUG_PRESENT, ALREADY_FIXED, NOT_APPLICABLE, TURTLE_INTENTIONAL_DIVERGENCE, UNCERTAIN	Bug prover determination
Verification Mode	Fast, Normal, Deep	Verification intensity level
Build Profile	world, auth, sql-only, playerbots, docs-only	Selected MSVC build target
AI Usage	NONE, ADVISORY_ONLY, AMBIGUITY_SYNTHESIS	AI role in candidate evaluation

Category	Canonical Allowed Values	Meaning
Exit Codes	0 (PASS), 1 (VALIDATION_FAIL), 2 (TOOL_FAIL), 3 (SCHEMA_FAIL)	Process return codes

25. Architectural Strengths & Engineering Guarantees

The build and porting automation architecture provides a high-assurance, non-destructive, enterprise-grade engineering framework:

Architectural Dimension	Modern Autonomous Implementation	Tangible Engineering Guarantee
Git Working Tree Safety	Strict Git worktree isolation in ephemeral <code>.worktrees/candidate-PORT-XXXX/</code> .	Target repo checkout is 100% clean and immune to accidental corruption or debris.
Rollback & Cleanup	Non-destructive: simply unlinks the worktree (<code>Remove-IsolatedWorktree</code>).	Eliminates catastrophic data loss risk; never discards uncommitted work.
Commit Staging & Branches	Changes committed exclusively to candidate branches (<code>port/PORT-XXXX-<sha></code>).	Enables clean PR reviews, branch audits, and CI smoke testing before integration.
Bug Existence Verification	Deterministic Bug Prover (<code>BugProver.ps1</code> / <code>task prove</code>).	Classifies <code>BUG_PRESENT</code> , <code>ALREADY_FIXED</code> , <code>NOT_APPLICABLE</code> , or <code>TURTLE_DIVERGENCE</code> before touching code.
Build Efficiency	Patch-Aware Build Profiles (<code>world</code> , <code>auth</code> , <code>sql-only</code> , <code>docs-only</code>).	Bypasses compilation for SQL/docs (0s), targets single daemons (15-45s), maximizing iteration speed.
Database Migration Safety	Cached 413-table schema catalog (<code>DbAuditor.ps1</code>) and strict boundary guards.	Blocks forbidden progressive columns (<code>patch</code> , <code>build</code>) and protects custom ranges (<code>spell</code> \$ge 40k\$, world \$ge 300k\$).
Client Data Parity	Automated binary WDBC parser (<code>ParityAuditor.ps1</code> / <code>task parity</code>).	Guarantees code parity with 1.18.1 client DBCs (<code>MAX_RACES = 11</code> , maps, spell definitions).
State Tracking & Resumption	Atomic canonical JSON state store (<code>state_store.json</code>) with 30-state transition guards.	Deterministic run IDs (<code>RUN-yyyyMMdd-HHmms-xxxx</code>), transition guards, and resume capability.
AI Token Efficiency	Deterministic-first gating, bounded context (\$\le 200\$ lines), composite SHA256 caching.	0 AI tokens spent on deterministic rejections; prevents hallucination via <code>ADVISORY_ONLY</code> .
Runtime Reliability	Disposable startup smoke tests (<code>SmokeTest.ps1</code>) and 17-category log triage.	Catches assertion failures, heap corruptions, and missing DBCs before candidate commits are certified.
Automated Testing & CI	Comprehensive 38-spec test suite (<code>task test</code>) + 2 GitHub Actions CI workflows.	Sub-7-second automated verification ensuring every invariant, schema, and command passes.

26. Daily Cheat Sheet & Top Fast Commands

This quick-reference cheat sheet summarizes the most frequent commands you will run on a day-to-day basis.

26.1. The Top Commands at a Glance

Command	Full Syntax	Primary Purpose	When to Use
Batch Auto-Pilot	<code>task auto-pilot 10</code>	Full autonomous pipeline: lore scouting, DB audit, AI context dossier, MSVC worktree compile, and candidate branch commit for 10 commits.	Your primary hands-free daily command for high-velocity porting.
Tier-Filtered Auto-Pilot	<code>task auto-pilot 10 1</code>	Same end-to-end auto-pilot pipeline, but restricted strictly to Tier 1 (Crash, Exploit, and Critical Security fixes).	When focusing specifically on server stability, security, or crash elimination.
Batch Auto-Commit	<code>task port-batch 10 -AutoCommit</code>	Equivalent to <code>task auto-pilot 10</code> . Runs all research stages (lore, DB audit, AI context) and triggers the MSVC compile & commit gate.	Exact semantic alias for batch auto-pilot.
Single Auto-Port	<code>task auto-port <sha></code>	One-command end-to-end port, compile, and commit for a single specific upstream commit SHA.	When investigating or porting a specific upstream commit SHA directly.
Refresh Upstream Roadmap	<code>task roadmap-refresh -FetchLatest</code>	Connects to upstream <code>vmangos/core</code> , fetches the latest commits, audits against Turtle core, recalculates priority scores, and updates <code>docs/ROADMAP.md</code> .	Weekly or when new upstream commits are released and you want to catch them.
Offline Roadmap Audit	<code>task roadmap-refresh</code>	Re-evaluates and ranks all cached candidate commits offline without network requests.	When re-ranking local candidates or updating queue files offline.
Compile Server	<code>task build</code> (or <code>task build world</code>)	Directly invokes CMake / MSVC 2022 to build the target server daemon (<code>world</code> , <code>auth</code> , <code>sql-only</code> , <code>playerbots</code>).	To verify current core builds cleanly without running the porting pipeline.
Run All Unit Tests	<code>task test</code>	Runs the universal 38-spec automated Pester test suite in under 7 seconds.	Before and after any major tooling or policy change.

Command	Full Syntax	Primary Purpose	When to Use
Prove Bug Existence	<code>task prove <sha></code>	Deterministically proves whether a bug exists in Tortoise-WoW Extended without modifying any code.	Quick triage to see if an upstream fix is already fixed or applicable.
Pipeline Status	<code>task status</code>	Outputs current target Git HEAD, active worktree count, staged ready packages, and active run IDs.	Anytime you want a rapid health check of the engineering environment.
Entity Scalp & Diff	<code>task scalp <table/type> <id> - Diff</code>	Extracts item, NPC, spell, or quest records from historical database, strips progressive columns, and generates sanitized SQL diff.	When fixing or verifying custom database entities against vanilla data.
Worktree Cleanup	<code>task cleanup</code>	Safe, non-destructive disposal of ephemeral <code>.worktrees/candidate-*</code> directories.	Periodic cleanup after large batch runs; leaves working tree 100% clean.
Regenerate PDF & HTML	<code>task pdf</code>	Converts <code>COMMAND_REFERENCE.md</code> into cleanly formatted <code>COMMAND_REFERENCE.html</code> and publication-ready <code>COMMAND_REFERENCE.pdf</code> .	Whenever documentation or command specifications are updated.

26.2. Clean CLI Invocations (From Default Location / Any Prompt)

You do not need to change directory (`cd`) to run any of these commands. You can execute them directly from `C:\Users\Admin>` or any terminal prompt:

1. Autonomous Auto-Pilot & Batch Porting:

```
# Run 10 commits through full auto-pilot (natural priority)
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" auto-pilot 10

# Run 10 Tier-1 (critical crash / exploit / security) commits through auto-pilot
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" auto-pilot 10 1

# Run 10 Tier-2 (combat accuracy, spells, mechanics) commits through auto-pilot
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" auto-pilot 10 2

# Port, compile, and commit a specific candidate commit end-to-end
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" auto-port <sha>

# Batch port 10 commits with immediate compilation & commit (semantic equivalent to auto-pilot)
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" port-batch 10 -AutoCommit

# Preview batch auto-pilot execution plan without touching code or worktrees
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" auto-pilot 10 -DryRun
```

2. Upstream Research, Roadmap & Priority Ranking:

```
# Connect to upstream vmangos/core, fetch latest commits, and audit roadmap
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" roadmap-refresh -FetchLatest

# Offline audit and re-ranking of all cached candidate commits
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" roadmap-refresh

# Inspect the single next highest-priority candidate to investigate
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" next

# Display 12-factor priority rankings across all candidate commits
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" rank

# Search 22,155 indexed official forum threads for mechanics or lore
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" 2 "<sha_or_topic>"
```

3. Build Toolchain, Verification & Testing Gates:

```
# Compile target server world daemon (mangosd.exe) via MSVC 2022
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" build world

# Compile authentication daemon (realmd.exe) via MSVC 2022
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" build auth

# Compile and commit all staged candidate packages in isolated worktrees
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" build-packages

# Run the complete 38-spec automated orchestration test suite
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" test

# Deterministically prove whether a bug exists before touching code
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" prove <sha>

# Verify target repository baseline health and SHA pinning
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" baseline

# Execute disposable server startup smoke test
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" smoke
```


4. Database Scalping & Parity Auditing:

```
# Scalp entity definition from historical DB, strip progressive columns, and diff
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" scalp item_template 19019 -Diff

# Audit pending database migration SQL against 413 cached table schemas
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" db-audit

# Audit client binary DBC parity against server source code (MAX_RACES = 11)
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" parity dbc
```

5. Workspace Status, Maintenance & Documentation:

```
# Display live pipeline state, target Git HEAD, and active run IDs
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" status

# Cleanly dispose of ephemeral candidate worktrees in .worktrees/
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" cleanup

# Regenerate COMMAND_REFERENCE HTML and printable PDF
& "C:\Users\Admin\AntigravityProfiles\Projects\twow project\tools\task.ps1" pdf
```

26.3. Target Repository Authority & Local Workspace Guarantees

IMPORTANT

Repository Authority & Target Server: - **Sole Server Target:** All ported fixes, investigations, and compiled commits target **Ildourol/tortoise-wow-extended** exclusively. - **Local Toolchain Execution:** All automation scripts, analysis engines, and state trackers operate strictly locally on this machine with zero remote orchestration repository connections.