

```
MINGW64/c/Users/USER/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis
$ mkdir learn_git_again

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis
$ cd learn_git_again

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again
$ touch third.txt

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again
$ git init
Initialized empty Git repository in C:/Users/USER/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again/.git/

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git add "third.txt"

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git commit -m "commit third.txt"
[master (root-commit) fbbbd19] commit third.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 third.txt

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git log
commit fbbbd1973de0abe25875c5b227fdd766ca257952 (HEAD -> master)
Author: IlhemBaroud <i.lhem.baroud21@gmail.com>
Date:   Wed Sep 8 11:15:00 2021 +0200

    commit third.txt

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git touch fourth.txt
git: 'touch' is not a git command. See 'git --help'.

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ touch "fourth.txt"

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git add "fourth.txt"

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git commit -m "adding fourth.txt"
[master 55b2564] adding fourth.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 fourth.txt

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git rm "third.txt"

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git add .
```

```
MINGW64/c/Users/USER/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git add .

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git commit -m "removing third.txt"
[master 0b9deb8] removing third.txt
1 file changed, 0 insertions(+), 0 deletions(-)
delete mode 100644 third.txt

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git log
commit 0b9deb8d08cb8f766115c091bc4196515cc86bcf (HEAD -> master)
Author: IlhemBaroud <i.lhem.baroud21@gmail.com>
Date:   Wed Sep 8 11:25:44 2021 +0200

    removing third.txt

commit 55b2564ced83fec3282707af41f09d460657fe86
Author: IlhemBaroud <i.lhem.baroud21@gmail.com>
Date:   Wed Sep 8 11:19:03 2021 +0200

    adding fourth.txt

commit fbbbd1973de0abe25875c5b227fdd766ca257952
Author: IlhemBaroud <i.lhem.baroud21@gmail.com>
Date:   Wed Sep 8 11:15:00 2021 +0200

    commit third.txt

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git config --global core.pager cat

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git config
usage: git config [<options>]

Config file location
--global      use global config file
--system      use system config file
--local       use repository config file
--worktree    use per-worktree config file
-f, --file <file> use given config file
--blob <blob-id> read config from given blob object

Action
--get         get value: name [value-pattern]
--get-all    get all values: key [value-pattern]
--get-regexp  get values for regexp: name-regex [value-pattern]
--get-urlmatch get value specific for the URL: section[.var] URL
```

```
MINGW64/c/Users/USER/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again
--blob <blob-id> read config from given blob object

Action
--get get value: name [value-pattern]
--get-all get all values: key [value-pattern]
--get-regexp get values for regexp: name-regex [value-pattern]
--get-urlmatch get value specific for the URL: section[.var] URL
--replace-all replace all matching variables: name value [value-pattern]

ern]
--add add a new variable: name value
--unset remove a variable: name [value-pattern]
--unset-all remove all matches: name [value-pattern]
--rename-section rename section: old-name new-name
--remove-section remove a section: name
-l, --list list all
--fixed-value use string equality when comparing values to 'value-pattern'

ttern'
-e, --edit open an editor
--get-color find the color configured: slot [default]
--get-colorbool find the color setting: slot [stdout-is-tty]

Type
-t, --type <v> value is given this type
--bool value is "true" or "false"
--int value is decimal number
--bool-or-int value is --bool or --int
--bool-or-str value is --bool or string
--path value is a path (file or directory name)
--expiry-date value is an expiry date

Other
-z, --null terminate values with NUL byte
--name-only show variable names only
--includes respect include directives on lookup
--show-origin show origin of config (file, standard input, blob, command line)
--show-scope show scope of config (worktree, local, global, system, command)
--default <value> with --get, use default value when missing entry

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ git config --global --list
user.name=ilhem.baroud
user.email=ilhem.baroud21@gmail.com
core.pager=cat
alias.init=

USER@ASUS MINGW64 ~/Desktop/GOMYCODE/ILHEM/CP7bis/learn_git_again (master)
$ |
```