

# Revealing Network Structure, Confidentially (Improved Rates for Node-Private Graphon Estimation)

Ilias Zadik<sup>1</sup>,  
joint work with Christian Borgs<sup>2</sup>, Jennifer Chayes<sup>2</sup> and Adam Smith<sup>3</sup>

<sup>1</sup>Massachusetts Institute of Technology (MIT),

<sup>2</sup>Microsoft Research (MSR) and

<sup>3</sup>Boston University (BU)

CS Theory Seminar at Northeastern, 2018

**Large and complicated networks** arise everywhere in society! For example,

- the Facebook graph,
- the disease transmission graph
- the collaboration graph
- and many others..

**Large and complicated networks** arise everywhere in society! For example,

- the Facebook graph,
- the disease transmission graph
- the collaboration graph
- and many others..

## **Statistical Analysis of Networks:**

Important across *scientific fields* (sociology, medicine etc)  
rich in *theory* (random graphs, graph algorithms etc)

# The privacy issue

## Facts

**Network data with human users** is sensitive.

Analyzing network data can **leak sensitive information**.

# The privacy issue

## Facts

**Network data with human users** is sensitive.

Analyzing network data can **leak sensitive information**.

...this leads to **high societal concerns!**

(e.g. Cambridge Analytica Scandal)



Cambridge  
Analytica

# The privacy issue

## Facts

**Network data with human users** is sensitive.

Analyzing network data can **leak sensitive information**.

...this leads to **high societal concerns!**

(e.g. Cambridge Analytica Scandal)



Cambridge  
Analytica

## Natural Question

How can we **analyze** network data with human users,  
but **respect individual privacy**?

# Privacy and the Loss in Accuracy

**An interesting solution** (*Differential privacy!* [DMNS '06]):

Restrict yourself on statistical algorithms whose output imply provably **almost nothing** for any specific user.

# Privacy and the Loss in Accuracy

**An interesting solution** (*Differential privacy!* [DMNS '06]):

Restrict yourself on statistical algorithms whose output imply provably **almost nothing** for any specific user.



Restricting the class of algorithms may cause **significant accuracy loss!**



# Privacy and the Loss in Accuracy

**An interesting solution** (*Differential privacy!* [DMNS '06]):

Restrict yourself on statistical algorithms whose output imply provably **almost nothing** for any specific user.



Restricting the class of algorithms may cause **significant accuracy loss!**

**Main Motivation:** Quantify the trade-off

How much accuracy is necessarily **sacrificed**  
if we **restrict** ourselves to differentially private algorithms?

# This work: Limits of Network Estimation under Privacy

## **New algorithms** and **impossibility results**

for estimating complex network models,  
subject to rigorous **privacy constraints** (node differentially privacy).

# This work: Limits of Network Estimation under Privacy

**New algorithms** and **impossibility results**  
for estimating complex network models,  
subject to rigorous **privacy constraints** (node differentially privacy).

## (1) **Stochastic Block Model-Estimation of probability matrix:**

- ▶ new analysis of recent private algorithm (BCS'15)  
matches in many regimes the **optimal non-private estimation rate**
- ▶ general lower bounds

# This work: Limits of Network Estimation under Privacy

## New algorithms and impossibility results

for estimating complex network models,  
subject to rigorous **privacy constraints** (node differentially privacy).

### (1) Stochastic Block Model-Estimation of probability matrix:

- ▶ new analysis of recent private algorithm (BCS'15)  
matches in many regimes the **optimal non-private estimation rate**
- ▶ general lower bounds

### (2) Erdos-Renyi-Estimation of probability $p$ :

- ▶ Compute (almost) tightly **the optimal estimation rate**
- ▶ Uses a **novel extension lemma**, potentially of broad use

- (1) Node Differential Privacy and Stochastic Block Model
- (2) The Statistical Task
- (3) Main Results
  - ▶ Upper Bound for  $k$ -SBM (optimal in many regimes)
  - ▶ Lower Bound for  $k$ -SBM,  $k \geq 2$
  - ▶ The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate
- (4) The Extension Lemma

- (1) **Node Differential Privacy and Stochastic Block Model**
- (2) The Statistical Task
- (3) Main Results
  - ▶ Upper Bound for  $k$ -SBM (optimal in many regimes)
  - ▶ Lower Bound for  $k$ -SBM,  $k \geq 2$
  - ▶ The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate
- (4) The Extension Lemma

# Differential Privacy for Networks

## D.P. algorithms: General Idea

If two input datasets “*differ only on the data of one user*”, then outputs are “*close*” (in distribution).

# Differential Privacy for Networks

## D.P. **network** algorithms: General Idea

If two input **networks** “*differ only on the data of one user*”, then outputs are “*close*” (in distribution).



# Differential Privacy for Networks

## D.P. **network** algorithms: General Idea

If two input **networks** “*differ only on the data of one user*”, then outputs are “*close*” (in distribution).

*What does “differ on one user” means for two networks (graphs)?*

# Differential Privacy for Networks

## D.P. **network** algorithms: General Idea

If two input **networks** “*differ only on the data of one user*”, then outputs are “*close*” (in distribution).

*What does “differ on one user” means for two networks (graphs)?*

- **(Edge-DP)** Two graphs are close if they differ in an **edge**.  
(a simple “*local*” notion, protects “*relationships of individuals*”.)  
*Big literature* [NRS '07], [GRU '12], [XCT '14] and many others

# Differential Privacy for Networks

## D.P. **network** algorithms: General Idea

If two input **networks** “*differ only on the data of one user*”, then outputs are “*close*” (in distribution).

*What does “differ on one user” means for two networks (graphs)?*

- **(Edge-DP)** Two graphs are close if they differ in an **edge**.  
(a simple “*local*” notion, protects “*relationships of individuals*”.)  
*Big literature* [NRS '07], [GRU '12], [XCT '14] and many others
- **(Node-DP)** Two graphs are close if they differ in a **node**.  
(a stronger “*global*” notion, protects “*individuals*”.)  
*Limited literature* [KNRS'13], [BBDS '13], [CZ '13] and few others

# Differential Privacy for Networks

## D.P. **network** algorithms: General Idea

If two input **networks** “*differ only on the data of one user*”, then outputs are “*close*” (in distribution).

*What does “differ on one user” means for two networks (graphs)?*

- **(Edge-DP)** Two graphs are close if they differ in an **edge**.  
(a simple “*local*” notion, protects “*relationships of individuals*”.)  
*Big literature* [NRS '07], [GRU '12], [XCT '14] and many others
- **(Node-DP)** Two graphs are close if they differ in a **node**.  
(a stronger “*global*” notion, protects “*individuals*”.)  
*Limited literature* [KNRS'13], [BBDS '13], [CZ '13] and few others

**This work is for node-DP!**


# $\epsilon$ -Node Differential Private Algorithms

*Intuition:* If two  $n$ -vertex  $G, G'$  differ in **one node**, then outputs are “close” (in distribution).

# $\epsilon$ -Node Differential Private Algorithms

*Intuition:* If two  $n$ -vertex  $G, G'$  differ in **one node**, then outputs are “close” (in distribution).


**Node-neighbors:** We call  $G, G'$  node-neighbors if they differ only on the neighborhood of one node.



# $\epsilon$ -Node Differential Private Algorithms

*Intuition:* If two  $n$ -vertex  $G, G'$  differ in **one node**, then outputs are “close” (in distribution).

**Node-neighbors:** We call  $G, G'$  node-neighbors if they differ only on the neighborhood of one node.




*Node-Distance:* The path metric induced by node-neighbors relation

# $\epsilon$ -Node Differential Private Algorithms

*Intuition:* If two  $n$ -vertex  $G, G'$  differ in **one node**, then outputs are “close” (in distribution).

**Node-neighbors:** We call  $G, G'$  node-neighbors if they differ only on the neighborhood of one node.



*Node-Distance:* The path metric induced by node-neighbors relation

## Definition

A randomized  $\mathcal{A}$  on  $n$ -vertex graphs is  $\epsilon$ -**node-DP** if for **all** node-neighbors  $G, G'$  and  $v$  in the output space,

$$\exp(-\epsilon) \mathbb{P}(\mathcal{A}(G') = v) \leq \mathbb{P}(\mathcal{A}(G) = v) \leq \exp(\epsilon) \mathbb{P}(\mathcal{A}(G') = v).$$



# k-Stochastic Block Model for Large Networks

## Parameters

- $n$  **nodes (users)**
- $k$  **types** (based on characteristics such as *social status, cultural background, political identity*.)
- $B \in [0, 1]^{k \times k}$  symmetric **probability (frequency) matrix** between the  $k$  types.

# k-Stochastic Block Model for Large Networks

## Parameters

- $n$  **nodes (users)**
- $k$  **types** (based on characteristics such as *social status, cultural background, political identity*.)
- $B \in [0, 1]^{k \times k}$  symmetric **probability (frequency) matrix** between the  $k$  types.

## The k-Stochastic Block Model

- (1) Each node  $v$  chooses  $\text{type}(v)$  from  $[k]$  iid **u.a.r.**
- (2) Nodes  $v, w$  connect with an edge **w.p.**  $B_{\text{type}(v), \text{type}(w)}$  independently.




Figure:  $n = 12$




Figure:  $k = 4$




Figure: Assign Edges

# k-Stochastic Block Model for Large Networks


## Parameters

- $n$  **nodes (users)**
- $k$  **types** (based on characteristics such as *social status, cultural background, political identity*.)
- $B \in [0, 1]^{k \times k}$  symmetric **probability (frequency) matrix** between the  $k$  types.

## The k-Stochastic Block Model

- (1) Each node  $v$  chooses  $\text{type}(v)$  from  $[k]$  iid **u.a.r.**.
- (2) Nodes  $v, w$  connect with an edge **w.p.**  $B_{\text{type}(v), \text{type}(w)}$  independently.

If  $k = 1$ , simple **Erdos-Renyi** model  $G(n, p)$ !



# Modeling Large Networks: k-Stochastic Block Model

**k-SBM**,  $G(n, B)$ , for sym.  $B \in [0, 1]^{k \times k}$ :  
n **nodes**, k **types** (node's choice u.a.r.),  
each edge between  $v, w$  **with probability**  $B_{\text{type}(v), \text{type}(w)}$  **independently**.




Figure:  $n = 12$




Figure:  $k = 4$




Figure: Assign Edges

# Modeling Large Networks: k-Stochastic Block Model

**k-SBM**,  $G(n, B)$ , for sym.  $B \in [0, 1]^{k \times k}$ :  
n **nodes**, k **types** (node's choice u.a.r.),  
each edge between  $v, w$  **with probability**  $B_{\text{type}(v), \text{type}(w)}$  **independently**.

- Sparsity*: ( $\rho$ -sparse) **k-SBM**,  $G(n, B)$ , where  $B \in [0, \rho]^{k \times k}$ .




Figure:  $n = 12$




Figure:  $k = 4$




Figure: Assign Edges

# Modeling Large Networks: k-Stochastic Block Model

**k-SBM**,  $G(n, B)$ , for sym.  $B \in [0, 1]^{k \times k}$ :  
n **nodes**, k **types** (node's choice u.a.r.),  
each edge between  $v, w$  **with probability**  $B_{\text{type}(v), \text{type}(w)}$  **independently**.

- Sparsity*: ( $\rho$ -sparse) **k-SBM**,  $G(n, B)$ , where  $B \in [0, \rho]^{k \times k}$ .




Figure:  $n = 12$




Figure:  $k = 4$





Figure: Assign Edges

*Vast literature* (without privacy): connections with  
**community detection** (gene expressions, webpage sorting),  
**planted bisection problem**, **statistical physics models**.

- (1) Node Differential Privacy and Stochastic Block Model
- (2) **The Statistical Task**
- (3) Main Results
  - ▶ Upper Bound for  $k$ -SBM (optimal in many regimes)
  - ▶ Lower Bound for  $k$ -SBM,  $k \geq 2$
  - ▶ The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate
- (4) The Extension Lemma

# The Statistical Setting


Let (unknown)  $B \in [0, \rho]^{k \times k}$  for (known)  $k$ .





# The Statistical Setting

Let (unknown)  $B \in [0, \rho]^{k \times k}$  for (known)  $k$ .




## Task:

We observe **one**  $n$ -vertex sample  $G$  from  $G(n, B)$ .

The goal is to estimate  $B$  using an  $\epsilon$ -**node-DP**  $\mathcal{A}(G)$ .

# The Statistical Setting

Let (unknown)  $B \in [0, \rho]^{k \times k}$  for (known)  $k$ .



## Task:

We observe **one**  $n$ -vertex sample  $G$  from  $G(n, B)$ .

The goal is to estimate  $B$  using an  $\epsilon$ -**node-DP**  $\mathcal{A}(G)$ .

Metric (types-order invariant) for fixed  $B$

$$\delta_2(\mathcal{A}(G), B) = \min_{\pi: [k] \rightarrow [k]} \frac{1}{k} \|\mathcal{A}(G)_\pi - B\|_2,$$

where  $\mathcal{A}(G)_\pi = \left( \mathcal{A}(G)_{\pi(i), \pi(j)} \right)_{i,j}$ .

For  $G \sim G(n, B)$ , focus on **MSE**  $\mathbb{E}_{G \sim G(n, B)} \left[ \delta_2(\mathcal{A}(G), B)^2 \right]$ .

# The Statistical Question

## Performance of Algorithm for general B

Each  $\mathcal{A}$  has (worst-case over B) **error**

$$\text{err}(\mathcal{A}) = \max_{B \in [0, \rho]^{k \times k}} \mathbb{E}_{G \sim G(n, B)} \left[ \delta_2(\mathcal{A}(G), B)^2 \right]$$

# The Statistical Question

## Performance of Algorithm for general B

Each  $\mathcal{A}$  has (worst-case over B) **error**

$$\text{err}(\mathcal{A}) = \max_{B \in [0, \rho]^{k \times k}} \mathbb{E}_{G \sim G(n, B)} \left[ \delta_2(\mathcal{A}(G), B)^2 \right]$$

## The Estimation Rate

$$R_k(\epsilon) = \min_{\mathcal{A} \text{ } \epsilon\text{-node-DP}} \text{err}(\mathcal{A}).$$

# The Statistical Question

## Performance of Algorithm for general B

Each  $\mathcal{A}$  has (worst-case over B) **error**

$$\text{err}(\mathcal{A}) = \max_{B \in [0, \rho]^{k \times k}} \mathbb{E}_{G \sim G(n, B)} \left[ \delta_2(\mathcal{A}(G), B)^2 \right]$$

## The Estimation Rate

$$R_k(\epsilon) = \min_{\mathcal{A} \text{ } \epsilon\text{-node-DP}} \text{err}(\mathcal{A}).$$

- Note that we assume  $G$  is generated from  $k$ -SBM.
- In paper, we generalize to the **agnostic setting** to fitting  $k$ -SBM to a  $k'$ -SBM for unknown  $k' > k$ .

- (1) Node Differential Privacy and Stochastic Block Model
- (2) The Statistical Task
- (3) **Main Results**
  - ▶ **Upper Bound for k-SBM (optimal in many regimes)**
  - ▶ Lower Bound for k-SBM,  $k \geq 2$
  - ▶ The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate
- (4) The Extension Lemma

# Upper Bound for k-SBM

Theorem (informal, (BCSZ FOCS '18))

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

.

# Upper Bound for k-SBM

Theorem (informal, (BCSZ FOCS '18))

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

- *Intuition:*  $\frac{k^2}{n^2}$  parametric rate for B,  $\frac{\log k}{n} = \frac{\log k^n}{n^2}$  combinatorial rate
- Via a new detailed analysis of an  $\epsilon$ -node-DP algorithm proposed in (BCS '15).



# Upper Bound for k-SBM

Theorem (informal, (BCSZ FOCS '18))

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

# Upper Bound for k-SBM

Theorem (informal, (BCSZ FOCS '18))

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = \underbrace{O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right)}_{\text{Optimal non-private rate!}} + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

# Upper Bound for k-SBM

## Theorem (informal, (BCSZ FOCS '18))

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = \underbrace{O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right)}_{\text{Optimal non-private rate!}} + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

Comments:

- (GLZ'14), (MS'17), (KTV'17): Optimal  $\epsilon$ -independent part.
- Many regimes (e.g.  $\epsilon, k$  constant and  $\frac{1}{n} < \rho < \frac{1}{\log n}$ ):
  - **No additional accuracy loss** by imposing privacy!
  - (BCS'15) algorithm, optimal accuracy loss over **all** algorithms!

# Upper Bound: Proof Idea

- (1) (BCS'15) algorithm is a (quite non-trivial) combination of **exponential, laplace mechanism and Lipschitz extensions** ideas applied to the optimal non-private algorithm (KTV'17).

# Upper Bound: Proof Idea

- (1) (BCS'15) algorithm is a (quite non-trivial) combination of **exponential, laplace mechanism and Lipschitz extensions** ideas applied to the optimal non-private algorithm (KTV'17).
- (2) All these mechanisms provide **additive error** guarantees.

# Upper Bound: Proof Idea

- (1) (BCS'15) algorithm is a (quite non-trivial) combination of **exponential, laplace mechanism and Lipschitz extensions** ideas applied to the optimal non-private algorithm (KTV'17).
- (2) All these mechanisms provide **additive error** guarantees.
- (3) Adjust the analysis from (KTV'17)- a delicate net argument- to show that it **is not much affected** by additive errors.

# Upper Bound: Tightness?

Theorem (informal (BCSZ FOCS '18) )

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = \underbrace{O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right)}_{\text{Optimal non-private rate!}} + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

# Upper Bound: Tightness?

Theorem (informal (BCSZ FOCS '18) )

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = \underbrace{O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right)}_{\text{Optimal non-private rate!}} + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right)$$

**What about the  $\epsilon$ -dependent parts?**



# Upper Bound: Tightness?

Theorem (informal (BCSZ FOCS '18) )

For any  $\epsilon > 0$ ,

$$\mathcal{R}_k(\epsilon) = \underbrace{O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right)}_{\text{Optimal non-private rate!}} + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \underbrace{\frac{1}{n^2\epsilon^2}}_{\text{necessary, } k \geq 2}\right)$$

**What about the  $\epsilon$ -dependent parts?**

We prove  $\frac{1}{n^2\epsilon^2}$  is (almost) necessary if  $k \geq 2$ .

- (1) Node Differential Privacy and Stochastic Block Model
- (2) The Statistical Task
- (3) **Main Results**
  - ▶ Upper Bound for  $k$ -SBM (optimal in many regimes)
  - ▶ **Lower Bound for  $k$ -SBM**,  $k \geq 2$
  - ▶ The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate
- (4) The Extension Lemma

## A lower bound for $k \geq 2$ : A variant of SBM

We prove that the term  $\frac{1}{n^2\epsilon^2}$  is **necessary** under a small model change.

# A lower bound for $k \geq 2$ : A variant of SBM

We prove that the term  $\frac{1}{n^2 \epsilon^2}$  is **necessary** under a small model change.

Recall for some underlying probability matrix  $B$ :




Figure:  $n = 12$




Figure:  $k = 4$   
u.a.r.




Figure: Assign Edges

# A lower bound for $k \geq 2$ : A variant of SBM

We prove that the term  $\frac{1}{n^2 \epsilon^2}$  is **necessary** under a small model change.

Recall for some underlying probability matrix  $B$ :




Figure:  $n = 12$




Figure:  $k = 4$   
**close to** u.a.r.




Figure: Assign Edges

## New $k$ -SBM

Suppose each node  $i \in [n]$  chooses its type in a **close to** uniform way.  
(Say each type has probability in  $[\frac{1}{4k}, \frac{4}{k}]$ .)

## A lower bound for $k \geq 2$ : Result

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right).$$

## A lower bound for $k \geq 2$ : Result

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right).$$

Proposition (informal, (BCSZ FOCS '18) )

For  $k \geq 2$  and any  $\epsilon > 0$ ,

$$\mathcal{R}_k^*(\epsilon) = \Omega\left(\frac{1}{n^2\epsilon^2}\right),$$

where  $\mathcal{R}_k^*$  stands for the rate for the new variant of the SBM.

## A lower bound for $k \geq 2$ : Result

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right).$$

Proposition (informal, (BCSZ FOCS '18) )

For  $k \geq 2$  and any  $\epsilon > 0$ ,

$$\mathcal{R}_k^*(\epsilon) = \Omega\left(\frac{1}{n^2\epsilon^2}\right),$$

where  $\mathcal{R}_k^*$  stands for the rate for the new variant of the SBM.

Proof: Reduction to privately estimating  $q \in [0, 1]$  out of  $n$  samples from  $\text{Bern}(q)$ .



## A lower bound for $k \geq 2$ : Result

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right).$$

Proposition (informal, (BCSZ FOCS '18) )

For  $k \geq 2$  and any  $\epsilon > 0$ ,

$$\mathcal{R}_k^*(\epsilon) = \Omega\left(\frac{1}{n^2\epsilon^2}\right),$$

where  $\mathcal{R}_k^*$  stands for the rate for the new variant of the SBM.

Proof: Reduction to privately estimating  $q \in [0, 1]$  out of  $n$  samples from  $\text{Bern}(q)$ .

**How crucial is that  $k \geq 2$ ?**

## A lower bound for $k \geq 2$ : Result

$$\mathcal{R}_k(\epsilon) = O\left(\rho\left(\frac{k^2}{n^2} + \frac{\log k}{n}\right)\right) + O\left(\frac{\rho^2(k-1)^2 \log n}{n\epsilon} + \frac{1}{n^2\epsilon^2}\right).$$

Proposition (informal, (BCSZ FOCS '18) )

For  $k \geq 2$  and any  $\epsilon > 0$ ,

$$\mathcal{R}_k^*(\epsilon) = \Omega\left(\frac{1}{n^2\epsilon^2}\right),$$

where  $\mathcal{R}_k^*$  stands for the rate for the new variant of the SBM.

Proof: Reduction to privately estimating  $q \in [0, 1]$  out of  $n$  samples from  $\text{Bern}(q)$ .

**How crucial is that  $k \geq 2$ ?**

If  $k = 1$ , the rate can be improved to  $\frac{1}{n^3\epsilon^2}$ .

- (1) Node Differential Privacy and Stochastic Block Model
- (2) The Statistical Task
- (3) **Main Results**
  - ▶ Upper Bound for  $k$ -SBM (optimal in many regimes)
  - ▶ Lower Bound for  $k$ -SBM,  $k \geq 2$
  - ▶ **The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate**
- (4) The Extension Lemma

# The case $k = 1$ : Learning privately Erdos Renyi graphs

A fundamental open problem

Observe simply a  $G(n, p)$ : estimate **privately**  $p \in [0, 1]$

# The case $k = 1$ : Learning privately Erdos Renyi graphs

## A fundamental open problem

Observe simply a  $G(n, p)$ : estimate **privately**  $p \in [0, 1]$

## Task for $k = 1$

Compute

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A} \text{ } \epsilon\text{-node-DP}} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} \left[ |\mathcal{A}(G) - p|^2 \right].$$

# The case $k = 1$ : Learning privately Erdos Renyi graphs

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

# The case $k = 1$ : Learning privately Erdos Renyi graphs

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Standard Techniques

$$\Omega\left(\frac{1}{n^2} + \frac{1}{n^4 \epsilon^2}\right) = \mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{1}{n^2 \epsilon^2}\right).$$

# The case $k = 1$ : Learning privately Erdos Renyi graphs

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Standard Techniques

$$\Omega\left(\frac{1}{n^2} + \frac{1}{n^4 \epsilon^2}\right) = \mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{1}{n^2 \epsilon^2}\right).$$

**Upper bound** by Laplace mechanism (and our main result for  $k = 1$ ).



# The case $k = 1$ : Learning privately Erdos Renyi graphs

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Standard Techniques

$$\Omega\left(\frac{1}{n^2} + \frac{1}{n^4 \epsilon^2}\right) = \mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{1}{n^2 \epsilon^2}\right).$$

**Upper bound** by Laplace mechanism (and our main result for  $k = 1$ ).

**Lower bounds** by standard methods.

# The case $k = 1$ : Learning privately Erdos Renyi graphs

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Standard Techniques

$$\Omega\left(\frac{1}{n^2} + \frac{1}{n^4 \epsilon^2}\right) = \mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{1}{n^2 \epsilon^2}\right).$$

**Upper bound** by Laplace mechanism (and our main result for  $k = 1$ ).

**Lower bounds** by standard methods.

What is the true  $\epsilon$ -dependent rate?!

# The case $k = 1$ : Learning privately Erdos Renyi graphs

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Standard Techniques

$$\Omega\left(\frac{1}{n^2} + \frac{1}{n^4 \epsilon^2}\right) = \mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{1}{n^2 \epsilon^2}\right).$$

**Upper bound** by Laplace mechanism (and our main result for  $k = 1$ ).

**Lower bounds** by standard methods.

What is the true  $\epsilon$ -dependent rate?! **(Almost tight) answer:**  $\frac{1}{n^3 \epsilon^2}$

The case  $k = 1$ :  $\frac{1}{n^4 \epsilon^2} \leq \epsilon - \text{dep.} \leq \frac{1}{n^2 \epsilon^2}$

### Theorem (BCSZ FOCS '18 )

For  $\epsilon > \frac{\log n}{n}$ ,

$$\mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{\log n}{n^3 \epsilon^2}\right).$$

Furthermore, if  $G$  is sampled u.a.r. from graphs with a fixed number of edges (conditional Erdos Renyi) for  $\epsilon$  constant,

$$\mathcal{R}'_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right).$$

# Upper Bound: The Laplace estimator (suboptimal)

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Laplace Estimator

For any  $f$ ,  $f(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  is  $\epsilon$ -node-DP for

$$\Delta = \max_{G, G': d_v(G, G')=1} |f(G) - f(G')|.$$

# Upper Bound: The Laplace estimator (suboptimal)

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Laplace Estimator

For any  $f$ ,  $f(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  is  $\epsilon$ -node-DP for

$$\Delta = \max_{G, G': d_v(G, G')=1} |f(G) - f(G')|.$$

Best non-private estimator is  $e(G) = \frac{|E[G]|}{\binom{n}{2}}$ .

# Upper Bound: The Laplace estimator (suboptimal)

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

## Laplace Estimator

For any  $f$ ,  $f(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  is  $\epsilon$ -node-DP for

$$\Delta = \max_{G, G': d_v(G, G')=1} |f(G) - f(G')|.$$

Best non-private estimator is  $e(G) = \frac{|E[G]|}{\binom{n}{2}}$ .

We consider the  $\epsilon$ -node-DP,  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for

$$\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')|$$

## Upper Bound: The Laplace estimator (suboptimal)

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

### Laplace Estimator

For any  $f$ ,  $f(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  is  $\epsilon$ -node-DP for

$$\Delta = \max_{G, G': d_v(G, G')=1} |f(G) - f(G')|.$$

Best non-private estimator is  $e(G) = \frac{|E[G]|}{\binom{n}{2}}$ .

We consider the  $\epsilon$ -node-DP,  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for

$$\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')| = \Theta\left(n / \binom{n}{2}\right) = \Theta\left(\frac{1}{n}\right).$$



## Upper Bound: The Laplace estimator (suboptimal)

$$\mathcal{R}_1(\epsilon) = \min_{\mathcal{A}} \epsilon\text{-node-DP} \max_{p \in [0,1]} \mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = ?$$

### Laplace Estimator

For any  $f$ ,  $f(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  is  $\epsilon$ -node-DP for

$$\Delta = \max_{G, G': d_v(G, G')=1} |f(G) - f(G')|.$$

Best non-private estimator is  $e(G) = \frac{|E[G]|}{\binom{n}{2}}$ .

We consider the  $\epsilon$ -node-DP,  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for

$$\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')| = \Theta\left(n / \binom{n}{2}\right) = \Theta\left(\frac{1}{n}\right).$$

### Same upper bound


$$\mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{1}{n^2 \epsilon^2}\right).$$

# Upper Bound: Learning from the Laplace estimator

- Recall:  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for  
 $\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')| = \Theta(\frac{1}{n}).$


# Upper Bound: Learning from the Laplace estimator

- Recall:  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for  
 $\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')| = \Theta(\frac{1}{n})$ .
- $\Delta = \Theta(\frac{1}{n})$  requires  $\Theta(n)$  change in one degree and no change in rest.  
**Deviation  $\Theta(n)$  from average degree in  $G$  or  $G'$ .**




# Upper Bound: Learning from the Laplace estimator

- Recall:  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for  
 $\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')| = \Theta(\frac{1}{n})$ .
- $\Delta = \Theta(\frac{1}{n})$  requires  $\Theta(n)$  change in one degree and no change in rest.  
**Deviation  $\Theta(n)$  from average degree in  $G$  or  $G'$ .**
- All degrees from  $G(n, p)$  are  $(n-1)p + O(\sqrt{n \log n})$ :  $\sqrt{n \log n}$ -window.  
 $\Rightarrow G$  or  $G'$  very **atypical** for any Erdos-Renyi graph.



# Upper Bound: Learning from the Laplace estimator

- Recall:  $e(G) + \text{Lap}(\frac{\Delta}{\epsilon})$  for  
 $\Delta = \max_{G, G': d_v(G, G')=1} |e(G) - e(G')| = \Theta(\frac{1}{n})$ .
- $\Delta = \Theta(\frac{1}{n})$  requires  $\Theta(n)$  change in one degree and no change in rest.  
**Deviation  $\Theta(n)$  from average degree in  $G$  or  $G'$ .**
- All degrees from  $G(n, p)$  are  $(n-1)p + O(\sqrt{n \log n})$ :  $\sqrt{n \log n}$ -window.  
 $\Rightarrow G$  or  $G'$  very **atypical** for any Erdos-Renyi graph.
- How to exclude **atypical graphs**?  
(Challenge: need to be **private for all pairs** of graphs: )



# Upper Bound: Improving the Laplace estimator


We construct a **subset**  $\mathcal{H}$  of all  $n$ -vertex graphs

- **typical** for ER graphs

$$\max_{p \in [0,1]} \mathbb{P}_{G \sim G(n,p)} (G \notin \mathcal{H}) = O\left(\frac{1}{n^2}\right),$$


- with **lower sensitivity**

$$\max_{G, G' \in \mathcal{H}: d(G, G')=1} |e(G) - e(G')| = O(\sqrt{n \log n} / \binom{n}{2}) = O\left(\frac{\sqrt{\log n}}{n^{\frac{3}{2}}}\right).$$





# Upper Bound: Improving the Laplace estimator

- (Privacy in  $\mathcal{H}$ ): Let  $\hat{\mathcal{A}}(G) = e(G) + \text{Lap}(\frac{2\sqrt{\log n}}{n^2\epsilon})$ ,  $G \in \mathcal{H}$ .
  - (1)  $\frac{\epsilon}{2}$ -node-DP estimator on  $\mathcal{H}$  and
  - (2) For  $G \in \mathcal{H}$ ,  $\mathbb{E} \left[ (\hat{\mathcal{A}}(G) - p)^2 \right] = O(\frac{1}{n^2} + \frac{\log n}{n^3\epsilon^2})$ .



# Upper Bound: Improving the Laplace estimator

- (Privacy in  $\mathcal{H}$ ): Let  $\hat{\mathcal{A}}(G) = e(G) + \text{Lap}(\frac{2\sqrt{\log n}}{n^2\epsilon})$ ,  $G \in \mathcal{H}$ .
  - (1)  $\frac{\epsilon}{2}$ -node-DP estimator on  $\mathcal{H}$  and
  - (2) For  $G \in \mathcal{H}$ ,  $\mathbb{E} \left[ (\hat{\mathcal{A}}(G) - p)^2 \right] = O(\frac{1}{n^2} + \frac{\log n}{n^3\epsilon^2})$ .
- (Privacy in the whole space+ same accuracy:)  
**Extension lemma** which **extends**  $\hat{\mathcal{A}}$  to  $\mathcal{A}$ 
  - (1)  $\epsilon$ -node-DP estimator on every  $n$ -vertex graph and
  - (2)  $\mathcal{A}(G) = \hat{\mathcal{A}}(G)$  in distribution, when  $G \in \mathcal{H}$ .





# Upper Bound: Improving the Laplace estimator

- (Privacy in  $\mathcal{H}$ ): Let  $\hat{\mathcal{A}}(G) = e(G) + \text{Lap}(\frac{2\sqrt{\log n}}{n^2\epsilon})$ ,  $G \in \mathcal{H}$ .

(1)  $\frac{\epsilon}{2}$ -node-DP estimator on  $\mathcal{H}$  and

(2) For  $G \in \mathcal{H}$ ,  $\mathbb{E} \left[ (\hat{\mathcal{A}}(G) - p)^2 \right] = O\left(\frac{1}{n^2} + \frac{\log n}{n^3\epsilon^2}\right)$ .



- (Privacy in the whole space+ same accuracy:)

**Extension lemma** which **extends**  $\hat{\mathcal{A}}$  to  $\mathcal{A}$

(1)  $\epsilon$ -node-DP estimator on every  $n$ -vertex graph and

(2)  $\mathcal{A}(G) = \hat{\mathcal{A}}(G)$  in distribution, when  $G \in \mathcal{H}$ .

$\mathcal{H}$  typical for  $G_{n,p}$  implies  $\mathbb{E}_{G \sim G_{n,p}} [|\mathcal{A}(G) - p|^2] = O\left(\frac{1}{n^2} + \frac{\log n}{n^3\epsilon^2}\right)$ .



# The case $k = 1$ : Main Result and Extension Lemma

## Theorem (BCSZ FOCS '18 )

For  $\epsilon > \frac{\log n}{n}$ ,

$$\mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{\log n}{n^3 \epsilon^2}\right).$$

Furthermore, if  $G$  is sampled u.a.r. from graphs with a fixed number of edges (conditional Erdos Renyi) for  $\epsilon$  constant,

$$\mathcal{R}'_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right).$$

# The case $k = 1$ : Main Result and Extension Lemma

## Theorem (BCSZ FOCS '18 )

For  $\epsilon > \frac{\log n}{n}$ ,

$$\mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{\log n}{n^3 \epsilon^2}\right).$$

Furthermore, if  $G$  is sampled u.a.r. from graphs with a fixed number of edges (conditional Erdos Renyi) for  $\epsilon$  constant,

$$\mathcal{R}'_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right).$$

Special Importance for Upper Bound

### **Extension Lemma**

*Extended private algorithm from typical instances  
to private algorithm on the whole space.*

- (1) Node Differential Privacy and Stochastic Block Model
- (2) The Statistical Task
- (3) Main Results
  - ▶ Upper Bound for  $k$ -SBM (optimal in many regimes)
  - ▶ Lower Bound for  $k$ -SBM,  $k \geq 2$
  - ▶ The case  $k = 1$  (Erdos-Renyi case)-an almost tight optimal rate
- (4) **The Extension Lemma**

# The extension lemma: beyond networks

Technical challenge with *designing* differential private algorithms:

- **Privacy** constraint should hold for **any** pair of datasets
- **Accuracy** guarantee suffice to hold for **typical** datasets of our input distribution.

# The extension lemma: beyond networks

Technical challenge with *designing* differential private algorithms:

- **Privacy** constraint should hold for **any** pair of datasets
- **Accuracy** guarantee suffice to hold for **typical** datasets of our input distribution.

*Key contribution:* Suffices to be **private** only for **typical** datasets

# The extension lemma: beyond networks

Technical challenge with *designing* differential private algorithms:

- **Privacy** constraint should hold for **any** pair of datasets
- **Accuracy** guarantee suffice to hold for **typical** datasets of our input distribution.


*Key contribution:* Suffices to be **private** only for **typical** datasets

Proposition ( “Extending any DP Algorithm, (BCSZ FOCS’18) )

Let  $\hat{\mathcal{A}}$   $\epsilon$ -DP on a subset of the input space  $\mathcal{H} \subseteq \mathcal{M}$ . Then there exists  $\mathcal{A}$  defined on  $\mathcal{M}$  which is 1)  $2\epsilon$ -DP on  $\mathcal{M}$  and 2)  $\forall D \in \mathcal{H}, \mathcal{A}(D) \stackrel{d}{=} \hat{\mathcal{A}}(D)$ .


Generalizes “extensions”: (KNRS’13), (BBDS’13), (CZ’13), (RS’15).

**Note** on arXiv: “Private Algorithms Can Always Be Extended”



# Proof Ideas of Extension Lemma

- Differential-privacy can be translated into an  $\epsilon$ -**Lipschitz condition**.  
(small input changes leads to small output changes)






# Proof Ideas of Extension Lemma

- Differential-privacy can be translated into an  $\epsilon$ -**Lipschitz condition**.  
(small input changes leads to small output changes)

$$\max_v \frac{\mathbb{P}(\mathcal{A}(G)=v)}{\mathbb{P}(\mathcal{A}(G')=v)} \leq e^{\epsilon d_v(G, G')} \Rightarrow$$

$$\max_v |\log \mathbb{P}(\mathcal{A}(G) = v) - \log \mathbb{P}(\mathcal{A}(G') = v)| \leq \epsilon d_v(G, G')$$




# Proof Ideas of Extension Lemma

- Differential-privacy can be translated into an  $\epsilon$ -**Lipschitz condition**.  
(small input changes leads to small output changes)

$$\max_v \frac{\mathbb{P}(\mathcal{A}(G)=v)}{\mathbb{P}(\mathcal{A}(G')=v)} \leq e^{\epsilon d_v(G, G')} \Rightarrow$$

$$\max_v |\log \mathbb{P}(\mathcal{A}(G)=v) - \log \mathbb{P}(\mathcal{A}(G')=v)| \leq \epsilon d_v(G, G')$$

- Lipschitz extensions are well-studied in **functional analysis**.




# Proof Ideas of Extension Lemma

- Differential-privacy can be translated into an  $\epsilon$ -**Lipschitz condition**.  
(small input changes leads to small output changes)

$$\max_v \frac{\mathbb{P}(\mathcal{A}(G)=v)}{\mathbb{P}(\mathcal{A}(G')=v)} \leq e^{\epsilon d_v(G,G')} \Rightarrow$$

$$\max_v |\log \mathbb{P}(\mathcal{A}(G)=v) - \log \mathbb{P}(\mathcal{A}(G')=v)| \leq \epsilon d_v(G, G')$$

- Lipschitz extensions are well-studied in **functional analysis**.
- Standard result: functions with  $\ell_\infty(\Gamma)$ -**output space** *can always be Lipschitz-extended* with the same Lip constant.




# Proof Ideas of Extension Lemma

- Differential-privacy can be translated into an  $\epsilon$ -**Lipschitz condition**.  
(small input changes leads to small output changes)

$$\max_v \frac{\mathbb{P}(\mathcal{A}(G)=v)}{\mathbb{P}(\mathcal{A}(G')=v)} \leq e^{\epsilon d_v(G,G')} \Rightarrow$$

$$\max_v |\log \mathbb{P}(\mathcal{A}(G)=v) - \log \mathbb{P}(\mathcal{A}(G')=v)| \leq \epsilon d_v(G, G')$$

- Lipschitz extensions are well-studied in **functional analysis**.
- Standard result: functions with  $\ell_\infty(\Gamma)$ -**output space** *can always be Lipschitz-extended* with the same Lip constant.
- $\epsilon$ -DP has **almost this property** but not exactly.  
Yet similar proof (alongside with measure-theory techniques) works by doubling the Lip constant.



# Summary of Contributions

- (1) We focus on optimal private estimation of **Stochastic Block Model** and **Erdos Renyi** models.

# Summary of Contributions

- (1) We focus on optimal private estimation of **Stochastic Block Model** and **Erdos Renyi** models.
- (2) **Stochastic Block Model**: new analysis of existing algorithm (BCS'15) matches **optimal non-private rate** in many regimes.  
*Graphons (k-SBM for  $k \rightarrow +\infty$ ) and agnostic learning in the paper!*

# Summary of Contributions

- (1) We focus on optimal private estimation of **Stochastic Block Model** and **Erdos Renyi** models.
- (2) **Stochastic Block Model**: new analysis of existing algorithm (BCS'15) matches **optimal non-private rate** in many regimes.  
*Graphons ( $k$ -SBM for  $k \rightarrow +\infty$ ) and agnostic learning in the paper!*
- (3) **Erdos-Renyi**: “almost” tight optimal rate.

# Summary of Contributions

- (1) We focus on optimal private estimation of **Stochastic Block Model** and **Erdos Renyi** models.
- (2) **Stochastic Block Model**: new analysis of existing algorithm (BCS'15) matches **optimal non-private rate** in many regimes.  
*Graphons (k-SBM for  $k \rightarrow +\infty$ ) and agnostic learning in the paper!*
- (3) **Erdos-Renyi**: “almost” tight optimal rate.
- (4) Proved an **extension lemma** - potentially of broad use.



# Open Questions

(1) **SBM**: Study of the term  $\rho^2 \frac{(k-1)^2 \log n}{n\epsilon}$  (exponential mechanism term).

# Open Questions

- (1) **SBM**: Study of the term  $\rho^2 \frac{(k-1)^2 \log n}{n\epsilon}$  (exponential mechanism term).
- (2) Complete the lower bound proof of  $\frac{1}{n^3 \epsilon^2}$ -rate for **Erdos-Renyi** model.

# Open Questions

- (1) **SBM**: Study of the term  $\rho^2 \frac{(k-1)^2 \log n}{n\epsilon}$  (exponential mechanism term).
- (2) Complete the lower bound proof of  $\frac{1}{n^3 \epsilon^2}$ -rate for **Erdos-Renyi** model.
- (3) **Time-efficiency!**  
No non-trivial efficient private algorithm even for 2-SBM!

# Open Questions

- (1) **SBM**: Study of the term  $\rho^2 \frac{(k-1)^2 \log n}{n\epsilon}$  (exponential mechanism term).
- (2) Complete the lower bound proof of  $\frac{1}{n^3\epsilon^2}$ -rate for **Erdos-Renyi** model.
- (3) **Time-efficiency!**  
No non-trivial efficient private algorithm even for 2-SBM!
- (4) Statistically optimal private results using **extension lemma!**  
-Recent work on **private estimation of**  $\mathcal{N}(\mu, \Sigma)$  [KV'18],[KLSU'18]  
What is the **tight statistical rate**? Ongoing work with C. Tzamos.

# Open Questions

- (1) **SBM**: Study of the term  $\rho^2 \frac{(k-1)^2 \log n}{n\epsilon}$  (exponential mechanism term).
- (2) Complete the lower bound proof of  $\frac{1}{n^3 \epsilon^2}$ -rate for **Erdos-Renyi** model.
- (3) **Time-efficiency!**  
No non-trivial efficient private algorithm even for 2-SBM!
- (4) Statistically optimal private results using **extension lemma!**  
-Recent work on **private estimation of**  $\mathcal{N}(\mu, \Sigma)$  [KV'18],[KLSU'18]  
What is the **tight statistical rate**? Ongoing work with C. Tzamos.

## Thank you!!

# The case $k = 1$ : Lower Bound Sketch

## Theorem (BCSZ FOCS '18 )

For  $\epsilon > \frac{\log n}{n}$ ,

$$\mathcal{R}_1(\epsilon) = O\left(\frac{1}{n^2} + \frac{\log n}{n^3 \epsilon^2}\right).$$

Furthermore, if  $G$  is sampled u.a.r. from graphs with a fixed number of edges (conditional Erdos Renyi) for  $\epsilon$  constant,

$$\mathcal{R}'_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right).$$

# Lower Bound: Estimation to Testing

## Goal

$$\mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^3\epsilon^2}\right).$$

Proof for u.a.r  $n$  vertices,  $m$  edges (conditional ER), call it  $G(n, m)$ .

# Lower Bound: Estimation to Testing

## Goal

$$\mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^3\epsilon^2}\right).$$

Proof for u.a.r  $n$  vertices,  $m$  edges (conditional ER), call it  $G(n, m)$ .

- **From estimation to testing:** If

$$\mathcal{R}_1(\epsilon) = o\left(\alpha_n^2\right)$$

then we can distinguish between  $G_{n,p}$  and  $G_{n,p+\alpha_n}$ .



# Lower Bound: Estimation to Testing

## Goal

$$\mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right).$$

Proof for u.a.r  $n$  vertices,  $m$  edges (conditional ER), call it  $G(n, m)$ .

- **From estimation to testing:** If

$$\mathcal{R}_1(\epsilon) = o\left(\alpha_n^2\right)$$

then we can distinguish between  $G_{n,p}$  and  $G_{n,p+\alpha_n}$ .

- **General privacy limitation:** By using  $\epsilon$  (-node)-DP algorithms, inputs of (node-)distance at most  $O\left(\frac{1}{\epsilon}\right)$  are indistinguishable!

# Lower Bound: Estimation to Testing

## Goal

$$\mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right).$$

Proof for u.a.r  $n$  vertices,  $m$  edges (conditional ER), call it  $G(n, m)$ .

- **From estimation to testing:** If

$$\mathcal{R}_1(\epsilon) = o\left(\alpha_n^2\right)$$

then we can distinguish between  $G_{n,p}$  and  $G_{n,p+\alpha_n}$ .

- **General privacy limitation:** By using  $\epsilon$  (-node)-DP algorithms, inputs of (node-)distance at most  $O\left(\frac{1}{\epsilon}\right)$  are indistinguishable!

## Random Graphs Question

For which  $\alpha_n$ ,  $G_{n,p}$  and  $G_{n,p+\alpha_n}$  have node-distance  $O\left(\frac{1}{\epsilon}\right)$ ?

# Lower Bound: Coupling Random Graphs

## Goal and an Easy Coupling

Need couple  $G_{n,p}$  and  $G_{n,p+\alpha_n}$  with *node-distance*  $O\left(\frac{1}{\epsilon}\right)$ .

Each edge  $\alpha_n$ -probability slack, easy to couple with  $O\left(\alpha_n \binom{n}{2}\right)$  new edges.

# Lower Bound: Coupling Random Graphs

## Goal and an Easy Coupling

Need couple  $G_{n,p}$  and  $G_{n,p+\alpha_n}$  with *node-distance*  $O\left(\frac{1}{\epsilon}\right)$ .

Each edge  $\alpha_n$ -probability slack, easy to couple with  $O\left(\alpha_n \binom{n}{2}\right)$  new edges.

- **Easy**  $\alpha_n = \frac{1}{n^2 \epsilon} \left( \Rightarrow \mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^4 \epsilon^2}\right) \right)$   
 $O\left(\frac{1}{\epsilon}\right)$  new edges, hence *node-distance*  $O\left(\frac{1}{\epsilon}\right)$ .

# Lower Bound: Coupling Random Graphs

## Goal and an Easy Coupling

Need couple  $G_{n,p}$  and  $G_{n,p+\alpha_n}$  with *node-distance*  $O\left(\frac{1}{\epsilon}\right)$ .

Each edge  $\alpha_n$ -probability slack, easy to couple with  $O\left(\alpha_n \binom{n}{2}\right)$  new edges.

- **Easy**  $\alpha_n = \frac{1}{n^2 \epsilon} \left( \Rightarrow \mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^4 \epsilon^2}\right) \right)$   
 $O\left(\frac{1}{\epsilon}\right)$  new edges, hence *node-distance*  $O\left(\frac{1}{\epsilon}\right)$ .
- **Harder**  $\alpha_n = \frac{1}{n^2 \epsilon} \left( \Rightarrow \mathcal{R}_1(\epsilon) = \Omega\left(\frac{1}{n^3 \epsilon^2}\right) \right)$   
 $O\left(\frac{\sqrt{n}}{\epsilon}\right)$  new edges, can we assign  $\sqrt{n}$ -edges per vertex?

## Proposition (Key Step)

*For appropriate choice of  $m = \Theta(n^2)$ , there is a coupling between  $G(n, m)$  and  $G(n, m + o(\sqrt{n}))$  where instances are always node-neighbors.*