TECHNICAL REFERENCE & SYSTEM DOCUMENTATION

SAILAB

Simulation & Analytics for Inundation, Loss, Assets & Built Environment

A tiered, physics-grounded flood intelligence platform for Pakistan

Complete technical reference covering system architecture, the physics engine, every mathematical model and formula in use, every data source, every feature, the validation record, the major bugs found and fixed, and the stated limitations.

Third edition, 31 October 2026 (supersedes the second edition of 12 October 2026).

Contents

Part I — Overview

What changed in this edition 4
1. Executive Summary 6
2. System Architecture 8
3. Data Sources 10

Part II — The Physics Engine

4. Shallow Water Hydrodynamics & LISFLOOD-FP 12
5. Solvers: ACC, DG2, and the GPU/CUDA Port 14
6. Boundary Conditions & Forcing 16
7. Numerical Stability Findings 17

Part III — The Prediction Tiers

8. The Tiered Workflow 18
9. Tier 2: Instant HAND-Based Flood Preview 19
10. Tier 3: Full Physics Simulation 20

Part IV — Rainfall & Climate

11. Rainfall Forcing & Design Storms 21
12. Real Recorded IDF Curves 22
13. Climate Change Scaling 23
14. Antecedent Moisture, Infiltration & Friction 24

Part V — Hazard-Specific Modules

15. Fluvial Flooding 25
16. Glacial Lake Outburst Floods (GLOF) 26
17. Dams & Reservoirs 28
18. Snow & Glacier Melt 29
19. Coastal & Tidal Flooding 31
20. Pluvial / Flash-Flood Risk Tiering 34
21. Geomorphology, Landslides & Sediment 35

Part VI — Impact, Risk & Economics

22. Buildings & Infrastructure Risk 36
23. Land-Use Damage & Hotspot Analysis 38
24. Estimated Monetary Loss 39
25. Average Annual Loss (AAL) 40

Part VII — Mitigation & Decision Support

26. Nature-based Solutions (NbS) 41
27. Grey Infrastructure Protection Scenarios 42
28. Mystic-Driven Auto-Optimization 43

Part VIII — Monitoring & Discovery

29. Live Continuous Monitoring & Alerts 44
30. Glacier SAR Displacement Monitoring 45
31. Storm-Motion Nowcasting 46
32. Discovery Tools: Basins, Tehsils, Rainfall Hotspots 47

Part IX — Validation

33. Validation & Accuracy Record 48

Part X — Visualization & Reporting

34. 3D Visualization 51
35. Reports, Comparisons & Exports 53
36. User Interface Design System 54

Part XI — Engineering History & Operations

37. Chronicle of Major Bugs Found and Fixed 55
38. Considered and Declined 59
39. Known Limitations 60
40. Operations & Testing 61
41. References 63

What changed in this edition

Changes in the third edition (31 October 2026)

AREA	CHANGE
Coastal datum	The Khan et al. (2020) Karachi return levels are heights above the tide gauge's own zero, not above mean sea level; they had been applied to the DEM as if above MSL. The gauge puts MSL 1.849 m above its zero, so the 100-year level is 1.91 m above MSL, matching the independent GTSM value (1.79 m). The "2× disagreement" reported earlier was this error. Coastal results made before 14 October 2026 with the Khan source overstate flooding (§19.10).
Astronomical tide	A 23-constituent harmonic fit to the supplied Karachi hourly record, validated on two unseen years (RMSE 0.118 m), adds real tide to the dynamic coastal run and the animated preview, with the surge placed at spring high water, an ordinary high water or a low water (§19.10).
Vector data	A local PostGIS database is now the first source for roads, hospitals, schools, power and railway lines, airports and stations, with the shapefiles as fallback; inside Islamabad, drivable roads and six extra facility categories are added, and road results gain major/local, bridge and length figures (§22.6–22.8).
Entry points	`/` is now a landing page and the application is at `/app`; an optional access token protects non-local requests; a separate client plugin lets other programs call a running SAILAB (§2.4, §40.2).
Operations agents	A data-health watchdog, a forecast-validation ledger and automatic run QA run in the background and alert only on change; they detect and suggest and never alter a result (§40.1).
Observed-flood scoring	Upload a mapped flood extent and score any finished run (CSI, POD, FAR, F1, area ratio); scenes can be rebuilt without re-simulating; a cache-cleanup tool (dry run by default) was added (§35.4–35.6).
Validation, corrected	The 2022 Sindh test box (CSI 0.66) was 98% flooded in the observed map, so it showed no skill. A controlled study on three half-flooded areas against ANUGA, SFINCS and TELEMAC-2D found accuracy on par with them, and no model clearly better than a trivial "flood everything" guess under rain-only forcing (§33.1).
LISFLOOD-FP 8.3	Built and benchmarked against 8.2; identical results, no speed gain on our cases; not adopted (§4.3).
Earth Engine	Re-authenticated on 13 October 2026 and verified live (glacier baseline, SAR displacement, storm-motion nowcast); the project reports a restricted compute quota. The previous "credential revoked" statements are superseded (Ch. 3, 30, 39).
Tests	420 fast tests passing at the last full run.

Changes in the second edition (12 October 2026)

The September 2026 edition was compiled before a month of further work, and several of its statements are no longer true. This table lists every substantive change; the chapters themselves have been rewritten to match the code as of 8 October 2026.

AREA	CHANGE
Tier 1	The Tier 1 ML discharge estimator (Caravan-trained LSTM) has been retired; its code and model are gone and the UI now has Tier 2, Tier 3 and Coastal tabs. Discharge for Tier 2 now comes from manual entry, a GLOF estimate, a dam event or the melt model (Ch. 8).
GPU inflow	River, GLOF, snowmelt and dam inflows now run on the GPU. The earlier "CUDA silently drops boundary inflow" finding was a misdiagnosis caused by inlets placed on NODATA cells (Ch. 5, §37.25).
Coastal on GPU	A local patch to LISFLOOD-FP's CUDA kernel makes coastal stage (HVAR) boundaries work on the GPU (Ch. 5, §37.26).
Solver choice	ACC is now used everywhere (`FORCE_ACC_ONLY`) with an empirical depth correction on steep terrain; the steep-terrain starting timestep is 1.0 s, not 0.2 s (Ch. 5, 7).
Formula fix	The Popov (1991) GLOF formula was printed incorrectly in the previous edition. The code uses $Q = 0.0048 \cdot V^{0.896}$ (Ch. 16).
Correction	The "dormant 1000× rainfall-column bug" fix described previously was itself wrong for this build and has been reversed (§37.14, §37.21).
New chapters	Dams & reservoirs (17), Snow & glacier melt with IceBoost ice thickness and a debris factor (18), Geomorphology, landslides & sediment (21), Validation (33), Operations (40).
Data paths	All shared-drive paths now live in one module (`data_paths.py`), checked at start-up; the Pakistan DEM moved and the silent Bahawalpur fallback was removed (Ch. 3, §37.22).
Validation	2022 Sindh flood re-validated with a corrected storm: CSI 0.659 (48 h) and 0.694 (10-day) (Ch. 33).
Ops	GPU throttling/temperature caps removed; the app applies none.
Coastal data	42-station GTSM return levels (selectable; the apparent ~2× disagreement with the gauge anchors was a datum error, corrected in the third edition, §19.10), sea mask, mangroves, sea-level-rise input, susceptibility index and instant level explorer (Ch. 19.6–19.9).
Run control	Queue position, the run ahead, and a Cancel button; run summaries and reports carry the SAILAB version (6.1); finished runs can download a susceptibility-style map (Ch. 35).
GLOF	Documented-event list (HMAGLOFDB), a Popov-vs-observed check with an empirical range on every estimate, and the PMD 2024 lake inventory as a lake source (Ch. 16.2a–c).
Glacier speed	ITS_LIVE recent-versus-same-season glacier speed that needs no Earth Engine account (Ch. 30.1).

1. Executive Summary

SAILAB (Simulation & Analytics for Inundation, Loss, Assets & Built Environment) is a web-based flood intelligence platform built for Pakistan, with particular depth of testing in Gilgit-Baltistan's high-mountain, glacier-fed terrain. It combines a GPU-accelerated 2D hydrodynamic engine (LISFLOOD-FP 8.2) with free national and global datasets — Google Open Buildings, OpenStreetMap/HOTOSM exports, government infrastructure layers, ESA WorldCover, SoilGrids, HydroSHEDS/HydroLAKES, Global Dam Watch, the PMD glacier and lake inventory, IceBoost glacier thickness, ERA5-Land, GloFAS, GTSR tide-and-surge reanalysis, a Pakistan extreme-rainfall/IDF cube and Open-Meteo's live APIs — to answer one question: if a given amount of rain, river discharge, glacial-lake outburst, dam release, snowmelt or coastal surge occurs over an area, how deep will the water get, which buildings and roads are affected, what will it cost, and what can be done about it?

The workflow is tiered by speed and fidelity. Tier 2 gives a sub-second terrain-index flood extent for a given discharge; Tier 3 runs the full shallow-water physics on the GPU and is the authoritative answer; a Coastal tab covers tide and storm surge. Every number the system reports is either a measurement, a published formula applied to real inputs, or an explicitly labelled approximation. This document states which, formula by formula and dataset by dataset.

1.1 What SAILAB computes

Given an area of interest (AOI) in Pakistan — drawn, uploaded, picked by tehsil name or chosen from HydroSHEDS basins — SAILAB:

1. crops the national SRTM DEM to the AOI's exact polygon and burns in existing dams and reservoirs;
2. conditions real building footprints into the terrain as flow obstacles;
3. sets per-cell Manning's roughness from ESA WorldCover and an AOI infiltration rate from a flat value, an antecedent-moisture slider or SoilGrids soil texture;
4. drives the terrain with a chosen forcing: a design storm (manual, CMIP6 return period or observed IDF), an uploaded rain-gauge series, a river hydrograph, a GLOF, a dam spillway release or failure, a snowmelt hydrograph, or a coastal water-level series;
5. solves the 2D shallow-water equations with LISFLOOD-FP on the GPU;
6. samples the per-timestep depth and velocity against buildings, roads, hospitals, schools, airports, railways, ports and power lines, using published hazard (DEFRA) and damage (Huizinga et al. 2017) curves;
7. converts damage into an estimated loss in PKR and, across return periods, an Average Annual Loss;
8. tests nature-based and grey-infrastructure mitigation with full physics re-runs; and
9. renders an animated 3D scene and shareable HTML/PDF reports.

1.2 Status of the evidence

Numerical correctness has been checked more than real-world accuracy. SAILAB's solver gives the same flood as three independent codes (ANUGA, TELEMAC-2D, SFINCS) on identical inputs, with 90–94% of flooded cells in common (Ch. 33.1), and matches its own CPU build to the displayed digit where tested. Accuracy against an observed flood is much weaker: the only observed-flood test used a rain-only storm on a 2022 flood that came mostly from river overflow, and no model, SAILAB

included, scored clearly better than the trivial guess of flooding everything. SAILAB is therefore documented as comparable in accuracy to other open 2D models, faster on its GPU, and far more integrated, not as demonstrably more accurate.

2. System Architecture

2.1 Components

LAYER	TECHNOLOGY	ROLE
Web application	Flask (Python), one long-lived process, no auto-reload	Routes every action, orchestrates async jobs, serves the single-page UI (`fis_app.py` , 74 routes).
Physics engine	LISFLOOD-FP 8.2 (C++/CUDA), subprocess per run	Solves the 2D shallow-water equations on the conditioned DEM (`flood_model.py` writes inputs and reads outputs). Its own report template still carries the older "PluviSim" name.
Melt model	`hydro_model.py` (NumPy), subprocess per basin	Daily distributed snow/glacier/soil/lake model on ERA5-Land (Ch. 18).
Geoprocessing	rasterio, GDAL, shapely 2, geopandas, pyogrio, pysheds	DEM cropping/reprojection, polygon clipping, HAND and flow direction, vector filtering.
Map and 3D	Mapbox GL JS v3.6.0, mapbox-gl-draw	AOI drawing/upload, basemap, search, native 3D terrain with animated flood overlay.
Optimization	mystic (differential evolution)	Protection-structure placement; every trial a real physics run.
ML	PyTorch (GPU)	Storm-motion nowcasting LSTM.
Reports	WeasyPrint, matplotlib, imageio-ffmpeg	HTML/PDF reports, diff/trend plates, MP4 export.

2.2 The async job and caching pattern

Every expensive action (a physics run, a scenario re-run, a dynamic surge, a melt-model run, an optimization or calibration search) starts a background thread, returns a job id at once, and is polled through a progress endpoint. Physics runs report named stages (`dem → buildings → model → postprocess → scene → done`). Results are cached on disk, keyed by a hash of the exact polygon geometry plus every parameter that affects the result and, for flood runs, a pipeline signature (pipeline version + dam-data fingerprint) so that results computed before a pipeline change are never served. A cache hit returns in milliseconds; it never regenerates outputs written by older code.

2.3 Concurrency and hardware

SAILAB runs on a shared NVIDIA GB10 (DGX Spark, CUDA 13, compute capability 12.1). A global `threading.Semaphore(1)` (`SIM_SLOT`) serializes SAILAB's own physics runs; it is released before, and re-acquired after, any nested confirmation run inside the optimizer because it is not re-entrant. The app no longer applies any GPU throttling, temperature monitoring or headroom waits (removed October 2026 at the owner's request). `SAILAB_FORCE_CPU=1` forces the CPU build when needed.

2.4 Entry points, vector data, access and the client plugin NEW

- **Landing page.** `/` serves `landing.html` (read from disk on each request): a full-screen WebGL fragment-shader scene of a tsunami wave with the product name and an "Open SAILAB" button.

The button plays a 1.5 s surge, then opens `/app` (the application). Links with `?import=<id>` skip the landing page so the SimCity hand-over still works. Ctrl-click, middle-click and reduced-motion users navigate directly; without WebGL a CSS gradient is shown.

- **Access token.** If `SAILAB_ACCESS_TOKEN` is set in `.env`, every request not from `127.0.0.1` needs `?token=...` once (it sets a cookie) or a Bearer header. An SSH tunnel to port 8000 arrives from loopback and needs no token.
- **Vector data.** A local PostGIS database (the SimCity database; read-only connection from `SAILAB_PG_URL`, never committed) is tried first for roads, hospitals, schools, power and railway lines, airports and stations. On any failure it backs off for 60 s and the shapefiles take over (§22.6).
- **Solver slot.** A tracked slot serialises solver use; `/solver-status` shows the holder and waiters, queued runs report their position, and a run can be cancelled while queued or while the solver is running (not during post-processing).
- **Client plugin.** `sailab-client` (in `sailab-plugin/` of the GitHub repository) is a thin HTTP client for a running SAILAB, used by the Islamabad SimCity project. SAILAB must stay reachable because the data and the GPU solver remain on the server.
- **Source control.** The whole application, tests, documentation and plugin are published to `github.com/Iliyan2004/Flood` (branch master). Secrets, data files, caches, the virtual environment and the PostGIS password are never committed.

3. Data Sources

Every dataset is real and free/open or licensed for this use; none is synthetic. Shared-drive paths are defined once in `data_paths.py` (overridable per machine with `SAILAB_<NAME>`); `check_data_paths()` runs at start-up and is exposed at `/data-status`, so a missing required dataset produces a clear error rather than a silent fallback.

DATASET	PROVIDER	USED FOR	ACCESS
Pakistan SRTM DEM	User-supplied, 13.48 GB, EPSG:32642, ~29 m	Physics terrain for every run	Shared drive (required)
Copernicus DEM GLO-30	ESA / AWS Open Data	Opt-in terrain outside Pakistan	Anonymous range reads
Google Open Buildings	Google Research	Footprints, burned in as obstacles and risk-classified	Local Parquet tiles, network fallback
HOTOSM roads / buildings	Humanitarian OSM Team	1,113,962 roads (indexed GeoPackage); building height tags	Local
Hospitals, schools, power lines, airports, sea ports, railway stations and lines	Government/OSM-derived shapefiles	Critical and strategic infrastructure risk	Shared drive
ESA WorldCover 2021	ESA, 10 m	Per-cell Manning's n, land-use damage, NbS	Windowed HTTP read
SoilGrids 2.0	ISRIC	Sand/clay → USDA texture → Ksat; sediment d_{50}	Local Pakistan extract
HydroSHEDS level-08 basins	WWF / USGS (Lehner & Grill 2013)	Basin discovery and melt-model basins (1,131 polygons)	Local
HydroLAKES	Messager et al. 2016	953 Pakistani lakes for GLOF scenarios	Shared drive
Global Dam Watch	GDW / GOODD	101 dams, 86 reservoirs burned into every run	Local
Spillway events	Compiled records	10 Mangla/Tarbela openings (4 with numeric outflow)	Local CSV
PMD glacier & lake inventory 2024	Pakistan Meteorological Department	Glacier mask and lake nodes for the melt model	Shared drive
IceBoost v2.0 ice thickness **NEW**	RGI v7 region 14, Zenodo 21220985	Modelled ice thickness (m), 26.6 m grid	Local
Debris melt factor **NEW**	User-supplied, same grid	Ice-melt multiplier	Local

ERA5-Land hourly t2m and precipitation	ECMWF / Copernicus, 0.1°, 1980–May 2026	Melt-model forcing	Shared drive (Zarr)
GloFAS historical reanalysis	Copernicus EMS, 0.05°	Melt-model plausibility check (discharge and runoff)	Shared drive
GTSR	Muis et al. 2016	Daily-maxima surge 1979–2014, 94 Pakistan-coast stations	Local (~1.3 GB)
Pakistan rainfall/IDF cube + tehsils	ERA5-Land and IMERG V07, sibling task	Per-cell extreme indices, IDF curves, 578 tehsils	Local
CMIP6 (NEX-GDDP)	NASA, 34 models	Design storms and climate scaling	Shared drive
GLiM lithology	Hartmann & Moosdorf 2012	Rock-type erodibility	Local
ML landslide susceptibility, valley depth, confinement	Shared national rasters	Geomorphology (KPK/GB/AJK for the ML map)	Shared drive
Open-Meteo Forecast, Historical, Flood, Marine	Open-Meteo	Forecasts, climatology, GloFAS discharge context, waves	Live HTTPS
Sentinel-1, GLIMS, IMERG via Earth Engine	ESA / NSIDC / NASA	Glacier SAR displacement; storm tracks	Earth Engine (re-authenticated 13 Oct 2026; restricted compute quota)

Earth Engine. Glacier SAR monitoring (Ch. 30) and storm-motion nowcasting (Ch. 31) need a live Earth Engine OAuth credential. The earlier token was revoked (`invalid_grant`); it was renewed on 13 October 2026 with the Drive and Storage scopes dropped (the default client blocks them) and verified live: a GLIMS baseline (52 glaciers, 217 km²), a two-month Shishper SAR job (mean displacement 1.24 m, maximum 11.46 m) and a storm-motion nowcast. The project reports "restricted mode" (non-commercial compute quota exceeded). If the token lapses again, both features return a plain "not available" message instead of a fabricated result, and the health watchdog (§40.1) refreshes the token every 15 minutes so a lapse is reported.

4. Shallow Water Hydrodynamics & LISFLOOD-FP

All physical flooding in SAILAB is governed by the two-dimensional shallow water (depth-averaged Saint-Venant) equations, in conservative form:

$$\partial h/\partial t + \partial(hu)/\partial x + \partial(hv)/\partial y = R - I$$
$$\partial(hu)/\partial t + \partial(hu^2 + \tfrac{1}{2}gh^2)/\partial x + \partial(huv)/\partial y = -gh\,\partial z/\partial x - c_f\,u\,\sqrt{(u^2+v^2)}$$
$$\partial(hv)/\partial t + \partial(huv)/\partial x + \partial(hv^2 + \tfrac{1}{2}gh^2)/\partial y = -gh\,\partial z/\partial y - c_f\,v\,\sqrt{(u^2+v^2)}$$

where h is depth, u, v depth-averaged velocities, z bed elevation, g gravity, R the rainfall/inflow source, I infiltration, and $c_f = g\,n^2 / h^{1/3}$ from Manning's n. LISFLOOD-FP 8.2 (University of Bristol / Sheffield, GPLv3, DOI 10.5281/zenodo.13121102) integrates these equations; SAILAB implements no shallow-water solver of its own.

4.1 Why LISFLOOD-FP, and why GPU

SAILAB began on the CPU-only v5.9 binary and was upgraded to the official 8.2 source with its CUDA solvers. On the Bahawalpur benchmark the 8.2 CPU build was bit-identical to v5.9, and the GPU build agreed with it (2.816 vs 2.818 m max depth) at ~10–11× the speed. Building 2022-era code against CUDA 13 on ARM64/Blackwell needed four fixes, each root-caused from the compiler error: a C++17 bump, a Windows-only `cbrt` macro gated to MSVC, removed `cudaDeviceProp` fields replaced with `cudaDeviceGetAttribute`, and a `sync()` collision with POSIX renamed. NUMA is satisfied by a stub; NetCDF is off in the main build and on in a second build used for spatial rainfall.

4.2 Local changes to LISFLOOD-FP

CHANGE	FILE(S)	WHY
Missing `acceleration` argument restored in the `MaxField` constructor call	`cuda_dg2/fv1/fv2_simulate.cu`	Unpadded buffer, out-of-bounds GPU write, DG2 crash on large domains (§37.18).
HVAR stage boundary applied when stage − DEM > DepthThresh, not only to already-wet cells **NEW**	`cuda/acc/cuda_acc_solver.cu` (all four edges)	A dry coastal edge received no water at all on the GPU (§37.26).

The patched kernel source is kept in the working copy as `lisflood_patches/cuda_acc_solver.cu` and must be re-applied after any re-extraction of the LISFLOOD-FP source. Both `build` and `build_netcdf` are rebuilt after each patch.

4.3 LISFLOOD-FP 8.3 evaluated, not adopted NEW

Version 8.3 (Zenodo 10.5281/zenodo.13121119, 13 October 2026, Rehman and Teferle, University of Luxembourg) is 8.2 with the maximum-depth grid of the FV1/FV2/DG2 solvers kept on the GPU at full size (the same bug fixed by hand in §4.2), no per-step shared mass counter for dry NoData cells, thread-synchronised flux kernels, and a Metal back end for Apple Silicon; the numerical method is unchanged. The archive's MD5 matched. It was built with the local fixes re-applied (its sources use CRLF line endings, so patches need `--binary`) and run against 8.2 on the same cases:

CASE	8.2	8.3
Bahawalpur, ACC, 104 km²	5 s	4 s, byte-identical `res.max`
400×400 DG2, steep synthetic	344 s	345 s
700×700 DG2 (490,000 cells)	913 s	1,137 s (confounded by machine load)

8.3 writes depths to six decimals against three in 8.2; rounded to three decimals the flooded cell count matches exactly (621), while the unrounded files count 666 cells between 0.0495 and 0.05 m as wet. No speed gain appeared at our sizes (the published gain is for grids of about 10 million cells) and its main fix is one already patched locally, so `flood_model.LISFLOOD_BIN` still points at 8.2. The 8.3 build is kept in `~/flood/lisflood-fp-8.3` for a future multi-million-cell test.

5. Solvers: ACC, DG2, and the GPU/CUDA Port

5.1 The local-inertial (ACC) solver

ACC drops the convective-acceleration terms from the momentum equation (Bates, Horritt & Fewtrell 2010):

$$q^{t+\Delta t} = [\ q^t - g\ h\ \Delta t\ \partial(h+z)/\partial x\ ] \ /\ [\ 1 + g\ n^2\ |q^t|\ \Delta t\ /\ h^{7/3}\ ]$$

where q = hu is unit discharge. It is fast and accurate on gentle floodplains but is genuinely wrong on steep terrain, where the dropped terms matter. On a 400×400 crop of Gilgit-Baltistan terrain (92.5% mean slope) DG2 gave 4.65 m maximum depth; ACC gave 140.43 m at a 5.0 s start step and 37.54 m even at 0.2 s.

5.2 The second-order discontinuous Galerkin (DG2) solver

DG2 solves the full shallow-water system with a piecewise-linear representation of each variable per cell, a Godunov-type flux and a slope limiter. It is the physically correct choice on steep terrain, at 10–60× the wall-clock cost of ACC (higher per-cell cost and smaller stability-limited steps). A measured-scaling estimate puts a 30 m DG2 run of a ~5,600 km² Karakoram basin at about 5 hours.

5.3 Solver selection, current setting

`choose_solver_for_terrain` computes the DEM's mean slope (nearest-valid-neighbour NODATA fill, then a gradient) and would choose DG2 above `DG2_SLOPE_THRESHOLD_PCT` = 10 %, with two overrides: any boundary inflow forces ACC (DG2's timestep collapses under an injected flux), and domains above `DG2_CUDA_MAX_CELLS` = 4,000,000 force ACC (the largest size tested clean after the crash fix).

Current setting: **`FORCE_ACC_ONLY = True`.** ACC is used everywhere, trading DG2's accuracy for speed. On terrain above 10 % mean slope the raw ACC depth is divided by an empirical correction factor fitted to a 7-point ACC-vs-DG2 benchmark (15–200 % slope; $R^2 = 0.992$; maximum corrected-depth error 4.9 %):

```
correction     = 2.9664 + 0.037 × mean_slope_%
depth_reported = depth_ACC / correction        (only when mean slope > 10 %)
```

> The correction fixes depth magnitude only. It cannot fix flow-path errors from ACC's missing momentum terms, and it was fitted on one storm, one synthetic ramp and one domain size. Set `FORCE_ACC_ONLY = False` to return to slope-based DG2.

5.4 GPU and CPU paths UPDATED

RUN TYPE	BUILD USED	EVIDENCE
Rain only	GPU	~10–11× faster than CPU, same result (Bahawalpur).
River, GLOF, snowmelt, dam inflow (QVAR)	GPU when the inlet is on valid terrain; CPU if any inflow cell is NODATA	Stored volume 1.9672×10^5 / 1.5746×10^6 m³ at 1 h / 4 h on both builds; full runs equal to the displayed digit (2.4701 km²/ 2.38 m constant; 2.8298 km²/2.57 m hydrograph; 6.6365 km²/ 2.62 m with rain and outlets).

Constant inflow	Written as a flat two-point QVAR	CUDA ACC has no QFIX case and injects zero.
Coastal stage (HVAR)	GPU (patched kernel)	Karachi SRTM crop, 0 → 4 m over 24 h: 41.4370 km² / 4.00 m on both builds; 34 s vs 97 s.

The GPU is not always faster: a 41,000-cell inflow-only run took 62 s on the GPU and 29 s on the CPU; with rain and free outlets it was 105 s vs 180 s. The CPU path pins `OMP_NUM_THREADS=1` (§7.4).

5.5 Diagnostics the GPU path does not write

MISSING UNDER CUDA	REPLACEMENT
`res.maxHaz` (peak DEFRA hazard)	Recomputed from the per-timestep depth and de-staggered velocity rasters.
Cumulative rainfall column in `res.mass`	Exact integral of the hyetograph actually written.
River inflow (`Qin`) column	Exact integral of the hydrograph actually applied (whole-cell width).

5.6 The GPU-MWDG2 adaptive solver — evaluated, not adopted

LISFLOOD-FP 8.2's multiwavelet DG solver with dynamic mesh refinement (Aureli et al. 2025) compiled and ran, and its mesh genuinely coarsened (97.5 % compression on a steep test). It has no rainfall source; a CUDA rainfall kernel written for it made it slower than DG2 at small scale and produced a physically impossible negative total volume (723 of 4,096 cells negative, one at −0.46 m). Not adopted.

6. Boundary Conditions & Forcing

6.1 Rainfall

Rainfall uses LISFLOOD-FP's own mechanism, never a custom source term. A design storm is a triangular hyetograph (linear rise to the peak at half the duration, linear fall to zero by the full duration). An uploaded gauge series drives the solver directly (`write_rain_file_from_series`; tied timestamps merged keeping the larger rate). Storm-centred or moving rain is written as a per-timestep NetCDF field and run through the NetCDF build.

6.2 River, GLOF, snowmelt and dam inflow (QVAR)

Discharge is injected over a localized channel-width segment of one AOI edge, not the whole edge (which would dilute it to nothing). Three corrections are built in:

- boundary coordinates are absolute: the DEM's own `xllcorner` / `yllcorner` is added (§37.12);
- the segment is clamped to the edge before the per-metre flux is computed (§37.13);
- the segment is snapped to whole cells, because the solver applies a boundary on whole cells — a 40 m channel on a 29 m grid previously delivered 1.46× the requested discharge (§37.27).

Hydrograph shapes: triangular with the peak at half the duration for rivers, at 10 % for GLOF, or an arbitrary time series (snowmelt, dam events) with its last value held to the end of the run. Delivered volume is checked analytically (2.160047×10^6 vs 2.16×10^6 m³ on a real DEM after the width fix).

6.3 Coastal water level (HVAR)

A time-varying stage boundary on the lowest-elevation edge that has land. The dynamic case uses a GTSR-anchored rise/peak/recede episode (Ch. 19). It now runs on the GPU (§5.4).

6.4 Outlets

Chosen edges are `FREE` (slope 0.001) and the rest `CLOSED`; individual outflow segments can also be placed.

7. Numerical Stability Findings

7.1 Timestep collapse on steep terrain

A controlled bisection (fixed synthetic domain, identical storm, varying only slope and starting timestep) showed that at the original 5.0 s start, maximum depth grew unphysically with slope alone (18 → 247 → 387 → 559 m from 15 % to 200 %), while the mass-balance error actually shrank — so mass error alone is not a reliable warning here. At ≤ 0.2 s every slope converged to the same answer.

The current rule: 5.0 s for rain-only runs on gentle terrain; 0.2 s for any river or GLOF inflow; 5.0 s for coastal-only HVAR (tested at 0.2, 2 and 5 s with matching mass balance, 13–17× faster); and **1.0 s** whenever a run would otherwise start at 5.0 s and the mean slope exceeds 10 %. The 1.0 s tier is a graduated compromise: at 200 % slope it only partly converged in testing (0.86 m vs 0.56 m at 0.2 s).

> **Residual.** On the full Gilgit-Baltistan basin (6.6 M cells; 851.8 % max slope, 72.2 % mean) the fix cut maximum depth from 348.40 m to 255.01 m but the mass-balance error grew 3.1×. ACC results on terrain this extreme should not be trusted; DG2 at 116 m gave 0.83 m for the same basin.

7.2 The DG2 CUDA crash

DG2 crashed (`cudaErrorIllegalAddress`) above a bisected domain size. compute-sanitizer traced it to an upstream copy-paste defect: the `MaxField` constructor call in the DG2, FV1 and FV2 simulate files was missing its `acceleration` argument, so an unpadded buffer was allocated for a padded grid. The correct call survives commented-out in the ACC file. Fixed in all three; a 4,000,000-cell run completed in 606.5 s.

7.3 Dead ends tested and rejected

- **Single-precision DG2:** 2.73× faster, but 2.59 m vs 4.65 m maximum depth on identical input — float32 cancellation between 2,000–5,500 m elevations and centimetre-to-metre depths.
- **Raising `depththresh`:** tripled flooded area and sextupled mass error; not a stability lever.

7.4 CPU threading: more cores were slower

Forcing the CPU solver's OpenMP region to use more than one thread made an identical inflow benchmark 6–7× slower, already at two threads. A `#pragma omp critical` inside the parallel loop serializes most work while every thread pays fork-join overhead each step. `OMP_NUM_THREADS` is pinned to 1.

7.5 Minor levers and checks

- `mint_hk`: ~8.5 % faster at ~0.2–0.35 % depth difference on a 4 M-cell benchmark; available, off by default.
- Friction floor `ABS_MIN_FPFRIC` = 0.01; numerical diffusion θ = 0.8 written when the lowest friction in use is below 0.02.
- Mass conservation, measured: closed rain-only synthetic domains at 300 m, 2 km and 6 km conserve mass on both builds (stored/analytic 1.000 CPU, 0.997–0.998 GPU).

8. The Tiered Workflow

Operational flood systems trade speed against physical fidelity. SAILAB exposes that trade-off directly:

TIER	ANSWERS	SPEED	METHOD
Tier 2 — Instant Flood	Where would this discharge go?	< 1 s	HAND terrain index + Manning rating curve (Ch. 9)
Tier 3 — Physics Run	How deep, how fast, what is hit, what does it cost?	seconds to hours	LISFLOOD-FP on the GPU (Ch. 10)
Coastal / Tidal	What does a surge or tide do?	< 1 s to minutes	Static bathtub, animated preview, dynamic HVAR (Ch. 19)

Tier 1 retired. The previous edition described a Tier 1 discharge estimator: an LSTM trained on 630 Caravan basins (held-out-basin NSE 0.450) with nearest-analog regionalization. It has been removed from the app, together with its model and training sample, and is no longer part of SAILAB. Discharge for Tier 2 and Tier 3 now comes from manual entry, real GloFAS context (Open-Meteo Flood API), a GLOF estimate (Ch. 16), a dam spillway or failure scenario (Ch. 17), or the melt model (Ch. 18).

9. Tier 2: Instant HAND-Based Flood Preview

Tier 2 uses the terrain-index technique behind NOAA's CONUS Flood Inundation Mapping (Zheng et al. 2018, GeoFlood), computed per AOI on demand. No freely downloadable HAND dataset covering Pakistan exists (MERIT Hydro's is registration-gated), and per-AOI computation takes well under a second.

9.1 HAND

pysheds fills pits and depressions, resolves flats, computes D8 flow direction and accumulation, extracts streams where accumulation ≥ 500 cells, and labels every cell with its Height Above Nearest Drainage.

9.2 Discharge to depth

Channel width follows hydraulic-geometry scaling (Leopold & Maddock 1953):

$$W = \max(0.60 \cdot A_{km^2}^{0.50},\ 0.5)\ \text{m}$$

Manning's equation for a trapezoidal channel (side slope 1.5, n = 0.035) is solved by bisection for the stage that carries Q:

$$Q = (1/n) \cdot A_x \cdot R^{2/3} \cdot S^{1/2}$$

Cells whose HAND is below that stage flood. Verified monotonic: 50, 500 and 5,000 m³/s gave 4.0, 10.5 and 26.1 m maximum depth on a test AOI.

9.3 Caching and the discharge library

HAND is cached per AOI and DEM source (0.337 s cold, 0.014 s cached). A library at 1, 2, 5, 10, 20, 50, 100, 200, 500, 1,000, 2,500 and 5,000 m³/s lets the slider interpolate log-log in the browser with no server round-trip.

10. Tier 3: Full Physics Simulation

10.1 Pipeline stages

1. **DEM** — crop to the exact polygon (cells outside it NODATA), then burn in dams and reservoirs (Ch. 17).
2. **Buildings** — fetch Google Open Buildings and rasterize each full footprint onto valid cells as a +6 m obstacle; keep a bare copy for 3D.
3. **Model** — write the DEM, rainfall, boundary, friction and infiltration inputs and run LISFLOOD-FP (Ch. 4–7).
4. **Postprocess** — read the per-timestep depth/velocity stack (velocity de-staggered from the Arakawa C grid; spatially strided above 5,000,000 frame×cells so the 3D page stays loadable), classify buildings and infrastructure, compute loss, and rewrite `summary.json` with every enrichment.
5. **Scene** — build the animated Mapbox 3D page (Ch. 34).

Buildings, infrastructure and land cover (for Manning's n) are fetched in parallel background threads and joined only when needed.

11. Rainfall Forcing & Design Storms

11.1 The triangular design storm

A peak intensity (mm/hr) and duration become a triangular hyetograph: linear rise to the peak at half the duration, linear fall to zero at the full duration. Its depth is half the peak times the duration, and that analytic total is what the summary reports.

11.2 Areal Reduction Factor

Opt-in (`--enable-arf`): Keers & Wescott (1977) / FSR-FEH, ARF = $1 - b \cdot D^{-a}$ with five area bands, 1.0 below 1 km², clamped to (0.05, 1].

11.3 Uploaded rain-gauge data

A CSV (built against a 17-station, 15-minute network export) becomes one series per station: mm per interval → mm/hr using each interval's own length, negatives clamped to zero, real timestamps carried through to the 3D animation clock. Text locations are geocoded with ", Pakistan" appended (a bounding-box bias alone mis-resolved Islamabad sectors); when no station has coordinates and there is more than one, the user picks the station.

11.4 Storm-centred and moving rainfall

A weight $w = \exp(-r/L)$, normalised to mean 1 over the AOI ($L = \sqrt{(\text{area}/\pi)}$ by default), is written as a per-timestep NetCDF field; the centre may move at a set or LSTM-predicted velocity (Ch. 31).

11.5 Running on the live forecast

The forecast peak is the maximum future hourly rate; the duration is the contiguous span above 0.1 mm/hr around it, measured in the forecast's own local time (§37.19).

12. Real Recorded IDF Curves

A separately built Pakistan extreme-precipitation cube — ERA5-Land (1980–2026, ~9 km) and GPM IMERG V07 30-minute precipitation (2000–2026, ~11 km) — provides per-cell observed alternatives to a statistical design storm.

12.1 Per-cell indices (ETCCDI)

INDEX	MEANING
RX1day / RX5day	Maximum 1-day / 5-day total in a season or year
R95p / R99p	Total precipitation on days above the 95th/99th percentile (a seasonal aggregate)
SDII	Mean rate on wet days
R20mm	Days above 20 mm
PRCPTOT	Total precipitation
Peak hourly / peak 30-min	Highest recorded rate
Trend	Theil-Sen trend on RX1day

12.2 The intensity-duration curve

Points at 30, 60, 90, 120 and 180 min (IMERG) and 1, 2, 3, 6, 12 and 24 h (ERA5-Land). IMERG is preferred where both exist — the sources can disagree (11.06 vs 15.87 mm/hr at the same 1-hour point) and duplicates would break interpolation. Requested durations are interpolated log-log and clamped to the curve's range, never extrapolated. The default year is the latest complete one (2025; 2026 is partial), read from the dataset's manifest.

12.3 Not used to recompute pluvial risk

R95p/R99p are seasonal aggregates, a different statistic from the single-day percentile threshold of Ch. 20, so they are shown as a separate reference and not folded into that tier.

13. Climate Change Scaling

Annual-maximum daily rainfall from up to 8 of 34 NEX-GDDP-CMIP6 models (1985–2014) is fitted with a Gumbel (EV-I) distribution to give return-period depths (2, 5, 10, 25, 50, 100, 200 years), taken as the ensemble median. The intensification factor is the ratio of the same return-period value fitted for a future window (2036–2065 or 2071–2100) to the historical one (delta-change method). This is a statistical model projection; the observed IDF curve (Ch. 12) remains available alongside because the two answer different questions. Uncached, it reads dozens of files and takes 1–3 minutes.

14. Antecedent Moisture, Infiltration & Friction

14.1 Antecedent Moisture Condition

The solver takes one flat infiltration rate, so a full Curve-Number recalculation is not possible. A 0–100 slider multiplies the user's baseline (treated as AMC-II), interpolated linearly between three reference points approximating the CN(II)→CN(I)/CN(III) retention ratios:

```
multiplier(0)   = 1.8    AMC-I, dry
multiplier(50)  = 1.0    AMC-II, average
multiplier(100) = 0.25   AMC-III, saturated
```

Reports always show the baseline, the multiplier and the effective rate used.

14.2 Soil-derived infiltration (SoilGrids)

Sand and clay (0–5 cm) are classified into a USDA texture class (§37.16 fixed a gap for sand ≥ 45 % and clay ≥ 35 %), mapped to Rawls, Brakensiek & Miller (1983) saturated conductivity, and reduced to one area-weighted mean rate for the AOI, because the CUDA ACC solver has no per-cell infiltration. An optional Green-Ampt average rate solves the implicit cumulative-infiltration equation numerically.

14.3 Per-cell Manning's friction

Unlike infiltration, per-cell Manning's n is consumed by the CUDA ACC solver (`initialise_manning` , traced in source). ESA WorldCover classes map to overland-flow roughness (Chow 1959; USACE HEC-RAS; FEMA):

LAND COVER	MANNING'S N
Mangroves	0.140
Tree cover	0.130
Shrubland	0.070
Herbaceous wetland	0.045
Built-up (open ground between conditioned buildings)	0.045
Cropland	0.037
Grassland	0.035
Snow/ice, Moss/lichen	0.030
Bare/sparse vegetation, Permanent water	0.025

A floor of 0.01 and the θ = 0.8 numerical-diffusion term below 0.02 guard against the documented low-friction instability.

15. Fluvial Flooding

15.1 Automatic river siting

OSM waterways (river/stream/canal) that cross the AOI are found by distance to each edge; the inlet position is snapped to the nearest valid edge cell. Channel widths are documented estimates: river 40 m, stream 8 m, canal 15 m, other 20 m.

15.2 Discharge context

Open-Meteo's Flood API (GloFAS reanalysis and forecast) gives a 37-day discharge window so the user can set an informed peak. The physics is driven by the scenario the user sets, informed but not dictated by this context.

15.3 Channel conditioning and its limit

The DEM has no river bathymetry. An optional conditioning step carves a channel along the buffered waterway using the Tier 2 width/depth relations — an approximation of the sub-grid channel solver, which the CUDA build lacks. Without it, a large discharge forced into an estimated width can produce locally very deep results; that is a property of bare-DEM routing, not a bug.

16. Glacial Lake Outburst Floods (GLOF)

16.1 Peak-discharge formulas CORRECTED

Popov (1991): $Q_{peak} = 0.0048 \cdot V^{0.896}$

Huggel et al. (2002): $V = 0.1217 \cdot A^{1.4129}$

Froehlich (1995): $Q_{peak} = 0.607 \cdot V^{0.295} \cdot h^{1.24}$

V is lake volume (m³), A lake area (m²), h breach height (m), Q in m³/s. Huggel's area–volume relation is used only when no volume is known.

The previous edition printed the Popov formula incorrectly; the form above is the one in the code. Applied to Shishper Glacier Lake's 2022 event (38,987,000 m³) it gives 30,388 m³/s against a reported 3,737 m³/s — about 8× too high. That is why the curated Shishper preset uses the reported event numbers directly; the formula is used for lakes with no documented event. Froehlich is used when a breach height is known, including landslide-dam scenarios.

16.2 Lakes: a curated preset plus HydroLAKES

The curated list (Shishper) carries reported event data. Any of 953 Pakistani HydroLAKES lakes can be chosen by id or distance from the AOI, with the note that it is "a real lake, not individually validated against a documented GLOF event".

16.2a PMD 2024 lake inventory as a third lake source

The PMD glacial-lake inventory (3,378 lake polygons, northern Pakistan) can be searched by distance from the AOI. Each lake carries a dam type (morainic, ice-dammed, mixed, bedrock; spelling variants in the source are normalised), glacier relation and the nearest village. The inventory has no volume, so volume comes from the Huggel et al. (2002) area relation, which can be off by an order of magnitude. Newly formed lakes such as Shishper (2018) are not in it; use the curated preset for those.

16.2b Documented outburst events (HMAGLOFDB)

The High Mountain Asia GLOF database lists 774 events, 151 of them in Pakistan (140 in Gilgit-Baltistan, 47 since 2000). The app lists the events within 100 km of the drawn area with year, lake, dam type, mechanism, volume, peak discharge, deaths and impact, and an event with a documented discharge or volume can be added as a scenario. The catalogue is a compilation, not a census, and Pakistan's records are thin: only 9 report a volume and 3 a peak discharge (all Shisper, 85 to 142 m³/s).

16.2c How good is the Popov formula? NEW

On the 32 events worldwide that report both volume and peak discharge, the Popov estimate divided by the documented peak discharge has a median of 1.05 for moraine-dammed lakes (16 events; 10th to 90th percentile 0.11 to 14.3), 2.8 for supraglacial lakes (11 events) and 17 for ice-dammed lakes (5 events). Popov was fitted to moraine-dam failures, so it badly overestimates ice-dammed lakes, which are about half of Pakistan's recorded events; the 17 rests on only five events. Every volume-based discharge now shows a documented-event range (the Popov value divided by the ratio spread for that

dam type; all lake types when the type is unknown or has fewer than five events) with the event count and a caution. It is an empirical spread of the formula's error, not a forecast for the lake.

16.3 Hydrograph and routing

The peak arrives at 10 % of the event (default 3 h), matching the fast-rise, slow-recede shape of documented GLOFs. The peak can go to a Tier 3 inflow (needs siting) or straight to Tier 2 (no siting). Results link to the nearest HydroSHEDS basin, and a glacier SAR displacement result for a known lake links back to this estimator.

17. Dams & Reservoirs NEW

17.1 Burned into every run

Global Dam Watch (101 dams, 86 reservoirs, including Tarbela, Mangla, Chashma, Marala, Rasul, Hub, Warsak, Khanpur, Simly, Rawal, Tanda and Satpara) is applied to every run's bare DEM before buildings: reservoir polygons are lowered by their mean depth (10 m when missing) and dam points are raised by their height (15 m when missing) as a 60 m-radius patch, because GDW has no as-built alignment. The run cache key includes a fingerprint of the dam data, so results computed without dams are never served.

17.2 Spillway events

Ten documented Mangla/Tarbela spillway openings are available; four have a numeric outflow, converted from cusecs (× 0.0283168466 → m³/s) and added as an inflow at the dam. The 48 h duration is an estimate.

17.3 Dam-failure scenarios

Peak breach discharge from Froehlich (1995) with the reservoir's real volume. Only 23 of 101 dams have a recorded height. For 64 more, height is estimated from reservoir depth using the ratio measured on the 22 dams that have both (low / central / high = 1.14 / 2.30 / 3.17) and reported as a range; 14 have neither and are refused. Froehlich is fitted to small dams, so Tarbela-class results are order-of-magnitude only.

17.4 Spillway outlook

The GloFAS inflow forecast at the dam is compared with the lowest documented inflow at which the spillway opened. Validated only for Tarbela (GloFAS 6,576 m³/s vs documented 6,881 and 5,947: −4 % / +11 %). Mangla is refused: GloFAS gives 2.2 m³/s at the dam (808 m³/s at the best of 25 nearby cells) against a documented 8,495 m³/s.

18. Snow & Glacier Melt NEW

18.1 Short snowmelt forecasts (SRM)

Snowmelt Runoff Model style (Martinec & Rango 1986): the AOI is split into elevation bands, temperature is lapsed at 6.5 °C/km per band, and melt uses a degree-day factor of 4.5 mm $°C^{-1}$ day^{-1} (within the 2–6 range of the SRM manual and Hock 2003) above 0 °C. It gives a single-day discharge or a multi-day forecast hydrograph that can be used as a time-varying inflow.

18.2 Distributed snow and glacier model

`hydro_model.py` is a daily, pixel-distributed model run per basin:

- **Snow:** degree-day melt with a sub-daily temperature spread, rain/snow transition between 0 and 2 °C, refreeze (5 %) and liquid-water holding (10 %).
- **Glacier ice:** melt = DDF_{ice} × positive degree-days × terrain factor × debris factor, limited by the ice that remains; thickness evolves.
- **Soil, groundwater, fast runoff;** lakes with weir outflow and rapid-release rules.
- **Routing:** D8 with Manning-based travel time; outlet discharge is the sum over exit cells.

Forcing is ERA5-Land hourly temperature and precipitation clipped to the basin plus 0.3°. Temperature is lapsed to each pixel from its ERA5 cell's mean DEM height (−6.5 °C/km), because ERA5 cells span thousands of metres of relief in the Karakoram. Basins are prepared from SRTM in their UTM zone at max(30 m, area/40,000 pixels), typically ~260–270 m, with pysheds fill and D8, and PMD 2024 glacier and lake polygons. Default factors: DDF_{snow} 4 and DDF_{ice} 8 mm $°C^{-1}$ day^{-1}, precipitation factor 1, temperature offset 0.

18.3 Ice thickness and debris (October 2026)

IceBoost v2.0 modelled ice thickness (RGI v7 region 14) and a debris melt-factor raster, both on a 26.6 m grid, are averaged onto each basin's model grid over ice-covered source pixels only, so a half-ice cell gets the thickness of its ice rather than half of it. Glacier-inventory pixels where IceBoost models no ice are treated as ice-free (previously they received a flat 50 m).

BASIN	ICEBOOST ICE	MEAN THICKNESS	PMD GLACIER SHARE	PMD-ONLY CELLS
Hunza 4080566900	1,016 km² (37 %)	175 m	44 %	1,439
4080575700 (Ghizar side)	577 km² (20 %)	81 m	28 %	1,331

What changed the results was treating PMD-only pixels as ice-free: they carried about 15 % of all ice melt. Thickness itself matters little in a one-year run, because most ice is far thicker than a season's melt; it will matter for multi-year runs. The debris factor differs from 1 on only 0.5–1.3 % of ice pixels in both basins (mean 0.994–1.000), so it has almost no effect there and under-represents real Karakoram debris cover.

18.4 Plausibility check against GloFAS

GloFAS is itself a model, not gauge data; agreement is a plausibility check. The comparison cell is chosen by water balance: within ±3 cells of the outlet, the cell whose 2003–2012 mean discharge

matches the basin's own GloFAS-generated runoff (runoff × area) within 1.5×; otherwise no comparison is made. The old rule — the highest-flow cell inside the basin — picked a neighbouring river for Hunza (78 vs 20 m³/s). Skill is reported for the melt season (April–September) as KGE, NSE, bias and r, with a warning when |bias| > 40 % or KGE < 0.3.

$$KGE = 1 - \sqrt{[\ (r - 1)^2 + (\sigma_{sim}/\sigma_{obs} - 1)^2 + (\mu_{sim}/\mu_{obs} - 1)^2\ ]}$$

18.5 Per-basin calibration with a hold-out year

A grid of temperature offset (−3 to +1 °C) × precipitation factor (0.5 to 4) × degree-day pair (4/8 or 7/16) — 50 runs — is evaluated on a calibration year; the winner and the defaults are then run on a different hold-out year. A trial is rejected if glacier-wide mass balance is below −1.5 m w.e./yr (the regional geodetic range is −0.1 to −0.5; Hugonnet et al. 2021), so GloFAS cannot be matched by melting ice that does not exist. A basin is marked transferable when the hold-out KGE ≥ 0.3, |bias| ≤ 40 % and the mass balance is plausible.

BASIN	SETTING	CALIBRATION YEAR (OCT 2024–OCT 2025)	HOLD-OUT (OCT 2023–OCT 2024)	GLACIER BALANCE	VERDICT
Hunza	Defaults	KGE 0.86, bias +9 %	KGE 0.83, bias +13 %	+0.04	—
Hunza	−2 °C, precip ×0.5, DDF 7/16	KGE 0.95, bias −2 %	KGE 0.87, bias +3 %	−0.40	Transferable
4080575700	Best of grid	KGE −1.50, bias +192 %	KGE −1.16, bias +157 %	−0.69	Not transferable

Basin 4080575700 overshoots GloFAS 2–3× under every plausible setting. GloFAS's own water balance there is consistent, so the comparison cell is not the cause. Possible causes, none confirmed: glacier outlines, too little modelled accumulation on low glacier tongues (3,500–4,500 m melt 7–10 m w.e./yr at defaults), or GloFAS under-counting ice melt (it has no explicit glacier model). A stream gauge is needed. Melt discharge for that basin should not be used.

19. Coastal & Tidal Flooding

19.1 Static method: the Khan et al. (2020) bathtub

Published Karachi Port total water levels (tide + surge) at 50 / 100 / 1,000 years — 3.73 / 3.76 / 3.92 m, log-interpolated between them, with sea-level rise of 3.6 mm/yr and a mean tidal range of 2.3 m — flood every cell at or below the level that is connected (4-neighbour) to a seed: boundary cells below the level or cells at or below 0 m. The reference is regional (Karachi), labelled as such.

> **Datum.** These levels are heights above the tide gauge's own zero (chart datum), the record Khan et al. analysed. They are converted to heights above mean sea level by subtracting the gauge's measured MSL offset (1.849 m): the 100-year level is 1.91 m above MSL, not 3.76 m (§19.10).

19.2 Wave run-up (Stockdon et al. 2006)

$$R_{2\%} = 1.1 \cdot \left(0.35\,\beta\,\sqrt{(H_0 L_0)} + \tfrac{1}{2}\sqrt{(H_0 L_0\,(0.563\,\beta^2 + 0.004))} \right), \quad L_0 = gT^2/2\pi$$

H_0 and T from the Open-Meteo Marine API; β measured from DEM shore-to-inland transects, falling back to 0.03. On a Karachi test: 0.565 m of run-up on a 3.76 m still-water level, total 4.325 m. Opt-in.

19.3 Animated preview

The static method applied at 12 points along a GTSR-shaped water-level series; each frame assumes instant equilibrium (no routing between frames). Under one second.

19.4 Dynamic surge (GTSR + HVAR)

A GTSR daily-maxima episode at the nearest of 94 Pakistan-coast stations is rescaled to an anchor — the static total water level, or the station's own recorded peak, optionally plus the 2.3 m tidal range (a conservative "surge at high tide" sum, not a non-linear interaction) — and applied as an HVAR boundary on the lowest edge that has land. It now runs on the GPU after the kernel patch (§4.2). A coastal-only run starts at a 5.0 s step (tested at 0.2, 2 and 5 s with matching mass balance; 13–17× faster than 0.2 s). Compound mode adds rain in the same run.

19.5 Limitation

The dynamic boundary injects water only through the AOI's rectangular edge. If that edge sits on land above the surge, the dynamic run can show less flooding than the static method, which also seeds from low cells anywhere in the domain. Draw the AOI so its edge reaches the real coastline.

19.6 Local water levels: 42 GTSM stations

A second water-level source is selectable beside the Karachi tide-gauge anchors: GTSM-ERA5-E v2 return levels (2, 5, 10, 25, 50, 100 years) at 42 stations along the Pakistan coast. The nearest station to the AOI centroid is used, log-interpolated in return period and extended log-linearly beyond 100 years (flagged as extrapolated). The 100-year level varies from about 1.44 m in the west to 1.90 m near Karachi. At Karachi the corrected gauge anchor (1.91 m above MSL) and GTSM (1.79 m) agree closely; the factor-of-two gap reported earlier was the datum error described in §19.10. On a Karachi

test area the corrected gauge level floods 31.1 km² (peak depth 2.85 m) and GTSM 28.1 km². GTSM is modelled and coarse near the coast, and the SRTM DEM is referenced to a geoid that only approximates local MSL. Neither is validated against an observed coastal flood.

19.7 Sea mask, mangroves and sea-level rise

A 30 m sea mask seeds the connected-bathtub flood from real sea cells, in addition to the previous edge and below-0 m seeds. Global Mangrove Watch 2025 cover reports the mangrove area in the AOI and how much of it floods; mangroves do not attenuate water in the flood calculation. A user-set sea-level rise (metres, presets +0.25 to +1.0) is added to either source and stacks with the Karachi trend by target year. The presets are scenario values, not sourced projections.

19.8 Coastal susceptibility index and instant level explorer

A screening index (0 to 1, five classes at 0.2 / 0.4 / 0.6 / 0.8) combines elevation above mean high water (MSL plus half the 2.3 m tidal range; weight 0.25), distance to the sea (0.10, ramp 20 km to 0), slope (0.10, 5° to 0) and mangrove buffer (0.07). The weights are expert defaults from the supplied coastal model, not fitted; missing factors are dropped and the weights renormalised. It is shown on the map and as a downloadable static map. A level explorer precomputes the connected-bathtub flood every 0.25 m from 0 to 8 m for the AOI, so a slider shows area, depth and volume instantly; the chosen level can be drawn on the 3D map.

19.9 Not adopted from the supplied coastal model

Harmonic tide analysis and nuisance-flood frequency need tide-gauge records that are not available; the validation metrics need an observed flood map; the datum reconciliation is left as an open task. The model's own README states inundation is blocked until the vertical datum is verified.

19.10 Tide gauge, datum correction and astronomical tide NEW

An hourly sea-level record for Karachi (file `h147b.csv`, 31 January 2007 to 15 December 2016, 86,547 hours of which 541 are flagged missing, millimetres above the gauge zero) was added as `global_data/tide/karachi_hourly_h147b.csv`.

- **Datum correction.** Khan et al. analysed this same record, so their return levels are above the gauge zero. The record's mean sea level is 1.849 m above that zero. `karachi_anchors_above_msl()` subtracts it. The 50/100/1,000-year levels become 1.88 / 1.91 / 2.07 m above MSL (from 3.73 / 3.76 / 3.92). On the Karachi test box the static 100-year flood fell from about 80 km² (4.7 m) to 31.1 km² (2.85 m). Custom surge heights and the GTSM source were never affected.
- **Gauge facts.** Mean daily range 2.29 m (Khan: 2.3 m); largest constituents M2 0.80 m, K1 0.40, S2 0.31, O1 0.21, N2 0.19; highest observed level +1.79 m above MSL; annual maxima 3.42–3.64 m on the gauge scale.
- **Harmonic fit (`tide_utils.py`).** Least-squares fit of 23 constituents without nodal correction, stored in `karachi_tide_constants.json`. Fitted on 2007–2014 and used to predict the final two unseen years: RMSE 0.118 m, correlation 0.987 (fit RMSE 0.096 m).
- **Tide plus surge.** `build_tide_surge_series` builds an hourly series: the real GTSR surge episode shape plus the predicted tide, with the surge peak placed at spring high water (worst case), an ordinary high water or a low water. With the GTSR anchor the total is surge plus tide; with the static anchor the surge scale is solved so the highest total level equals the return-period level, so tide changes only when it happens. It replaces the older flat "add mean tidal range" box when chosen, in both the dynamic run and the animated preview.

Limits. One gauge for the whole coast (the tidal range is smaller toward Gwadar); the gauge file's own clock (assumed UTC) means only tidal phase at the surge peak is offered, not a calendar date; tide–surge interaction, wave set-up and Coriolis are not modelled (the last is negligible on 30 m grids and already inside the tide and surge data). EOT20, an open global tide model, was considered for spatial variation and not downloaded. A zip of 27 GRDC daily discharge gauges (1978–1982) was also supplied; only 1980–82 overlaps the ERA5 forcing, and a Hunza test would need the union of upstream sub-basins, so it has not been used.

20. Pluvial / Flash-Flood Risk Tiering

Forecast or recent rainfall is compared with a 20-year daily-precipitation climatology at the AOI point (Open-Meteo Historical Weather API, ERA5-backed): ≥ p90 watch, ≥ p95 warning, ≥ p99 severe, otherwise none. The observed IDF reference (Ch. 12) is shown alongside, not mixed in. The resolution ceiling is ~10 km hourly; no ground-radar product covers Pakistan (NOAA MRMS was checked and is US-only).

21. Geomorphology, Landslides & Sediment

NEW

21.1 Rock type and slope

GLiM lithology (Hartmann & Moosdorf 2012, Pakistan clip) gives each of its 16 classes an erodibility from 1 to 5 (e.g. unconsolidated sediments and evaporites 5, pyroclastics 4). Combined with DEM slope (breaks at 15 % and 35 %) and erodibility (breaks at 2.0 and 3.5) it gives a negligible / low / moderate / high landslide and debris-flow susceptibility.

21.2 ML landslide susceptibility

A national CNN/DNN ensemble map (KPK, GB and AJK only; AUC ≈ 0.88) is summarised by class shares inside the AOI; a verdict is given only when at least 50 % of the AOI is covered. The simple rock-type rating can disagree with it (Hunza: "low" vs "elevated"); where the ML map exists it should be preferred, and the UI says so. Valley-depth and confinement statistics come from national rasters.

21.3 Sediment transport risk

A post-processing indicator on the run's own depth and velocity at every saved step:

$$\tau = \rho\, g\, n^2\, V^2 / h^{1/3}$$
$$\theta = \tau / ((\rho_s - \rho_w)\, g\, d_{50}), \quad \theta_c = 0.047$$
$$q_b = 8 \cdot \max(\theta - \theta_c, 0)^{1.5} \cdot \sqrt{((s - 1)\, g\, d_{50}^3)}$$

Bed-load transport after Meyer-Peter & Müller (1948).

d_{50} comes from the SoilGrids texture. There is no feedback to the DEM (LISFLOOD-FP has no sediment capability), and the indicator is refused when the depth stack was spatially strided.

22. Buildings & Infrastructure Risk

22.1 Footprints and heights

Google Open Buildings footprints are the primary source (OSM building coverage was measured ~14× sparser in a comparison box). Height follows a cascade: OSM `height`, then `building:levels` × 3.0 m, then a flat 6 m estimate (OSM height tags covered only ~2 % of buildings in a dense Lahore test). The OSM lookup uses a spatial index, taking a 450,000-building AOI from hours to 3.8 s (§37.15).

22.2 Building damage band

The Huizinga et al. (2017) Asia "Built-up" depth-damage curve converts the peak depth at each footprint's centroid into a damage fraction, banded minor ≤ 0.30, moderate ≤ 0.55, major ≤ 0.72, severe above. Green is reserved for dry. Depth ÷ height (submersion fraction) is still reported, but no longer decides the colour: against a 6 m assumed height, real pluvial depths (0.81 m maximum at any centroid in one test) made "severe" unreachable.

22.3 DEFRA hazard rating

```
HR = d × (v + 1.5)
low ≤ 0.75 · moderate ≤ 1.25 · significant ≤ 2.0 · extreme > 2.0
```

Velocity is de-staggered from LISFLOOD-FP's Arakawa-C grid (Vx on vertical faces with one extra column, Vy on horizontal faces with one extra row) by averaging adjacent faces onto cell centres. A negative or NODATA hazard is "outside domain", never "extreme".

22.4 Animated risk colour

The building damage fraction and road hazard rating are recomputed at every saved timestep, so a 3D view's colours rise through the storm and fade as water recedes.

22.5 Infrastructure categories

CATEGORY	SOURCE	COUNT (NATIONAL)
Roads	HOTOSM, indexed GeoPackage	1,113,962 lines
Hospitals, schools	Government shapefiles	35,561 / 65,909
Power transmission lines	Government shapefile	419
Railway lines	OSM-derived shapefile (MultiLineStrings exploded)	659
Airports, railway stations, sea ports	Shapefiles (ports reprojected from Web Mercator)	136 / 655 / 3
Trees/forest	Overpass (retry on timeout/5xx)	live

22.6 PostGIS as the primary vector source NEW

The SimCity PostGIS database (PostGIS 3.6, about 926 MB, GiST indexes on every table) holds national tables (`pk` : roads 1.1 million, hospitals 35,561, schools 65,909, power and railway lines, railway stations, airports, tehsils, HydroLAKES) and an Islamabad subset (`isb`). `pg_vector_utils.py` returns the same record shapes as the shapefile readers and is tried first; any failure returns nothing and backs off for 60 s so the files take over. Compared on two boxes it was a strict superset of the files (every file feature at the same place plus one or two extras from multi-part lines) and faster: roads 0.2 s against 3.1 s on a small box, 2.4 s against 41 s on all of Islamabad and Rawalpindi. Sea ports are not in the database and still come from their shapefile. The connection is read-only and the password lives only in `.env` .

The first live run exposed a silent failure: PostGIS returns numeric columns as `Decimal` , which `json.dump` rejects, so infrastructure risk finished empty with zero roads. Values are now coerced at the source and a regression test covers it.

22.7 Six Islamabad-only facility categories NEW

For areas that intersect the Islamabad extent, `islamabad_layers_utils.py` reads the Islamabad SmartCity GeoPackage (104 layers, spatially indexed) and adds **shelters, police, water facilities** (supply, storage, wastewater), **fuel and chemical, governance** and **industry** (plants, waste processing, quarries) to the infrastructure risk, sampled at each feature's centroid against the run's depth and hazard. Waterways and canals are deliberately excluded, since they are where the water is meant to be. On the saved Islamabad run: shelters 3, police 4, water 17, fuel/chemical 5, governance 8, industry 6; one of two in-domain shelters and five of 15 water facilities flooded. Outside Islamabad nothing is added. Facility status (open or damaged) is not available.

22.8 Drivable roads and road detail NEW

For a box completely inside the Islamabad study area, roads come from `isb.roads_drivable` , a materialised view without footways, paths, steps, pedestrian ways, cycleways, tracks, bridleways, corridors and construction or proposed roads (76,867 of 82,451 lines). Anywhere else, or when the box extends past the study area, the national table is used unfiltered, so national numbers are unchanged. Records carry `lanes` , `surface` , `oneway` , `bridge` and `width` . New `road_detail` results report major roads (motorway to tertiary and links) against local roads, bridges, and total against flooded length. On a central-Islamabad run: 11 of 169 major roads, 36 of 767 local roads, 5 of 18 bridges and 4.13 of 168.3 km flooded. A flooded bridge means the depth at its centroid, because the DEM has no deck, so bridge figures are an upper bound. Lanes, width and surface are carried but not yet used in any calculation.

23. Land-Use Damage & Hotspot Analysis

23.1 Land-use damage

ESA WorldCover classes (resampled to the run grid) are combined with the Huizinga et al. (2017) Asia depth-damage curves per class (Built-up: 0 m → 0, 0.5 m → 0.30, 1 m → 0.45, … 6 m → 0.90), counting only cells inside the true AOI polygon. Before that mask was added, every statistic was diluted by out-of-polygon cells counted as dry (a typical polygon fills ~64 % of its box).

23.2 Getis-Ord Gi* hotspots

A published spatial-statistics test (`esda` / `libpysal`), queen contiguity, 99 permutations; a cell is a hotspot when $Z > 1.96$ and $p < 0.05$ (cold spot $Z < -1.96$). Per-class cell counts sum exactly to the valid-cell total in every run checked.

24. Estimated Monetary Loss

24.1 Source

Huizinga et al. (2017) Table 3-21 (2010 EUR/m²). Pakistan has no country value, so the Asia continental averages are used: residential 111 EUR/m², agriculture 0.03 EUR/m².

24.2 Building loss

$$\text{Loss}_{\text{structure}} = \text{area} \times \text{storeys} \times 111\ \text{EUR/m}^2 \times \text{damage fraction}$$
$$\text{Loss}_{\text{content}} = 0.50 \times \text{Loss}_{\text{structure}}$$
$$\text{Loss}_{\text{total}} = \text{Loss}_{\text{structure}} + \text{Loss}_{\text{content}}$$

Storeys = height / 3 m; the 0.50 content ratio is the FEMA/HAZUS residential value.

24.3 Agricultural loss

Cropland area × that cell's damage fraction × 0.03 EUR/m². Built-up land is excluded (already valued through buildings), and natural land cover is not priced because the JRC tables have no class for it.

24.4 Currency

$$\text{PKR} = \text{EUR (2010 prices)} \times 322.5$$

A current exchange rate applied to 2010 prices — not an inflation-adjusted conversion.

24.5 Where loss appears

Run summaries, NbS and protection scenarios (loss before, after and avoided, from the baseline's own footprints), run comparisons, batch reports and AAL. Every enrichment is written back to `summary.json` (§37.22).

25. Average Annual Loss (AAL)

The standard catastrophe-risk metric, by trapezoidal integration of loss against annual exceedance probability (FEMA HAZUS method):

$$AAL = \int_0^1 Loss(p)\, dp, \quad p = 1/T$$

Beyond the rarest return period tested the loss is held constant; below the most frequent it falls linearly to zero at p = 1. AAL is its own action (several physics runs with buildings), and refuses — naming the missing return period — rather than computing from incomplete data. Verified by hand: two runs (10 yr Rs 52.8 M, 50 yr Rs 199.7 M) gave Rs 37,872,545.84/yr, matching an independent calculation to the cent.

26. Nature-based Solutions (NbS)

Reforestation, grassland restoration or wetland restoration, applied "active" (full conversion) or "passive" (one step along an ecological order), change land cover; per-cell Manning's n and the area-mean infiltration are re-derived (land-cover infiltration: tree 75, mangroves 60, shrub 40, grass 20, crop 12, built 8, bare 5, moss 10, wetland 2, snow 2, water 0 mm/hr) and the physics is re-run with the baseline's own forcing. The cell-by-cell comparison reports area protected and, never hidden, a displacement percentage. Auto-recommend evaluates all six combinations and ranks them by building loss avoided (by area when there are no buildings).

27. Grey Infrastructure Protection Scenarios

STRUCTURE	HEIGHT / DEPTH	HALF-WIDTH	EFFECT
Dam / embankment	+3.0 m	8 m	Raise (square end caps)
Barrage	+2.5 m	12 m	Raise
Diversion canal	−2.0 m	6 m	Lower (flat end caps)
Drainage pipe	−1.0 m (diameter)	1.5 m	Lower
Rainwater catchment / retention basin	dug depression	~40 m across	Lower; storage volume reported

Drawn lines are buffered into corridor polygons and burned onto a copy of the baseline's building-conditioned DEM; the re-run keeps the baseline's rain, friction, AMC and boundary conditions. Results: area protected, displacement, and loss avoided in PKR. A structure that lands entirely outside valid terrain is reported as a failure, not run.

28. Mystic-Driven Auto-Optimization

28.1 No surrogate

mystic's differential evolution (`diffev2`) searches placement and sizing; every candidate is a full LISFLOOD-FP re-run with the structure burned in. Each evaluation is expensive, so the user picks a small budget (Quick / Balanced / Thorough) rather than searching to convergence.

28.2 Variables and objective

Seven variables per structure: centre (two, normalised to the AOI box), orientation, length (0.15–0.9 of the box diagonal), height and width multipliers (0.5–1.5 of the type default) and a continuous type index floored to a choice.

```
objective = −loss_reduction_% + 0.5 × displacement_%
```

Area reduction replaces loss reduction when the baseline has no buildings.

Failed or outside-AOI candidates get a fixed penalty of 10^6, and failures are logged to `optimizer_errors.log` . The final answer re-runs the best evaluated trial's own structures through the manual pipeline. With a tiny budget the search can return a placement with a small positive area reduction but a small negative loss avoided — an honest, unconverged result the loss-weighted objective is designed to surface.

29. Live Continuous Monitoring & Alerts

A watch (an AOI plus a rainfall threshold) is checked every 10 minutes against the Open-Meteo forecast. A crossing starts a Tier 3 run and, when a webhook URL is set, posts JSON readable by Slack (`text`) and Discord (`content`) plus structured fields (peak, duration, threshold, run id); a report link is added only when `PUBLIC_BASE_URL` is set. Delivery success is recorded per alert. "Now" is computed in the forecast's own local time (§37.19).

30. Glacier SAR Displacement Monitoring

Sentinel-1 offset tracking via Earth Engine measures monthly glacier surface displacement, combining ascending and descending passes (mean where both are valid), corrected for a stable-ground bias estimated in a 1,500 m ring around the GLIMS glacier bodies (other glaciers masked out). Cumulative-displacement and velocity (cm/day) thumbnails are auto-scaled to each run's own maximum; the confidence threshold is user-tunable (default 0.5). A known-lake result links to the GLOF estimator.

> Working since the credential was renewed on 13 October 2026 (Ch. 3). If the token lapses the feature returns "not available"; only the account owner can re-authenticate, and the health watchdog (§40.1) reports the lapse.

30.1 ITS_LIVE glacier speed (no login) NEW

As an alternative that needs no Earth Engine account, NASA ITS_LIVE image-pair velocities (Sentinel-2 and Landsat feature tracking, public STAC search, granules on AWS) are fetched for the AOI. Pairs of 5 to 40 days with at least 30% valid pixels are used. Speed statistics are computed over the PMD glacier polygons inside the AOI, and the median of the last 45 days is compared with the median of the same calendar window in the previous two years, so the seasonal cycle cancels. A pair is used only if at least 10% of the glacier cells carry a velocity. A ratio of 1.5 or more is reported as a marked speed-up and 1.25 to 1.5 as a possible one; with fewer than three pairs in either set the verdict is "inconclusive", and a caution is added when the recent and baseline pairs come from different sensors or track very different shares of the glacier. These are screening thresholds, not validated against surge or outburst precursors. On a Hunza test area the recent Sentinel-1 pairs gave a median of 76 m/yr against 50 m/yr for the two usable baseline pairs (ratio 1.5), which the app correctly reports as inconclusive because the baseline is two pairs from different sensors. Granules (2 to 30 MB each) are cached locally, with a thumbnail of the latest speed map. Pair coverage is cloud- and snow-limited, each pair has its own error, and a speed-up is a possible warning sign, not proof that an outburst is coming.

31. Storm-Motion Nowcasting

A small LSTM (window of six 30-minute displacements, 32 hidden units) trained on 72 IMERG monsoon storm-days (2021–2023) predicts a storm cell's next displacement for the moving-storm rainfall option (§11.4). Tracks are never bridged across a missing half-hour, the train/test split is by storm-day, and the error metric uses each row's own latitude. Live inference depends on Earth Engine and is currently blocked by the same revoked credential.

32. Discovery Tools: Basins, Tehsils, Rainfall Hotspots

32.1 River basins (HydroSHEDS)

1,131 level-08 basins, indexed once and browsable by region, ranked by area, nearest to a point, or nearest to a GLOF site; one click sets a basin as the AOI. The same basins feed the melt model (Ch. 18).

32.2 Tehsils

578 tehsil boundaries searchable by name in the main map search (name, then district, then province); a result becomes the AOI.

32.3 National rainfall hotspots

The highest-recorded individual grid cells nationally for any IDF-cube metric, labelled with their tehsil, district and province, usable before any AOI is drawn.

33. Validation & Accuracy Record NEW

CHECK	RESULT
Bahawalpur, SRTM vs FABDEM, same polygon	1.436 vs 1.449 km² flooded
LISFLOOD-FP v5.9 CPU vs 8.2 CPU vs 8.2 GPU (Bahawalpur, 104 km²)	v5.9 = 8.2 CPU bit-identical; GPU 2.816 vs 2.818 m max depth; GPU ~10–11× faster
GPU vs CPU river inflow, valid inlet (Lahore-area DEM)	Identical to the displayed digit (§5.4)
GPU vs CPU coastal HVAR (Karachi)	41.4370 km² / 4.00 m on both
Mass conservation, closed synthetic domains	Stored/analytic 1.000 (CPU), 0.997–0.998 (GPU)
Inflow volume after whole-cell snap	2.160047×10^6 vs 2.16×10^6 m³ analytic
ACC depth correction vs DG2 (15–200 % slope)	$R^2 = 0.992$, max corrected-depth error 4.9 %
2022 Sindh flood vs UNOSAT extent, 48 h ERA5 storm (253.5 mm)	CSI 0.659, POD 0.669, FAR 0.021 (73.5 vs 107.7 km²). **The test box was 98% flooded in the observed map, so this does not demonstrate skill** (§33.1).
Same AOI, 10-day window (424.6 mm)	CSI 0.694, POD 0.705, FAR 0.022 (77.6 vs 107.7 km²). Same caveat.
Same AOI, 30-day window	Not completed — no report was produced
Melt model vs GloFAS (melt season)	Hunza KGE 0.86 default, 0.95/0.87 calibrated; basin 4080575700 not reconcilable (Ch. 18)
Tarbela spillway outlook vs documented inflows	−4 % / +11 %; Mangla refused (Ch. 17)
Multi-model study, three half-flooded 2022 Sindh areas	Mean CSI: SAILAB 0.504, ANUGA 0.503, SFINCS 0.500, TELEMAC-2D 0.497, "flood everything" 0.500 (§33.1)
Wet-cell overlap between codes (mean of three areas)	SAILAB–ANUGA 0.94, SAILAB–TELEMAC-2D 0.90, SAILAB–SFINCS 0.82
LISFLOOD-FP 8.3 against 8.2	Identical results; no speed gain on our cases (§4.3)
Tide harmonic fit, two unseen years	RMSE 0.118 m, correlation 0.987 (§19.10)

The 2022 validation was re-run after a bug that fed the storm at half its real depth (§37.23); the earlier CSI of 0.42 was from the under-fed storm. Closed vs open boundaries made no difference at 48 h.

Open question. On the 2022 AOI, CPU and GPU maximum depth differ at a few sink cells (16.3 vs 8.95 m) while the wet footprint matches (55,483 of ~55,500 cells), and the CPU run stored ~4.9 % more water than its own rain column. Synthetic closed domains conserve mass on both builds, so this is terrain-specific and unexplained. Compare wet area or CSI across builds, not maximum depth.

33.1 Multi-model case study NEW

The Sindh test above used a box inside the largest flooded patch, 98% flooded in the observed map, where a model that floods everything would score a CSI near 0.98. A controlled study replaced it. Full report: `model_comparison/SAILAB_Model_Comparison_Report.pdf` (code and raw results alongside; published in the repository).

- **Design.** Three 13 km boxes on the edge of the observed flood (49%, 50% and 51% flooded, UNOSAT VIIRS map of 29 November 2022). Every model got the same SRTM terrain, 253.5 mm of rain over 48 h (the wettest ERA5 window at the site), Manning n = 0.05, no infiltration, closed boundaries and no calibration. Scoring used a 5 cm cut-off, plus two baselines: flood everything, and flood the lowest terrain up to the true flooded fraction.
- **Models run.** SAILAB (LISFLOOD-FP 8.2 ACC, GPU); ANUGA 4.1 (finite volume, 90 m mesh); SFINCS v2.5.0-beta (Deltares, built from source); TELEMAC-2D v9.2-dev (built from source, serial, 90 m mesh).

MODEL	MEAN CSI	MEAN POD	MEAN FAR	MEAN RUN TIME
Flood everything	0.500	1.00	0.50	–
Lowest terrain (told the true fraction)	0.415	0.58	0.42	–
SAILAB (ACC, GPU)	0.504	0.89	0.46	58 s
ANUGA (CPU)	0.503	0.86	0.45	477 s
SFINCS (CPU)	0.500	1.00	0.50	528 s
TELEMAC-2D (1 core)	0.497	0.84	0.45	141 s

- **Findings.** The three physics codes agree closely with each other (90–94% of wet cells in common) and over-predict wet area by 1.5–1.7×. SFINCS scores like "flood everything" because it keeps more than 5 cm of water in every cell; its maximum depths match the others. As the wet-depth cut-off rises every model falls below both baselines from 20 cm. The likely reason, untested, is that rain alone cannot reproduce a flood that came mainly from river overflow.
- **Meaning.** SAILAB's solver is numerically consistent with independent codes; no model, SAILAB included, shows skill above the trivial guess on this test. Speed comparisons mix a GPU with CPU codes and different meshes.
- **Time to result.** Through the live app, a drawn 13 km polygon to a finished result with 6,000–10,400 buildings, roads, risk, loss and a 3D scene took 81–187 s. The three open models each needed a hand-written converter (59, 69 and 114 lines).
- **Not run.** HEC-RAS, TUFLOW, MIKE, InfoWorks, Flood Modeller and FLO-2D need a licence or Windows/x86, and this server is ARM with no emulator; Delft3D-FM ships x86 binaries; TRITON, SERGHEI, RIM2D and HiPIMS were not attempted. DG2 on these flat rainy domains stalled with its timestep collapsing to about 0.01 s and was dropped. No GPU support for the HEC-RAS 2D solver was found in the public release notes read (unconfirmed against the official notes).

- **Published comparisons.** Checked against the papers' own text: on the River Lis (Portugal) HEC-RAS and LISFLOOD-FP inundated areas overlapped by 65% and HEC-RAS ran much faster; on the Thessaly plain (Greece) run times were about 3 h (LISFLOOD-FP), 2 h (FLO-2D) and 10 min (HEC-RAS). Others were read from abstracts only (see the report). No study comparing SWAT with LISFLOOD-FP was found; SWAT is a catchment water-balance model, not a flood-extent model.

34. 3D Visualization

34.1 Mapbox-native, not a custom Three.js scene

An earlier custom Three.js pipeline accumulated a long bug history (camera-angle illusions, floating buildings, a `DoubleSide` material rendering almost nothing) and was replaced by Mapbox GL JS native 3D terrain (`map.setTerrain` on `mapbox.mapbox-terrain-dem-v1`), `fill-extrusion` buildings and line roads. The physics still runs on SAILAB's own DEM; only the visual terrain uses Mapbox's global elevation. Everything is positioned by lon/lat, so it aligns regardless of the terrain mesh.

34.2 Animation and water rendering

The depth overlay is a live Mapbox canvas source driven by a WebGL2 fragment shader. Per-timestep depth and velocity are uploaded as textures (depth sqrt-encoded to 8 bits, velocity as 2×8 bits scaled to the run's 98th-percentile speed) and interpolated on the GPU between the two nearest saved timesteps, so shorelines are smooth rather than blocky cells. Colour shades from light to dark blue with depth by Beer–Lambert-style absorption; the surface is lit with a sun term and specular glint, ripples are advected along the solver's own velocity field (flow-map technique), and foam appears at the wet/dry edge. This is a rendering change only: depth and velocity are the run's own LISFLOOD-FP output. Custom colour ramps (damage, nature-based-solution and run-comparison overlays) and browsers without WebGL2 use the previous CPU canvas path.

Playback is a fixed loop mapped onto the run's real simulated duration; rain intensity follows the actual hyetograph or uploaded series, and the clock shows real time for uploaded series. Building and road colours animate with per-frame risk (§22.4): buildings stay neutral until water reaches them and then take the Huizinga damage colour; roads are drawn only while wet. White flow lines are particles advected by the solver velocity and drawn brighter where flow is faster.

34.2a Viewer controls and probe

- **What to show:** depth over time, maximum depth (per-cell peak across all timesteps), flow speed, flow paths.
- **Map style:** Dark, Light, Satellite, Streets, Terrain, Night. A style change removes every custom layer, so the viewer waits for the new style to finish loading, re-adds the scene, and retries on error; a frame error is logged and skipped rather than stopping the animation.
- **On the map:** buildings, terrain (exaggeration slider), labels, flow lines; fine-tune cutoff depth, opacity and particle count.
- **Timeline card:** live flooded area, deepest water and water volume per frame (cell count × cell area; depth sum × cell area), a rainfall bar chart over a flooded-area curve with playhead, hover tooltip and click/drag seeking, export as PNG or MP4.
- **Click-to-pin probe:** depth and velocity at the clicked cell, its peak depth, ground elevation from the run's bare DEM, and a depth-over-time chart. Values are read from the embedded run grid (strided only for very large domains), not from Mapbox terrain.

The page is assembled from three asset files (`mapbox3d_style.css` , `mapbox3d_body.html` , `mapbox3d_app.js`) by `mapbox3d_utils.py` ; they must be deployed together. Cached runs keep the script they were built with; only new runs (or a rebuilt scene) use the current viewer.

34.3 Safeguards found necessary

- **Camera bounds:** edge-on views of correct geometry repeatedly looked like data bugs; distance and pitch are bounded, and Reset View runs automatically before every export.
- **Payload size:** a 6.6 M-cell run embedded a 2.64 GB HTML file; the depth stack is now spatially strided above 5,000,000 frame×cells (peak depth still taken at full resolution), and any scene over 150 MB is logged.

35. Reports, Comparisons & Exports

- **Single-run report** (HTML and PDF via WeasyPrint) built from the run's own data.
- **Compare two runs:** a cell-by-cell diff (only A wet / only B wet / both wet), mean depth change and building-loss difference; refused unless both runs share an identical grid. Coastal dynamic jobs are supported.
- **Batch report:** flooded area and maximum depth across a list of runs (e.g. a return-period sweep) with a trend chart.
- **Shared report style:** one light, print-friendly `REPORT_CSS` with a dark-teal banner, verified in both the browser and the PDF pipeline.
- **Susceptibility-style map (PNG):** any finished run can download a static classified map of peak flood depth (five classes, hillshade base, graticule, scale bar, north arrow, legend with area and percentage per class, key figures, notes). The same renderer produces the coastal susceptibility map.
- **Video export:** browser WebM → `/export-video` → H.264 MP4 via the bundled imageio-ffmpeg, with dimensions rounded to even numbers for libx264.

35.4 Comparing a run with an observed flood NEW

`POST /runs/<id>/validate-observed` (button "Compare with observed flood" on a finished run) accepts a mapped extent as polygons (GeoJSON, GeoPackage, shapefile or zipped shapefile) or a GeoTIFF where values above zero mean flooded, and returns CSI, POD, FAR, F1 and the modelled and observed wet areas. Only valid cells inside the AOI are scored, the ACC depth correction is applied, and the wet threshold is 0.05 m. On the corrected 48 h Sindh run against the UNOSAT extent it reproduced `validate_2022_flood.py` exactly (CSI 0.6592, POD 0.6686, FAR 0.0209). Interpret with the observed fraction in mind (§33.1).

35.5 Rebuilding a scene without re-simulating NEW

`POST /runs/<id>/rebuild-scene` redraws a run's 3D page from its saved results. A rebuild of the Islamabad run (6,000 buildings, 30,931 road segments) took about 3.5 minutes on a healthy machine; one took 7 hours only because the machine was swapping.

35.6 Coastal and GLOF PDFs; cache cleanup NEW

`POST /report/coastal.pdf` and `/report/glof.pdf` render the result the browser already holds (HTML-escaped) as a one-page PDF. `cache_cleanup.py` is a dry run by default; `--apply` deletes runs older than `--days` (30) outside the newest `--keep-newest` (20) and not listed in `keep_runs.txt`. The first dry run found 125 runs and 4.5 GB reclaimable; nothing has been deleted.

36. User Interface Design System

A dark "operations dashboard" identity: a near-black base with a soft radial vignette, the existing cyan/teal brand accent with a violet secondary, glass panels, gradient buttons with hover and press feedback, focus rings, a shimmer progress bar and a single MutationObserver that animates every newly rendered result without touching the hundreds of rendering call sites. The 3D view's controls share the same styling. Tabs: Tier 2 · Instant Flood, Tier 3 · Physics Run, and Coastal / Tidal, with discovery panels (rainfall hotspots, river basins) above the AOI controls. Mobile layouts were deliberately out of scope.

37. Chronicle of Major Bugs Found and Fixed

Each entry was root-caused from direct evidence (a compiler error, a sanitizer trace, a hand-computed reference, a controlled bisection) and re-verified against real data. Entries 37.21 onward are new in this edition.

37.1 Overpass 406 (missing Accept header)

python-requests sends no Accept header and Overpass's Apache front-end rejected the requests; set explicitly.

37.2 Flow accumulation double-counted backflow

Pit cells were given an uphill "downstream" direction; a 3×3 test accumulated more than its 9 cells. Zero drop now terminates.

37.3 Buildings corrupting the physics

Buildings on NODATA cells turned −9999 into −9993, read downstream as real terrain — a ~10,000 m false cliff inside the simulation. Only valid cells are now conditioned.

37.4 Lines reconnecting across AOI gaps

Roads leaving and re-entering the AOI were drawn straight across the gap; split at each exit and entry.

37.5 Buildings rendered as terrain blobs

The 3D terrain used the conditioned DEM; a bare copy is now kept and real footprints are extruded on top.

37.6 Camera-angle illusions mistaken for data bugs

Several reports traced to near-edge-on views of correct geometry; camera bounds and automatic Reset View before export.

37.7 Hazard fallthrough for invalid data

Negative/NODATA hazard fell through to "extreme"; now "outside domain".

37.8 Green for a flooded building

Green is now reserved for dry; wet bands use yellow to red.

37.9 Staggered velocity combined without de-staggering

Vx/Vy sit on an Arakawa-C grid; averaged onto cell centres before use.

37.10 Water past the terrain edge

After exact terrain clipping, water triangles must have all three vertices inside the AOI.

37.11 "Boundary inflow silently zero under CUDA" (superseded)

The previous edition reported that the CUDA path drops all boundary inflow and routed such runs to the CPU. That diagnosis was wrong; see 37.25 and 37.26.

37.12 Boundary conditions a no-op on every real DEM

LISFLOOD-FP reads boundary coordinates as absolute, from the DEM header; boundaries written in local coordinates collapsed to a zero-width point. The DEM corner is now added.

37.13 Discharge under-delivered near an edge corner

Flux was computed from the unclamped width (75 % delivered in one case); the width is clamped first.

37.14 The "dormant 1000× rainfall-column bug" (reversed)

A ×1000 was added on the strength of the LISFLOOD-FP manual's units. In this build the column is plain m^3, so the fix inflated CPU-run rainfall 1000× and made mass checks meaningless; reversed (37.21).

37.15 O(buildings × OSM candidates) post-processing

cProfile showed a per-building linear scan taking 98 % of the time; replaced with shapely 2 vector operations and an STRtree (3.79 s at whole-Islamabad scale), with byte-identical results verified first.

37.16 Soil-texture misclassification

Sand ≥ 45 % with clay ≥ 35 % fell through to "loam" (Ksat 13.2 instead of 1.2 mm/hr, 215 of 5,151 combinations); the missing "sandy clay" rule was added.

37.17 Shapefile inside a zip sub-folder

GDAL's plain `zip://` form only finds root-level shapefiles; entries are scanned and the nested path used.

37.18 The DG2 CUDA crash

A missing `MaxField` constructor argument gave an unpadded buffer; found with compute-sanitizer and fixed in three files (§7.2).

37.19 Timezone in forecast peak detection

Open-Meteo labels are local time; comparing with UTC shifted the future/past boundary by 5 h and could fire alerts on past rain. "Now" is now computed in the forecast's own frame.

37.20 Duplicate rain timestamps

Sorting does not guarantee strictly increasing times; ties are merged keeping the larger rate.

37.21 Rainfall volume 1000× too high on CPU runs

Measured 13.9×10^6 m^3 in the column vs 14.3×10^6 analytic: this build writes plain m^3. The ×1000 was removed and a regression test added.

37.22 Stale DEM path and a silent fallback

A wrong path made every Pakistan run fall back to a small Bahawalpur sample. All paths now live in `data_paths.py`, the DEM moved to its new location, and the fallback (and its sample file) were deleted, so a missing DEM is now an error.

37.23 Validation storm fed at half depth

`validate_2022_flood.py` passed the window average as the triangle's peak, delivering 127 instead of 253.5 mm. Peak = 2 × average; the earlier CSI 0.42 is superseded.

37.24 A mis-escaped apostrophe blanked the map

One quote in the Python-rendered JavaScript killed the whole page script. Guarded by a `node --check` test of the rendered script and a headless-Chromium smoke test.

37.25 "CUDA inflow bug" was an inlet on NODATA cells

The test DEM's first six west columns were NODATA, so the inflow was injected into NODATA cells; CUDA zeroes their water every step and the −9999 m pit blew up (0.3 → 8.7 m in seconds, 496 m by 4 h). With the inlet on valid terrain, GPU and CPU agree. Inflow runs now use the GPU unless an inflow segment covers NODATA. CUDA's missing QFIX case is handled by writing constant inflow as QVAR.

37.26 Coastal stage boundary never wetted a dry edge on GPU

The CUDA HVAR code acted only on cells already wet (unpatched: 0.0 m, 0 wet cells; CPU: 6.18 km²). Patched to act when the stage exceeds the ground, as the CPU build does; GPU and CPU now agree.

37.27 Inflow 1.46× too large

The solver applies boundaries on whole cells; a 40 m channel on 29 m cells received 58 m of flux. The segment is snapped to whole cells.

37.28 Melt-model routing pointed uphill

`derive_d8_pointer` had swapped slices, so every pointer pointed uphill and the routing graph was cyclic. Fixed; outlet discharge is also now the sum over exit cells, not the maximum.

37.29 Wrong GloFAS cell for the melt check

The highest-flow GloFAS cell inside the Hunza polygon sat on a neighbouring river (78 vs 20 m³/s generated in the basin), which made Hunza look like it needed a ×3–4 precipitation factor. The cell is now chosen by water balance; with it, Hunza's defaults already agree.

37.30 Slow GloFAS reads

Reading ten years of netCDF through a lazy concatenation for every check took over 15 minutes; 2003–2012 means are precomputed once (~20 s) and checks take ~2 s.

37.31 Upload failure in the test sandbox only

Every multipart upload failed with `ERR_ALPN_NEGOTIATION_FAILED` in headless Chromium while Node `fetch()` succeeded; a test-environment artifact. The defensive warning added during the investigation was kept.

37.32 2.64 GB scene file

Fixed by spatial striding above an element budget (§34.3); three affected runs were regenerated (35.7× smaller).

37.33 Tide-gauge datum error in every Khan-based coastal result

Return levels above the gauge zero were applied as above mean sea level; the true 100-year level is 1.91 m, not 3.76 m. Found when the hourly gauge record showed MSL 1.849 m above its zero (§19.10).

37.34 PostGIS Decimal values silently emptied infrastructure risk

`json.dump` rejects `Decimal`, so a run finished with no roads and no error beyond one log line. Coerced at the source with a regression test (§22.6).

37.35 A validation box that could not show skill

The first Sindh test box was 98% flooded in the observed map, so a CSI of 0.66 and a false-alarm ratio of 0.02 were uninformative. Replaced by half-flooded areas and trivial baselines (§33.1).

37.36 Wrong package, same name

The conda-forge package "sfincs" is a stellarator plasma code, not the Deltares flood model; it failed at once on a missing input file. Removed; the real model was built from source.

37.37 DG2 timestep collapse on flat rainy terrain

On the study areas DG2 stalled for 42 minutes with its timestep near 0.01 s; the existing slope-based choice already selects ACC there (§33.1).

37.38 Token validity cached for the life of the process

`_ee_init` keeps its first Earth Engine result forever, so a token revoked later was invisible. The watchdog now performs a real refresh (§40.1). The same check found that Overpass's `/api/status` page answers 406 to every client; the probe is now a tiny real query.

37.39 Test runner stalled by plugin auto-loading

pytest hung for tens of minutes loading an installed plugin's heavy imports on the loaded machine; `PYTEST_DISABLE_PLUGIN_AUTOLOAD=1` avoids it.

38. Considered and Declined

TOOL / TECHNIQUE	REASON DECLINED
TauDEM	Static-DEM flow direction only — less informative than LISFLOOD-FP's own velocity; needs an MPI build without root.
xHydro	Catchment streamflow calibration/frequency analysis; no 2D inundation.
dfm_tools	Delft3D-FM pre/post-processing; cannot read LISFLOOD-FP output.
FABDEM	Non-commercial licence; buildings are already conditioned into the DEM.
Global HydroATLAS/HAND precompute	Multi-terabyte batch job; per-AOI HAND takes under a second.
Full GRDC gauges	Registration-gated (the retired Tier 1 used Caravan instead).
NOAA MRMS, USGS dataretrieval	US-only.
SWMM	No sewer-network data exists on the share for any Pakistan AOI.
GPU-MWDG2 adaptive solver	No rainfall forcing; an added rainfall kernel produced negative total volume (§5.6).
Single-precision DG2	2.73× faster but 44 % different depth at altitude (§7.3).
Raising depththresh for stability	Made steep runs worse (§7.3).
LISFLOOD-FP 8.3	Identical results and no speed gain on our cases; its main fix is already patched locally (§4.3).
HEC-RAS, TUFLOW, MIKE, InfoWorks, Flood Modeller, FLO-2D, Delft3D-FM	Licence, Windows or x86 only; this server is ARM with no emulator. Compared through published results instead (§33.1).
TRITON, SERGHEI, RIM2D, HiPIMS	Source builds with untested GPU support on this machine; not attempted.
Single-model "better than all" claims	Not supported: accuracy is on par with other open 2D models (§33.1).

39. Known Limitations

- **ACC everywhere, with a narrow correction.** `FORCE_ACC_ONLY` trades DG2's accuracy for speed; the depth correction fixes magnitude, not flow paths, and was fitted on one storm and geometry (§5.3).
- **Extreme Karakoram relief remains unstable under ACC** (255 m depth, growing mass error on the 852 %-slope basin) (§7.1).
- **No river bathymetry**; large discharges into estimated widths can give locally deep results (§15.3).
- **Earth Engine features depend on one personal OAuth credential** (glacier SAR, storm-motion nowcasting) that has been revoked once; the project is also in restricted compute mode.
- **Melt model:** one basin (4080575700) cannot be reconciled with GloFAS; the debris raster barely marks debris; ice thickness is modelled, not measured; GloFAS is a model, not a gauge (Ch. 18).
- **Dams:** Froehlich is fitted to small dams; 64 dam heights are estimated; the spillway outlook is valid only for Tarbela (Ch. 17).
- **Loss and AAL** use regional (Asia) maximum-damage values at a current exchange rate applied to 2010 prices (Ch. 24).
- **Coastal dynamic runs** need an AOI edge that reaches the coastline (§19.5).
- **GPU vs CPU maximum depth** can differ at a few sink cells; compare wet area (Ch. 33).
- **Validation** covers one major event (2022 Sindh). No model, SAILAB included, scored clearly above a trivial "flood everything" guess on rain-only forcing there; the 30-day window run did not complete; no depths have been validated (§33.1).
- **Coastal** results use one tide gauge (Karachi) for the whole coast; results made with the Khan source before 14 October 2026 overstate flooding (§19.10).
- **Vector data** depend on a local PostGIS database that can be down; the shapefile fallback is then used, which lacks the Islamabad-only categories (§22.6).
- **Global DEM** outside Pakistan is opt-in only; mobile layouts are out of scope.

40. Operations & Testing NEW

- **Server:** Flask on port 8000 with no auto-reload. Restart after any backend change: find the PID with `ss -ltnp | grep :8000` and kill it; never `pkill -f` a pattern that also appears in your own command line.
- **Copies:** the working copy on the external SSD and the live copy in `~/flood/` are separate; copy changed files across and confirm with `cmp`.
- **Data check:** `/data-status` lists every dataset path and whether it exists.
- **Tests:** fast suite `pytest tests -q -m "not slow"` (420 tests passing at the last full run). Slow tests include real LISFLOOD-FP runs (GPU vs CPU for inflow and coastal HVAR, closed-domain mass balance, NODATA-inlet fallback) and live HTTP routes. Front-end guards: `node --check` on the rendered script and a headless-Chromium smoke test.
- **LISFLOOD-FP patches:** keep `lisflood_patches/cuda_acc_solver.cu`; after any re-extraction re-apply it and the MaxField fix, and rebuild both `build` and `build_netcdf`.
- **Melt calibration:** `/area/melt-model/calibrate` or `calibrate_melt_basin.py HYBAS_ID CAL_START CAL_END VAL_START VAL_END` (~10 minutes per basin when uncached).
- **Environment switches:** `SAILAB_FORCE_CPU=1`, `SAILAB_FORCE_CUDA=1` (test only), `SAILAB_<DATASET>` path overrides, `PUBLIC_BASE_URL` for alert links, `MAPBOX_TOKEN` in `.env`, `SAILAB_ACCESS_TOKEN`, `SAILAB_PG_URL`, `SAILAB_ALERT_WEBHOOK`, `SAILAB_DISABLE_OPS_LOOP=1` (used by the test server), and `PYTEST_DISABLE_PLUGIN_AUTOLOAD=1` when running tests on a loaded machine.
- **Technical index:** `DATA_SOURCES_AND_METHODS.md` lists every path, constant and formula in compact form; `CLAUDE.md` holds the full engineering log.

40.1 Operations agents NEW

`ops_agents.py` runs three rule-based background checks every 15 minutes. They detect, record, alert and suggest; none alters a model, setting or result. Alerts go to `SAILAB_ALERT_WEBHOOK` (Slack, Discord, ntfy or a custom receiver) and the log.

- **Data-health watchdog** (`GET /ops/health`, `POST /ops/health/run`; state in `ops_state.json`). Checks the Earth Engine token (a real refresh), PostGIS, Open-Meteo, GloFAS, Overpass (a tiny real query), disk space, GPU temperature, required datasets and the solver binary. A check must fail a set number of times in a row (1 for local resources, 2–3 for public services) before one alert, and one "recovered" message follows. Its first run found PostGIS genuinely down (nothing listening on its port; the files were being used) and a transient Overpass 502.
- **Forecast validation** (`GET /ops/forecast-skill`; ledger `forecast_ledger.jsonl`). Every live-monitoring forecast is logged; once 54 h old, its first 48 h are scored against Open-Meteo's later past-day analysis (a model-blended product, not rain gauges): peak error, total error, peak-timing error and threshold hit, false alarm or miss. After ten forecasts it reports an advisory observed/forecast peak ratio, which is never applied automatically. No scored data existed at the time of writing.
- **Run QA** (`GET /runs/<id>/qa`, `POST /ops/run-qa-scan`; `run_qa.json` per run and `summary["qa"]`). After each run it checks for non-finite results, depth above 100 m (above 40 m from rain alone), mass-balance error above 5% or 20% of the water input, more than 95% of the domain flooded, buildings used but not assessed, and CUDA, FAILED or nan lines in the log; it records which automatic fallbacks were in play (ACC forced by size, CPU forced by a NODATA inlet, CUDA restart) with a suggested action per issue. A daily scan covers earlier runs; 25 existing runs all passed.

40.2 Access, queue and publishing NEW

- **Reaching the app.** Open an SSH tunnel to port 8000 (`ssh -L 8000:localhost:8000 user@host`) and browse to `http://localhost:8000`; direct access from another machine needs the access token. The host has several addresses (Ethernet, Wi-Fi, Tailscale); use the one on your network.
- **Queue and cancel.** `/solver-status` and the queue position in `/runs/<id>/progress.json` show what is holding the solver; `POST /runs/<id>/cancel` stops a queued or running job. Protection scenarios, NbS scenarios and coastal surge runs also use the slot.
- **Publishing.** Every change to the application, tests, documentation and plugin is copied into the git clone, secret-scanned, committed and pushed to GitHub; secrets, data, caches and the PostGIS password are excluded.

41. References

- Aureli, F., et al. (2025). LISFLOOD-FP 8.2: GPU-accelerated multiwavelet discontinuous Galerkin solver for rapid, multiscale flood simulation. Geoscientific Model Development, 18, 9827.
- Bates, P. D., Horritt, M. S., & Fewtrell, T. J. (2010). A simple inertial formulation of the shallow water equations for efficient two-dimensional flood inundation modelling. Journal of Hydrology, 387, 33–45.
- Chow, V. T. (1959). Open-Channel Hydraulics. McGraw-Hill.
- DEFRA / Environment Agency (2006). Flood Risks to People, Phase 2 (FD2321) — hazard rating methodology.
- Froehlich, D. C. (1995). Peak outflow from breached embankment dam. Journal of Water Resources Planning and Management, 121(1), 90–97.
- Getis, A., & Ord, J. K. (1992). The analysis of spatial association by use of distance statistics. Geographical Analysis, 24(3), 189–206.
- Gupta, H. V., Kling, H., Yilmaz, K. K., & Martinez, G. F. (2009). Decomposition of the mean squared error and NSE performance criteria. Journal of Hydrology, 377, 80–91.
- Hartmann, J., & Moosdorf, N. (2012). The new global lithological map database GLiM. Geochemistry, Geophysics, Geosystems, 13, Q12004.
- Hock, R. (2003). Temperature index melt modelling in mountain areas. Journal of Hydrology, 282, 104–115.
- Huggel, C., Kääb, A., Haeberli, W., Teysseire, P., & Paul, F. (2002). Remote sensing based assessment of hazards from glacier lake outbursts. Canadian Geotechnical Journal, 39, 316–330.
- Hugonnet, R., et al. (2021). Accelerated global glacier mass loss in the early twenty-first century. Nature, 592, 726–731.
- Huizinga, J., de Moel, H., & Szewczyk, W. (2017). Global flood depth-damage functions: Methodology and the database with guidelines. JRC Technical Report EUR 28552 EN.
- IceBoost v2.0 glacier ice thickness, RGI v7.0 region 14. Zenodo record 21220985.
- Keers, J. F., & Wescott, P. (1977). A computer-based model for design rainfall in the United Kingdom. Met Office Scientific Paper 36.
- Khan, et al. (2020). Coastal flood hazard assessment, Karachi, Pakistan. Entropy, 22(7), 796.
- Lehner, B., & Grill, G. (2013). Global river hydrography and network routing: baseline data and new approaches (HydroSHEDS). Hydrological Processes, 27, 2171–2186.
- Leopold, L. B., & Maddock, T. (1953). The hydraulic geometry of stream channels and some physiographic implications. USGS Professional Paper 252.
- Martinec, J., & Rango, A. (1986). Parameter values for snowmelt runoff modelling. Journal of Hydrology, 84, 197–219; and the SRM User's Manual.
- Messager, M. L., et al. (2016). Estimating the volume and age of water stored in global lakes (HydroLAKES). Nature Communications, 7, 13603.
- Meyer-Peter, E., & Müller, R. (1948). Formulas for bed-load transport. Proc. 2nd IAHR Congress, Stockholm.
- Muis, S., et al. (2016). A global reanalysis of storm surges and extreme sea levels (GTSR). Nature Communications, 7, 11969.
- Muñoz-Sabater, J., et al. (2021). ERA5-Land: a state-of-the-art global reanalysis dataset for land applications. Earth System Science Data, 13, 4349–4383.
- Nash, J. E., & Sutcliffe, J. V. (1970). River flow forecasting through conceptual models. Journal of Hydrology, 10, 282–290.
- Poggio, L., et al. (2021). SoilGrids 2.0. SOIL, 7, 217–240.
- Popov, N. (1991). Assessment of glacial debris flow hazard in the north Tien-Shan. Proc. Soviet-China-Japan Symposium on Natural Disasters.
- Rawls, W. J., Brakensiek, D. L., & Miller, N. (1983). Green-Ampt infiltration parameters from soils data. Journal of Hydraulic Engineering, 109(1), 62–70.

- Stockdon, H. F., Holman, R. A., Howd, P. A., & Sallenger, A. H. (2006). Empirical parameterization of setup, swash, and runup. Coastal Engineering, 53, 573–588.
- Thrasher, B., et al. (2022). NASA Global Daily Downscaled Projections, CMIP6. Scientific Data, 9, 262.
- Zanaga, D., et al. (2022). ESA WorldCover 10 m 2021 v200.
- Zheng, X., et al. (2018). GeoFlood: Large-scale flood inundation mapping based on high-resolution terrain analysis. Water Resources Research, 54(12).
- Fernandez, M. & Mourato, S. Comparison of HEC-RAS and LISFLOOD-FP flood inundation models on the River Lis, Portugal. Recursos Hídricos 34(1) (APRH; University of Évora).
- Oikonomou, A., et al. Floodplain mapping via 1D and quasi-2D numerical models in the valley of Thessaly, Greece (HEC-RAS, LISFLOOD-FP, FLO-2D).
- Rehman, H. u. & Teferle, F. N. R. (2026). LISFLOOD-FP 8.3 hydrodynamic model. Zenodo, doi:10.5281/zenodo. 13121119.
- Roth, F., et al. (2023). Sentinel-1 flood extent maps for the 2022 Pakistan floods. Natural Hazards and Earth System Sciences, 23, 3305.
- Shustikova, I., et al. (2019). Comparing 2D capabilities of HEC-RAS and LISFLOOD-FP on complex topography. Hydrological Sciences Journal, 64(14), 1769–1782.
- Leijnse, T., et al. (2021). Modeling compound flooding in coastal systems using a computationally efficient reduced-physics solver (SFINCS). Coastal Engineering.
- Néelz, S. & Pender, G. (2013). Benchmarking the latest generation of 2D hydraulic modelling packages. Environment Agency, Bristol.