

Electronic Supplementary Information

Recall, not verification, is the bottleneck when frontier LLMs elucidate molecular structures from real spectra

Ilkham Yabbarov, Rudra Sondhi, Rodrigo A. Vargas-Hernández

This document contains the Supporting Information figures referenced in the main article. Data, predictions, and the code that regenerates every figure are released with the manuscript; see *Data and code availability* in the main text.

This document records the operational detail behind the article: which model answered which arm and when (§S1), the prompts and agent protocol (§S2), how the benchmark was assembled (§S3), what the correctness criterion accepts and rejects (§S4), the construction of the forward-verification arm (§S5) and of the two non-LLM verifiers (§S6), the four-vendor replication (§S7), the contamination controls (§S8) and the frozen expert-audit package (§S9). Where the repository does not pin a value it says so rather than supplying one, and every number is copied from a released artifact or from a companion note issued with the manuscript (docs/MODELS.md, docs/BENCHMARK.md, docs/FORWARD_VERIFY.md, docs/CROSS_VENDOR.md, docs/VERIFIER_PROBE.md, docs/MODALITY_ABLATION.md, docs/EXPERT_AUDIT_PROTOCOL.md).

S1. Models, versions and collection windows

Every LLM result in the article was produced by Anthropic Claude models invoked as independent sub-agents through the Agent tool under a single consumer claude.ai subscription: no paid API, no fine-tuning, no model training in the core protocol. The two trained probes — the learned ^{13}C verifier of §5.4 (§S6) and the generator of §5.6 (contrib/generator_probe/) — are not Claude models.

Table S1. Which model answered which arm, and when. “Collected” is the UTC author-date of the commit that first added the prediction artifact. Each raw agent-output file was committed once, in the session that produced it, so first-add is the best available proxy for collection time — a proxy, not a harness timestamp.

arm	model	data directory	collected (UTC)
pilot, n=21, single context, no tools	Claude Opus 4.8	data/benchmark/	2026-06-09 04:40
within-compound control, arm (a): n=20, one context, no tools	Claude Opus	data/benchmark_v2/	2026-06-09 06:28
controlled round v3, n=40, decoupled agents	Claude Opus	data/benchmark_v3/	2026-06-09 06:47–07:37
within-compound control, arm (b): same n=20, 4 agents of 5 compounds, RDKit formula check	Claude Opus	data/benchmark_v2_ctrl	2026-06-09 17:43
forward verification: 8 blind forward-prediction agents, 126 candidates, 60 compounds	Claude Opus	data/fverify/	2026-06-09 19:51

arm	model	data directory	collected (UTC)
generate-wide: 10 solver agents, 6 compounds each, up to 6 candidates per compound	Claude Opus	data/gw/	2026-06-10 18:15
forward verification of the widened pool: 4 agents, 65 new candidates	Claude Opus	data/fverify2/	2026-06-10 18:19
cross-model recall check on V3-R01...R12 (n=12), identical blind 6-candidate protocol	Claude Sonnet	data/gw/raw/sonnet_b1.json sonnet_b2.json	2026-06-10 18:33–18:38
headline main round, 140 problems (134 spectrally validated), decoupled agents	Claude Opus	data/benchmark_main/raw/	2026-06-11 06:48–09:16
four-model comparison, fixed 24-compound subset	Claude Haiku	data/benchmark_main/haiku/	2026-06-11 16:16
four-model comparison, same subset	Claude Sonnet	data/benchmark_main/sonnet/	2026-06-11 16:41–17:10
electrolyte subset, 48 curated / 46 scored, 8 batches	Claude Opus	data/benchmark_electrolyte/	2026-06-11 18:29–18:43
four-model comparison, same subset	Claude Fable 5	data/benchmark_main/fable5/	2026-06-11 23:06–23:32
formula-only contamination control, same 60 compounds, spectra masked	Claude Opus	data/modality/	2026-07-28 18:37
forward verification extended to the whole benchmark: 15 agents, 247 main-round candidates	Claude Opus	data/fverify_main/	2026-08-07 02:45–02:53
generate-wide coverage gap closed: 9 agents, the 152 wide candidates that had no prediction	Claude Opus	data/fverify_gw/	2026-08-07 03:20–03:30
trained-generator arm re-run: 5 agents, 75 outstanding candidates	Claude Opus	data/fverify_gen/	2026-08-07 03:55–04:05
cross-vendor sweep, non-Claude models (§S7)	see Table S4	sweep_out/	2026-08-13 to 2026-08-17

27 Invocations fall into three dated windows, not one. **2026-06-09 to 2026-06-11** produced every
 28 candidate structure behind the headline results and behind the pools all of §5 re-ranks. **2026-07-28**
 29 is the formula-only control, which generates its own candidates (3/60 correct) by design, a masked-
 30 input control being meaningful only as a fresh run. **2026-08-07** carries three forward-prediction
 31 collections that predict ^{13}C for candidates the June solver had already produced, so none introduces
 32 a new candidate or moves a recall number. All later commits re-score frozen outputs and re-query
 33 no model.

34 S1.1 Version strings, snapshots and decoding parameters

35 **Claude Opus 4.8** is the only Claude version string anywhere in the repository, and it is evidenced
 36 only for the 2026-06-09 pilot (docs/BENCHMARK.md). It is a display version, not a snapshot identifier:
 37 it pins no checkpoint. **Fable 5** appears as a display name; **no version number of any kind**

appears for Claude Sonnet or Claude Haiku, and no dated snapshot identifier exists for any of the four, because the consumer harness exposes no checkpoint identifier, announces no build change, and records nothing about which build served a request. Two numbers from one window are therefore known to share a window and *not* known to share a build: **a mid-window build change cannot be excluded**, and the article does not claim the pilot build served the main round two days later. **No sampling parameters were set for any run and none are recorded** — no temperature, `top_p`, `top_k`, `max_tokens`, generation seed or thinking budget appears in any script, document, config or artifact; the `seed=` values in the repository are for analysis determinism only. Reproduction is distributional, not exact.

One protocol asymmetry belongs here, because §4.3 measures a large effect of the variable it concerns. The Opus column of the four-model comparison is not a fresh 24-compound run: it re-scores the main-round predictions on that subset (the SRC map in `scripts/score_models.py`), whose 24 items came from one 6-compound and two 12-compound contexts (`raw/b1.json`, `raw/redo_b23.json`, `raw/redo_b45.json`) where Sonnet, Haiku and Fable each saw four 6-compound contexts. Prompts and compounds are identical; context packing is not.

S2. Prompts and agent protocol

What the solver was shown: the molecular formula (as from HRMS), the IR band list, and the ^1H and ^{13}C shift lists with multiplicities and J-couplings where the source paper reported them.

What it was not shown: the compound name, any SMILES, any starting material or scaffold hint, the ground truth, and any other benchmark record. Solver agents were closed-book — no web access, no ground-truth access, no tools beyond an RDKit formula/parse check — except the arm (a) baseline of §4.3, which had no tools at all, that being the variable it isolates. Closed-book status was grep-audited over the task transcripts at run time; the transcripts are not committed (§7).

Candidate budget: up to **three ranked candidate SMILES per compound**, best first, in every arm except generate-wide, where ten independent solver agents each proposed up to **six regiochemistry-aware candidates** and the pools were merged. Scoring reads the first three for top-1 and recovered (top-3); generation recall reads the whole pool.

Context discipline: one small batch per agent, in a context reset between batches — 6 compounds per released batch file (`data/benchmark_main/batch_*.txt`, 23 files: 22 of six plus one of two = the 134 spectrally-validated problems), some batch pairs merged into a single 12-compound context (`data/benchmark_main/raw/redo_*.json`). Range released: **2–12 compounds per context**.

Forward-prediction agents had **zero tools**, pure reasoning, and were blind: anonymised SMILES only, pooled across compounds, canonicalised, de-duplicated, shuffled and re-labelled, in fixed batches of 17. They saw neither the observed spectrum, nor the compound’s identity, nor which candidates belong to one target. Shuffling does not keep a target’s own candidates in separate batches — in the §5.2 arm 5 of the 8 batches held two candidates for some one compound — but with no observed spectrum in hand there is nothing for that to leak: at most a predictor notices that two structures are isomers, evident from either alone.

Verbatim prompts, and what they are not. The prompts below are committed (`sweep_prompts/solve_01.md ... solve_10.md`, `sweep_prompts/verify/`) and emitted by `scripts/cross_vendor_sweep.py`. They are the harness prompts for the cross-vendor replication (§S7). The instruction text dispatched to the Claude solver and forward-prediction sub-agents in the main rounds was **not captured** — only the per-compound batch data it wrapped is released

81 — so the prompts below state the task as posed, but are not a transcript of the main arms. This
82 is a reproducibility gap and we name it rather than let the committed files stand in for something
83 they are not. The elucidation header:

```
84 # Blind structure-elucidation task
85
86 You are given real experimental spectra (from the published literature) for a set of
87 organic molecules. For EACH compound you are given the molecular formula (from HRMS),
88 the IR band list, and the 1H and 13C NMR shift lists. No name, SMILES, or scaffold hint is given deliberately; in 1
89
90 For each compound, propose the 3 most likely structures, best first, as SMILES.
91
92 Rules:
93 - Use only the spectra provided. Do not use external lookups or tools.
94 - Candidates must match the given molecular formula exactly.
95 - Order candidates by your own confidence (most likely first).
96
97 Return ONLY a JSON object mapping each id to a list of 3 SMILES strings, e.g.:
98 {"M001": ["CCO", "COC", "..."], "M002": [...], "...", "..."], ...}
99
100 Compounds:
```

101 The forward-prediction header:

```
102 # Forward 13C prediction task
103
104 For each candidate structure below (given as SMILES), predict its 13C NMR chemical
105 shift list (in ppm) from the structure alone. This is the forward direction only:
106 you are NOT given any observed spectrum and must not assume one.
107
108 Return ONLY a JSON object mapping each id to a list of predicted 13C shifts (numbers
109 in ppm), e.g.: {"P001": [21.0, 60.5, 171.2], "P002": [...], ...}
110
111 Candidates:
```

112 Each compound follows as one block in exactly this form, the NMR strings being the source pa-
113 per’s own text reproduced unedited (hence the chemical-shift symbol and whatever assignment
114 annotations the authors wrote):

```
115 ### M001
116 Molecular formula: <formula>
117 IR bands (cm-1): <list of wavenumbers>
118 1H NMR: <string as reported>
119 13C NMR: <string as reported>
```

120 The real blocks are released per arm:

- 121 • solving — data/benchmark_main/batch_*.txt, data/gw/batch_*.txt
- 122 • forward prediction — data/fverify_main/fbatch_*.txt, data/fverify_gw/gbatch_*.txt
- 123 • contamination control — data/modality/prompt_*.txt

124 **One gap, stated rather than papered over.** The wording above is the harness prompt used
125 verbatim for the four-vendor replication, and it is the only instruction text committed in the
126 repository. The Claude sub-agents behind the headline arms were dispatched through the Agent
127 tool with their instruction supplied at dispatch, and **that instruction text was not captured.**
128 What is released for those arms is the per-compound data exactly as the agents received it, plus
129 the candidate budget, tool policy and context sizes above.

S3. Benchmark construction

IRSpectra-Bench is drawn from `irexp_resolved`, the 43,060-record structure-complete split of IR-exp. A record enters the sampling pool only if it carries an IR band list, a ^1H and a ^{13}C shift list and a resolved structure; the structure has **8–60 heavy atoms**; each NMR string carries at least three parenthesised entries; and the raw ^1H string, re-fetched from the source article, contains genuine J information. Draws are balanced between the difficulty strata, and every compound revealed in a prior round is excluded by InChIKey-14 beforehand, so none appears twice (`scripts/benchmark_v2.py`).

Table S2. Rounds behind the n=194 cohort.

round	data directory	problems	in the cohort	role
main	<code>data/benchmark_main/</code>	140	134	headline, spectrally validated
controlled v3	<code>data/benchmark_v3/</code>	40	40	difficulty control, pre-registered
within-compound control	<code>data/benchmark_v2_ctrl/</code>	20	20	context/tooling control, pre-registered
electrolyte case study	<code>data/benchmark_electrolyte/</code>	48	—	domain subset, 46 scored, held apart

What was excluded, and why. Every main-round ground truth passes an automated RDKit self-consistency check — ^{13}C peak count against symmetry-unique carbons, formula match, SELFIES round-trip — which excluded 6 of 140: five report more ^{13}C peaks than the structure has carbons (R03 28>24, R14 11>8, R65 26>18, R67 23>16, R131 34>17: merged or contaminated spectra) and one is too sparse to constrain (R82, 5 peaks for 22 symmetry-unique carbons). The two controlled rounds are used **whole**, being fixed and pre-registered as controls before the audit existed; the same audit is reported on them rather than applied (57/60 pass), and §4.1 gives the strictly-validated 191-compound cohort as a robustness check. The filter (`scripts/validate_benchmark.py`, which regenerates every `clean_qids.json` from the released questions and answers) tests ^{13}C against the carbon count and does not gate on ^1H : in **13 of the 194** retained records the reported ^1H integral exceeds the reference structure’s hydrogen count. These are printed as a diagnostic, not excluded, because the cohort was fixed in advance; dropping all 13 moves the headline from 28.4% to 29.3% (53/181).

Complexity stratification, and when it was defined. Difficulty is a declared property of the compound, assigned by RDKit ring analysis at sampling time — before anything was solved — and exhaustive by construction, so nothing falls between the classes. A compound is **complex** if it has a spiro atom, a bridgehead atom, three or more rings, any fused ring system, **or** more than 24 heavy atoms; **simple** if it has at most two rings and at most 22 heavy atoms; anything else (the 23–24-heavy-atom band, 13 compounds) is complex on size alone. The cohort splits 98 simple / 96 complex. The 22-atom threshold is not load-bearing: sweeping it from 18 to 26 moves the simple-minus-complex top-1 gap only between 36 and 40 points, against 39.6 at the released value (`scripts/difficulty_sensitivity.py`). This axis is distinct from the heavy-atom bands (≤ 15 / $16\text{--}25$ / >25) of §4.1 and Fig. S3.

The battery-electrolyte subset (§4.5) came from the same corpus by SMARTS filters for six electrolyte functional classes, eight per class (48 curated, 46 scored), J-enriched and spectrally validated identically to the main rounds and excluding every compound used elsewhere.

S4. Scoring: what the criterion accepts and rejects

A prediction is **correct** if the first 14 characters of the RDKit InChIKey computed from its SMILES equal those of the reference — the InChIKey **connectivity layer**, which hashes the molecular skeleton; the later blocks, carrying stereochemistry, isotopic substitution and protonation state, are not compared. Top-1 asks this of the first-ranked candidate, recovered (top-3) of the up-to-three returned, generation recall of the whole pool. Nothing is model-mediated: RDKit only, in `scripts/score_main.py` and `scripts/specmetrics.py`. Morgan(2, 2048) Tanimoto¹ is reported alongside as a graded signal, 0.45 being the scaffold-level threshold; intervals are bootstrap 95% over compounds (2,000 resamples, analysis seed 0), model comparisons McNemar exact with Holm correction.

What it accepts. A candidate with the right constitution and the wrong stereochemistry scores correct. This is a deliberate floor whose cost is measured rather than assumed: re-scoring the *full* InChIKey gives **21.1% top-1 and 25.8% recovered (41/194 and 50/194)** against 28.4% / 33.5% at the connectivity layer, so fourteen top-1 answers are accepted here that a stereochemistry-sensitive scorer rejects. The floor exists because 1D ¹H/¹³C/IR rarely fixes absolute configuration and only 10.3% (20/194) of answers carry a defined (assigned R/S) stereocentre. Worked cases of acceptance come from the cross-vendor arm: on structures those models got constitutionally right whose reference carries assigned stereocentres, Grok 4.6 reproduced 0/3 correct descriptors, Gemini 3.7 Flash 0/2 and GPT-5.6 Sol 0/2 — all scored correct here.

What it rejects: every constitutional isomer, however close, and every structure of the wrong composition. Three worked cases, all from released artifacts:

- *A regioisomer the verifier separates.* Picolinamide and nicotinamide differ only in which ring position bears the carboxamide, so they have different connectivity layers and proposing one for the other scores zero; forward-predicted ¹³C separates them at a chamfer of 0.42 ppm against 1.30 ppm (Fig. 6).
- *A regioisomer it does not.* On the 2-(nitrophenyl)-2,3-dihydroquinazolin-4(1H)-one targets (C₁₄H₁₁N₃O₃) the predictor cannot resolve the *ortho*- and *meta*-nitrophenyl isomers: it ranks the 2-nitrophenyl isomer first at a chamfer of 1.35 ppm against 1.36 ppm for the true 3-nitrophenyl one, a 0.01 ppm margin. The answer is rejected, as it must be.
- *A pilot miss of the same kind.* The n=21 pilot returned the right hydrazinecarbothioamide skeleton with the **3-pyridyl** isomer where the truth is **2-pyridyl** (`docs/BENCHMARK.md`): right formula, right scaffold, rejected.

That is the dominant shape of failure: of the 137 analysable top-1 misses (139 in all; two predictions did not parse), **76.6% are constitutional isomers** of the true structure and 23.4% have the wrong formula outright, 22.6% share the true Murcko scaffold, and the median isomeric-miss Tanimoto is 0.39 (`scripts/analyze_misses.py`). Formula adherence is not part of the criterion — a wrong-composition answer is simply a miss — and it is not uniform across rounds: on top-1 answers, 95.0% (38/40) in v3, 90.0% (18/20) in the within-compound control and 77.6% (104/134) in the main round.

S5. Forward-verification detail

The distance. Candidates are ranked by a symmetric chamfer distance between the forward-predicted and observed ^{13}C peak sets: a mean of two nearest-neighbour means, so no equal-count requirement is imposed and lower is better. The implementation is the single source of truth for every scorer (`scripts/specmetrics.py`):

```
def chamfer(pred, obs):
    """Symmetric chamfer distance between predicted and observed 13C shift lists."""
    if not pred or not obs:
        return 999.0
    a = sum(min(abs(x - y) for y in obs) for x in pred) / len(pred)
    b = sum(min(abs(y - x) for x in pred) for y in obs) / len(obs)
    return (a + b) / 2
```

The re-ranking. Within a compound the candidate of smallest chamfer becomes the top-1 answer and the solver’s own ordering is discarded. The sentinel matters: a candidate with no forward prediction takes 999.0, effectively infinite, and can never be selected, so an arm with unpredicted candidates reports a lower bound on verified top-1 rather than a measurement — which is why the generate-wide arm was re-run to completion.

Table S3. Forward-prediction coverage, by arm. Batch size is 17 anonymised SMILES throughout.

arm	data directory	candidates	forward-predicted	agents
original 60-compound arm	data/fverify/	126	126	8
widened candidate pool	data/fverify2/	65 new	65	4
extension to the whole benchmark	data/fverify_main/	247	247	15
generate-wide coverage-gap closure	data/fverify_gw/	152	152	9
trained-generator arm, re-run	data/fverify_gen/	75	75	5
		outstanding		

Across the whole benchmark that is **373 of 373** candidates forward-predicted by 23 independent agents over 194 targets, so nothing in Table 7 is a lower bound. In the generate-wide arm all **217 of 217** distinct new candidates are now predicted where the original pass had predicted 65, and **not one number moves**: recall 42%, forward-verified top-1 30%, precision 72%. The added coverage buys a direct view of the mechanism — on **18 of the 60** compounds the verifier abandons its previous pick for a newly-selectable candidate, and in **not one** does the outcome change; every switch is wrong structure to wrong structure.

The margin the method works on. Taking the chamfer between the *predicted* spectra of every pair of candidates proposed for one target (`scripts/isomer_separability.py`), isomeric pairs sit at a median separation of **1.21 ppm** (quartiles 0.84 and 1.78) and **82% are predicted closer together than the predictor’s own ~2 ppm error** — usually within the noise. What shows that a ranking on so thin a margin is nonetheless real is the derangement control of §5.5: over 1,000 permutations of which observed spectrum each candidate set is scored against, conditional-on-recall

precision falls from **89.2% (58/65)** to a permuted mean of **73.8%** (one-sided $p=0.001$). The floor sits high because recall-positive compounds carry few, near-identical candidates.

The same distance fails as an absolute confidence gauge — ranked by chamfer margin, the 138 multi-candidate compounds give top-1 22% / 24% / 28% / 24% at 100%, 75%, 50% and 25% coverage — which is why the article claims it only as a re-ranker (§5.5).

S6. Non-LLM verifiers: a deterministic lookup and a learned model

Both non-LLM ^{13}C predictors are built from the **same nmrshiftdb2 dump**² and dropped into the verifier slot on the **same candidate sets**, so only the predictor changes.

The deterministic lookup realises the HOSE-code idea³ natively in RDKit: the Morgan per-atom identifier at radius r hashes an atom’s environment out to r bonds, so a (radius, identifier) bin groups carbons with identical local environments. The mean assigned shift per bin is learned from nmrshiftdb2, and prediction walks the deepest sphere holding at least 3 samples, $r=4 \rightarrow 3 \rightarrow 2 \rightarrow 1$, falling back to a hybridisation prior. Training used **31,000 molecules, 332,595 assigned carbons and 263,366 environment bins**, held-out **MAE 3.23 ppm (median 1.73)** over 17,456 carbons of 1,647 molecules (`scripts/hose_predict.py`).

The learned model is a message-passing GNN — 4 layers, hidden width 256, GRU node update, bond features, per-carbon ^{13}C regression — trained on the identical dump: 32,647 molecules and 350,313 assigned carbons, split by molecule into 29,383 train / 1,632 validation / 1,632 test at seed 5 (the lookup’s figures above are this set minus its random 5% held-out split). Optimisation is Adam at learning rate $1e-3$, weight decay $1e-5$, batch size 64, smooth-L1 loss, plateau learning-rate halving, early stopping. Held-out **MAE 1.70 ppm (median 1.02)**, roughly twice as sharp as the lookup (`scripts/gnn_predict.py`, `data/nmrshiftdb/gnn_c13.pt`). It is deliberately modest — purpose-built ^{13}C models reach ~ 1 ppm⁴ and 0.94 ppm coupled to DFT shielding tensors⁵ — the question being only whether the predictor slot is where the leverage sits.

Held-out error against benchmark behaviour. Table 9 gives the four verifiers conditional on recall. The lookup’s tie with self-ranking there is not agreement: at $n=65$ it **gains seven compounds and loses seven** (McNemar $b=c=7$, $p=1.00$), reshuffling energetically while carrying no net discriminative signal. Its coverage diagnosis is that of the **6,360 candidate carbons only 2.1% match a training environment at the most specific sphere ($r=4$)**, 71% resolving only at $r \leq 2$ or falling through to the prior. The GNN’s margins are directional and none reaches significance (against the lookup $p=0.34$, against self-ranking $p=0.22$, against the LLM verifier $p=1.00$).

Leakage analysis is the decisive control for a *learned* verifier, which can memorise a molecule’s spectrum where a bin average cannot. Exact overlap with the whole nmrshiftdb2 database is **2 of 364** distinct candidate structures by InChIKey-14 — both wrong candidates on recall-negative compounds, which never enter the conditional analysis — and **no benchmark answer appears in the database at all** (0/373; the 60-compound arm is 0/126). Analog overlap is likewise absent: median Morgan(2, 2048) Tanimoto to the nearest training molecule is **0.44**, three candidates above 0.80, and over the **65 true structures the verifier must identify** the nearest training analog has median Tanimoto **0.50** and maximum **0.81** — no compound the conditional analysis scores has a near-duplicate in training. A Y-randomisation control (1,000 derangements) places the learned verifier above the 97.5th percentile of chance ($n=19$: real 84% against a permuted mean of 58.6%, 95% range 42.1–73.7%, one-sided $p<0.05$). Both checks regenerate via `scripts/verifier_leakage.py`;

neither predictor is redistributable end-to-end, the nmrshiftdb2 dump being one a reader must supply.

S7. Cross-vendor replication

Non-Claude models were run through `scripts/cross_vendor_sweep.py` on the `fverify60` arm — the same 60 compounds as the first column of Table 7 — between 2026-08-13 and 2026-08-17. Two arms went through OpenRouter (`scripts/openrouter_run.py`); the rest were driven by cloud coding agents against the committed `sweep_prompts/`, one fresh subagent per batch, at no API cost. Raw replies are in `sweep_out/`.

Table S4. Generation stage, every model run on the 60-compound arm, with the article’s Claude Opus arm for reference.

model	route	answered	recall	top-1	parse	matches the given formula
grok-4.6	cloud	60/60	53%	38%	99%	95%
gemini-3.7-flash	agent					
	cloud	60/60	50%	38%	98%	94%
gpt-5.6-sol	agent					
	cloud	60/60	42%	35%	100%	100%
<i>Claude Opus (reference arm)</i>	subscription	60/60	<i>32%</i>	<i>23%</i>	—	<i>78–95%</i>
composer-2.5	cloud	57/60	20%	17%	95%	67%
gpt-5.6-luna	agent					
	cloud	60/60	15%	10%	90%	76%
deepseek/deepseek-v4-pro	agent					
	OpenRouter	18/60	13%	12%	94%	94%
nvidia/nemotron-3.5-lightning	OpenRouter	60/60	0%	0%	61%	2%

Read the formula-adherence column first: nemotron’s zero is not a chemistry result but a model that could not return a structure of the requested composition, and the deepseek arm answered 18 of 60 compounds, having exhausted its token ceiling on most batches without emitting an answer.

Matched across arms: the compounds, the two-stage protocol, the three-candidate budget, the context packing (six compounds per fresh context), the closed-book instruction, the anonymised blind forward-prediction stage, the scorer. **Not matched:** verification ran only for the three models whose output contract justified it, Composer 2.5 and GPT-5.6 Luna being excluded at 67% and 76% formula adherence.

Table S5. Decomposition, the three replicated arms. Recall and precision have different denominators, so the criterion is the inequality, not a difference.

model	generation recall	verification precision given recall	multi-candidate only
<i>Claude Opus (reference arm)</i>	19/60 = 32% [21, 44]	16/19 = 84% [62, 94]	10/13 = 77%
grok-4.6	32/60 = 53% [41, 65]	20/32 = 62% [45, 77]	20/32 = 62%
gemini-3.7-flash	30/60 = 50% [38, 62]	22/30 = 73% [56, 86]	22/30 = 73%
gpt-5.6-sol	25/60 = 42% [30, 54]	17/25 = 68% [48, 83]	16/24 = 67%

What these identifiers name. The models are as served by the coding-agent harness, not stock vendor endpoints, and the harness supplies its own agent system prompt above the task text. Its allowlist reads `gpt-5.6-sol-xhigh`, `gpt-5.6-sol-high`, `gpt-5.6-luna-high`, `gemini-3.7-flash-high`, `cursor-grok-4.6-high-fast`, `composer-2.5` — every identifier but the last carries a **reasoning-effort suffix**, a decoding parameter the Claude reference arm never had (§S1.1). **The tier used for each arm is not recorded**, because the run did not report which allowlist entry it selected; a run at `-xhigh` is not the same measurement as one at `-high`, which is why the article reports these as vendor-family results.

Contamination control. The cloud agents cloned the whole repository and the answer files for these 60 compounds are tracked, so blindness rested on an instruction nothing verifies after the fact. The control is a re-solve with those files out of the workspace: Grok 4.6 re-ran all ten batches from a clean clone (`sweep_out/grok-4.6-clean/`).

Table S6. Clean-clone contamination control, Grok 4.6.

arm	recall	95% CI	parse	formula match
original (answer files present)	32/60 = 53%	[41, 65]	179/180	171/180
clean clone (answer files absent)	28/60 = 47%	[35, 59]	176/180	174/180

Paired, that is **b=8, c=4, McNemar exact p=0.39**. The decisive detail is the asymmetry rather than the totals: a model reading the key would solve a superset, and instead **four compounds were solved only in the arm that had no key**, with 24 of the 60 solved by both, while formula adherence did not degrade (174/180 candidates in the clean arm against 171/180 in the original). The control covers Grok alone; Gemini 3.7 Flash and GPT-5.6 Sol rest on the shared instruction and the stereochemistry evidence of §S4.

S8. Modality ablation and contamination controls

The leave-one-modality-out ablation was specified and never run, and no leave-one-out result appears in the article. The staged prompts `prompt_noIR.txt`, `prompt_noH.txt` and `prompt_noC.txt` sit under `data/modality/` (2026-06-16) with no corresponding `out_*.json`. Two attempts were discarded, and why is instructive. The first used one solver agent per condition, so agent quality was a single draw that swamped the modality effect: full modality came out worst at

3/16, —IR best at 8/16. The second ran a fresh —IR arm against the *archived* benchmark predictions as its control, giving full 10/30, —IR 22/30 and formula-only 2/30 on the simple stratum — —IR beating full modality by 40 points, McNemar $p=0.004$, impossible on the modality reading and diagnostic of the confound. The rule this yielded: every arm of an ablation must be generated in one campaign, the control included (`docs/MODALITY_ABLATION.md`).

The formula-only control shares that structure and is not impugned by it, because the confound runs against the finding: only the formula-only arm was freshly generated (2026-07-28), its comparison arm re-using the archived June predictions (whose 60 top-1 answers are byte-identical to that run), and fresh agents reason harder per compound, so the bias favours the formula-only arm — which still collapsed. That solver received the formula and nothing else, was barred from reading any repository file or searching the web, and was allowed RDKit only to check that a proposed SMILES parses and matches the formula. The outcomes are perfectly nested: **eleven** compounds are solved with the spectra and not without, **none** the other way round ($b=11$, $c=0$, McNemar exact $p=0.001$), for 3/60 against 14/60 top-1 and 3/60 against 19/60 recovered (Table 5).

The three formula-only successes are named rather than rounded away, because they do not all support one reading: **C₁₅H₁₅ClF₂O₃SSi**, a 2-(trimethylsilyl)aryl sulfonate whose composition is a near-unique benzyne-precursor signature and which is absent from PubChem, so the formula is close to determining; **C₁₃H₁₉NO₄S**, *N*-tosyl-leucine (CAS 67368-40-5), where inference and recall are both available; and **C₁₇H₂₆O₃**, [6]-paradol (CAS 27113-22-0), a catalogued natural product that composition alone constrains very little.

The recency control is independent and agrees. Publication years were resolved for all 194 compounds from their accessions (`scripts/contamination_recency.py`) and span 2008–2026. Accuracy is flat: **28.6%** for the older half (≤ 2020 , $n=112$) against **28.0%** for the newer ($n=82$), point-biserial r between year and correctness of **−0.007**, the most recent bucket (≥ 2024 , $n=25$) in fact highest at 40% [23, 59]. The raw split is biased against the newer half, since newer papers skew larger (median 22 heavy atoms against 20) and size dominates accuracy; stratifying by heavy-atom band removes that (≤ 15 : 64% against 58%; 16–25: 34% against 25%; > 25 : 6% against 8%). The size-adjusted older-minus-newer difference is **−5.1 points, 95% CI [−17.2, +7.0]** (Cochran–Mantel–Haenszel $\chi^2=0.42$, $p=0.51$, continuity-corrected) — a bound on any recency effect, not a reversed one.

S9. Human-expert audit: protocol and status

Solver and verifier are both LLMs, so the one validation the authors cannot perform themselves is an expert-chemist review of the outputs. The audit package is blinded, pre-registered and **frozen** before any review, and regenerates deterministically at seed 0 from `scripts/make_audit_sample.py` into `data/audit/`.

The panel is three independent PhD-level synthetic or analytical chemists with no prior exposure to the benchmark answers, at roughly 3–4 person-hours each. The sample is a difficulty-stratified draw (15 simple, 15 complex) from the 60-compound forward-verification set, the only split carrying both the ranked candidates and the observed spectra. Per compound a reviewer sees the exact solver prompt — formula, IR, ¹H, ¹³C — and the model’s top-ranked candidate rendered as a 2D structure, with model identity and ground truth hidden.

Table S7. Composition of the frozen audit kit.

item	count
compounds in the kit	37
Task 1 panel (unbiased stratified draw)	30
Task 2 ranking items	37
...carrying the true structure and a real choice, scoring precision	13
...carrying the true structure but a single candidate, excluded	3
...carrying no correct candidate, measuring expert calibration	21
model top-1 exact on the Task 1 panel (held in the withheld key only)	7/30

Task 1 scores the model’s top-1 for consistency with all provided spectra (1–5), gives a categorical verdict (correct / wrong-regiochemistry / wrong-scaffold / uninterpretable) and names the single most diagnostic peak; the read-outs are inter-rater agreement and the fraction of mechanically-wrong top-1 answers judged spectrally consistent but a different regioisomer. Task 2 presents the shuffled, unlabelled candidate set for ranking by spectral fit, against the LLM forward-verifier’s and the deterministic lookup’s picks on identical sets. Task 2 is shown on **every** compound, so its presence signals nothing: an earlier version showed it only on recall-positive compounds, which leaked Task 1 twice over and moved the apparent rate of correct answers from 12% to 67%. The seven extra compounds carry Task 2 only, because a correct top-1 is recall-positive by definition, so enriching the Task 1 draw for recall-positive compounds would raise the very rate Task 1 judges.

Status. The panel has not been run and the article reports no audit result (§7). One reviewer file is deposited at `data/audit/responses/` (submitted 2026-08-18 UTC), incomplete against the 37-item kit; a single partial reviewer supports neither read-out, inter-rater agreement needing at least two reviewers and the pre-registered panel being three. Scoring is mechanical (`scripts/score_audit.py`), and the three Task 2 sets holding a single candidate (A19, A21, A30) cannot be ranked, so the scorer excludes and flags them. Until expert results are in, the two claims the panel targets — what a miss actually is (§4), and whether forward verification is a trustworthy re-ranker (§5) — should be read as machine-validated (RDKit InChIKey) but not yet human-validated.

References

- 1 D. Rogers and M. Hahn, *J. Chem. Inf. Model.*, 2010, **50**, 742–754.
- 2 S. Kuhn and N. E. Schlörer, *Magn. Reson. Chem.*, 2015, **53**, 582–589.
- 3 W. Bremser, *Anal. Chim. Acta*, 1978, **103**, 355–365.
- 4 D. Williamson, S. Ponte, I. Iglesias, N. Tonge, C. Cobas and E. K. Kemsley, *J. Magn. Reson.*, 2024, **368**, 107795.
- 5 C. Han, D. Zhang, S. Xia and Y. Zhang, *J. Chem. Theory Comput.*, 2024, **20**, 5250–5258.



Fig. S1: Study design: open multimodal data (IReXP) → blind, complexity-stratified benchmark → decoupled blind solving → forward-verification re-ranking; training-free core pipeline.




Fig. S2: IReXP composition: IR records, NMR-paired, structure-linked, and full IR+¹H+¹³C+structure quadruples.




Fig. S3: Accuracy versus molecular size; the monotonic 60% $\rightarrow$ 7% top-1 gradient with heavy-atom count.




Fig. S4: IRSpectra-Bench-Electrolyte by battery-electrolyte class (n=46): $\text{sp}^3\text{-C-F}$ easiest (50%), sulfonyl and nitrile hardest (12%).




Fig. S5: Trained-generator probe (§5.6; a complement, not part of the training-free protocol). Candidate recall and deterministic-HOSE top-1 on the 194-compound benchmark for Claude / + scaffold enumeration / + trained generator: enumeration’s near-degenerate isomers collapse the verifier (28.4→16.0%) while the generator’s formula-correct candidates convert (28.4→35.1%).




Fig. S6: Learned-verifier probe (§5.4; a complement, not part of the training-free protocol). (A) Conditional-on-recall top-1 over the whole benchmark ($n=65$) across four verifiers: a GNN trained on the same nmrshiftdb2 data as the HOSE lookup reaches the LLM verifier’s level (91% against 89%) where the lookup (85%) does not move off the solver’s own ranking. (B) Held-out ^{13}C MAE — the learned model is roughly 2× sharper (1.70 vs 3.23 ppm).