

AI Planning

Exercise Sheet 2

Date: 06.11.2014
 Students: Axel Perschmann, Tarek Saier

Exercise 2.1

(a) Transform the operator

original

$\langle \neg e \vee f, (a \triangleright (b \triangleright c)) \wedge (\neg d \triangleright c) \wedge (\neg(\neg c \wedge \neg a) \triangleright (d \wedge \neg d)) \wedge (d \triangleright \neg e) \rangle$

(7)

$\langle \neg e \vee f, ((a \wedge b) \triangleright c) \wedge (\neg d \triangleright c) \wedge (\neg(\neg c \wedge \neg a) \triangleright (d \wedge \neg d)) \wedge (d \triangleright \neg e) \rangle$

(9)

$\langle \neg e \vee f, (((a \wedge b) \vee \neg d) \triangleright c) \wedge (\neg(\neg c \wedge \neg a) \triangleright (d \wedge \neg d)) \wedge (d \triangleright \neg e) \rangle$

(8)

$\langle \neg e \vee f, (((a \wedge b) \vee \neg d) \triangleright c) \wedge (\neg(\neg c \wedge \neg a) \triangleright d) \wedge (\neg(\neg c \wedge \neg a) \triangleright \neg e) \wedge (d \triangleright \neg e) \rangle$

(9)

$\langle \neg e \vee f, (((a \wedge b) \vee \neg d) \triangleright c) \wedge (\neg(\neg c \wedge \neg a) \triangleright d) \wedge ((\neg(\neg c \wedge \neg a) \vee d) \triangleright \neg e) \rangle$

2x deMorgan

$\langle \neg e \vee f, (((a \wedge b) \vee \neg d) \triangleright c) \wedge ((c \vee a) \triangleright d) \wedge ((c \vee a \vee d) \triangleright \neg e) \rangle$

(b) Transform the ENF operator

original

$\langle \neg e \vee f, (((a \wedge b) \vee \neg d) \triangleright c) \wedge ((c \vee a) \triangleright d) \wedge ((c \vee a \vee d) \triangleright \neg e) \rangle$

Exercise 2.2

(a)

Listing 1: set cover problem as a PDDL domain

```
(define (domain set-cover)
  (:requirements :adl)
  (:types set elem)
  (:predicates (contains ?s - set ?e - elem)
    (selected ?s - set)
    (covered ?e - elem))
  (:action select-set
    :parameters(?s - set)
```

```

:precondition (not (selected ?s))
:effect (and (selected ?s)
             (forall (?e - elem)
              (when (contains ?s ?e)
                    (covered ?e))))))

```

(b)

Listing 2: set cover instance as a PDDL problem

```

(define (problem set-cover-i-1)
  (:domain set-cover)
  (:objects e1 e2 e3 e4 - elem s1 s2 s3 s4 s5 - set)
  (:init (contains s1 e1)
         (contains s2 e2)
         (contains s2 e3)
         (contains s3 e4)
         (contains s4 e1)
         (contains s4 e2)
         (contains s5 e3)
         (contains s5 e4))
  (:goal (and (covered e1)
              (covered e2)
              (covered e3)
              (covered e4))))

```

(c)

Listing 3: solving set cover instance with fast-downward

```

$ ./fast-downward.py scprob.pddl --search "astar(blind())"
[...]
select-set s4 (1)
select-set s5 (1)
Plan length: 2 step(s).
Plan cost: 2
Initial state h value: 1.
Expanded 6 state(s).
Reopened 0 state(s).
Evaluated 16 state(s).
Evaluations: 16
Generated 21 state(s).
Dead ends: 0 state(s).
Expanded until last jump: 1 state(s).
Reopened until last jump: 0 state(s).
Evaluated until last jump: 6 state(s).
Generated until last jump: 5 state(s).
Number of registered states: 16
Search time: 0s
Total time: 0s
Solution found.
Peak memory: 2924 KB
$ cat sas_plan
(select-set s4)
(select-set s5)

```

```
|; cost = 2 (unit cost)|
```