

Version History

When	Who	Comment
05/09/25	Yaw Adu-Boahene	v1.0 Initial Document Delivery
05/16/25	Veronica Williams	v1.0 Submitted to DHS
06/11/25	Yaw Adu-Boahene	v2.0 Updates to address DHS comments. • Tab: Request File – Field: Authorization Status (Cell J15) Added FEI Response to the DHS comment.
06/26/25	Michael Hodge	v3.0 Updates to address DHS comments • Tab: Request File, Field: Authorization Status: Added a response to DHS comment and a note in the "Request File Layout Notes" column: "Note: Per DHS, auths can only be deleted the day that they are created in WISITS. This prevents the need to send a "voided" auth to MMIS". Also added a similar note as a response to the DHS comment. • Tab: Request File, Field: Units by Frequency: Added a response to DHS comment: Specifics of calculations by unit type will be discussed and agreed upon by DHS.
07/15/25	Yaw Adu-Boahene	v4.0 Updates to address DHS comments. • Tab: Request File, Field: Units by Frequency: Added a response to DHS comment: Specifics of calculations by unit type will be discussed and agreed upon by DHS. They will be added to the final submission as part of the FG6 submission.
07/23/25	Veronica Williams	v4.0 Approved by DHS

Approval

[illegible]

	Blue Compass (Source)				File Layout								
Descriptive Name	Source Table	Source Column	Data Type	Length	Layout Data Element	Data Type	Length	Required (R/O/C)	Request File Layout Notes	Allowable Values	Default Value	Related BRs	Mapping Notes
Header Record													
Record Type	System Generated	n/a	n/a	n/a	Record Type	AN	3	R	Identifies the record type (header record).	HDR	HDR	BR-005-012	
Control Number	System Generated	n/a	n/a	n/a	Control Number	AN	20	R	Unique ‘file identifier’ which identifies this particular file and must match the Control Number in the Trailer Record. The “Control Number” is made up of: •The 8-digit Payer ID for the FEA •The Creation Date (CCYYMMDD) •The Creation Time (HHMM)			BR-005-001	
Payer Identifier	System Generated	n/a	n/a	n/a	Payer Identifier	AN	8	R	Unique identifier for the program payer. This constant value will be provided to each program payer by DHS. This is the ID that the MMIS uses to identify the FEA.				
Creation Date	System Generated	n/a	n/a	n/a	Creation Date	N	8	R	YYYYMMDD – Must not be > than today’s date				
Creation Time	System Generated	n/a	n/a	n/a	Creation Time	N	6	R	HHMMSS – Creation time in 24HR format				
Detail Record													
Record Type	System Generated	n/a	n/a	n/a	Record Type	AN	3	R	Identifies the record type (detail record).	DTL	DTL	BR-005-019	
Record Number	System Generated	n/a	n/a	n/a	Record Number	N	10	R	Start at 1 increment by 1. Must be unique in the file and count each individual authorization in the file.				
Member ID	PersonModule. PersonMedicaidNumbers	Value	nvarchar	50	Member ID	AN	10	R	The member’s Medicaid ID Number. MCI; Test it against MMIS's existing member matching protocol in the interface . Example:1000054870			BR-005-002, BR-005-004, BR-005-005, BR-005-006	
Billing Provider ID	OrganizationModule. OrganizationIdentifiers	Value	nvarchar	50	Billing Provider ID	AN	10	R	The Billing Provider agency ID. MCD ID or NPI This is existing. This is the ID of provider that will be paid for the service (FEAs are used for self-directed services) A billing provider ID is required for all service authorizations. For PHWs: *Send the FEA Billing ID (which is the FEA MAID). For organization providers if it is an EVV service: *Send enumeration ID (MAID) and null if none. For organization providers if it is not an EVV service: *Send enumeration ID (MAID) if there is one *If no MAID, send the EIN *If no EIN, send the SSN. For IR providers: *Send the SSN and fall back on the EIN if there isn’t an SSN. The billing provider ID qualifier should be consistent with the type of ID provided.				This will always be "MMIS Provider Number" of the Blue Compass Organization. Use the value in the ProviderReferenceLocationKey (in the ServiceAuthorization record) to lookup the Organization and locate the OrganizationIdentifier with type "Provider Number". By the time that Blue Compass goes live, the only type of ID that will be used for the “Billing Provider ID” is the MMIS Provider Number. DHS has plans to discontinue the provider type “IR”. There may not be any authorizations after 1/1/26 that use this provider type. Assumption: PHW's (Locations) will be created as Locations under FEA Organizations in Blue Compass.
Authorization Number	ServiceAuthorizationModule. ServiceAuthorization	ServiceAuthorizationNumber	nvarchar	20	Authorization Number	AN	30	R	The Authorization Number assigned by the payer.			BR-005-019, BR-005-021	

Request File

Descriptive Name	Blue Compass (Source)				File Layout								
	Source Table	Source Column	Data Type	Length	Layout Data Element	Data Type	Length	Required (R/O/C)	Request File Layout Notes	Allowable Values	Default Value	Related BRs	Mapping Notes
Authorization Status	ServiceAuthorizationModule. Decision	TypeDisplayName	nvarchar	4000	Authorization Status	AN	1	R	The Status of the authorization. Initially, only approved authorizations will be sent. Similar purpose as Authorization Type (active/voided or deleted) Note: Per DHS, auths can only be deleted the day that they are created in WISITS. This prevents the need to send a "voided" auth to MMIS.	A, V		BR-005-002, BR-005-003	File Layout Values "A" (Active), "V" (Voided or Deleted). Blue Compass Values: "Approved", "Deny", "Request Clarification", "Canceled". Service Line Records that are "Approved" will be sent with value "A" in this field. Service Line Records that are "Canceled" voided/deleted will be sent with value "V" in this field.
Service Code	ServiceDefinitionModule. ServiceDefinition	ProcedureCodeDisplayName	nvarchar	4000	Service Code	AN	5	R	Format examples can include but are not limited to: T1019, T1020, S5125, S5126 There will be revenue codes included in service codes. 00### or 0####				
Modifier 1	ServiceDefinitionModule. ServiceDefinition	Modifier1DisplayName	nvarchar	4000	Modifier 1	AN	2	O	Modifier 1				
Modifier 2	ServiceDefinitionModule. ServiceDefinition	Modifier2DisplayName	nvarchar	4000	Modifier 2	AN	2	O	Modifier 2				
Modifier 3	ServiceDefinitionModule. ServiceDefinition	Modifier3DisplayName	nvarchar	4000	Modifier 3	AN	2	O	Modifier 3				
Modifier 4	ServiceDefinitionModule. ServiceDefinition	Modifier4DisplayName	nvarchar	4000	Modifier 4	AN	2	O	Modifier 4				
Authorized Effective Date	ServiceAuthorizationModule. ServiceLine	AuthorizedEffectiveDateStar tDate	date	n/a	Authorized Effective Date	N	8	R	Authorized effective date for the service code in YYYYMMDD format.				
Authorized End Date	ServiceAuthorizationModule. ServiceLine	AuthorizedEffectiveDateEnd Date	date	n/a	Authorized End Date	N	8	O	Authorized end date for the service code in YYYYMMDD format.				
Authorization Type	System Generated	n/a	n/a	n/a	Authorization Type	N	1	R	Same as “Authorization Type” in the AUTHORIZATIONS_EXTRACT View 2 (when auth reported has been deleted) Else 0 (If auth updated date = created date), else it is 1 <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>	2, 1, 0			Valid Values "0", "1", "2". Send value "2" when a previously approved Auth in Blue Compass is "Deleted" or a previously approved Service Line is "Cancelled". Else, send value "0" for "Approved" Auths that haven't been sent before (New). Else send value "1" for "Approved" Auths that have been sent before (Update).
Participant DOB	PersonModule. Person	BirthDate	date	n/a	Participant DOB	N	8	R	Participant’s DOB in YYYYMMDD format.				
Participant SSN	PersonModule. PersonIdentifiers	Value	nvarchar	50	Participant SSN	N	9	R	Participant’s SSN in 6666666666 format.				
Participant Name	PersonModule. Person	NameFirstName	nvarchar	100	Participant Name	A	255	R	Format: Last, First Format example: Brower, Kara				
	PersonModule. Person	NameLastName	nvarchar	100									

	Blue Compass (Source)				File Layout								
Descriptive Name	Source Table	Source Column	Data Type	Length	Layout Data Element	Data Type	Length	Required (R/O/C)	Request File Layout Notes	Allowable Values	Default Value	Related BRs	Mapping Notes
Rendering Provider ID	OrganizationModule.LocationIdentifiers	Value	nvarchar	50	Rendering Provider ID	N	10	O	This is the ID of the provider that is providing the service to the participant. This ID is only sent if the service is rendered by a PHW For PHWs: *send the enumeration ID (MAID) *If no enumeration ID, send SSN *If no SSN, send the EIN For non PHW: *Services don't send any Rendering Provider ID. The ID rendering ID qualifier should be consistent with the type of ID provided.			BR-005-022	Only populate for PHW providers. This will always be "MMIS Provider Number". Use the value in the ProviderReferenceLocationKey in the ServiceAuthorization record to locate the Location's LocationIdentifier with type "Provider Number". Assumption: PHW's (Locations) will be created under FEA Orgs in Blue Compass.
Rendering Qualifier ID	OrganizationModule.LocationIdentifiers	TypeDisplayName	nvarchar	4000	Rendering Qualifier ID	N	2	O	Similar to "Qualifier ID" in AUTHORIZATIONS_EXTRACT but for the rendering provider 24 for EIN, 34 for SSN, Value to be determined for enumeration ID/MAID The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the "FEA Authorization File". These references are pointing out similarities in the two files.	24,34,44			Only populate for PHW providers. Valid Values = "24", "34", "44". When the value for Rendering/service Provider ID is an SSN, send value "34". When EIN, send "24". When Enumeration ID, send "44"
Rendering Provider NPI	OrganizationModule.LocationIdentifiers	Value	nvarchar	50	Rendering Provider NPI	N	10	O	Similar to "NPI" in AUTHORIZATIONS_EXTRACT but for the rendering provider The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the "FEA Authorization File". These references are pointing out similarities in the two files.			BR-005-023	Only populate for PHW providers.
Billing provider ID	n/a	n/a	nvarchar	50	Billing provider ID	N	9	O	Layout notes moved to row 13 (Billing Provider ID) above.				Data will not be populated in this field. This field is considered a duplicate to row 13
Billing Qualifier ID	OrganizationModule.OrganizationIdentifiers	TypeDisplayName	nvarchar	4000	Billing Qualifier ID	N	2	R	Similar to "Qualifier ID" in AUTHORIZATIONS_EXTRACT but for the billing provider 24 for EIN, 34 for SSN, Value to be determined for enumeration ID/MAID The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the "FEA Authorization File". These references are pointing out similarities in the two files.	24,34,44			Enumeration ID should be available for all valid providers. This should always be value "44". Valid Values = "24", "34", "44". When the value for Billing Provider ID is an SSN, send value "34". When EIN, send "24". When Enumeration ID, send "44".
Billing Provider NPI	OrganizationModule.OrganizationIdentifiers	Value	nvarchar	50	Billing Provider NPI	N	10	O					

	Blue Compass (Source)				File Layout								
Descriptive Name	Source Table	Source Column	Data Type	Length	Layout Data Element	Data Type	Length	Required (R/O/C)	Request File Layout Notes	Allowable Values	Default Value	Related BRs	Mapping Notes
Service Code Qualifier	ServiceDefinitionModule. ServiceDefinition	SericeCodeTypeDisplayName	nvarchar	4000	Service Code Qualifier	A	7	R	This is the “Service Type Code” Values “Revenue”, “CPT”, “HCPCS”	Revenue, CPT, HCPCS			Valid Values = “Revenue”, “CPT”, “HCPCS”. Product changes required to support this data element.
Service Description	ServiceDefinitionModule. ServiceDefinition	Name	nvarchar	300	Service Description	AN	255	R	This is the Service Name Same as “Service Description” in AUTHORIZATIONS_EXTRACT <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>				
Total Dollar Amount	ServiceAuthorizationModule. ServiceLine	AuthorizedTotalCostAmount	decimal	19,5	Total Dollar Amount	N	50	R	Same as “Total Dollar Amount” in AUTHORIZATIONS_EXTRACT (allow for 2 characters after decimals) <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>				
Total Units	ServiceAuthorizationModule. ServiceLine	AuthorizedTotalUnitCount	decimal	19,5	Total Units	N	50	R	Same as “Total Units” in AUTHORIZATIONS_EXTRACT (allow for 2 characters after decimals) There is a formula the current WISITS system that calculates “Total Units” using “Units by Frequency”, “Frequency”, “Begin Date” and “End Date”. <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>				
Unit Rate	ServiceAuthorizationModule. ServiceLine	AuthorizedRateAmount	decimal	19,5	Unit Rate	N	50	R	Same as “Unit Rate” in AUTHORIZATIONS_EXTRACT (allow for 2 characters after decimals) <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>				
Unit Type	ServiceDefinitionModule. ServiceDefinition		nvarchar	4000	Unit Type	A	50	R	Same as “Unit Type” in AUTHORIZATIONS_EXTRACT <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>	Hour, Day, Night, Month, Each, Mile			In the file layout, the “Unit Type” field does not include “Minutes” as an acceptable value. This may be a change on MMIS side to accept “Minutes”.

	Blue Compass (Source)				File Layout								
Descriptive Name	Source Table	Source Column	Data Type	Length	Layout Data Element	Data Type	Length	Required (R/O/C)	Request File Layout Notes	Allowable Values	Default Value	Related BRs	Mapping Notes
Frequency	ServiceAuthorizationModule.ServiceLine	AuthorizedFrequencyDisplay Name	nvarchar	4000	Frequency	A	50	R	Same as “Frequency” in AUTHORIZATIONS_EXTRACT <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>	Weekly, Monthly, Each, Annually			Valid Values = "Weekly", "Monthly", "Each", "Annually".
Units by Frequency	ServiceAuthorizationModule.ServiceLine	AuthorizedDurationLength	decimal	19,5	Units by Frequency	N	50	R	Same as “Units by Frequency” in AUTHORIZATIONS_EXTRACT (allow for 2 characters after decimals) <i>The AUTHORIZATIONS_EXTRACT (referenced in the IRIS Authorization specification document provided by DHS) is a reference to the “FEA Authorization File”. These references are pointing out similarities in the two files.</i>				Calculation: Total Units divided by Frequency. Specifics of calculations by unit type will be discussed and agreed upon by DHS. They will be added to the final submission as part of the FG6 submission. Example: (52 Total Units Authorized for the year) divided by frequency "weekly" (52 weeks in a year) = ("1" Unit Per Week). The contents of this field would be "1". The “Units by Frequency” field represents for example “10” Units per week. If a unit is 1 hour, then "10" hours per week". Similar concept of duration in Blue Compass. Related Action Item #405.
Created Date	ServiceAuthorizationModule.ServiceLine	EntityCreatedTimestamp	datetime	n/a	Created Date	N	8	R	Authorization’s creation date in YYYYMMDD format. Reflects when SA created; does not change.				
Updated Date	ServiceAuthorizationModule.ServiceLine	EntityUpdatedTimestamp	datetime	n/a	Updated Date	N	8	R	Authorization’s update date in YYYYMMDD format. Reflects when SA updated, changes when updated.				
Participant Status	ProgramEnrollmentModule.ProgramEnrollment	StatusDisplayName	nvarchar	4000	Participant Status	A	50	R	Participant Status. The “Participant Status” field contains the text name of the participant’s status (RF State Name). Values include “Enrolled”, “Voluntary Disenrollment”, “Involuntary Disenrollment”, “Suspended”, etc. This represents the current state of the participant when the Auth file was generated.				
Retroactive Authorization Reason Code	ServiceAuthorizationModule.ServiceAuthorization	RetroactiveReasonCode	nvarchar	4000	Retroactive Authorization Reason Code	N	1	O	When creating an authorization with a start date in the past, the user entering the authorization must fill in a “Retroactive Authorization Reason Code”. The values for this code are: Justified Correction = “1”, IC Error = “2”, or Budget Mismanagement = “3”.	1,2,3			Product changes required to support this data element.
Units Change Reason Code	ServiceAuthorizationModule.ServiceLine	UnitsChangeReasonCode	nvarchar	4000	Units Change Reason Code	N	1	O	The “Units Change Reason Code” is required if there is an existing auth and the units are changed. Justified Correction = “1”, IC Error = “2”, or Budget Mismanagement = “3”.	1,2,3			Product changes required to support this data element.
Trailer Record													
Record Type	System Generated	n/a	n/a	n/a	Record Type	AN	3	R	Identifies the record type (trailer record).	TLR	TLR	BR-005-013	
Detail Record Count	System Generated	n/a	n/a	n/a	Detail Record Count	N	10	R	Count of detail records between the Header and the Trailer excluding the Header and Trailer record.			BR-005-014	

Descriptive Name	File Layout					Blue Compass Tables (Destination)								Response File Layout Notes	Mapping Notes
	Layout Data Element	Data Type	Length	Required (R/O/C)	Allowable Values	Target Table	Target Column	Data Type	DB Field Length	UI Field Length	Related BRs				
Detail Record - Each instance represents a line item for the authorization															
Reported Date	Reported Date	N	8	R		n/a	n/a	n/a	n/a	n/a		Authorized effective date for the service code in YYYYMMDD format.			
Payer Identifier	Payer Identifier	AN	8	R		n/a	n/a	n/a	n/a	n/a		Unique identifier for the program payer. This constant value will be provided to each program payer by DHS. The same “Payer Identifier” value echoed back from the request file.			
Authorization Number	Authorization Number	AN	30	R		n/a	n/a	n/a	n/a	n/a	BR-005-025	The Authorization Number assigned by the payer. If the authorization number returned does not match an existing authorization number in Blue Compass, Error: RV-005-001.			
Billing Provider ID	Billing Provider ID	AN	10	R		n/a	n/a	n/a	n/a	n/a		The Billing Provider agency ID. MCD ID or NPI			
Member ID	Member ID	AN	10	R		n/a	n/a	n/a	n/a	n/a		The member’s Medicaid ID Number. MCI; Test it against MMIS’s existing member matching protocol in the interface . Example:1000054870			
Service Code	Service Code	AN	5	R		n/a	n/a	n/a	n/a	n/a		Format examples can include but are not limited to: T1019, T1020, S5125, S5126 There will be revenue codes included in service codes. 00### or 0####			
Modifier 1	Modifier 1	AN	2	O		n/a	n/a	n/a	n/a	n/a		Modifier 1			
Modifier 2	Modifier 2	AN	2	O		n/a	n/a	n/a	n/a	n/a		Modifier 2			
Modifier 3	Modifier 3	AN	2	O		n/a	n/a	n/a	n/a	n/a		Modifier 3			
Modifier 4	Modifier 4	AN	2	O		n/a	n/a	n/a	n/a	n/a		Modifier 4			
Error Description	Error Description	AN		O		ServiceAuthorizationModule.ServiceLine	ResponseErrorNote	nvarchar	MAX	10000	BR-005-018, BR-005-024	Example: Billing Provider ID missing or invalid	The description returned in this field by MMIS, will be populated in the "Error Description" field found under the Response section (Service Details) in Blue Compass UI.		
Authorized Effective Date	Authorized Effective Date	N	8	R		n/a	n/a	n/a	n/a	n/a		Authorized effective date for the service code in YYYYMMDD format.			
Authorized End Date	Authorized End Date	N	8	O		n/a	n/a	n/a	n/a	n/a		Authorized effective date for the service code in YYYYMMDD format.			
Authorization Type	Authorization Type	N	1	R	2, 1, 0	n/a	n/a	n/a	n/a	n/a		Same as “Authorization Type” in the AUTHORIZATIONS_EXTRACT View 2 (when auth reported has been deleted) Else 0 (If auth updated date = created date), else it is			
Participant DOB	Participant DOB	N	8	R		n/a	n/a	n/a	n/a	n/a		Participant’s DOB in YYYYMMDD format.			
Participant SSN	Participant SSN	N	9	R		n/a	n/a	n/a	n/a	n/a		Participant’s SSN in 6666666666 format.			
Participant Name	Participant Name	A	255	R		n/a	n/a	n/a	n/a	n/a		Format: Last, First Format example: Brower, Kara			

Context

Item Description	Details
Purpose of this interface	Case Management sends Service Authorization records to MMIS to be verified, approved or denied. With a response file providing validation outcome.
External system that Blue Compass will interface with	Wisconsin MMIS
Interface Direction (Inbound/Outbound/Both)	Both
Transfer Protocol (Webservice, SFTP, etc.)	SFTP
Where is the file sent to or picked up from (End-point or Landing Zone location URL)?	Gainwell Connect
Connectivity Protocols/Encryption/Authentication (VPN Tunnel, SSL Certificate swap, etc.)	SSH Key
File Type (xml, .csv, delimited flat file etc.)	Pipe delimited Flat File
Frequency	Daily (The processing of the file will occur daily, including weekends, regardless of holidays).
Timing Considerations (e.g. Day of the week and/or time of day files will be sent or available for pickup), or (When files are not available e.g. system maintenance windows, etc.)	12:00 am EST
Retry procedure for file expected but not (received/available) or otherwise successfully delivered.	n/a
For inbound, what field(s) are used to match to data in Blue Compass?	Authorization Number
Is every file a full file (reconciliation), or a delta? If a delta, will full files occasionally be sent/received? If so, how often?	Delta
Is there a field that represents the last time a row was edited, either a date or a datetime?	n/a
How are deletions handled? That is, if a data was sent previously but is no longer valid.	n/a
How are updates handled?	If an update is applied to any of the Blue Compass data elements, a request record is generated for the authorization.
If there are multiple files in the interface: What field(s) are used to link them together? If there is an update in one file, will all the matching records be updated as well? For example, when a person's address changes will the update record include only the new address, or will it include a refresh of all of the person's addresses, or a refresh of all of the person's information?	n/a

Context

Item Description	Details
What is the file naming convention? (Ideally all files will have CCYYMMDD_HHmm as part of the file name)	File naming standards: • File names shall follow the format of: [Source system 3 character code]-[Target system 3 character code]-[File name]-[File frequency 1 character code('D','W','M','Y')]-[Timestamp YYYYMMDD_HHMMSS_ 3 character millisecond].[file extension] • File name segments shall be separated by a hyphen character “-” • File name segments shall not contain a period character “.” • A period character “.” shall be used to separate the file name and the file name extension. • Separate words and content within a file segment shall be separated using an underscore character “_” • File names shall not exceed 186 characters in length, including the file name extension.

Business Rules

BR #	Description	Source Notes
BR-005-001	The Interface will generate a set of four individual "IRIS" Authorization Request Files , with each file representing one of the four different FEAs on file in Blue Compass. There are 4 daily request files to MMIS and 4 daily response files from MMIS.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-002	Only the most recent (created or updated) version of the authorization with status = "Processed" should be included in the IRIS Authorization Request File .	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-003	An IRIS Authorization Request File should only contain approved or cancelled (voided) authorizations. If an authorization was sent initially in error (mistake), then it will need to be resent as voided, using the Authorization Status of 'V'.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-004	An IRIS Authorization Request File should include newly created or updated authorization records with a funding source of either, "IRIS Waiver", "IRIS SDPC" and "IRIS One-Time Expense Authorizations", depending on funding source selection in Blue Compass.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-005	If an already approved authorization has been updated in Blue Compass, resend it with the updated value(s) in the next IRIS Authorization Request File generation. When resending, ensure the "Authorization Number" field value is the same as what was sent in original request file.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-006	When a MMIS Provider Number is updated in Blue Compass, all active authorizations for that provider should be flagged and re-sent as part of the next IRIS Authorization Request File generation.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-007	In the IRIS Authorization Request File, each request record must contain the correct number of delimited fields per the record specification. When the contents are null, the field is still represented with no data between the delimiters.	IRIS Service Authorization Data to MMIS File Specification
BR-005-008	In the IRIS Authorization Request File all contents should be accounted for. Spaces are considered part of a field and should not be ignored.	IRIS Service Authorization Data to MMIS File Specification
BR-005-009	In the IRIS Authorization Request File , the last field in each record must not be followed by a pipe. Example: John Smith 100 N Main Street, Apt 1 555-555-5555 City State Greg Jones 123 Green Ave. City State ß Note phone number was not supplied but is accounted for with delimiters.	IRIS Service Authorization Data to MMIS File Specification
BR-005-010	In the IRIS Authorization Request File , a column header row is not allowed.	IRIS Service Authorization Data to MMIS File Specification
BR-005-011	In the IRIS Authorization Request File , each file will contain three distinct record types: Header, Detail and Trailer.	IRIS Service Authorization Data to MMIS File Specification
BR-005-012	In the IRIS Authorization Request File , the file must contain exactly one Header record and it must be the first record in the file.	IRIS Service Authorization Data to MMIS File Specification
BR-005-013	In the IRIS Authorization Request File , the file must contain exactly one Trailer record and it must be the last record in the file.	IRIS Service Authorization Data to MMIS File Specification
BR-005-014	In the IRIS Authorization Request File , the number of detail records must reconcile with the count of detail records indicated in the Trailer record Detail Record Count. If no Detail records, then the value of '0' may be in that field.	IRIS Service Authorization Data to MMIS File Specification
BR-005-015	In the IRIS Authorization Request File , only printable ASCII characters are allowed. Note: ASCII codes 0 through 31 are specifically prohibited, with the exception of a carriage return and line feed at the end of each line. HTML reserved characters (ampersands, tildes, and asterisks and < and > symbols) are prohibited.	IRIS Service Authorization Data to MMIS File Specification

Business Rules

BR #	Description	Source Notes
BR-005-016	In the IRIS Authorization Request File , fields, such as character strings, should not be surrounded by quotes. Number and string types should be presented in the same manner.	IRIS Service Authorization Data to MMIS File Specification
BR-005-017	In the IRIS Authorization Request File , fields should not contain line feeds or carriage returns.	IRIS Service Authorization Data to MMIS File Specification
BR-005-018	An "Error Report" will be generated for all errors returned in the IRIS Authorization Response File, after each job run. Each error description will appear as a row and associated with the appropriate "Authorization Reference Number".	20250409_WI DHS Care Management - MMIS - Interface Meeting
BR-005-019	Each authorization number in the IRIS Authorization Request File represents one service. There can be multiple Detail Record rows with the same authorization number. Note: In some instances, it will be possible to have multiple detail rows in the file with the same authorization number but different service line numbers.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-020	IRIS Authorization Request detail records can contain EVV service codes or a Non-EVV service codes.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-021	Blue Compass will be the issuer of the “Authorization Numbers” sent to MMIS in an IRIS Authorization Request File . Note: To prevent duplicates, before transition, DHS will provide the last authorization number issued. “Authorization Numbers” are currently 8-digit numbers (sequentially incremented). As of November 2024, the 8-digit authorization numbers began with “4269”. Example: 42690001.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-022	The “Rendering Provider” details are only sent for PHWs (not sent for organization providers), in the IRIS Authorization Request File . Only the "MMIS Provider Number" value shall be sent in this field.	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-023	Due to most PHW's not having NPI values, the “Rendering Provider NPI” field can be sent as a "blank" in the IRIS Authorization Request File .	20250402_WI DHS Care Management - MMIS - Interface Meeting
BR-005-024	An IRIS Authorization Response File, will only include "error descriptions" for each authorization that has errors. If there are no errors, an IRIS Authorization Response File is returned indicating that there were no errors.	20250409_WI DHS Care Management - MMIS - Interface Meeting
BR-005-025	If an IRIS Authorization Response File includes an authorization number that cannot be matched to an existing record in Blue Compass, an error will be generated in the error report.	20250409_WI DHS Care Management - MMIS - Interface Meeting

Error Handling

This tab will be populated during development phase

System Error			
Error Code	Error Message	Corrective Action	
SE-005-001			
SE-005-002			
SE-005-003			

Rule Violation			
Error Code	Error Message	Corrective Action	Related BRs
RV-005-001	No match found in system for Authorization Number <Service Authorization Number> .		
RV-005-002			
RV-005-003			

Requirements

Requirement Tracking		
Requirement ID	Description	Traceability Notes
R370	The Solution data exchanges must comply with CMS security and HIPAA transaction	
R385	Solution must include various data exchange methods as necessary to support program-specific business needs.	
R386	Solution must allow for import and integration of data from multiple data sources to support program-specific Care Management System rules.	"Response from MMIS"
R394	Solution must utilize real-time notification to authorized users in the event of data exchange error or failure.	
R454	Solution must allow for the regular export of complete participant authorization information to other data sources on a schedule approved by DHS.	
R455	Solution must automate participant authorization changes that are triggered by program-specific events, including but not limited to Participant case changes, Participant eligibility and functional screen changes, Provider changes, reference data changes and service rate changes as approved by DHS.	
Exhibit J	1. Medicaid Management Information System (MMIS): e. Authorization: i. Authorization information including the service code(s) information, the participant, units and frequency, and the provider. 1. Extract from the Care Management system and sent to other systems.	