

# Robust Kernel Hypothesis Testing under Data Corruption

**Antonin Schrab\***

AI Centre, Gatsby Unit, Inria London  
University College London, UK



**Ilmun Kim\***

Department of Statistics & Data Science  
Yonsei University, South Korea



**AISTATS 2025, Mai Khao, Thailand**

\*equal contributions

# General Robust Testing Framework

- Space of distribution:  $\mathcal{P}$  partitioned into disjoint  $\mathcal{P}_0$  and  $\mathcal{P}_1$

# General Robust Testing Framework

- **Space of distribution:**  $\mathcal{P}$  partitioned into disjoint  $\mathcal{P}_0$  and  $\mathcal{P}_1$
- **(Abstract) Goal:** given data related to some fixed  $P \in \mathcal{P}$ , determine whether


$$\mathcal{H}_0: P \in \mathcal{P}_0 \quad \text{or} \quad \mathcal{H}_1: P \in \mathcal{P}_1$$

# General Robust Testing Framework

- **Space of distribution:**  $\mathcal{P}$  partitioned into disjoint  $\mathcal{P}_0$  and  $\mathcal{P}_1$
- **(Abstract) Goal:** given data related to some fixed  $P \in \mathcal{P}$ , determine whether


$$\mathcal{H}_0: P \in \mathcal{P}_0 \quad \text{or} \quad \mathcal{H}_1: P \in \mathcal{P}_1$$

Standard framework



vs

Robust framework



Up to **r** samples may have been corrupted **arbitrarily**

# General Robust Testing Framework

- Space of distribution:  $\mathcal{P}$  partitioned into disjoint  $\mathcal{P}_0$  and  $\mathcal{P}_1$
- (Abstract) Goal: given data related to some fixed  $P \in \mathcal{P}$ , determine whether

$$\mathcal{H}_0: P \in \mathcal{P}_0 \quad \text{or} \quad \mathcal{H}_1: P \in \mathcal{P}_1$$

- (Specific) Goal: given  $\tilde{X}_1, \dots, \tilde{X}_N$  related to some fixed  $P \in \mathcal{P}$ , determine whether

$$\mathcal{H}_0: \tilde{X}_1, \dots, \tilde{X}_N \text{ are exchangeable} \quad \text{or} \quad \mathcal{H}_1: \tilde{X}_1, \dots, \tilde{X}_N \text{ are not exchangeable}$$

# General Robust Testing Framework

- **Space of distribution:**  $\mathcal{P}$  partitioned into disjoint  $\mathcal{P}_0$  and  $\mathcal{P}_1$
- **(Abstract) Goal:** given data related to some fixed  $P \in \mathcal{P}$ , determine whether

$$\mathcal{H}_0: P \in \mathcal{P}_0 \quad \text{or} \quad \mathcal{H}_1: P \in \mathcal{P}_1$$

- **(Specific) Goal:** given  $\tilde{X}_1, \dots, \tilde{X}_N$  related to some fixed  $P \in \mathcal{P}$ , determine whether

$$\mathcal{H}_0: \tilde{X}_1, \dots, \tilde{X}_N \text{ are exchangeable} \quad \text{or} \quad \mathcal{H}_1: \tilde{X}_1, \dots, \tilde{X}_N \text{ are not exchangeable}$$

- **Challenge:** we don't observe  $\tilde{X}_1, \dots, \tilde{X}_N$  but observe  $X_1, \dots, X_N$  where

- Up to  $r$  samples might have been corrupted arbitrarily
- $N - r$  samples are from  $P$

 **Robustness parameter**  $r$  is specified by the user depending on the application

# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$

# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$

 Input

Corrupted data

$X_1, \dots, X_N$




# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$

 Input

Corrupted data  
 $X_1, \dots, X_N$



 For i in 1:B

Generate a permutation  $\pi$  of  $[N]$   
Compute  $T_i = T(X_{\pi_1}, \dots, X_{\pi_N})$


# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$


 **Input**

Corrupted data  
 $X_1, \dots, X_N$



 **For i in 1:B**

Generate a permutation  $\pi$  of  $[N]$   
Compute  $T_i = T(X_{\pi_1}, \dots, X_{\pi_N})$



 **Quantile**

Compute  $(1 - \alpha)$   
quantile  $q$  of  
 $T_0, T_1, \dots, T_B$


# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$


 **Input**

Corrupted data  
 $X_1, \dots, X_N$



 **For i in 1:B**

Generate a permutation  $\pi$  of  $[N]$   
Compute  $T_i = T(X_{\pi_1}, \dots, X_{\pi_N})$




 **Quantile**

Compute  $(1 - \alpha)$   
quantile  $q$  of  
 $T_0, T_1, \dots, T_B$

 **Output**

Reject  $\mathcal{H}_0$  if  
 $T_0 > q + 2r\Delta_T$




# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$


 **Input**

Corrupted data  
 $X_1, \dots, X_N$



 **For i in 1:B**

Generate a permutation  $\pi$  of  $[N]$   
Compute  $T_i = T(X_{\pi_1}, \dots, X_{\pi_N})$



 **Quantile**

Compute  $(1 - \alpha)$   
quantile  $q$  of  
 $T_0, T_1, \dots, T_B$

 **Output**

Reject  $\mathcal{H}_0$  if

$T_0 > q + 2r\Delta_T$

Adjustment factor  
for data corruption

# DC Procedure for Robust Testing

- **Global sensitivity:** maximum possible change in  $T$  when one data point is **arbitrarily** changed

$$\Delta_T := \sup_{\pi \in \Pi_n} \sup_{\mathcal{X}_n, \mathcal{Y}_n : d_{\text{ham}}(\mathcal{X}_n, \mathcal{Y}_n) \leq 1} |T(\mathcal{X}_n^\pi) - T(\mathcal{Y}_n^\pi)|$$

 **Input**

Corrupted data  
 $X_1, \dots, X_N$

 **For i in 1:B**

Generate a permutation  $\pi$  of  $[N]$   
Compute  $T_i = T(X_{\pi_1}, \dots, X_{\pi_N})$

 **Quantile**

Compute  $(1 - \alpha)$   
quantile  $q$  of  
 $T_0, T_1, \dots, T_B$

 **Output**

Reject  $\mathcal{H}_0$  if

$T_0 > q + 2r\Delta_T$

Adjustment factor  
for data corruption

We coin this as the “**DC test**”:  
A permutation test under data corruption

# DC Procedure for Robust Testing

We prove two **fundamental** results for the **DC test**

- **Level:** the DC test is **well-calibrated** non-asymptotically

$$\mathbb{P}_{P_0}(\text{DC rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha \quad \left\{ \begin{array}{l} \text{for any distribution } P_0 \in \mathcal{P}_0 \\ \text{for any value } \alpha \in (0,1) \\ \text{for any } N \geq 1 \end{array} \right.$$

# DC Procedure for Robust Testing

We prove two **fundamental** results for the **DC test**

- **Level:** the DC test is **well-calibrated** non-asymptotically

$$\mathbb{P}_{P_0}(\text{DC rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha \quad \left\{ \begin{array}{l} \text{for any distribution } P_0 \in \mathcal{P}_0 \\ \text{for any value } \alpha \in (0,1) \\ \text{for any } N \geq 1 \end{array} \right.$$

- **Consistency:** the DC test is **consistent** in the sense that

$$\lim_{N \rightarrow \infty} \mathbb{P}_{P_1}(\text{DC rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) = 1 \text{ for any fixed distribution } P_1 \in \mathcal{P}_1$$

$$\text{whenever } \lim_{N \rightarrow \infty} \mathbb{P}_{P_1}(T(\mathbb{X}_n) > T(\mathbb{X}_n^\pi) + 4r\Delta_T) = 1$$

1. Two-Sample Testing

2. Independence Testing



1. Two-Sample Testing

2. Independence Testing


# Robust Two-Sample Testing

- **Two-sample problem:** Given mutually independent
  - i.i.d. samples  $\tilde{X}_1, \dots, \tilde{X}_m$  from a distribution  $P$
  - i.i.d. samples  $\tilde{Y}_1, \dots, \tilde{Y}_n$  from a distribution  $Q$


test whether  $\mathcal{H}_0: P = Q$  or  $\mathcal{H}_1: P \neq Q$

# Robust Two-Sample Testing

- **Two-sample problem:** Given mutually independent
  - i.i.d. samples  $\tilde{X}_1, \dots, \tilde{X}_m$  from a distribution  $P$
  - i.i.d. samples  $\tilde{Y}_1, \dots, \tilde{Y}_n$  from a distribution  $Q$test whether  $\mathcal{H}_0: P = Q$  or  $\mathcal{H}_1: P \neq Q$
- **Robust testing:** Up to  $r$  samples from either  $P$  or  $Q$  can be corrupted




i.i.d. Samples from  $P$




i.i.d. Samples from  $Q$

# Robust Two-Sample Testing

- **Two-sample problem:** Given mutually independent
  - i.i.d. samples  $\tilde{X}_1, \dots, \tilde{X}_m$  from a distribution  $P$
  - i.i.d. samples  $\tilde{Y}_1, \dots, \tilde{Y}_n$  from a distribution  $Q$test whether  $\mathcal{H}_0: P = Q$  or  $\mathcal{H}_1: P \neq Q$
- **Robust testing:** Up to  $r$  samples from either  $P$  or  $Q$  can be corrupted



Corrupted Samples from  $P$



Corrupted Samples from  $Q$

# dcMMD Procedure

- Maximum Mean Discrepancy:

$$\text{MMD} = \sqrt{\mathbb{E}_{P,P}[k(\textcolor{red}{X}, \textcolor{red}{X}')] - 2\mathbb{E}_{P,Q}[k(\textcolor{red}{X}, \textcolor{blue}{Y})] + \mathbb{E}_{Q,Q}[k(\textcolor{blue}{Y}, \textcolor{blue}{Y})']}$$

# dcMMD Procedure

- Maximum Mean Discrepancy:

$$\text{MMD} = \sqrt{\mathbb{E}_{P,P}[k(\textcolor{red}{X}, \textcolor{red}{X}')] - 2\mathbb{E}_{P,Q}[k(\textcolor{red}{X}, \textcolor{blue}{Y})] + \mathbb{E}_{Q,Q}[k(\textcolor{blue}{Y}, \textcolor{blue}{Y}')]}$$

- Statistic (plug-in estimator):

$$\widehat{\text{MMD}} = \sqrt{\frac{1}{m^2} \sum_{1 \leq i, i' \leq m} k(\textcolor{red}{X}_i, \textcolor{red}{X}_{i'}) - \frac{2}{mn} \sum_{i=1}^m \sum_{j=1}^n k(\textcolor{red}{X}_i, \textcolor{blue}{Y}_j) + \frac{1}{n^2} \sum_{1 \leq j, j' \leq n} k(\textcolor{blue}{Y}_j, \textcolor{blue}{Y}_{j'})}$$

# dcMMD Procedure

- Maximum Mean Discrepancy:

$$\text{MMD} = \sqrt{\mathbb{E}_{P,P}[k(\textcolor{red}{X}, \textcolor{red}{X}')] - 2\mathbb{E}_{P,Q}[k(\textcolor{red}{X}, \textcolor{blue}{Y})] + \mathbb{E}_{Q,Q}[k(\textcolor{blue}{Y}, \textcolor{blue}{Y}')]}$$

- Statistic (plug-in estimator):

$$\widehat{\text{MMD}} = \sqrt{\frac{1}{m^2} \sum_{1 \leq i, i' \leq m} k(\textcolor{red}{X}_i, \textcolor{red}{X}_{i'}) - \frac{2}{mn} \sum_{i=1}^m \sum_{j=1}^n k(\textcolor{red}{X}_i, \textcolor{blue}{Y}_j) + \frac{1}{n^2} \sum_{1 \leq j, j' \leq n} k(\textcolor{blue}{Y}_j, \textcolor{blue}{Y}_{j'})}$$

- Global sensitivity of  $\widehat{\text{MMD}}$ :  $\Delta_{\widehat{\text{MMD}}} = \sqrt{2\textcolor{blue}{K}/\textcolor{red}{N}}$  where  $\textcolor{blue}{K}$ : kernel bound and  $\textcolor{red}{N} = \min(m, n)$

# dcMMD Procedure

- Maximum Mean Discrepancy:

$$\text{MMD} = \sqrt{\mathbb{E}_{P,P}[k(\textcolor{red}{X}, \textcolor{red}{X}')] - 2\mathbb{E}_{P,Q}[k(\textcolor{red}{X}, \textcolor{blue}{Y})] + \mathbb{E}_{Q,Q}[k(\textcolor{blue}{Y}, \textcolor{blue}{Y}')]}$$

- Statistic (plug-in estimator):

$$\widehat{\text{MMD}} = \sqrt{\frac{1}{m^2} \sum_{1 \leq i, i' \leq m} k(\textcolor{red}{X}_i, \textcolor{red}{X}_{i'}) - \frac{2}{mn} \sum_{i=1}^m \sum_{j=1}^n k(\textcolor{red}{X}_i, \textcolor{blue}{Y}_j) + \frac{1}{n^2} \sum_{1 \leq j, j' \leq n} k(\textcolor{blue}{Y}_j, \textcolor{blue}{Y}_{j'})}$$

- Global sensitivity of  $\widehat{\text{MMD}}$ :  $\Delta_{\widehat{\text{MMD}}} = \sqrt{2\textcolor{blue}{K}/\textcolor{red}{N}}$  where  $\textcolor{blue}{K}$ : kernel bound and  $\textcolor{red}{N} = \min(m, n)$
- dcMMD test: Apply DC procedure with  $\widehat{\text{MMD}}$  and  $\Delta_{\widehat{\text{MMD}}}$



# dcMMD Guarantees

- **Level:** for any distribution  $P$  and any sample size

$$\mathbb{P}_{P,P}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha$$

# dcMMD Guarantees

- **Level:** for any distribution  $P$  and any sample size

$$\mathbb{P}_{P,P}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha$$

- **Pointwise Power / Consistency:** for any fixed  $P \neq Q$  and  $r/N \rightarrow 0$

$$\lim_{m,n \rightarrow \infty} \mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) = 1$$

# dcMMD Guarantees

- **Level:** for any distribution  $P$  and any sample size

$$\mathbb{P}_{P,P}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha$$

- **Pointwise Power / Consistency:** for any fixed  $P \neq Q$  and  $r/N \rightarrow 0$

$$\lim_{m,n \rightarrow \infty} \mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) = 1$$

- **Uniform Power:** for any distributions  $P$  and  $Q$  separated as

$$\text{MMD}(P, Q) \gtrsim \max \left\{ \sqrt{\frac{\max \{ \log(1/\alpha), \log(1/\beta) \}}{\min(m, n)}}, \frac{r}{\min(m, n)} \right\}$$

dcMMD achieves high test power

$$\mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \geq 1 - \beta$$

This **rate is minimax optimal** with respect to  $m, n, r, \alpha, \beta$ .

# dcMMD Guarantees

- **Level:** for any distribution  $P$  and any sample size

$$\mathbb{P}_{P,P}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha$$

- **Pointwise Power / Consistency:** for any fixed  $P \neq Q$  and  $r/N \rightarrow 0$

$$\lim_{m,n \rightarrow \infty} \mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) = 1$$

- **Uniform Power:** for any distributions  $P$  and  $Q$  separated as

$$\text{MMD}(P, Q) \gtrsim \max \left\{ \sqrt{\frac{\max \{ \log(1/\alpha), \log(1/\beta) \}}{\min(m, n)}}, \frac{r}{\min(m, n)} \right\}$$

dcMMD achieves high test power

$$\mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \geq 1 - \beta$$

This **rate is minimax optimal** with respect to  $m, n, r, \alpha, \beta$ .

# dcMMD Guarantees

- **Level:** for any distribution  $P$  and any sample size

$$\mathbb{P}_{P,P}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \leq \alpha$$

- **Pointwise Power / Consistency:** for any fixed  $P \neq Q$  and  $r/N \rightarrow 0$

$$\lim_{m,n \rightarrow \infty} \mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) = 1$$

- **Uniform Power:** for any distributions  $P$  and  $Q$  separated as

$$\text{MMD}(P, Q) \gtrsim \max \left\{ \sqrt{\frac{\max \{ \log(1/\alpha), \log(1/\beta) \}}{\min(m, n)}}, \frac{r}{\min(m, n)} \right\}$$


dcMMD achieves high test power

$$\mathbb{P}_{P,Q}(\text{dcMMD rejects } \mathcal{H}_0 \mid r \text{ corrupted data}) \geq 1 - \beta$$

This **rate is minimax optimal** with respect to  $m, n, r, \alpha, \beta$ .

# Experiments

# dcMMD Experiments: Gaussian Mean Shift



- Generate two samples

$$\tilde{X}_1, \dots, \tilde{X}_m \stackrel{\text{iid}}{\sim} N_d(0, 0.1)$$


$$\tilde{Y}_1, \dots, \tilde{Y}_n \stackrel{\text{iid}}{\sim} N_d(0, 0.1)$$

- Corrupt one sample using

$$Z_1, \dots, Z_k \stackrel{\text{iid}}{\sim} N_d(1000, 0.1)$$

- ▲--- dcMMD: Our proposal
- dpMMD: Procedure via differential privacy (Kim & Schrab)
- .....●..... MMD: Standard non-robust MMD
- $r$  : Robustness parameter

# dcMMD Experiments: IMDb movie reviews



- Generate two samples

$$\tilde{X}_1, \dots, \tilde{X}_m \stackrel{\text{iid}}{\sim} \text{IMDb}(3330)$$

$$\tilde{Y}_1, \dots, \tilde{Y}_n \stackrel{\text{iid}}{\sim} \text{IMDb}(3330)$$

- Corrupt one sample using

$$Z_1, \dots, Z_k \stackrel{\text{iid}}{\sim} \text{Geometric}(3330)$$

- ▲--- dcMMD: Our proposal
- dpMMD: Procedure via differential privacy (Kim & Schrab)
- ...●... MMD: Standard non-robust MMD
- $r$  : Robustness parameter



# Summary

# Summary

- **DC procedure**: a general approach for constructing robust tests under data corruption
- Non-asymptotic **validity** and **consistency** under  $r$  data corruption
- Construct **dcMMD** and **dcHSIC** for two-sample and independence robust testing
- Prove that dcMMD/dcHSIC are **minimax rate optimal**
- Provide public **implementations** and illustrate the **practicality**

# Any Question?

Paper:



Code:

