

№13

UNIX.

UNIX.

1

getopts grep,

task1.sh

```
#!/bin/bash
ignore_case="" line_numbers=""
while getopts "i:o:p:cn" opt; do case $opt in i) input = "OPTARG" ;; o)
output="OPTARG";; p) pattern = "OPTARG" ;; c) ignore_case="-i" ;; n)
line_numbers="-n" ;; *) echo " "; exit 1 ;; esac done
grep $ignore_case $line_numbers "$pattern" "$input" > "output"
echo " " ###
./task1.sh -i text.txt -o result.txt -p hello -c -n ###
cat result.txt "text 1:Hello 2:hello 4:HELLO"
```

2

C,

task2.c

```
c #include <stdio.h> #include <stdlib.h>
int main() { int n;
printf(" : ");
scanf("%d", &n);
```

```

if (n > 0) {
    printf("          \n");
    exit(1);
}
else if (n < 0) {
    printf("          \n");
    exit(-1);
}
else {
    printf("  \n");
    exit(0);
}
}

```

```
bash gcc task2.c -o task2
```

```
bash ./task2
```

```
text          : 4
```

```
bash echo $?
```

3

task3.sh

```

bash #!/bin/bash
N=$1
for ((i=1; i<=N; i++)) do touch "$i.tmp" done
echo "      $N      "
ls *.tmp
rm -f *.tmp
echo "      "

```

```
bash ./task3.sh 5
```

```
text      5      1.tmp 2.tmp 3.tmp 4.tmp 5.tmp
```

4

, .

task4.sh

```
bash #!/bin/bash
```

```
dir=$1
```

```
find "$dir" -type f -mtime -7 | tar -czf archive.tar.gz -T -
```

```
echo "      "
```

```
bash ./task4.sh .
```

```
bash ls
```

```
text archive.tar.gz
```

UNIX,

shell,

, grep, find, tar getopt.

1. getopt?

getopt

shell- .

2. `if [ $? = 0 ]` .

3. `if [ $? = 0 ]` .

4. `if [ $? = 0 ]` .

5. `if [ $? = 0 ]` .

6. `if test -f manf/i.$s?` .
