

CryMore – Solution > Experience

Author: EngineerShell

Introduction

Well, I'm a beginner in reverse engineering, but I have a good foundation in cybersecurity. At first, I tried using Windows in a VM, since I have a robust toolkit. I knew the file would be difficult to execute because it wasn't an .exe; I tried some improvisations, but it didn't work, and I ended up using Parrot OS (VM).

Initially, using Windows, I opened the source code of crymore.c in Notepad++ to see the logic of CryMore and what it exactly did.

```
int main() {
    struct sockaddr_in revsockaddr;

    int sock = socket(AF_INET, SOCK_STREAM, 0);
    revsockaddr.sin_family = AF_INET;
    revsockaddr.sin_port = htons(44333);
    revsockaddr.sin_addr.s_addr = inet_addr("127.0.0.1");

    if(connect(sock, (struct sockaddr *)&revsockaddr, sizeof(revsockaddr)) == -1) {
        printf("Malware executed. you are screwed. Have a nice day.\n");
        return 0;
    }

    char request[] = "GET /neutralize HTTP/1.1\r\nHost: 127.0.0.1\r\nUser-Agent:crackme.one\r\n\r\n";
    size_t bytesSent = send(sock, request, strlen(request), 0);

    char response[4096];
    size_t bytesRead;

    if(recv(sock, response, sizeof(response), 0) < 0) {
        printf("Error receiving response.\n");
        return 0;
    }

    char* found = strstr(response, "200 OK");
    if(found == NULL) {
        printf("Malware executed. You are screwed. Have a nice day.\n");
    } else {
        printf("Malware successfully neutralized. Good job.\n");
    }

    close(sock);

    return 0;
}
```

Identifying the port, local HTTP, and what the malware showed based on certain actions, I had the idea to create a kill switch in Python. I have experience with kill switches, as I've created several kill switches before in PowerShell and shell scripts.

```
from http.server import BaseHTTPRequestHandler, HTTPServer

class KillSwitchHandler(BaseHTTPRequestHandler):
    def do_GET(self):
        if self.path == '/neutralize':
            self.send_response(200)
            self.send_header('Content-type', 'text/html')
            self.end_headers()
            self.wfile.write(b"OK")
            print("[+] KillSwitch: Malware neutralized")
        else:
            self.send_response(404)
            self.end_headers()

    def log_message(self, format, *args):
        print(f"[*] Request Recivied: {args[0]}")

PORT = 44333
server = HTTPServer(('127.0.0.1', PORT), KillSwitchHandler)
print(f"[*] KillSwitch server running 127.0.0.1:{PORT}")
print("[*] Waiting malware connection...")
server.serve_forever()
```

Solution

```
#python3 killswitch.py  
[*] KillSwitch server running 127.0.0.1:44333  
[*] Waiting malware connection...
```

```
#!/crymore  
Malware successfully neutralized. Good job.  
[root@parrot-80f6]~/Documents/crymore#  
#python3 killswitch.py  
[*] KillSwitch server running 127.0.0.1:44333  
[*] Waiting malware connection...  
[*] Request Recivied: GET /neutralize HTTP/1.1  
[+] KillSwitch: Malware neutralized
```