

Document Loading


Note to students.

During periods of high load you may find the notebook unresponsive. It may appear to execute a cell, update the completion number in brackets [#] at the left of the cell but you may find the cell has not executed. This is particularly obvious on print statements when there is no output. If this happens, restart the kernel using the command under the Kernel tab.

Retrieval augmented generation

In retrieval augmented generation (RAG), an LLM retrieves contextual documents from an external dataset as part of its execution.

This is useful if we want to ask question about specific documents (e.g., our PDFs, a set of videos, etc).



```
In [1]: #! pip install langchain
```

```
In [2]: import os
import openai
import sys
sys.path.append('../..')

from dotenv import load_dotenv, find_dotenv
_ = load_dotenv(find_dotenv()) # read local .env file

openai.api_key = os.environ['OPENAI_API_KEY']
```

PDFs

Let's load a PDF [transcript \(https://see.stanford.edu/materials/aimlcs229/transcripts/MachineLearning-Lecture01.pdf\)](https://see.stanford.edu/materials/aimlcs229/transcripts/MachineLearning-Lecture01.pdf) from Andrew Ng's famous CS229 course! These documents are the result of automated transcription so words and sentences are sometimes split unexpectedly.

```
In [3]: # The course will show the pip installs you would need to install packages c
# These packages are already installed on this platform and should not be ru
#! pip install pypdf
```

```
In [4]: from langchain.document_loaders import PyPDFLoader
loader = PyPDFLoader("docs/cs229_lectures/MachineLearning-Lecture01.pdf")
pages = loader.load()
```

Each page is a Document .

A Document contains text (page_content) and metadata .

```
In [5]: len(pages)
```

22

```
In [6]: page = pages[0]
```

```
In [7]: print(page.page_content[0:500])
```

MachineLearning-Lecture01

Instructor (Andrew Ng): Okay. Good morning. Welcome to CS229, the machine learning class. So what I wanna do today is ju st spend a little time going o ver the logistics of the class, and then we'll start to talk a bit about machine learning. By way of introduction, my name's Andrew Ng and I'll be instru ctor for this class. And so I personally work in machine learning, and I' ve worked on it for about 15 ye ars now, and I actually think that machine learning i

```
In [8]: page.metadata
```

```
{'source': 'docs/cs229_lectures/MachineLearning-Lecture01.pdf', 'page': 0}
```

YouTube

```
In [9]: from langchain.document_loaders.generic import GenericLoader
from langchain.document_loaders.parsers import OpenAIWhisperParser
from langchain.document_loaders.blob_loaders.youtube_audio import YoutubeAuc
```

```
In [10]: # ! pip install yt_dlp
# ! pip install pydub
```

Note: This can take several minutes to complete.

```
In [11]: url="https://www.youtube.com/watch?v=jGwO_UgTS7I"
save_dir="docs/youtube/"
loader = GenericLoader(
    YoutubeAudioLoader([url],save_dir),
    OpenAIWhisperParser()
)
docs = loader.load()

--> 226 resp, got_stream = self._interpret_response(result, stream)
227 return resp, got_stream, self.api_key

File /usr/local/lib/python3.9/site-packages/openai/api_requestor.py:619, i
n APIRequestor._interpret_response(self, result, stream)
611 return (
612     self._interpret_response_line(
613         line, result.status_code, result.headers, stream=True
614     )
615     for line in parse_stream(result.iter_lines())
616 ), True
617 else:
618 return (
--> 619     self._interpret_response_line(
620         result.content.decode("utf-8"),
621         result.status_code,
622         result.headers,
623         stream=False,
624     ),
---
```

```
In [ ]: docs[0].page_content[0:500]
```

URLs

```
In [ ]: from langchain.document_loaders import WebBaseLoader

loader = WebBaseLoader("https://github.com/basecamp/handbook/blob/master/37s

In [ ]: docs = loader.load()


In [ ]: print(docs[0].page_content[:500])
```

Notion

Follow steps [here](#)

(https://python.langchain.com/docs/modules/data_connection/document_loaders/integrations/notion) for an example Notion site such as [this one](https://yolospace.notion.site/Blendle-s-Employee-Handbook-e31bff7da17346ee99f531087d8b133f) (<https://yolospace.notion.site/Blendle-s-Employee-Handbook-e31bff7da17346ee99f531087d8b133f>):

- Duplicate the page into your own Notion space and export as Markdown / CSV .
- Unzip it and save it as a folder that contains the markdown file for the Notion page.



```
In [12]: from langchain.document_loaders import NotionDirectoryLoader
loader = NotionDirectoryLoader("docs/Notion_DB")
docs = loader.load()
```

```
In [13]: print(docs[0].page_content[0:200])
```

```
# Blendle's Employee Handbook
```

This is a living document with everything we've learned working with people while running a startup. And, of course, we continue to learn. Therefore it's a document that

```
In [14]: docs[0].metadata
```

```
{'source': "docs/Notion_DB/Blendle's Employee Handbook e367aa77e225482c849111687e114a56.md"}
```

```
In [ ]:
```