EEC289Q: Modeling and Optimization for Computer Engineers

Homework 1

Name: Tzi Hwee Chew **Student ID:** 927429340

a) Dataset

The MNIST dataset of handwritten digits is in a 28x28 pixel grid of 0~255 values. Each image has a corresponding label of the digit (0~9). The dataset has been presplit into training and testing sets, and we load the dataset using the MNIST Data Loader class from [https://www.kaggle.com/code/hojjatk/read-mnist-dataset]

For this experiment, we filter the MNIST dataset to include only images labeled 0, 5, and 8. The remaining digits are excluded from both training and testing.

b) Preprocessing

We apply normalization to the pixels to scale the values to the range [0,1] by dividing each pixel value by 255.

$$x_{\text{normalized}} = \frac{x}{255}$$

Given that we are trying to interpret 0, 5 and 8 using 3 values, we need to pick such features that will be unique enough to be seperatable by our perceptron. We picked the following:

- Average Intensity of the center 3x3 pixels

$$f_2 = \frac{1}{9} \sum_{r=13}^{16} \sum_{c=13}^{16} I_{r,c}$$

- Average Intensity of the image


$$f_1 = \frac{1}{784} \sum_{r=0}^{27} \sum_{c=0}^{27} I_{r,c}$$

- Average of the row of the pixels


$$f_3 = \frac{1}{28} \sum_{c=0}^{27} I_{14,c}$$

For our labels, depending on the digit, we assign a binary label, where 1 indicates the correct digit (0/5/8) and -1 indicates the incorrect digit, which is the digits that are not being classified.


Plotting the features with each axis representing a feature and the color as the label, we can see the features are NOT linearly seperable, but still have some seperation between the classes.



Average Intensity vs Mid Row Mass



Center Intensity vs Average Intensity



Center Intensity vs Mid Row Mass

We process the images of the dataset by extracting the features and creating a new dataset, each sample of which is a 3-dimensional vector of the features.

c) Labels for each digit classifier

From the MNIST Training set, we will split it into 5 equal subsets for cross-validation. We will keep out the test set for final evaluation of our model.

For each digit classifier model, we first create a new label set where the samples of the digit being classified are labeled as 1, and all other samples are labeled as -1.

$$y_i = \begin{cases} +1, & \text{if digit } i \text{ is the target digit} \\ -1, & \text{otherwise} \end{cases}$$

We then train our perceptron model using the training set with 5-fold cross-validation, which involves using 4 of the subsets for training and 1 subset for validation, and repeating this process 5 times, each time using a different subset for validation.

d) Training and Validation

We will be using the Sign() activation function in our perceptron.

For each epoch of 1000 epochs: Our model with weights and biases of

$$X = \begin{bmatrix} f_1 \\ f_2 \\ f_3 \\ 1 \end{bmatrix}, \qquad W = \begin{bmatrix} w_1 \\ w_2 \\ w_3 \\ b \end{bmatrix}$$

will be trained using the following update rule: We predict the output using

$$y_pred = \text{sign}(W^T X_i)$$

Using the predicted output, we will update our weights as follows

$$W \leftarrow \begin{cases} W + y_i X_i, & y_pred_i \neq y_i \\ W, & y_pred_i = y_i \end{cases}$$

We then define our error function as the number of misclassified samples in our training and validation set, and we save the error for each epoch.

$$E = \sum_{i=1}^{N} \mathbb{1}(\hat{y}_i \neq y_i)$$

The original validation dataset is then used as our test set to evaluate the performance of our model in terms of "accuracy", which is defined as


$$\text{Accuracy} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}(\hat{y}_i = y_i)$$

Using our test set, we can find the following accuracies for each digit classifier:


Digit	Accuracy
0	92.25%
5	70.34%
8	82.04%

And our cross-validation error is defined as the average of the error of each fold:


$$\overline{E}(t) = \frac{1}{5}\sum_{k=1}^{5} E_k(t)$$



Average Loss for digit-0 classifier



Average Loss for digit-5 classifier



Average Loss for digit-8 classifier

The code for the perceptron model can be found in the `main.py` file.

e) Linear Regression

For our Linear Regression model, we create a new set of labels with the classifying digit as 1 and the others as 0. We use the same 5-fold cross-validation method. But we removed the Sign() activation function.

$$y_i = \begin{cases} 1, & \text{if the sample belongs to the target digit} \\ 0, & \text{otherwise} \end{cases}$$

For each epoch of 1000 epocs: We predict the outputs using

$$y_pred = W^T X_i$$

We use MSE as our loss function, which is defined as

$$\text{MSE} = \frac{1}{N} \sum_{i=1}^{N} (y_pred_i - y_i)^2$$


And we update our weights with the following

$$\nabla_W \text{MSE} = \frac{2}{N} \sum_{i=1}^{N} (y_{\text{pred},i} - y_i) X_i$$


$$W \leftarrow W - \nabla_W \text{MSE}$$

Since this is a linear regression model, we use a threshold of 0.5 to classify the outputs as 1 or 0, which is rounding up the numbers. Using our test set, we can find the following accuracies for each digit classifier:


Digit	Accuracy
0	92.66%
5	71.97%
8	83.85%



Average Loss for digit-0 classifier



Average Loss for digit-5 classifier




Average Loss for digit-8 classifier

The code for the linear regression model can be found in the `regression.py` file.

f) Learnings

Choosing Features

Before deciding on the final 3 features, I experimented with other features such as Horizontal Symmetry and Vertical Symmetry, but due to the nature of the digits, namely 0 and 8 being symmetrical on both axes, they were not seperable. Yieling a accuracy of 68.85. Effectively being random as the model was unable to learn the difference between the digits.



Trying to seperate digit 0 from 5 and 8

I find it very hard to find features that are unique enough to be seperatable by a perceptron without using a more complex algorithm, such as counting the number of holes and coutour detection, which would defeat the purpose of the perceptron and is prone to errors.

Perceptron vs Linear Regression

Our training shows a slight improvement for accuracy when using Linear Perceptron Models with +1% accuracy across the board, with classfier 8 having the largest improvement. A possible explanation is the objectives of the two models, as we can see in the error plots, the perceptron does not converge and only updates when it misclassifies a sample, while

the linear regression model updates its weights every epoch, which allows it to converge to a better solution.

However, we can see as Perceptron and Linear Regression losses barely change after 100 epochs, which indicates that the model has converged to a solution and is not learning anymore. This is likely due to the features we have chosen, which are not unique enough to be seperatable by a linear model.