

[← Back to dashboard](#)

API DOCUMENTATION

Face Liveness

Confirm a live person is present during identity capture: create a liveness session, then fetch the verification result.

[API documentation](#) [Credentials](#) [Usage](#)**POST** Create Session**GET** [Get Verification Result](#)

 This spec's base URL is blank until you generate a credential — open the Credentials tab to get yours.

Postman Collection for the Face Liveness REST API. Contains the Create Session and Get Verification Result endpoints with automatic session token propagation.

[{} Variables](#)

Get Verification Result

[Documentation](#) [Test](#)**GET** `{{baseUrl}}/v1/liveness/result/{{sessionToken}}`

Protected backend-to-backend endpoint to retrieve the final verification result (status, confidence score, and pre-signed selfie url) for a session using the verification token.

Recommended Security Threshold:

- **Verification Status:** Must be exactly "SUCCEEDED".
- **Confidence Score Threshold:** Must be **95.0 or higher** (out of 100.0).

- **Spoof Handling:** If the score is below 95.0 , your application should reject the session as high-risk and request a retry.

HEADERS

Key	Value
x-api-key	{{apiKey}}

EXAMPLE REQUEST

cURL 

```
curl --request GET \
  --url '{{baseUrl}}/v1/liveness/result/{{sessionToken}}' \
  --header 'x-api-key: {{apiKey}}'
```

EXAMPLE RESPONSES

200 Get Verification Result Exa... 

Response body · 200 OK 

```
{
  "status": "SUCCEEDED",
  "confidence_score": 98.71,
  "reference_image_url": "https://face-liveness-audit-staging-tokyo.s3.ap-northeast-1.amazonaws.com/liveness-audits/00000000-0000-0000-0000-000000000000/reference.jpg?AWSAccessKeyId=..."
}
```

► Response headers (1)