

[← Back to dashboard](#)

API DOCUMENTATION



Verify citizen identity against PhilSys in real time, with consent built into every check.

[API documentation](#) [Integration](#) [Credentials](#) [Usage](#)**POST** [Authenticate \(Generate Access Token\)](#)**POST** [Verify Personal Information](#)**POST** [QR Check](#)**POST** [QR Verify](#)

This spec's base URL is blank until you generate a credential — open the Credentials tab to get yours.

NIDAS eVerify Authentication Services (National ID) REST API for Relying Parties — Tier 1 and Tier 2 identity authentication.

[{} Variables](#)

Flow: (1) obtain an `access_token` from the Authentication endpoint, (2) secure a `face_liveness_session_id` via the Face Liveness Web SDK, (3) submit demographics + `face_liveness_session_id` to the Verify endpoint.

Authenticate (Generate Access Token)

[Documentation](#) [Test](#)**POST** `{{base_url}}/api/auth`

Generates a server-to-server `access_token` for the NIDAS eVerify API. Every call to the verification endpoints requires this token.

Request Body

Field	Type	Required	Description
client_id	string	Yes	Your assigned API Client ID.
client_secret	string	Yes	Your assigned API Client Secret.

Responses

Status	Description
200 OK	Access token successfully generated.
403 Forbidden	Invalid client credentials.

Notes

- Use the returned `access_token` as a Bearer token in the `Authorization` header of the verify endpoints.
- Store `client_secret` securely and never expose it on the client side.

BODY · RAW

Request body

```
{
  "client_id": "{{client_id}}",
  "client_secret": "{{client_secret}}"
}
```

EXAMPLE REQUEST

cURL

```
curl --request POST \
  --url '{{base_url}}/api/auth' \
  --header 'Content-Type: application/json' \
  --data '{
    "client_id": "{{client_id}}",
    "client_secret": "{{client_secret}}"
  }'
```

EXAMPLE RESPONSES

200 200 - Success

403 403 - Forbidden

Response body · 200 OK



```
{
  "data": {
    "access_token": "eyJ0eXAiOiJKV1Qi...",
    "token_type": "Bearer",
    "expires_at": "1724223772"
  }
}
```

► Response headers (1)