

[← Back to dashboard](#)

API DOCUMENTATION



Verify citizen identity against PhilSys in real time, with consent built into every check.

[API documentation](#) [Integration](#) [Credentials](#) [Usage](#)**eGOV**APIS**POST** QR Check**POST** QR Verify

This spec's base URL is blank until you generate a credential — open the Credentials tab to get yours.

NIDAS eVerify Authentication Services (National ID) REST API for Relying Parties — Tier 1 and Tier 2 identity authentication.

[{} Variables](#)

Flow: (1) obtain an `access_token` from the Authentication endpoint, (2) secure a `face_liveness_session_id` via the Face Liveness Web SDK, (3) submit demographics + `face_liveness_session_id` to the Verify endpoint.

QR Check

[Documentation](#) [Test](#)**POST** `{{base_url}}/api/query/qr/check`

Checks and decodes the scanned National ID QR code value. Decrypts and returns the verified demographics stored inside the QR code.

Headers

Header	Value
Authorization	Bearer <access_token>

Request Body

Field	Type	Required	Description
value	string	Yes	Raw string value scanned from the National ID QR code.

Responses

Status	Description
200 OK	Valid QR code. Returns decrypted profile data.
422 Unprocessable Content	Invalid QR code format.

AUTHORIZATION

 **Bearer token** Authorization: Bearer `{{access_token}}`

BODY · RAW

Request body 

```
{
  "value": "RAW_QR_CODE_VALUE"
}
```

EXAMPLE REQUEST

cURL 

```
curl --request POST \
  --url '{{base_url}}/api/query/qr/check' \
  --header 'Authorization: Bearer {{access_token}}' \
  --header 'Content-Type: application/json' \
  --data '{
    "value": "RAW_QR_CODE_VALUE"
  }'
```

EXAMPLE RESPONSES

is (Digital ID) **200** 200 - Success (National ID ... **200** 200 - Success (ePhilld) **200** 200 - Suc 





Response body · 200 OK

```
{
  "data": {
    "pcn": "1234-1234-1234-1234"
  },
  "meta": {
    "qr_type": "Philsys Card Number"
  }
}
```

► Response headers (1)