



Collect and reconcile government fees and charges through one gateway, with real-time settlement across accredited payment channels.

API documentation Credentials Usage

Q Search requests...

POST Generate Payment

GET [Check Transaction Details](#)

PUT Void Transaction

This spec's base URL is blank until you generate a credential — open the Credentials tab to get yours.

Variables

Check Transaction Details

Documentation Test

GET `{{base_url}}/api/v1/transaction/{{transaction_uuid}}`

Returns the details of a transaction by its `uuid`.

Headers

Header	Value	Required
X-eGovPay-Token	test_<TOKEN_KEY>	Yes

Path Parameters

Parameter	Type	Required	Description
uuid	uuid	Yes	The transaction UUID returned when the payment was generated.

HEADERS

Key	Value	Description
X-eGovPay-Token	{{api_token}}	Merchant API token. Prefix a test-mode token with test_.
Content-Type	application/json; charset=utf-8	

EXAMPLE REQUEST

cURL 

```
curl --request GET \
  --url '{{base_url}}/api/v1/transaction/{{transaction_uuid}}' \
  --header 'X-eGovPay-Token: {{api_token}}' \
  --header 'Content-Type: application/json; charset=utf-8'
```

EXAMPLE RESPONSES

- 200 200 - Success
- 404 404 - Not Found
- 401 401 - Unauthorized

Response body · 200 OK 

```
{
  "data": {
    "uuid": "a23977c3-f2f2-4e5c-bf53-94bcff48e49c",
    "refno": "0I0KUXQ5XX",
    "txnid": "TESTREF123",
    "environment_type": "TEST",
    "items": [
      {
        "name": "Item # 1",
        "amount": "1000"
      }
    ],
    "amount": "1000.0000",
    "system_fee": "0.0000",
    "channel_fee": "0.0000",
  }
}
```

```
"partner_fee": "0.0000",  
"currency": "PHP",  
"payment_status": "INITIAL",
```



► Response headers (18)