



Collect and reconcile government fees and charges through one gateway, with real-time settlement across accredited payment channels.

API documentation Credentials Usage

Q Search requests...

POST [Generate Payment](#)

GET [Check Transaction Details](#)

PUT [Void Transaction](#)

This spec's base URL is blank until you generate a credential — open the Credentials tab to get yours.

Variables

Generate Payment

Documentation Test

POST `{{base_url}}/api/v1/transaction`

Creates a payment transaction and returns a hosted payment-gateway link the customer can use to pay.

Headers

Header	Value	Required	Description
X-eGovPay-Token	test_<TOKEN_KEY>	Yes	Merchant API token. A <code>test_</code> -prefixed token runs in test mode and does not touch the live financial networks.
Content-Type	application/json; charset=utf-8	Yes	Request body is JSON.

Body Parameters

Field	Type	Required	Description
items	array	Yes	List of line items being paid for.
items[].name	string	Yes	Name of the item.
items[].amount	double	Yes	Amount of the item.
amount	double	Yes	Total transaction amount.
settlement_template_uuid	uuid	Yes	The settlement template used for bank settlements (see Templates).
redirect_url	url	Yes	URL to redirect the customer to once payment has been processed.
txnid	string	Yes	The transaction ID generated by the biller/merchant.
callback_url	url	Yes	URL notified for every transaction status change.
digest	string	Yes	HMAC-SHA256 of the transaction, keyed by the API token: <code>hash_hmac('sha256', "\$amount \$txnid", \$token)</code> .
currency	string	No	Currency code, e.g. <code>PHP</code> .
mobile	string	No	Customer mobile number (used for the e-receipt).
email	string	No	Customer email.
name	string	No	Customer name.
expires_at	datetime	No	Transaction expiry, <code>YYYY-MM-DD HH:MM:SS</code> .
link_expires_at	datetime	No	Payment-link expiry, <code>YYYY-MM-DD HH:MM:SS</code> .
description	object	No	Additional transaction information.

Notes

- The `digest` binds `amount` and `txnid` to your token; recompute it for every request.
- Use a `test_`-prefixed token while integrating so no live funds move.

HEADERS

Key	Value	Description
X-eGovPay-Token	<code>{{api_token}}</code>	Merchant API token. Prefix a test-mode token with <code>test_</code> .

Key	Value	Description
Content-Type	application/json; charset=utf-8	

BODY · RAW

Request body

```
{
  "amount": 1000,
  "settlement_template_uuid": "{{template_id}}",
  "currency": "PHP",
  "digest": "c5989a520055e65025a695bb1483b30b6cd7923c79c648fff5e757bbabc62fa2",
  "mobile": "09XXXXXXXXX",
  "expires_at": "2027-07-10 23:59:59",
  "callback_url": "https://your-app.com/callback",
  "redirect_url": "https://your-app.com/",
  "txnid": "TESTREF123",
  "link_expires_at": "2027-07-10 23:59:59",
  "email": "your@email.com",
  "name": "TEST",
  "items": [
    {
      "name": "Item # 1",
      "amount": 1000
    }
  ]
}
```

EXAMPLE REQUEST

cURL

```
curl --request POST \
  --url '{{base_url}}/api/v1/transaction' \
  --header 'X-eGovPay-Token: {{api_token}}' \
  --header 'Content-Type: application/json; charset=utf-8' \
  --data '{
    "amount": 1000,
    "settlement_template_uuid": "{{template_id}}",
    "currency": "PHP",
    "digest": "c5989a520055e65025a695bb1483b30b6cd7923c79c648fff5e757bbabc62fa2",
    "mobile": "09XXXXXXXXX",
    "expires_at": "2027-07-10 23:59:59",
    "callback_url": "https://your-app.com/callback",
    "redirect_url": "https://your-app.com/",
    "txnid": "TESTREF123",
    "link_expires_at": "2027-07-10 23:59:59",
    "email": "your@email.com",
  }'
```

```
"name": "TEST",
"items": [
  f
```

EXAMPLE RESPONSES

- 201 201 - Created
- 401 401 - Unauthorized
- 422 422 - Unprocessable Entity

Response body · 201 Created

```
{
  "data": {
    "uuid": "a23977c3-f2f2-4e5c-bf53-94bcff48e49c",
    "url": "https://egovpay-pgi-dev.oueg.info/a23977c3-f2f2-4e5c-bf53-94bcff48e49c",
    "channel": {
      "refno": "0I0KUXQ5XX"
    }
  }
}
```

► Response headers (16)