



Collect and reconcile government fees and charges through one gateway, with real-time settlement across accredited payment channels.

API documentation Credentials Usage

Q Search requests...

POST Generate Payment

GET Check Transaction Details

PUT Void Transaction

This spec's base URL is blank until you generate a credential — open the Credentials tab to get yours.

Variables

Void Transaction

Documentation Test

PUT `{{base_url}}/api/v1/transaction/{{transaction_uuid}}/void`

Voids a transaction by its `uuid`.

Headers

Header	Value	Required
X-eGovPay-Token	test_<TOKEN_KEY>	Yes

Path Parameters

Parameter	Type	Required	Description
uuid	uuid	Yes	The transaction UUID to void.

HEADERS

Key	Value	Description
X-eGovPay-Token	{{api_token}}	Merchant API token. Prefix a test-mode token with test_.
Content-Type	application/json; charset=utf-8	

EXAMPLE REQUEST

cURL 

```
curl --request PUT \
  --url '{{base_url}}/api/v1/transaction/{{transaction_uuid}}/void' \
  --header 'X-eGovPay-Token: {{api_token}}' \
  --header 'Content-Type: application/json; charset=utf-8'
```

EXAMPLE RESPONSES

ccess 400 400 - Bad Request 400 400 - Bad Request 401 401 - Unauthorized 404 4 



Response body · 200 OK 

```
{
  "data": {
    "message": "You have successfully voided this transaction."
  }
}
```

► Response headers (18)