

[← Back to dashboard](#)

API DOCUMENTATION



Let citizens file and track complaints and reports: submit a complaint, verify by OTP, then list and view report status by case number.



Q Search requests...

▼ Datasets

- GET Report Type List
- GET Region List
- GET Province List by Params
- GET Municipality List by Params
- GET Barangay List by Params
- POST **Generate Token**
- POST Submit Complaint
- POST Verify - Request OTP
- POST Verify - Confirm OTP
- GET Reports List
- GET View Report by Case Number

Variables

Generate Token

Documentation

Test

POST `{{base}}/api/integration/token`

Generate Token

Generates an integration access token used to authenticate subsequent API requests.

Request

Method: POST

URL: `{{base}}/api/integration/token`

Body (raw JSON)

```
{
  "access_code": "{{access_code}}"
}
```

Parameter	Type	Required	Description
access_code	string	Yes	A pre-issued access code that identifies and authorizes the integration. Set the <code>access_code</code> variable in your active environment before sending this request.

Response

On success, the API returns an `access_token` that must be included in subsequent authenticated requests.

```
{
  "access_token": "<token>"
}
```

Automation

The included test script automatically captures the `access_token` from the response and saves it to the `integration_token` environment variable, so it is immediately available for use in downstream requests without any manual steps.

Examples

- **Generate Token - Success** — Successful token generation with a valid `access_code` .
- **Generate Token - Error** — Error response when the `access_code` is invalid or missing.

BODY · RAW

Request body

```
{
  "access_code": "{{access_code}}"
}
```

EXAMPLE REQUEST

cURL



```
curl --request POST \
  --url '{{base}}/api/integration/token' \
  --header 'Content-Type: application/json' \
  --data '{
    "access_code": "{{access_code}}"
  }'
```

EXAMPLE RESPONSES

200 Generate Token - Success

401 Generate Token - Error



Response body · 200 OK



```
{
  "access_token": "00000000-0000-0000-0000-000000000000",
  "expires_at": "2026-07-19T23:08:06.672+08:00"
}
```

► Response headers (5)