

[← Back to dashboard](#)

API DOCUMENTATION



Let citizens file and track complaints and reports: submit a complaint, verify by OTP, then list and view report status by case number.



Q Search requests...

▼ Datasets

- GET Report Type List
- GET Region List
- GET **Province List by Params**
- GET Municipality List by Params
- GET Barangay List by Params
- POST Generate Token
- POST Submit Complaint
- POST Verify - Request OTP
- POST Verify - Confirm OTP
- GET Reports List
- GET View Report by Case Number

Variables

Province List by Params

Documentation

Test

GET {{base}}/api/integration/datasets/provinces?region_code=040000000

Province List by Params

Retrieves a list of provinces filtered by a specified region code. This endpoint is useful for populating province dropdowns or validating province data scoped to a particular region.

Query Parameters

Parameter	Type	Required	Description
region_code	string	Required	The region code used to filter the list of provinces. Example: 040000000

Authentication

This endpoint requires authentication via the {{integration_token}} variable, which should be set in your active environment. Ensure the token is valid and has the appropriate permissions before making a request.

Examples

The following saved examples are available for reference:

- **Province List by Params - Success** — Demonstrates a successful response containing the list of provinces for the given region code.
- **Province List by Params - Error** — Demonstrates an error response, such as when an invalid or missing region code is provided.

AUTHORIZATION

 **Bearer token** Authorization: Bearer {{integration_token}}

QUERY PARAMETERS

Key	Value
region_code	040000000

EXAMPLE REQUEST

cURL



curl --request GET \
 --url '{{base}}/api/integration/datasets/provinces?region_code=040000000' \
 --header 'Authorization: Bearer {{integration_token}}'

EXAMPLE RESPONSES

200 Province List by Params - S...**401** Province List by Params - E... Response body · 200 OK 

```
{
  "jsonapi": {
    "version": "1.0"
  },
  "data": [
    {
      "type": "provinces",
      "id": "041000000",
      "attributes": {
        "region_code": "040000000",
        "name": "BATANGAS",
        "district": null
      }
    },
    {
      "type": "provinces",
      "id": "042100000",
      "attributes": {
        "region_code": "040000000",
```

► Response headers (5)