


Software Design and Construction 1 SOFT2201 / COMP9201

OO Theory in Java

Dr. Xi Wu

School of Computer Science



Copyright warning

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Overview

- Types
- Encapsulation
- Inheritance
- Variable Binding & Polymorphism
- Virtual Dispatch
- Abstract Classes
- Interfaces

Types in Java

- Overview
 - Java is a strongly typed language
 - Primitive types: built-in types of the virtual machines
 - Cannot be changed by programs
 - Have same meaning across computer platforms
 - Compositional types
 - Interfaces
 - Classes

Primitive Types in Java

- Primitive types represent basic data-types
- In-built and cannot be changed in programs
- Integral types
 - `byte`, `short`, `int`, `long`
- Floating point number types
 - `float`, `double`
- Character type
 - `char`
- Boolean
 - `boolean`

Integral and Floating Types

Type	Internal	Smallest Value	Largest Value
byte	8 bits	-128	+127
short	16 bits	-32,768	+32,767
int	32 bits	-2,147,483,648	+2,147,483,647
long	64 bits	-2.3E+18	+2.3E+18
float	32 bits	-/+1.4e-45	-/+3.4e+38
double	64 bits	-/+4.9e-324	-/+1.7e+308d

Conversion between Primitive Types

- Implicit widening of integral & floating point number types
 - byte to short, int, long, float, or double
 - short to int, long, float, or double
 - char to int, long, float, or double
 - int to long, float, or double
 - long to float or double
 - float to double
- Everything else requires type casts or is not possible

Casting/Widening Matrix

From/To	byte	char	short	int	long	float	double	boolean
byte								n/a
char	(byte)		(short)					n/a
short	(byte)	(char)						n/a
int	(byte)	(char)	(short)					n/a
long	(byte)	(char)	(short)	(int)				n/a
float	(byte)	(char)	(short)	(int)	(long)			n/a
double	(byte)	(char)	(short)	(int)	(long)	(float)		n/a
boolean	n/a	n/a	n/a	n/a	n/a	n/a	n/a	

Example for Implicit Widening and Casting

```
...  
byte x = 10;  
  
/* implicit widening */  
short y = x;  
long z = x;  
float f = x;  
  
/* casting */  
byte p = (byte) z;  
short q = (short) f;
```

Silent Failure of Types

- Example:

```
...  
int i = Integer.MAX_VALUE;  
System.out.println(i);  
i = i + 1;  
System.out.println(i);  
...
```

- Integer overflow occurs for variable **i**
- Type system cannot prevent this at compile-time
 - weak notion of correctness

Primitive Types


- Basic data-types
 - Behave the same on all platforms running Java's virtual machine
- Primitive Types are not classes nor interfaces
- Primitive Types are building blocks for more complex types
- Beside the storing the actual value there are very little additional overheads
 - Note that classes have extra information to keep of dynamic runtime info
- Operations on primitive data-types are very efficient

Classes in Java

- Classes are types
 - Composite type consisting of fields(=state) and methods(=behavior)
- Class Abstraction
 - Separate class implementation from the use of a class
 - User of a class does not need to know the implementation / just the public methods
 - The implementor provides the implementation of the class
 - The details are encapsulated and hidden from the user
- Class creates objects (instantiate)
- Object communicates with each other via methods

Classes

- A basic class has a name, fields, and methods:



Classes (cont'd)

- The basic syntax for a class is

```
class <class name> [ extends <super class> ]  
{  
    <field declarations>  
    <method declarations>  
}
```

- Example:

```
class Rectangle  
{  
    <field declarations>  
    <method declarations>  
}
```

Adding Fields: Class Rectangle with Fields

- Add *fields*

```
public class Rectangle {  
    public double width, height;  
}
```

- The fields (data) are also called the *instance* variables
- Fields can be
 - Primitive types (int, bool, etc.)
 - References to other class instances

Adding Methods


- To change / retrieve state of a class, methods are necessary
- Methods are declared inside the body
 - Methods are messages in an object-oriented programming sense
 - A return type must be specified
 - A list of arguments with their types must be specified
- The general form of a method declaration is:

```
type Method (argument-list) {  
    Method-body;  
}
```


Adding Methods to Rectangle

```
public class Rectangle {  
    public double width, height; // fields  
  
    public void setWidth(double w) {  
        width = w;  
    }  
    public void setHeight(double h) {  
        height = h;  
    }  
    public double area() {  
        return width * height;  
    }  
}
```

Method Body



Mutators

- Methods that change the state of a class object are called mutators
- Example:

```
public void setWidth(double w) {  
    width = w;  
}  
public void setHeight(double h) {  
    height = h;  
}
```

- Gives clients of the class write access to the state

Accessor

- Methods that read the state of a class object are called accessor
- Example:

```
public double area() {  
    return width * height;  
}
```

- Gives clients of the class read access to the state

Constructors

- Special method in class whose task is to initialize fields of the class
- The name is the same name as class
- Constructors are invoked whenever an object of that class is created
- It is called constructor because it constructs values of data members.
- A constructor cannot return a value
- There can be several constructors for a class
 - Default constructor with no parameters
 - Parameterized constructors

Example: Default Constructor

- Default constructor

```
public class Rectangle {  
    public double width, height;  
    public Rectangle() { // default constructor  
        width = 1.0;  
        height = 1.0;  
    }  
}
```

- Java has a synthesized default constructor when not specified

Example: Parameterized Constructor

- Parameterized constructor:

```
public class Rectangle {  
    public double width, height;  
  
    // parameterized constructor  
    public Rectangle(double w, double h) {  
        width = w;  
        height = h;  
    }  
}
```

Example: Multiple Constructors

- Default and parameterized constructor (overloading)

```
public class Rectangle {  
    public double width, height;  
    // default constructor  
    public Rectangle() {  
        width = 1.0;  
        height = 1.0;  
    }  
    // parameterized constructor  
    public Rectangle(double w, double h) {  
        width = w;  
        height = h;  
    }  
}
```

Creating Instances of a Class

- Objects are created dynamically using the **new** keyword.
- The new operator creates a new object on the heap
 - The object will be selected as a candidate if not further used
 - The object becomes a candidate for automatic **garbage collection**
 - Garbage collection kicks in periodically and releases candidates
 - developers don't need to delete their own objects

- Example:

```
<Class> X = new <Class> (<args>);
```

- Define a reference variable X of type class that points to a new instance

Example: Creating Instances of a Class

- rec1 and rec2 refer to Rectangle objects

```
rec1 = new Rectangle();  rec2 = new Rectangle(10,1);
```



- First instance calls default constructor
- Second instance calls parameterized constructor

Copy Constructor

- Java has no copy constructor
- We can simulate copy constructor by having a constructor with objects of same type as argument
- All classes are derived from class Object
- Object has the method clone()

Example: Copy Constructor

- Copy constructor

```
public class Rectangle {  
    public double width, height;  
    // copy constructor  
    public Rectangle(Rectangle o) {  
        width = o.width;  
        height = o.height;  
    }  
}
```

Accessing Fields and Methods

- Access is done via the . operator
- Access to field and methods of an instance in the same style

```
<object> . <field>  
<object> . method(<args>)
```

- Access modifier is important
 - public/protected/private
 - Controls whether access is permitted at client or member level

Example: Accessing fields / methods

- Using object methods:

```
Rectangle rec = new Rectangle();  
  
rec.width = 1.0;  
rec.height = 100.0;  
double area = rec.area();
```

send 'message' area to an instance of type Rectangle which rec is referring to

Access Modifiers

- Access modifiers provide encapsulation for object-oriented programming
- Protect state from client
- Access modifiers work on different levels:
 - Class level
 - Member level
 - Client level

Access Modifier: public

- A class that is labeled as public is accessible to all other classes inside and outside a package

```
package com.foo.goo;

public class test1 {
    public void test();
}
```

```
package com.foo.hoo;
import com.foo.goo;

public class test2 {
    public void test(){
        test1 x = new test1();
    }
}
```

Access Modifier: public

- A class marked as public is accessible to all classes with the import statement
- There is no need for import statement if a public class is used in the same package

Access Modifier: default

- Default access is a class definition with no specified access qualifier
- Classes marked with default access are visible only in package but not outside of package
- Note that protected and private classes are not available for packages

Member access modifiers for methods and fields

- Public
 - Accessible for client, class, and sub-classes
- Protected
 - Accessible for class, and sub-classes
- Private
 - Accessible for class itself only

Example: Member access modifiers

- Example: public

```
public class Rectangle {  
    public double width, height;  
}
```

```
// client can access state  
Rectangle x = new Rectangle();  
x.width = 100;  
x.height = 100;
```

Example: Member access modifiers

- Example: protected

```
public class Rectangle {  
    protected double width, height;  
}
```

```
// client cannot access state  
Rectangle x = new Rectangle();  
x.width = 100; // access error!  
x.height = 100; // access error!
```

Example: Member access modifiers

– Example: private

```
public class Rectangle {
    private double width, height;
    Rectangle(double w, double h) {
        width = w; // access is ok
        height = h; // access is ok
    }
}

public class Square extends Rectangle {
    Square(double w) {
        super.Rectangle(w,w);
    }
    void setWidth(double w) {
        super.width = w; // access error!
        super.height = w; // access error!
    }
}
```

Encapsulation

- Wrap data/state and methods into a class as a single unit
- Multiple instances can be generated
- Protect state via setter (mutator)/getter (accessor) methods

```
class Rectangle {  
    double length; double width;  
    double getLength() { return length; }  
    double getWidth() { return width; }  
    double area() { return length * width; }  
}
```

Sub-Classes

- Classes permit inheritance
 - Methods and fields from a super-class can be inherited
- Ideal for software-engineering
 - Reuse of code
- Java uses “extends” keyword for extending from existing class
- Single-inheritance paradigm
 - Class hierarchy can be a tree most
- If no super-class is specified, default class Object becomes super-class

Inheritance

- Sub-class inherits from super-class: methods, variables, ...
- Reuse structure and behavior from super-class
- Single inheritance for classes

```
class Rectangle extends Object {  
    double length; double width;  
    double area() { return length * width; }  
}  
  
class ColouredRectangle extends Rectangle {  
    int colour;  
    int colour() { return colour; }  
}
```


Variable Binding, Polymorphism

- Object (on heap) has single type when created
 - Type cannot change throughout its lifetime
- Reference variables point to null or an object
- Type of object and type of reference variable may differ
 - e.g., `Shape x = new Rectangle(4,2);`
- Understand the difference
 - Runtime type vs compile-time type
- Polymorphism:
 - Reference variable may reference differently typed object
 - Must be a sub-type of

Virtual Dispatch

- Methods in Java permit a late binding
- Reference variable and its type does not tell which method is really invoked
- The type of reference variable and class instance may differ
- Class variables may override methods of super classes
- The method invoked is determined by the type of the class instance
- Binding is of great importance to understand OO

Example: Virtual Dispatch

– Example:

```
public class Shape{ // extends Object
    double area() { }
}

public class Rectangle extends Shape {
    double area() { }
}

...
Shape X = new Shape();
Shape Y = new Rectangle();

double a1 = X.area() // invokes area of Shape
double a2 = Y.area() // invokes area of Rectangle
```

Abstract Classes

- Method implementations are deferred to sub-classes
- Requires own key-word abstract for class/method
- No instance of an abstract class can be generated

```
abstract class Shape extends Object {  
    public abstract double area();  
}  
  
public class Rectangle extends Shape {  
    double width; double length;  
    double area() { return width * length; }  
}
```

Interfaces

- Java has no multi-inheritance
 - Interface is a way-out (introduction of multi-inheritance via the back-door)
- Interfaces is a class contract that ensures that a class implements a set of methods.
- Interfaces can inherit from other interfaces
- Ensures that a class has a certain set of behavior
- Interfaces are specified so that they form a directed acyclic graph
- Methods declared in an interface are always public and abstract
- Variables are permitted if they are static and final only

Example: Interface

```
// definition of interface
public interface A {
    int foo(int x);
}

// class X implements interface A
class X implements A {
    int foo(int x) {
        return x;
    }
}
```

Example: Interface

- Inheritance in interfaces

```
// definition of interface
public interface A {
    int foo(int x);
}

public interface B extends A{
    int hoo(int x);
}
```

- Interface B has methods foo() and hoo()

What are we going to learn next week?

- UML Modeling and Case Studies
 - Use Case Diagrams
 - Class Diagrams
 - Interaction Diagrams