

14 march

- ① We can not assign a string using assignment operator(=)  
for assigning a string we must use `strcpy`
- ② We can not assign a string using assignment operator(=)  
for assigning a string we must use `"strcpy"`
- ③ We can not assign a string using assignment operator(=)  
for assigning a string we must use `"strcpy"`
- ④ We can not assign a string using assignment operator(=) for assigning a string we must use `"strcpy"`
- ⑤ We can not assign a string using assignment operator(=) for assigning a string we must use `"strcpy"`
- ⑥ We can not assign a string using assignment operator(=) for assigning a string we must use `(strcpy)`
- ⑦ We can not assign a string using assignment operator(=) for assigning a string we must use `(strcpy)`

⑧ We can not assign a string using assignment operator (=) for assigning string, we must use "strcpy"

⑨ We can not assign a string using assignment operator (=) for assigning string, we must use "strcpy"

⑩ We can not assign a string using assignment operator (=) for assigning string we must use "strcpy"



① Malloc receives no. of bytes as input it ~~allow~~ allocates those many number of byte on heap sequentially & returns string/base address in a void pointer

Void \* malloc (int);

② malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & returns string/base address in a void pointer.

Void \* malloc (int);

③ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & returns string/base address in a void pointer

Void \* malloc (int);

④ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & returns string/base address in a void pointer.

Void \* malloc (int);

⑤ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & returns string/base address in a void pointer

Void \* malloc (int);

⑥ malloc receives no. of bytes as input it allocates those many number of bytes on heap sequentially & returns string/base address in a void pointer.

Void \* malloc (int);

⑦ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & return starting / base address in a void pointers

`Void* malloc(int);`

⑧ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & return starting / base address in a void pointers.

`Void* malloc(int);`

⑨ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & return starting / base address in a void pointers

`Void* malloc(int);`

⑩ malloc receives no. of bytes as input it allocates those many number of byte on heap sequentially & return starting / base address in a void pointers.

`Void* malloc(int);`