Imaad Hajwane
Department of Computer Engineering and Technology
School of Computer Science and Engineering
Dr. Vishwanath Karad MIT World Peace University
Pune 411038, Maharashtra, India
E-mail: iamimaad2kk3@gmail.com

10 October 2026

The Editor-in-Chief
Sādhanā – Academy Proceedings in Engineering Sciences
Indian Academy of Sciences
Bengaluru, India

Subject: Submission of an original research article for consideration in *Sādhanā*

Manuscript title	Neural architecture search via trie-based deduplication and zero-cost proxies, with hardware-aware coverage: An empirical study of LLM-guided warm-start
Authors	Imaad Hajwane (corresponding author) and Jayshree Ghorpade-Aher
Article type	Original research article
Subject area	Computer science and engineering – machine learning
Length	20 pages in the journal's LaTeX template; 17 figures, 8 tables, 1 algorithm, 1 appendix
Supplementary material	26 pages: 42 tables and 16 figures

Dear Editor,

We are pleased to submit the manuscript named above for consideration as an original research article in *Sādhanā*. It addresses a practical engineering problem in automated machine learning. Neural architecture search (NAS) spends almost all of its compute on training candidate networks, and part of that compute goes to architectures that were already trained or were unlikely to be good.

We study a search loop, ArchTree-RMG, that removes both kinds of waste. A prefix trie ensures that no architecture is trained twice, and a label-free zero-cost gate sends only the most promising 35% of proposals to real training. The study covers 12,289 seed-paired searches on four public benchmarks (NAS-Bench-201, NAS-Bench-101, NATS-Bench SSS and HW-NAS-Bench). Every method is compared at the same GPU-hour budget rather than the same number of evaluations, which is the fair comparison when methods train networks of different cost.

The main findings are:

1. The gate removes 59–60% of real evaluations and 53% of GPU-hours on NAS-Bench-201 with no significant loss of accuracy. At equal GPU-hours it raises the mean accuracy of all four search methods it was added to.
2. At equal GPU-hours, ArchTree-RMG has no Holm-significant loss in 261 comparisons against 13 alternatives on three benchmarks. It lies within the Nemenyi critical difference of the best method on each benchmark.
3. Zero-cost proxies track training cost in cell-based search spaces but not in a width-based space. A closed-form criterion, $r_{PA}r_{PD} - r_{DA}$, estimated from a labelled sample, tells in advance whether penalising cost in the gate can help.
4. An LLM prior speeds up the start of a search on CIFAR-10/100, and controls speak against simple recall of benchmark tables, but it does not change final accuracy.

We believe the paper suits the engineering readership of *Sādhanā*. It offers a low-cost method that can be added to existing search algorithms, an evaluation protocol for a fixed compute budget, and a criterion that can be checked before a search is run. We report negative results as clearly as positive ones, including the cases where simpler methods are as good or better.

The supplementary material lists every per-cell result and statistical test, the detailed search loop, the seeds, the reproducibility checks and the data checksums. All benchmarks are public. The code, configurations, seeds and result files are available at github.com/Imaadhajwane/Arch-Tree-LLM.

On behalf of both authors, I confirm that:

- the manuscript is original, has not been published before and is not under consideration by any other journal;
- both authors have read and approved the submitted version and agree to its submission;
- the authors declare no competing interests, and no external funding was received;
- the work involves no human participants or animals, so ethics approval is not applicable;
- the use of AI-assisted tools is disclosed in the Declarations section, in line with the journal's policy.

A list of suggested reviewers is provided with the submission. We would be grateful for your consideration of the manuscript and look forward to hearing from you.

Yours sincerely,

Imaad Hajwane
Corresponding author
M.Tech (Data Science and Algorithms)
Dept. of Computer Engineering and Technology
School of Computer Science and Engineering
Dr. Vishwanath Karad MIT World Peace University
Pune 411038, India
iamimaad2kk3@gmail.com

Dr. Jayshree Ghorpade-Aher
Co-author and research supervisor
Dept. of Computer Engineering and Technology
School of Computer Science and Engineering
Dr. Vishwanath Karad MIT World Peace University
Pune 411038, India
jayshree.aher@mitwpu.edu.in