



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Keras input and dense layers

Zach Deane-Mayer
Data Scientist



Course outline

- Chapter 1: Introduction to the Keras functional API (Refresher)
- Chapter 2: Models with 2 inputs
- Chapter 3: Models with 3 inputs
- Chapter 4: Multiple outputs



Course Datasets: College basketball data, 1989-2017

Dataset 1: Regular season

- Team ID 1
- Team ID 2
- Home vs Away
- Score Difference (Team 1 - Team 2)
- Team 1 Score
- Team 2 Score
- Won vs Lost

Dataset 2: Tournament games

- Same as Dataset 1
- Also has difference in Seed



Course Datasets: College basketball data, 1989-2017



Inputs and outputs

Two fundamental parts:

- Input layer
- Output layer





Inputs

```
from keras.layers import Input
input_tensor = Input(shape=(1,))
```



Inputs


```
from keras.layers import Input
input_tensor = Input(shape=(1,))
print(input_tensor)

<tf.Tensor 'input_1:0' shape=(?, 1) dtype=float32>
```



Outputs

```
from keras.layers import Dense  
output_layer = Dense(1)
```






Outputs

```
from keras.layers import Dense
output_layer = Dense(1)
print(output_layer)

<keras.layers.core.Dense at 0x7f22e0295a58>
```



Connecting inputs to outputs


```
from keras.layers import Input, Dense
input_tensor = Input(shape=(1,))
output_layer = Dense(1)
output_tensor = output_layer(input_tensor)
```



Connecting inputs to outputs

```
print(output_tensor)
```

```
<tf.Tensor 'dense_1/BiasAdd:0' shape=(?, 1) dtype=float32>
```





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON


Keras models

Zach Deane-Mayer
Data Scientist



Keras models


```
from keras.layers import Input, Dense
input_tensor = Input(shape=(1,))
output_tensor = Dense(1)(input_tensor)
```





Keras models


```
from keras.models import Model  
model = Model(input_tensor, output_tensor)
```





Compile a model

```
model.compile(optimizer='adam', loss='mae')
```



Summarize the model

```
model.summary()
```


Layer (type)	Output Shape	Param #
input_1 (InputLayer)	(None, 1)	0
dense_1 (Dense)	(None, 1)	2

Total params: 2
Trainable params: 2
Non-trainable params: 0

Plot model using keras

```
input_tensor = Input(shape=(1,))
output_layer = Dense(1, name='Predicted-Score-Diff')
output_tensor = output_layer(input_tensor)
model = Model(input_tensor, output_tensor)
plot_model(model, to_file='model.png')

from matplotlib import pyplot as plt
img = plt.imread('model.png')
plt.imshow(img)
plt.show()
```





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Fit and evaluate a model

Zach Deane-Mayer
Data Scientist



Basketball Data

Goal: Predict tournament outcomes

Data Available: team ratings from the tournament organizers

```
import pandas as pd
games_tourney = pd.read_csv('datasets/games_tourney.csv')
games_tourney.head()
```

Out[1]:

	season	team_1	team_2	home	seed_diff	score_diff	score_1	score_2	won
0	1985	288	73	0	-3	-9	41	50	0
1	1985	5929	73	0	4	6	61	55	1
2	1985	9884	73	0	5	-4	59	63	0
3	1985	73	288	0	3	9	50	41	1
4	1985	3920	410	0	1	-9	54	63	0

Basketball Data

Input: Seed difference

```
import pandas as pd
games_tourney = pd.read_csv('datasets/games_tourney.csv')
games_tourney.head()
```

Out[1]:

	season	team_1	team_2	home	seed_diff	score_diff	score_1	score_2	won
0	1985	288	73	0	-3	-9	41	50	0
1	1985	5929	73	0	4	6	61	55	1
2	1985	9884	73	0	5	-4	59	63	0
3	1985	73	288	0	3	9	50	41	1
4	1985	3920	410	0	1	-9	54	63	0

Basketball Data

Output: Score difference

```
import pandas as pd
games_tourney = pd.read_csv('datasets/games_tourney.csv')
games_tourney.head()
```

Out[1]:

	season	team_1	team_2	home	seed_diff	score_diff	score_1	score_2	won
0	1985	288	73	0	-3	-9	41	50	0
1	1985	5929	73	0	4	6	61	55	1
2	1985	9884	73	0	5	-4	59	63	0
3	1985	73	288	0	3	9	50	41	1
4	1985	3920	410	0	1	-9	54	63	0



Basketball Data

Input:

- Seed difference - one number: -15 to +15
- Seed range from 1-16
- Highest difference is $16-1 = +15$
- Lowest difference is $1-16 = -15$


Output:

- Score difference - one number: -50 to +50



Basketball Data


- Seed difference: 15
 - Team 1: 16
 - Team 2: 1
- Seed difference: -15
 - Team 1: 1
 - Team 2: 16





Basketball Data

- Score difference: -9
 - Team 1: 41
 - Team 2: 50
- Score difference: 6
 - Team 1: 61
 - Team 2: 55





Basketball Data

```
import pandas as pd
games_tourney = pd.read_csv('datasets/games_tourney_samp.csv')
games_tourney.head()
```


Out[1]:

	season	team_1	team_2	home	seed_diff	score_diff	score_1	score_2	won
0	2017	320	6323	0	13	18	100	82	1
1	2017	6323	320	0	-13	-18	82	100	0



Build the model

```
from keras.models import Model
from keras.layers import Input, Dense
input_tensor = Input(shape=(1,))
output_tensor = Dense(1)(input_tensor)
model = Model(input_tensor, output_tensor)
model.compile(optimizer='adam', loss='mae')
```



Fit the model

```
from pandas import read_csv
games = read_csv('datasets/games_tourney.csv')
model.fit(games['seed_diff'],
          games['score_diff'],
          batch_size=64,
          validation_split=.20,
          verbose=True)
```





Evaluate the model

```
model.evaluate(games_test['seed_diff'],
               games_test['score_diff'])

1000/1000 [=====] - 0s 26us/step
Out[1]: 9.742335235595704
```



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!




ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Category embeddings

Zach Deane Mayer
Data Scientist

Category embeddings


- Input: integers
- Output: floats
- Note: Increased dimensionality: output layer flattens back to 2D






Inputs

```
input_tensor = Input(shape=(1,))
```



Embedding Layer


```
from keras.layers import Embedding
input_tensor = Input(shape=(1,))
n_teams = 10887
embed_layer = Embedding(input_dim=n_teams,
                        input_length=1,
                        output_dim=1,
                        name='Team-Strength-Lookup')
embed_tensor = embed_layer(input_tensor)
```






Flattening

```
from keras.layers import Flatten  
flatten_tensor = Flatten()(embed_tensor)
```



Put it all together

```
input_tensor = Input(shape=(1,))
n_teams = 10887
embed_layer = Embedding(input_dim=n_teams,
                        input_length=1,
                        output_dim=1,
                        name='Team-Strength-Lookup')
embed_tensor = embed_layer(input_tensor)
flatten_tensor = Flatten()(embed_tensor)
model = Model(input_tensor, flatten_tensor)
```





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!




ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Shared layers

Zach Deane Mayer
Data Scientist


Shared layers

- Require the functional API
- Very flexible



Shared layers


```
input_tensor_1 = Input((1,))
input_tensor_2 = Input((1,))
```





Shared layers

```
shared_layer = Dense(1)
output_tensor_1 = shared_layer(input_tensor_1)
output_tensor_2 = shared_layer(input_tensor_2)
```



Sharing multiple layers as a model


```
input_tensor = Input(shape=(1,))
n_teams = 10887
embed_layer = Embedding(input_dim=n_teams,
                        input_length=1,
                        output_dim=1,
                        name='Team-Strength-Lookup')

embed_tensor = embed_layer(input_tensor)
flatten_tensor = Flatten()(embed_tensor)
model = Model(input_tensor, flatten_tensor)
```

```
input_tensor_1 = Input((1,))
input_tensor_2 = Input((1,))
output_tensor_1 = model(input_tensor_1)
output_tensor_2 = model(input_tensor_2)
```



Sharing multiple layers as a model





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Merge layers

Zach Deane Mayer
Data Scientist




Merge layers

- Add
- Subtract
- Multiply
- Concatenate


Merge layers

```
from keras.layers import Input, Add
in_tensor_1 = Input((1,))
in_tensor_2 = Input((1,))
out_tensor = Add()([in_tensor_1, in_tensor_2])
```



Merge layers


```
in_tensor_3 = Input((1,))  
out_tensor = Add()([in_tensor_1, in_tensor_2, in_tensor_3])
```






Create the model

```
from keras.models import Model
model = Model([in_tensor_1, in_tensor_2], out_tensor)
```



Compile the model

```
model.compile(optimizer='adam', loss='mean_absolute_error')
```





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!




ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Fitting and Predicting with multiple inputs

Zach Deane Mayer
Data Scientist

Fit with multiple inputs

```
model.fit([data_1, data_2], target)
```





Predict with multiple inputs

```
model.predict([np.array([[1]]), np.array([[2]])])  
array([[3.]], dtype=float32)
```

```
model.predict([np.array([[42]]), np.array([[119]])])  
array([[161.]], dtype=float32)
```




Evaluate with multiple inputs

```
model.evaluate([np.array([[-1]]), np.array([[-2]])], np.ar
```

```
1/1 [=====] - 0s 801us/step
```

```
Out[21]: 0.0
```





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!




ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Three-input models

Zach Deane Mayer
Data Scientist


Simple model with 3 inputs

```
from keras.layers import Input, Concatenate, Dense
in_tensor_1 = Input(shape=(1,))
in_tensor_2 = Input(shape=(1,))
in_tensor_3 = Input(shape=(1,))
out_tensor = Concatenate()([in_tensor_1, in_tensor_2, in_tensor_3])
output_tensor = Dense(1)(out_tensor)
```



Simple model with 3 inputs

```
from keras.models import Model
model = Model([in_tensor_1, in_tensor_2, in_tensor_3], out_tensor)
```






Shared layers with 3 inputs

```
shared_layer = Dense(1)
shared_tensor_1 = shared_layer(in_tensor_1)
shared_tensor_2 = shared_layer(in_tensor_1)
out_tensor = Concatenate()([shared_tensor_1, shared_tensor_2, in_tensor_3])
out_tensor = Dense(1)(out_tensor)
```

Shared layers with 3 inputs

```
from keras.models import Model
model = Model([in_tensor_1, in_tensor_2, in_tensor_3], out_tensor)
```



Fitting a 3 input model

```
from keras.models import Model
model = Model([in_tensor_1, in_tensor_2, in_tensor_3], out_tensor)
model.compile(loss='mae', optimizer='adam')
```

```
model.fit([[train['col1'], train['col2'], train['col3']],
          train_data['target']])
```

```
model.evaluate([[test['col1'], test['col2'], test['col3']],
                test['target']])
```



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Summarizing and plotting models

Zach Deane Mayer
Data Scientist

Understanding a model summary


Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 1)	0	
input_2 (InputLayer)	(None, 1)	0	
input_3 (InputLayer)	(None, 1)	0	
concatenate_1 (Concatenate)	(None, 3)	0	input_1[0][0] input_2[0][0] input_3[0][0]
dense_1 (Dense)	(None, 1)	4	concatenate_1[0]

Total params: 4
Trainable params: 4
Non-trainable params: 0

Understanding a model summary


Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 1)	0	
embedding_1 (Embedding)	(None, 1, 1)	10887	input_1[0][0]
flatten_1 (Flatten)	(None, 1)	0	embedding_1[0][0]
input_2 (InputLayer)	(None, 1)	0	
input_3 (InputLayer)	(None, 1)	0	
concatenate_1 (Concatenate)	(None, 3)	0	flatten_1[0][0] input_2[0][0] input_3[0][0]
dense_1 (Dense)	(None, 1)	4	concatenate_1[0]

=====
Total params: 10,891
Trainable params: 10,891
Non-trainable params: 0
=====





Understanding a model plot!





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's Practice



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Stacking models

Zach Deane Mayer
Data Scientist

Stacking models requires 2 datasets

```
from pandas import read_csv
games_season = read_csv('datasets/games_season.csv')
games_season.head()
```

	team_1	team_2	home	score_diff
0	3745	6664	0	17
1	126	7493	1	7
2	288	3593	1	7
3	1846	9881	1	16
4	2675	10298	1	12

```
games_tourney = read_csv('datasets/games_tourney.csv')
games_tourney.head()
```


	team_1	team_2	home	seed_diff	score_diff
0	288	73	0	-3	-9
1	5929	73	0	4	6
2	9884	73	0	5	-4
3	73	288	0	3	9
4	3920	410	0	1	-9

Enrich the tournament data

```
in_data_1 = games_tourney['team_1']
in_data_2 = games_tourney['team_2']
in_data_3 = games_tourney['home']
pred = regular_season_model.predict([in_data_1, in_data_2, in_data_3])
```

```
games_tourney['pred'] = pred
games_tourney.head()
```

	team_1	team_2	home	seed_diff	pred	score_diff
0	288	73	0	-3	0.582556	-9
1	5929	73	0	4	0.707279	6
2	9884	73	0	5	1.364844	-4
3	73	288	0	3	0.699145	9
4	3920	410	0	1	0.833066	-9




3 input model with pure numeric data

```
games_tourney[['home', 'seed_diff', 'pred']].head()
```

	home	seed_diff	pred
0	0	-3	0.582556
1	0	4	0.707279
2	0	5	1.364844
3	0	3	0.699145
4	0	1	0.833066



3 input model with pure numeric data



3 input model with pure numeric data

```
from keras.layers import Input, Dense
in_tensor = Input(shape=(3,))
out_tensor = Dense(1)(in_tensor)
```

```
from keras.models import Model
model = Model(in_tensor, out_tensor)
model.compile(optimizer='adam', loss='mae')
train_X = train_data[['home', 'seed_diff', 'pred']]
train_y = train_data['score_diff']
model.fit(train_X, train_y, epochs=10, validation_split=.10)
```

```
test_X = test_data[['home', 'seed_diff', 'pred']]
test_y = test_data['score_diff']
model.evaluate(test_X, test_y)
1066/1066 [=====] - 0s 14us/step
9.11321775461451
```



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Two-output models

Zach Deane-Mayer
Data Scientist




Simple model with 2 outputs

```
from keras.layers import Input, Concatenate, Dense
input_tensor = Input(shape=(1,))
output_tensor = Dense(2)(input_tensor)
```



Simple model with 2 outputs

```
from keras.models import Model
model = Model(input_tensor, output_tensor)
model.compile(optimizer='adam', loss='mean_absolute_error')
```





Fitting a model with 2 outputs

```
games_tourney_train[['seed_diff', 'score_1', 'score_2']].head()
```

	seed_diff	score_1	score_2
0	-3	41	50
1	4	61	55
2	5	59	63
3	3	50	41
4	1	54	63

```
X = games_tourney_train[['seed_diff']]  
y = games_tourney_train[['score_1', 'score_2']]  
model.fit(X, y, epochs=500)
```



Inspecting a 2 output model

```
model.get_weights()
```

```
[array([[ 0.60714734, -0.5988793 ]], dtype=float32),  
 array([70.39491, 70.39306], dtype=float32)]
```



Evaluating a model with 2 outputs

```
X = games_tourney_test[['seed_diff']]  
y = games_tourney_test[['score_1', 'score_2']]  
model.evaluate(X, y)
```

```
11.528035634635021
```



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Let's practice!




ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Single model for classification and regression

Zach Deane-Mayer
Data Scientist


Build a simple regressor/classifier

```
from keras.layers import Input, Dense
input_tensor = Input(shape=(1,))
output_tensor_reg = Dense(1)(input_tensor)
output_tensor_class = Dense(1, activation='sigmoid')(output_tensor_reg)
```




Make a regressor/classifier model

```
from keras.models import Model
model = Model(input_tensor, [output_tensor_reg, output_tensor_class])
model.compile(loss=['mean_absolute_error', 'binary_crossentropy'],
              optimizer='adam')
```



Fit the combination classifier/regressor


```
X = games_tourney_train[['seed_diff']]
y_reg = games_tourney_train[['score_diff']]
y_class = games_tourney_train[['won']]
model.fit(X, [y_reg, y_class], epochs=100)
```



Look at the model's weights

```
model.get_weights()

[array([[1.2371823]], dtype=float32),
 array([-0.05451894], dtype=float32),
 array([[0.13870609]], dtype=float32),
 array([0.00734114], dtype=float32)]
```





Look at the model's weights

```
model.get_weights()
```

```
[array([[1.2371823]], dtype=float32),  
 array([-0.05451894], dtype=float32),  
 array([[0.13870609]], dtype=float32),  
 array([0.00734114], dtype=float32)]
```

```
from scipy.special import expit as sigmoid  
print(sigmoid(1 * 0.13870609 + 0.00734114))
```

```
0.5364470465211318
```

Evaluate the model on new data

```
X = games_tourney_test[['seed_diff']]  
y_reg = games_tourney_test[['score_diff']]  
y_class = games_tourney_test[['won']]  
model.evaluate(X, [y_reg, y_class])
```

```
[9.866300069455413, 9.281179495657208, 0.585120575627864]
```



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Now you try!



ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Wrap-up

Zach Deane-Mayer
Data Scientist



So far...

- Functional API
- Shared layers
- Categorical embeddings
- Multiple inputs
- Multiple outputs
- Regression / Classification in one model


Shared layers

Useful for making comparisons

- Basketball teams
- Image similarity / retrieval
- Document similarity


Known in the academic literature as Siamese networks

- [Link to blog post](#)
- [Link to academic paper](#)






Multiple inputs






Multiple outputs



Skip connections

```
input_tensor = Input((100,))
hidden_tensor = Dense(256, activation='relu')(input_tensor)
hidden_tensor = Dense(256, activation='relu')(hidden_tensor)
hidden_tensor = Dense(256, activation='relu')(hidden_tensor)
output_tensor = Concatenate()([input_tensor, hidden_tensor])
output_tensor = Dense(256, activation='relu')(output_tensor)
```

Visualizing the Loss Landscape of Neural Nets





ADVANCED DEEP LEARNING WITH KERAS IN PYTHON

Best of luck!