
Columbia University
Columbia University Libraries Requ

Request It CLIO



Authors: Smith, Daniel P.; Flint, Mark; Merriam, Jack

Source: Proceedings of the Water Environment Federation, WEFTEC 2004: Session 81 through Session 90, pp. 541-549(9)

Publisher: Water Environment Federation

Buy Article: \$17.50 plus tax (Refund Policy)

ADD TO CART

BUY NOW

Or sign up for a free trial

Free trial available!

Abstract:

Biologically active zeolite filters have the potential to retain and oxidize ammonia nitrogen in stormwater, thereby enhancing overall nitrogen removal when incorporated into a stormwater treatment train. Bench scale evaluation and process modeling were conducted to provide proof of concept for zeolite filters as an innovative Best Management Practice. Stormwater from a collection pond in Hillsborough County, Florida was spiked with 2 mg/L ammonia nitrogen and supplied to a laboratory zeolite-packed filter operated at 0.9 hour detention time for 57 days. The prototype consistently removed over 99% ammonia, producing effluent levels of less than 0.1 mg/L. Biological nitrification was evidenced by an increase in oxidized inorganic nitrogen (nitrite and nitrate) in column effluent. After three weeks of operation, effluent nitrate and nitrite concentrations declined, suggesting that denitrification was also occurring in the prototype column. Two perturbation experiments were conducted to simulate non-steady stormwater events. Minimal ammonia breakthrough was observed following a sudden increase in flowrate and sudden increase in influent ammonia concentration. The combined action of ion exchange and biochemical within the zeolite filter resulted in a consistent and resilient ammonia removal performance. Zeolite filtration appears to have promise in accelerating the ammonia transformation step in stormwater nitrogen treatment. Potential applications of zeolite filters include in-ground or above-ground filtration of urban and residential runoff, side bank filtration for stormwater detention ponds, roof runoff treatment devices, and filtration of parking lot and roadway runoff.

References: 3 references open in new window

Articles that cite this article?

Document Type: Research Article

DOI: https://doi.org/10.2175/193864704784136649

Publication date: January 1, 2004

More about this publication?

We recommend

Achieving Low Effluent Total Nitrogen Concentration

Stensel, H.D. et al., Proceedings of the Water Environment Federation, 2013

Operational Keys to Nitrite Lock

Muirhead, Woodie Mark et al., Proceedings of the Water Environment Federation, 2007

Recent measurements of heavy metal removals using stormwater filters Clark, Shirley E. et al., Proceedings of the Water Environment Federation, 2004

Water Quality Performance of a Batch-Type Stormwater Detention Basin Middleton, John R et al., Water Environment Research,

Engineered Bioretention for Removal of Nitrate from Stormwater Runoff

Simple soil mixture reverses toxic stormwater effects Washington State University, ScienceDaily, 2015

Researchers devise hidden dune filters to treat coastal stormwater runoff

North Carolina State University, ScienceDaily, 2013

Filter bed substrates, plant types recommended for rain gardens American Society for Horticultural Science, ScienceDaily, 2014

Water Pollution Can Be Reduced With New Storm Water Analysis System

Virginia Tech, ScienceDaily, 2007

Canna can: Ornamental eliminates pollutants from stormwater runoff

Kim, Hunho et al., Water Environment Research,

American Society for Horticultural Science, ScienceDaily, 2010

Powered by