

Infra

Imahn Shekhzadeh
`imahn.shekhzadeh@posteo.de`

February 26, 2024

Contents

1. Bash & Linux	5
1.1. File Download	5
1.2. for-loops	5
1.3. Argument Retrieval	5
1.4. Colored Outputs	6
1.5. String/File/Directory Operations	6
1.6. Monitoring	7
1.7. Systems Information	7
1.8. CUDA	7
2. Slurm	9
3. Docker	11
3.1. Installation	11
3.2. Basics	11
3.3. Dockerfile	11
3.4. Docker images	13
3.5. Docker containers	13
3.5.1. Basics	13
3.5.2. Passing Arguments	15
3.5.3. Listing & Stopping	15
3.6. Storage	16
4. AWS S3	17
4.1. Installation & Configuration	17
4.2. AWS Credentials (Profiles)	18
4.3. Buckets	18
4.3.1. Creation	18
4.3.2. Listings	18
4.3.3. File Copying	19
4.3.4. Directory Copying	19
4.3.5. Directory/File Deletion	19
4.4. Cloudpathlib	19
5. Conda	21
5.1. Installation of Environments	21
5.2. Export	21
5.3. Installation & Removal of Packages	22
5.4. Usage in VSCode	22
6. Git	23
6.1. Branch Creation	23
6.2. Merging	23

6.3. Merge Conflicts	24
6.4. Checking History	24
6.5. Removing a File/Folder	25
6.6. Restore File	25
6.7. Repo Renaming	25
6.8. Remote URL	25
6.9. Repo Change	25
6.10. Remote Repo Creation	26
6.11. Pull Requests	26
6.12. Updating Files from other Branch	26
7. Remote Development	27
7.1. Connection	27
7.2. Troubleshooting	27
8. Python	29
8.1. Config File & JSON Files	29
8.2. Jupyter Notebooks	29
8.3. Map (Built-In Function)	30
8.4. CPU Brand	30
8.5. Inheritance	31
9. PyTorch	33
9.1. Leaf Tensors	33
9.2. Autograd & Backward	34
9.3. Half-Precision	34
9.4. Miscellaneous	35
10. Jax	37
A. .bashrc	39
B. Amazing Programs, Extensions, Plugins & Packages	49
C. Opening Programs from the CLI in Linux	51
D. VSCode	53
D.1. Recommended Extensions	53
D.2. Debugging	53
D.3. settings.json	53
D.4. Fix Unresolved Python Imports	53
D.5. Opening a Duplicate Workspace	53
D.6. settings.json	54

Note

The commands in this document might only run through if you use the `.bashrc` file provided in App. A

1. Bash & Linux

In Bash, `[[]]` over `[]` is preferred, since `[[]]` is safer and more capable within Bash scripts. Within `[]`, where word splitting and filename expansion do occur, it is good practice to double-quote variables. But it is safe to omit the double-quotes for e.g. `##` within `[[]]`.

1.1. File Download

Downloading file from URL and allowing for redirects,

```
1 curl -Lo output.out https://url.com
```

When taking a GitHub link, note that you need to take the URL of the raw file.

1.2. for-loops

For this directory structure,

```
1 infra_upd.tex
2 infra_upd.pdf
```

rename via

```
1 for file in infra_upd.*; do mv "$file" "${file/infra_upd/infra}"; done
```

What happens is a [substring replacement](#).

1.3. Argument Retrieval

Retrieving all but the first argument,

```
1 bash_func(){
2     shift
3
4     echo "all provided args (except the first): $@"
5 }
```

Doing this $N \geq 1$ -times,

```
1 test_sth(){
2     shift
3     ...
4     shift
5
6     echo "all provided args (except the first N): $@"
7 }
```

1.4. Colored Outputs

Using colored outputs in Bash, cf. `str_diff` in App. A.

Personally, I use the following color scheme for the CLI,

1. monokai color scheme, i.e. dark gray background (#272822) with light peach color for the text (#F8F8F2).
2. File paths are still displayed in blue, which is suboptimal, to change the color to the better readable cyan-blue color, click on the three horizontal lines in the CLI, then on **Preferences**, then choose the currently active color, switch to the **Colors** tab, then go to **Palette**, click on the blue color & instead use the color #66D9EF

where `-e` stands for human readability and `-s` for summarizing.

1.5. String/File/Directory Operations

Appending line to file (`-a`: appending, otherwise `tee` overwrites `output.out` if existent),

```
1 echo "this is a line" | tee -a output.out # -a: appending, important
```

Checking whether string is empty,

```
1 [[ -z "$env_name" ]] && echo "The string is empty."
```

Finding out size of file/directory,

```
1 du -hs <path_to_file_or_dir> # du -hs file.ext
2
3 # for shorter summary (single quotation strings required)
4 du -hs <path_to_file_or_dir> | awk '{print $1}'
```

Unzipping a file via the CLI,

```
1 unzip /path/to/file.zip -d /path/to/destination
```

Zipping a directory via the CLI,

```
1 zip -r archive_name.zip -d /path/to/directory
```

and zipping several files,

```
1 zip archive_name.zip /path/to/file1 /path/to/file2 /path/to/file3
```

Opening a file and automatically scrolling to the bottom,

```
1 less +G /path/to/file.ext
```

Searching for files with specific extension, e.g. `.ext`:

```
1 find . -name "*.ext"
2 # find . -name "*.png"
```

Creating new directory including all parent directories (`-p` option is safe, since if directory is already existent, no error will be outputted),

```
1 mkdir -p <dir>
```

Comparing the contents of two directories,

```
1 diff -r --color directory1 directory2 # `-r` for recursive comparison
2 diff -rq --color directory1 directory2 # `-q` suppresses the output of
  differences and only shows which files differ
```

Ignoring files only existent in one of the directories (which treats absent files as empty),

```
1 diff -rq --color --unidirectional-new-file directory1 directory2
```

1.6. Monitoring

```
1 htop
```

RAM usage,

```
1 free -h
```

1.7. Systems Information

Retrieving the number of available CPU resources,

```
1 echo "$(nproc)"
```

Print day and time from CLI,

```
1 echo "$(date +%d_%m_%y-%H_%M_%S)"
2 # echo "$(date +%dp%mp%y-%Hp%Mp%S)"
```

Listing all available kernels in Debian-based Linux systems,

```
1 dpkg --get-architecture | grep linux-image
```

Currently active kernel version,

```
1 uname -a
```

1.8. CUDA

- When you need to find out the CUDA version installed, install `nvidia-cuda-toolkit`, but do NOT reboot. After its use, immediately remove this package and any package installed alongside with it!
- In case NVIDIA drivers do not allow for boot into Ubuntu, e.g. because you did not uninstall the `nvidia-cuda-toolkit` package,
 1. Boot into an older kernel version of Linux (in order to get there, do a "hard" reboot, and then go into "Advanced options for Ubuntu", and choose an older kernel version).
 2. Once booted into the older kernel version, I removed 'nvidia-cuda-toolkit' and rebooted.

1. *Bash & Linux*

3. After a few more hard reboots and booting into the older kernel version, at some point, the newer kernel version was picked up and worker again.
4. Now to fix the monitors (because dual-monitor setup didn't work), I had to open the program "Additional Drivers" and change the driver from the open-source version to an NVIDIA proprietary one.
5. Then I had to install CUDA according to these instructions.
6. For PyTorch to recognize the GPU, I had to reboot.

2. Slurm

```
1 salloc --partition=shared-cpu --time=12:00:00 --nodes=1
```


3. Docker

3.1. Installation

- Follow this great tutorial by DigitalOcean.
- To use NVIDIA GPUs (both in PyTorch & Jax), install the NVIDIA Container Toolkit
- Once done with the installation of the NVIDIA Container Toolkit, proceed with the configuration. During the configuration, it will be necessary to restart the docker daemon, which you can achieve as follows:

```
1 sudo systemctl restart docker
```

- Checking that the docker installation was successful,

```
1 docker run hello-world
```

3.2. Basics

- Interactive start of containers:

```
1 d ps -a # find out ID (also docker container name)
2 d start -i ID
```

- Copying files from local system to docker container and vice versa; **run both commands from local CLI**

```
1 d cp file_name container_ID:/target_dir # local -> docker
2 d cp container_ID:/file_name dir_name # docker -> local
```

3.3. Dockerfile

- When you find the command for pulling a docker image on <https://hub.docker.com>, e.g.

```
1 d pull ubuntu:jammy-20231004
```

then in the Dockerfile, just write

```
1 FROM ubuntu:jammy-20231004
```

3. Docker

When no tag is specified, by default the *latest* one will be taken. However, using the *latest* tag can potentially cause issues with reproducibility and consistency, because you might pull a different version of the image at different times without knowing it if the latest tag gets updated. **For more predictable builds, it is advised to use a specific version tag.**

- Note that the structure of the *docker pull* command is

```
1 d pull [OPTIONS] NAME[:TAG|@DIGEST]
```

In general, the *NAME* is in the format *repository/image*. If *repository* is not specified, Docker assumes the image is located in the default DockerHub library repository. However, many images (like PyTorch) are hosted under a specific user or organization's namespace on DockerHub, rather than the top-level library. That's why the command for the docker pull (for the latest tag) reads

```
1 d pull pytorch/pytorch
```

- If using a Docker image like *pytorch/pytorch:latest*, conda is already installed. In this case, the default environment is named *base*, which is a common practice in Docker images with conda – unless otherwise stated.
- Copying local scripts into docker container,

```
1 COPY relative/path/to/script.py .
```

From the documentation:

Multiple `<src>` resources may be specified but the paths of files and directories will be interpreted as relative to the source of the context of the build.

It is also important to put the `.` at the end, since it represents the destination in the Docker image where the file should be copied. The dot `.` refers to the current working directory inside the Docker image, which is determined by the `WORKDIR` command in the Dockerfile. If `WORKDIR` is not set, it defaults to the root directory (`/`) of the image.

Also, each time the script `relative/path/to/script.py` changes, the Dockerfile needs to be rebuilt — **however, a cached version will be used, which speeds things up.**

- Copying local dirs into docker container,

```
1 COPY relative/path/to/dir/ .
```

- Running a Dockerfile,

```
1 d build -f file_name -t img_name .
2 d build -f file_name -t img_name:tag_name . # tag name optional, but
      recommended, e.g. 1.0 (no quotes required)
3 # d build -f file_name --no-cache -t [...] # forcing to rebuild from
      scratch, no cached version is used (only do if really required)
```

where `img_name` will be the name of the newly created image, `tag_name` the tag name and `file_name` the name of the docker file.

The `.` specifies the context of the build, which is the current directory in this case. If `custom_docker_file` is in another path, it can be easily provided,

```
1 d build -f file_name -t img_name:tag_name /path/to/build/context
```

- Via

```
1 EXPOSE custom-port-number
2 # EXPOSE 80
```

it is possible to expose a port. Note that port exposure is related to network access. Note that even though network access might not be needed, there is still no harm in exposing a port (since an exposure of the port does not make the docker container more vulnerable).

3.4. Docker images

- Check all available Docker images via

```
1 d images
```

- Cleaning up dangling docker images — these are the entries with `<none>` in the repository or tag name in the output of the previous algo:

```
1 d image prune -f
```

- Removing a Docker image — **only do this when finished with using the image**

```
1 d image rm img_name:tag_name
2 # d container rm <container_id> # in case some containers are using
   the image
```

3.5. Docker containers

3.5.1. Basics

- In case of shared memory issues in the docker container, the shared memory — which is by default 64 MB — needs to be increased when the docker container is run,

```
1 d run --shm-size 512m [...] # requesting memory in MB
2 # d run --shm-size 1G [...] # requesting memory in GB
```

- Running Docker images – without being able to utilize NVIDIA GPUs:

```
1 d run -it img_name # if `tag_name` was not provided
2 d run -it img_name:tag_name # if `tag_name` was provided during
   build (recommended)
```

3. Docker

- Running Docker images & utilizing GPUs:

```
1 d run --gpus all -it img_name
2 d run --gpus all -it img_name:tag_name # recommended
```

- To mount a local file to the container at runtime, do

```
1 d run -v /absolute/path/to/script.py:/path/to/workdir/script.py --
   gpus all -it img_name
2 d run -v /absolute/path/to/script.py:/path/to/workdir/script.py --
   gpus all -it img_name:tag_name # recommended, provide `img_name`
   & `tag_name`
```

The mounting expects **absolute** file paths on the side of the host machine.

- Note that you can include the bash command **pwd** to avoid having to manually pass absolute paths for the mounting

```
1 d run -v $(pwd)/script.py:/path/to/workdir/script.py --gpus all -it
   img_name:tag_name # recommended, provide `img_name` & `tag_name`
```

If you need the container to reflect changes made to the scripts on the host without rebuilding the image every time, you would use the `-v` flag to mount the directory. If the scripts won't change, or you don't need to reflect changes in real-time, you don't need to mount the directory, as the necessary scripts have already been copied into the image during the build process.

- It is also possible to directly mount directories:

```
1 d run -v $(pwd)/dir_path:/path/to/workdir --gpus all -it img_name:
   tag_name
```

Note that the specified directory from the host is mounted into the container at the specified mount point. If there are any existing files or directories in the container at the mount point, they become obscured by the mount.

- In several cases it can be useful to remove the docker container right after execution: When you...
 - ...are running many short-lived containers, like during development or testing,
 - ...want to avoid manual cleanup of stopped containers later on,
 - ...are running containers for one-off tasks that do not need to persist any state after they are finished.

In this case,

```
1 d run --rm -v $(pwd)/dir_path:/path/to/workdir --gpus all -it
   img_name:tag_name
```

- It is also possible to mount two separate host directories to two separate directories within the container,

```
1 d run --rm -v $(pwd)/dir_path1:/path/to/workdir1 -v $(pwd)/dir_path2
   :/path/to/workdir2 --gpus all -it img_name:tag_name
```

This will not cause any overwriting as each `-v` flag creates a unique mount point inside the container.

- Finding out the python version of the Docker image

```
1 d run -it --rm img_name:tag_name python3 --version
```

This command will immediately remove the container after execution.

- It is also possible to interact with a docker container,

```
1 docker run -it --rm img_name:tag_name /bin/bash
```

3.5.2. Passing Arguments

It is possible to pass arguments when running a docker container.

1. Assuming you have a bash script `run_scripts.sh`, in which a Python script, e.g.

```
1  #!/bin/sh
2  isort /app/scripts/*.py
3  black /app/scripts/*.py
4
5  python3 -B /app/scripts/test_script.py
6  python3 -B /app/scripts/test_anil.py
```

Modify this bash script s.t. any arguments passed to the CLI when running the docker container are picked up,

```
1  python3 -B /app/scripts/test_anil.py "$@"
2  # python3 -B /app/scripts/test_script.py "$@" # alternative
```

2. Rebuild (!) the docker image.
3. Now run the docker container as follows:

```
1  d run --rm -v $(pwd)/dir_path:/path/to/workdir --gpus all -it
   img_name:tag_name arg1 arg2
2  # d run --rm -v $(pwd)/dir_path:/path/to/workdir --gpus all -it
   img_name:tag_name --n_ways 1 --k_shots 1 # example
```

3.5.3. Listing & Stopping

- Listing all running containers,

```
1 d ps
```

Listing only the container ID of all running containers,

```
1 d ps -q
```

- Stopping a running container,

3. Docker

```
1 d stop container-ID
```

- Stopping a running container and removing it,

```
1 d stop container-ID && d rm container-ID
```

3.6. Storage

- In case you want `docker` to install images and containers in a separate drive, e.g. one under `/media/user-name/samsung_500`, you can follow these steps:

1. Stop the docker service,

```
1 sudo systemctl stop docker
```

2. Move the directory `/var/lib/docker` to the separate drive,

```
1 sudo mv /var/lib/docker /media/user-name/samsung_500/docker
```

Note that you should *not* create the `docker` directory directly under `/media/user-name/samsung_500`.

3. Configure `docker` to use the new directory by editing the `docker` daemon configuration file,

```
1 sudo nano /etc/docker/daemon.json
```

and then adding the following configuration,

```
1 {  
2   "data-root": "/media/user-name/docker"  
3 }
```

4. Restart the `docker` service,

```
1 sudo systemctl restart docker
```

5. Follow the instructions from the NVIDIA Container Toolkit configuration to ensure that NVIDIA GPUs can still be used inside the containers.

4. AWS S3

4.1. Installation & Configuration

1. Installation instructions
2. The CLI will display the path under which the *aws* package was installed, but it might be sufficient to simply run

```
1  aws
```

Double check by running

```
1  which aws
```

3. After installation, configuration is necessary. For this run

```
1  aws configure
```

You can leave these fields empty:

```
1  Default region name [None]:  
2  Default output format [None]:
```

A configuration file will be saved under

```
1  ~/.aws/credentials
```

4. In the case you are a member of UNIGE, you can obtain the AWS access key ID and the secret access key as follows:

```
1  echo -n "$user_name" | base64 # the `-n` is important in this  
    context  
2  echo -n "$passwd" | md5sum
```

where `$user_name` and `$passwd` need to be provided

Otherwise, you need login to the AWS Management Console.

5. To test the configuration was successful, do this:

```
1  aws s3 ls --endpoint-url https://your-custom-s3-endpoint.com
```

where you replace the endpoint-url `https://your-custom-s3-endpoint.com` with yours.

4.2. AWS Credentials (Profiles)

- It is possible to use several profiles in the file `~/.aws/credentials`.
- For example,

```
1 [default]
2 aws_access_key_id = YOUR_DEFAULT_ACCESS_KEY
3 aws_secret_access_key = YOUR_DEFAULT_SECRET_KEY
4
5 [profile1]
6 aws_access_key_id = ANOTHER_ACCESS_KEY_ID
7 aws_secret_access_key = ANOTHER_SECRET_ACCESS_KEY
8
9 [profile2]
10 aws_access_key_id = YET_ANOTHER_ACCESS_KEY_ID
11 aws_secret_access_key = YET_ANOTHER_SECRET_ACCESS_KEY
```

Using specific profile when running `aws cli` commands via `--profile` option in the command:

```
1 aws s3 --profile profile1 [...]
2 # aws s3 --profile default [...]
```

4.3. Buckets

One can have several buckets.

4.3.1. Creation

- Creating a new bucket,

```
1 aws s3api create-bucket --bucket custom-bucket-name --endpoint-url https://custom-s3-endpoint.com --profile default
```

4.3.2. Listings

- Directly “folder” contents of an s3 bucket,

```
1 aws s3 ls s3://custom-bucket-name --recursive --endpoint-url https://custom-s3-endpoint.com --profile default # `--recursive` optional
```

- Showing file contents,

```
1 aws s3 ls s3://custom-bucket-name/prefix/ --recursive --endpoint-url https://custom-s3-endpoint.com --profile default # `--recursive` optional
```

Note that the `/` at the end of the prefix (“folder”) is necessary.

4.3.3. File Copying

- Local machine → S3:

```
1  aws s3 cp path/to/custom_file.ext s3://custom-bucket-name/path/to/
   custom_file.ext --endpoint-url https://custom-s3-endpoint.com --
   profile default
```

- S3 → local machine:

```
1  aws s3 cp s3://custom-bucket-name/path/to/s3_file.ext custom/
   destination --endpoint-url https://custom-s3-endpoint.com --
   profile default
```

4.3.4. Directory Copying

- Local machine → S3:

```
1  aws s3 sync path/to/dir s3://custom-bucket-name/path/to --endpoint-
   url
2  https://custom-s3-endpoint.com --profile default
```

4.3.5. Directory/File Deletion

- Deleting a folder (which is essentially a prefix in S3) and its contents in an S3 bucket,

```
1  aws s3 rm s3://your-bucket-name/path-to-your-folder --recursive --
   endpoint-url https://custom-s3-endpoint.com --profile default
```

- Deleting a file,

```
1  aws s3 rm s3://your-bucket-name/path-to-your-file.out --recursive --
   endpoint-url https://custom-s3-endpoint.com --profile default
```

4.4. Cloudpathlib

- When you use the cloudpathlib module, and you want to specify a profile, do this:

```
1  from cloudpathlib import S3Path, S3Client
2
3  # Create an S3 client with a specific AWS profile
4  s3_client = S3Client(
5      aws_access_key_id=aws_access_key_id,
6      aws_secret_access_key=aws_secret_access_key,
7      endpoint_url=endpoint_url,
8      profile_name="profile1", # specify profile here
9  )
10
11 # Make `client` default:
12 client.set_as_default_client()
```


5. Conda

- Retrieving information about currently activated conda environment,

```
1 conda info
```

- Listing all installed environments,

```
1 conda env list
```

5.1. Installation of Environments

- Installing conda with specific python version,

```
1 # only `myenv` needs to be specified (quotation marks necessary)
2 env_name="myenv" && conda create -n "$env_name" python=3.11.3 -y &&
  conda activate "$env_name"
```

As of Oct 16, I wouldn't recommend installing python 3.12.0 yet — I got a lot of unmet dependency problems when trying to install torch 2.1 with NVIDIA Cuda version 11.8 afterwards.

- Installation of conda environment from bash file:

```
1 conda deactivate # go into base environment
2 source conda/filename.sh
3 touch .env
```

- Completely remove conda environment,

```
1 conda deactivate && conda remove -n custom-env-name --all -y
```

5.2. Export

- Exporting an .yaml-file to share with others for reproducibility,

```
1 conda env export > environment.yaml
```

- Line “Prefix:” at end of .yaml file can be safely deleted, for details cf. [here](#)

5.3. Installation & Removal of Packages

- Installation of packages from `pyproject.toml` file,

```
1 pip install -e .
```

If there is not enough free space, do

```
1 TMPDIR=[...] pip install -e .
```

where `TMPDIR` needs to exist.

If you want to install a specific version of a package via `pip` — and you do not use a `pyproject.toml` file — do

```
1 pip install package==version
```

- Installing specific conda package in a specific version — note that the specification of a version number is optional,

```
1 conda install -c conda-forge custom-pkg-name=version-number -y
2 # conda install -c conda-forge cloudpathlib=0.15.1 -y
3 # conda install -c conda-forge cloudpathlib -y
```

- Removing list of packages from conda environment,

```
1 conda remove -n custom-env-name pkg1 pkg2 ... pkgN -y
2 # conda remove -n google_jax matplotlib -y
```

5.4. Usage in VSCode


- Selecting a conda environment in VSCode, do `Ctrl + Shift + P` and type `Python: select interpreter`.

6. Git


6.1. Branch Creation

```
1 git switch -c <new_bname>
2 git push -u origin <new_bname>
```


6.2. Merging



When merging `main` and `new_branch`, the commits D and D' ' will either be auto-merged or there will be a merge conflict. For this commit history,



merging `main` with `new_feature` would result in a fast-forward,



Merging `new_feature` into `main` can be done via

```
1 git switch main && git merge new_feature
```

Removing the commit message Merge pull request #6 from [...],

```
1 git switch main && git merge new_feature --log
```

Running dry merges to proactively check for conflicts *if* a merge was performed,

```
1 git merge --no-commit --no-ff branch-name && git merge --abort
```

For a fast-forward only,

```
1 git merge branch_to_be_merged --ff-only
```

6.3. Merge Conflicts

1. Resolving a merge conflict,

```
1 git mergetool
```

2. Confirm with Enter that you want to use vimdiff as default editing tool. vimdiff display will resemble the following structure:

```
1 | LOCAL | BASE | REMOTE |
2 | MERGED
```

If file did not already exist in BASE, then we need this view:

```
1 | LOCAL | MERGED | REMOTE |
```

LOCAL – Current branch

BASE – Common ancestor (how did the file look like before both changes?)

REMOTE – File that I am merging into the current branch

MERGED – Merge result

3. It is probably easiest to take the merged view and edit it directly. In the vim editor, an entire line can be deleted by pressing D (no control before!). If I instead wanted the changes from either LOCAL, BASE or REMOTE, you have to do one of these,

```
1 :diffg L0
2 :diffg BA
3 :diffg L0
```

Of course, the merged view can also be edited directly.

4. Type

```
1 :wqa
```

into vim. Afterwards, do not forget to commit and push. And if you want, do

```
1 git clean -f
```

6.4. Checking History

- Viewing the history of commits,

```
1 git log
```

- Viewing a specific file,

```
1 git show <commit-hash>:<file-name>
2 # git show 123abc:example.txt
```


6.5. Removing a File/Folder

- To remove a file/folder that is already tracked, adding it to `.gitignore` won't remove it (though this also needs to happen). For this, do:

```
1 git rm --cached <file>
2 git rm -r --cached <folder>
```

- Adding the file/folder to `.gitignore` is still a good idea, though, since the file/dir won't be removed locally with the commands.

6.6. Restore File

Resetting specific file to state of previous commit,

```
1 git restore --source=<commit-hash> <file-path> && git push
2 # git restore --source=HEAD README.md && git push
```

6.7. Repo Renaming

```
1.
1 gh repo rename <new-repo-name>
2 # gh repo rename new-repo-name
```

```
2.
1 git remote set-url origin <new-repo-url>
2 # git remote set-url origin https://github.com/username/new-repo-
  name.git
```

double-check via

```
1 git remote -v
```

which lists the remote names and their URLs. No force push or the alike is necessary for the changes to take place.

6.8. Remote URL

Obtaining the remote URL,

```
1 git remote get-url origin
2 git remote get-url origin | sed 's/\.git$//' # optional: trim output
```

6.9. Repo Change

Moving all files from `branch-to-move` to `branch-to-merge-into` and preserving the commit history — do all of this while in the old repo,

6. Git

```
1 git remote -v # check existing remotes
2 git remote add <target> https://target-repo-url.git # add new remote
3 # git remote add new-remote url
4 git push target branch-to-move:branch-to-merge-into
```

Do all of this in the old repo. If issue emerges during the last step, reclone the new repo and check whether this solves the issue.

6.10. Remote Repo Creation

Then install GitHub CLI and do

```
1 gh repo create <repository-name> --public # --private
```

Then commit and push.

6.11. Pull Requests

```
1 gh pr create --base main --head "$bname" --title "Pin isort & black
2 versions" --body "This pull request fixes the issue that workflows fail
3 because of different isort/black versions used in the workflows &
4 specified in the \`pyproject.toml\` file."
```

Note that `bname` is a bash function defined in App. A. Escaping the `\` is necessary, since in shell commands, backticks (```) are used to execute commands and substitute their output into the command line.

6.12. Updating Files from other Branch

When working on `branch_my`, it is possible to incorporate changes from another branch `branch_x`,

```
1 git switch <branch_x>
2 git pull origin <branch_x>
3 git switch <branch_my>
4 git rebase -i <branch_x>
5 git push origin <branch_my> --force
```

Save the interactive view via `:wq` and make a force push to `branch_my`.

7. Remote Development

7.1. Connection

1. When connecting two machines remotely, install this extension on local machine (also directly in VSCode possible),
2. open VSCode on local machine,
3. press F1-button, choose “Remote-SSH: Connect to Host...” and type for the SSH host (optionally save it in the SSH config file) the same as in Algo. (B),
4. enter the passwd for the remote SSH host.

7.2. Troubleshooting

If you find you are getting a permission error for saving a file on the remote machine (in VSCode when doing the local coding), try

```
1 sudo chown custom-username path/to/custom/script.ext
```

`custom-username` here refers to the username on the remote machine. If the remote connection hung up,

```
1 fusermount -zu /path/to/dir
```


8. Python

8.1. Config File & JSON Files

- When using `argparse` in combination with a JSON configuration file, the JSON keys need to match the long option names specified in `parser.add_argument()` method calls. The `argparse` module itself does not automatically recognize abbreviated forms from a JSON file.

8.2. Jupyter Notebooks

- Converting jupyter notebooks into PDFs,

```
1  for nb in /path/one/Notebook1.ipynb /path/two/Notebook2.ipynb [...]
2  do
3  jupyter nbconvert --to pdf "$nb"
4  done
```

Wildcarding notation would also work,

```
1  # optionally: `output_dir="[...]"`
2
3  for nb in *.ipynb; do
4  nb_name="${nb%.ipynb}"
5  jupyter nbconvert --to pdf "$nb" # `--output "$output_dir/$nb_name.
   pdf"`
6  done
```

- Changing default theme of notebooks,

```
1  conda install conda-forge::jupyterthemes
2  jt -l # get list of all available themes
3  jt -t <theme-name> # change theme
4  # jt -t onedork
```

Alternative installation via pip,

```
1  pip install jupyterthemes
```

- Displaying all statements in a Jupyter NB, e.g.,

```
1  from IPython.core.interactiveshell import InteractiveShell
2  InteractiveShell.ast_node_interactivity = "all"
3
4  x = 2
```

8. Python

```
5   y = 3
6
7   x
8   y
```

8.3. Map (Built-In Function)

- Function signature:

```
1   map(function, iterable, *iterables)
```

Description provided in the documentation:

Return an iterator that applies function to every item of iterable, yielding the results. If additional iterables arguments are passed, function must take that many arguments and is applied to the items from all iterables in parallel. With multiple iterables, the iterator stops when the shortest iterable is exhausted. For cases where the function inputs are already arranged into argument tuples, see *itertools.starmap()*.

- Example usage: Natively multiplying Python lists elementwise,

```
1   from typing import List
2
3   def multiply(x: List, y: List):
4       return x * y
5
6   list_one = [i for i in range(1000)]
7   list_two = [j for j in range(1000, 2000)]
8   result = list(map(multiply, list_one, list_two)) # `map` is a built-
           in function, do not use `(list_one, list_two)` in this case
```

- Example usage: Converting NumPy arrays into PyTorch tensors,

```
1   a = np.array([1, 2, 3, 4])
2   tensor_list = list(map(torch.from_numpy, (a,))) # list containing
           tensor, use of additional brackets necessary
```

- Example usage: Converting NumPy arrays into PyTorch tensors,

```
1   a = np.array([1, 2, 3, 4])
2   b = np.array([5, 6, 7, 8])
3   a, b = map(torch.from_numpy, (a, b)) # tuple unpacking
```

8.4. CPU Brand

Installing py-cpuinfo,

```
1   conda install -c conda-forge py-cpuinfo
```

Obtaining the raw CPU info,

```
1  import cpuinfo
2
3  # Getting detailed CPU information
4  info = cpuinfo.get_cpu_info()
5
6  # If you want to print specific details like the brand, you can do so
   as follows:
7  print(f"CPU Brand: {info['brand_raw']}")
```

8.5. Inheritance

A class inheriting from another class needn't define an `__init__()` function. In that case, the `__init__()` function of the base class will be called.

9. PyTorch

9.1. Leaf Tensors

- If `requires_grad=False`, then the tensor will be leaf by convention. If `requires_grad=True`, then the tensor will be leaf if it was created directly by the user and is **not** the result of an operation, e.g. `.to(device)` when the tensor is on `cpu` and `device="cuda:0"`.
- However, by definition, leaf tensors themselves do not have a **gradient function** `.grad_fn` because they are not the result of a differentiable operation applied to other tensors, i.e. `grad_fn` on such tensors will return `None`. The gradient function in neural network libraries like PyTorch or TensorFlow is associated with tensors that are outputs of differentiable operations.
- The `.grad` attribute on leaf tensors that require gradients, i.e. those for which `requires_grad=True`, stores the gradient computed during backpropagation. (For leaf tensors that have `requires_grad=False`, calling the `.grad` attribute outputs `None`.) Note that for non-leaf tensors, calling `.grad` results in a `UserWarning`, since non-leaf tensors are generally intermediate results in the computation graph, and their gradients are usually not needed once the gradients of the leaf tensors have been obtained. However, there are cases where those gradients are needed, which can be enforced by setting `retain_grad=True` on those tensors,

```
1   x = torch.tensor([1., 2., 3.], requires_grad=True, device=torch.  
    device("cuda:0"))  
2  
3   # fwd pass  
4   y = x**2  
5  
6   # retain gradients  
7   y.retain_grad()  
8  
9   # backward pas  
10  y.sum().backward()  
11  
12  # access gradients  
13  y.grad # `torch.tensor([1., 1., 1.], device="cuda:0")`
```

Note that in the example of this code snippet, doing `y.grad` means that we access the gradient of the scalar loss function `y.sum()` — on which we performed `.backward()`. Correspondingly, doing `x.grad` implies the gradient of the scalar loss function `y.sum()` with respect to `x`.

- In general, it is **not** possible to perform **in-place** operations on leaf tensors for which `requires_grad=True`, since PyTorch dynamically builds a computational graph during the forward pass, which is used during backpropagation to calculate the gradients.

9. PyTorch

If leaf tensors that have `requires_grad=True` are changed in-place, then the values used during the forward pass are changed, which will affect the gradient calculations in the backward pass. However, note that when no gradients are required for the operations, e.g. when performing parameter updates manually, one can use the context manager with `torch.no_grad()`, in which case in-place operations on leaf tensors **can** be performed, since inside the context manager, `requires_grad=False`.

9.2. Autograd & Backward

- The function `torch.autograd.grad()` computes the gradient. If the gradient of a scalar (loss function) wrt a (weight) matrix is taken, then the output will also be a matrix, where each element corresponds to the partial derivative of the scalar (loss function) wrt to the (weight) matrix element.
- `torch.autograd.grad()` is particularly useful if more direct control over the gradient computation is desired, in particular compared to `.backward()`.
- Note that the default behavior of `.backward()` accumulates gradients in the `.grad` attribute of tensors,

```
1   x = torch.tensor([1., 2., 3.], requires_grad=True, device=torch.
2       device("cuda:0"))
3
4   # fwd pass
5   y = 2 * x
6
7   # first backward pass
8   y.sum().backward(retain_graph=True)
9   print(f"Gradients of `x` after first backward pass: {x.grad}") # `
10      torch.tensor([2., 2., 2.])`
11
12  # second backward pass
13  y.sum().backward()
14  print(f"Gradients of `x` after second backward pass: {x.grad}") # `
15      torch.tensor([4., 4., 4.])`, notice how gradients have
16      accumulated
```

However, this behavior can be suppressed by simply zeroing the gradients, i.e. `x.grad.zero_()` — note that `x.grad` returns a tensor, and `<tensor>.zero_()` is a general PyTorch function that sets all elements in-place to 0.

- When using a default iteration loop in PyTorch, `optimizer.zero_grad()` — where `optimizer` is an instance of `torch.optim.Optimizer` — can be put anywhere in the loop *except between* `loss.backward()` and `optimizer.step()`.

9.3. Half-Precision

This tutorial is a great starting point, explaining the advantages of half-precision, i.e. `float16`, training. Implementing this in PYTORCH is possible by following this general recipe, the

documentation of `torch.amp`, in particular the class `torch.autocast`, and some examples can be found [here](#).

A good starting point might also be my git repo, where I implemented a bidirectional LSTM on the MNIST data, which uses the class `torch.autocast`.

9.4. Miscellaneous

Calculating the MSE between two tensors,

```
1 torch.linalg.vector_norm(vt - ut, ord=2,) ** 2 / vt.numel()
```


10. Jax

Try to install via pip first. Only if this doesn't work use conda!

- Putting a Jax array onto a specific device,

```
1 import jax
2 from jax import devices, device_put, numpy as jnp
3
4 x = device_put(jnp.arange(10), device=devices("cpu")[0]) # NOTE: put
   `x` on the CPU
5 # x = device_put(jnp.arange(10), device=devices("gpu")[0]) # NOTE:
   # put `x` on the GPU
6 print(f"Device: {x.device_buffer.device()}")
```

- Dtype specification,

```
1 x = jnp.array([1, 2, 3], dtype=jnp.float32)
2 print(f"Dtype: {x.dtype}")
```

- Device inference,

```
1 x.device_buffer.device() # x: Jax array
```

- Making a Jax array out of a Python list or a NUMPY array (do not use for tensors),

```
1 from jax import numpy as jnp
2
3 a = jnp.array([1., 2., 3.])
4 b = jnp.array(np.array([1., 2., 3.]))
```

- jit (just-in-time compilation): sets up a function with XLA (extended linear algebra): check out the NB `test__jit-compil.ipynb`. Using jit,

```
1 import jax
2 from jax import numpy as jnp
3
4 @jax.jit
5 def selu(x: jnp.array, lamb: float = 1., alpha: float = 0.):
6     return lamb * jnp.where(x > 0, x, alpha * (jnp.exp(x) - 1.0))
```


A. .bashrc

```
1  ca() {
2      local conda_out="$(conda env list | grep -E "$env_name" | head -n 1 |
      awk '{print $1}')"
3
4      # check non-emptiness
5      if [ -z "$1" ]; then
6          echo "Usage: ca <env_name>"
7          return 1
8      fi
9
10     # check env existence
11     if [ ! -z "$conda_out" ]; then
12         conda activate "$1"
13     else
14         echo "Conda environment '$env_name' does not exist." # single quotes
            (') only for display
15         return 1
16     fi
17
18 }
19
20 # ----- CONDA -----
21
22 # activate conda environment
23 # usage: `ca custom-env-name`
24 ca() {
25     conda activate "$@"
26 }
27
28 # deactivate currently activated conda environment
29 cod() {
30     conda deactivate
31 }
32
33 # List all available conda envs:
34 cel() {
35     conda env list
36 }
37
38 # remove conda environment
39 # usage: `crme ant-migrate-dev`
40 crme() {
```

A. .bashrc

```
41
42 # check number of passed arguments via ` $# `
43 if [[ $# -ne 1 ]]; then
44     echo "NOTE: Exactly one argument needs to be provided"
45 else
46     conda deactivate && conda remove -n "$1" --all -y
47 fi
48
49 }
50
51 # alias for `conda__remove_packages`
52 # usage (e.g.): `crm myenv pkg1 pkg2`
53 crm() {
54     conda__remove_packages "$@"
55 }
56
57 # remove conda packages from environment
58 # usage (e.g.): `conda__remove_packages myenv pkg1 pkg2`
59 conda__remove_packages() {
60
61     # define local variables first
62     local env_name="$1"
63     local conda_out="$(conda env list | grep -E "$env_name" | head -n 1 |
64         awk '{print $1}')"
65
66     # forget first argument (which is saved in `env_name`)
67     shift
68
69     # check non-emptiness
70     if [ -z "$env_name" ]; then
71         echo "Usage: conda__remove_packages <env_name> [package1] [package2]
72         ... [packageN]"
73         return 1
74     fi
75
76     # check env existence
77     if [ ! -z "$conda_out" ]; then
78         conda remove -n "$env_name" "$@" -y
79         echo "Package(s) '$@" removed from environment '$env_name'"
80     else
81         echo "Conda environment '$env_name' does not exist." # single quotes
82         (') only for display
83         return 1
84     fi
85 }
86
87 # ----- AWS -----
```



```

87 # helper function
88 get__profile_endpoint_url() {
89
90     # check if the first argument contains "https://"
91     if [[ "$1" == https://* ]]; then
92         local endpoint_url="$1"
93
94         # if there's a second argument, it's the profile
95         if [ -n "$2" ]; then
96             local profile="$2"
97         fi
98
99     elif [ -n "$1" ]; then
100
101         # if the first argument doesn't contain "https://", it's the profile
102         local profile="$1"
103     fi
104
105     echo "$1 $2"
106
107 }
108
109 # define default vals and update based on provided args
110 update__profile_url() {
111     local endpoint_url="https://kalousis.s3.unige.ch"
112     local profile="default"
113
114     # update `endpoint_url` and `profile` if provided
115     if [[ "$2" == https://* ]]; then
116         read endpoint_url profile <<< $(get__profile_endpoint_url "$2" "$3")
117     else
118         read profile <<< $(get__profile_endpoint_url "$2" "$3") # for `
119             endpoint_url`, default val will be taken
120     fi
121
122     echo "$endpoint_url $profile"
123 }
124
125 # listing
126 # example usages (only bucket name provided):
127 # `lal path`
128 # `lal path default`
129 # `lal path https://kalousis.s3.unige.ch`
130 # `lal path https://kalousis.s3.unige.ch default`
131 lal() {
132     local path="$1"
133
134     read endpoint_url profile <<< $(update__profile_url "$2" "$3")

```

A. .bashrc

```
135     $(which aws) s3 ls s3://" $path" --recursive --endpoint-url "
        $endpoint_url" --profile "$profile"
136 }
137
138 # removing prefixes/files
139 # example usages (only bucket name provided):
140 # `larm path`
141 # `larm path default`
142 # `larm path https://kalousis.s3.unige.ch`
143 # `larm path https://kalousis.s3.unige.ch default`
144 larm() {
145     local path="$1"
146
147     read endpoint_url profile <<< $(update__profile_url "$2" "$3")
148
149     command_output=$(($(which aws) s3 rm s3://" $path" --recursive --endpoint
        -url "$endpoint_url" --profile "$profile"))
150
151     if [[ -z "$command_output" ]]; then
152         # no use of `--recursive`, which shouldn't be used for single file
        deletion
153         $(which aws) s3 rm s3://" $path" --endpoint-url "$endpoint_url" --
            profile "$profile"
154     fi
155 }
156
157 # ----- GIT -----
158
159 # list all local and remote branches
160 lb() {
161     git branch -a
162 }
163
164 # create remote branch
165 # usage:
166 # `lbc new-branch`
167 lbc() {
168     local branch_name="$1"
169
170     git branch $(branch_name) && git push origin $(branch_name)
171 }
172
173 # delete branch
174 lbd() {
175     local branch="$1"
176     local exists_locally=$(git branch --list "$branch")
177     local exists_remotely=$(git ls-remote --heads origin "$branch")
178
179     if [[ "$branch" == "main" || "$branch" == "master" ]]; then
```

```

180     echo "Deletion of 'main' or 'master' branch is not allowed."
181     return
182 fi
183
184 if [[ "$branch" == "$current_branch" ]]; then
185     echo "You are currently on branch $branch. Switching to 'main' before
        deletion..."
186     git switch main || git checkout master || { echo "Failed to switch
        branches. Aborting."; return; }
187 fi
188
189 if [[ -n $exists_locally ]]; then
190     echo "Deleting local branch: $branch"
191     git branch -D "$branch"
192 fi
193
194 if [[ -n $exists_remotely ]]; then
195     echo "Deleting remote branch: $branch"
196     git push origin --delete "$branch"
197 fi
198 }
199
200 # switch branches and create if non-existent
201 lsw() {
202     git switch "$@"
203 }
204
205 # cloning
206 # example usage:
207 # `lcl git@github.com:ImahnShekhzadeh/infra.git`
208 # `lcl git@github.com:ImahnShekhzadeh/infra.git infra`
209 # `lcl git@github.com:ImahnShekhzadeh/infra.git infra main`
210 lcl() {
211     local dir_name="${2:-$(pwd)}"
212     local branch_name="${3:-main}"
213
214     git clone "$1" "$dir_name" && cd "$dir_name" && lsw "$branch_name"
215 }
216
217 # example usage: `lsta 2` or `lsta`
218 lsta() {
219     local stash_index=${1:-0} # Default to 0 if no argument provided
220
221     # Check if the provided argument is an integer
222     if ! [[ $stash_index =~ ^[0-9]+$ ]]; then
223         echo "The provided index is not a valid integer."
224         return 1
225     fi
226

```

A. .bashrc

```
227 # Check if the stash index exists
228 if ! git rev-parse --verify stash@{$stash_index} >/dev/null 2>&1; then
229     echo "No stash found at index $stash_index"
230     return 1
231 fi
232
233 # If all checks pass, apply the stash
234 git stash apply "stash@{$stash_index}" --index
235 }
236
237 # Forward commands to `git stash`
238 lst() {
239     git stash "$@"
240 }
241
242 # Stash files, if arguments are provided, they are ignored
243 lstf() {
244     git stash --include-untracked
245 }
246
247 # https://stackoverflow.com/questions/19595067/git-add-commit-and-push-
    commands-in-one
248 # https://stackoverflow.com/questions/14763608/use-conditional-in-bash-
    script-to-check-string-argument
249 # if-else statements in bash: https://linuxhandbook.com/if-else-bash/
250 # example usage: lgit "bit" "add ..."
251 lpush() {
252
253     (
254         # use subshell to change directory to Git root and perform actions
255         cd "$(git rev-parse --show-toplevel)" || exit
256         git add . && git commit -a -m "$1" && git push origin $(bname) && llog
257     )
258
259 }
260
261
262 # https://stackoverflow.com/questions/3236871/how-to-return-a-string-
    value-from-a-bash-function
263 bname() {
264     branch=$(git branch --show-current)
265     echo $branch
266 }
267
268 lupd() {
269     git fetch origin $(bname) && git log HEAD..origin/$(bname) --oneline
270 }
271
272 lpull() {
```

```

273     git pull origin $(bname)
274 }
275
276 ldiff() {
277     git status "$@" && git diff --color "$@"
278 }
279
280 lforce() {
281     git push origin $(bname) --force
282 }
283
284 llog() {
285     git log
286 }
287
288 lrm() {
289     git rm -r "$@"
290 }
291
292 lreb() {
293     # Set default value to 5:
294     num1=${1:-5}
295     git rebase -i HEAD~$num1
296 }
297
298 # Reset entire repo to state of `HEAD`, or reset specific file to a
299 # specific commit hash.
300 lres() {
301     if [[ $# -eq 0 ]] || [[ $# -eq 1 ]]; then
302         local commit_hash=${1:-HEAD}
303         git reset --hard "$commit_hash"
304     elif [ $# -eq 2 ]; then
305         local commit_hash="$1"
306         local file_path="$2"
307         git restore --source="$commit_hash" "$file_path"
308     else
309         echo "Usage: lres [commit_hash file_path]"
310     fi
311 }
312
313 lsh(){
314     git show "$@"
315 }
316
317 lmv() {
318     git mv "$@"
319 }
320
321 # ----- PROTONVPN -----

```

A. .bashrc

```
321
322 p() {
323     protonvpn-cli "$@"
324 }
325
326 # ----- MISCELLANEOUS -----
327
328 # pdflatex
329 pd() {
330     /usr/bin/pdflatex "$@"
331 }
332
333 # convert input notebook to PDF
334 jconv() {
335     jupyter nbconvert --to pdf "$1"
336 }
337
338 # `less` with ANSI escape characters
339 less() {
340     /usr/bin/less -R "$@"
341 }
342
343 diff() {
344     /usr/bin/diff --color "$@"
345 }
346
347 # overload `shred` func, allow (recursive) shredding of dirs/files
348 # multiple files/dirs can be provided, mixing allowed
349 # usage (e.g.): `shred 10 <file_name>`
350 # shred <file_name>
351 # shred <dir_path>
352 # shred <file_name> <dir_path>
353 shred() {
354
355     # check whether first argument is a number
356     if [[ "$1" =~ ^[0-9]+$ ]]; then
357         local iterations="$1"
358         shift
359     else
360         iterations=5 # default
361     fi
362
363     # check file/dir existences
364     for path in "$@"; do
365         if check_existence "$path"; then
366             # check whether passed input is directory or not
367             if [[ -d "$path" ]]; then
368                 echo "Files to be shredded in $path:"
369                 find "$path" -type f -print0 | xargs -0 ls -ld
```

```

370     fi
371 else
372     echo "Error occurred in check_existence for file/dir: $path"
373     return 1
374 fi
375 done
376
377 # prompt user for confirmation
378 read -rp "Do you wish to proceed with shredding all files in $@ for
    $iterations iterations? (yes/no): " confirmation
379
380 if [[ $confirmation = [yY] || $confirmation = [yY][eE][sS] ]]; then
381     for path in "$@"; do
382         if [[ -d "$path" ]]; then
383             # shred all files within the directory
384             find "$path" -type f -exec /usr/bin/shred -uz -n "$iterations" {} \;
385             rm -rf "$path"
386             echo "All files in '$path' have been shredded for $iterations
                iterations."
387         elif [[ -f "$path" ]]; then
388             # shred the individual file
389             /usr/bin/shred -uz -n "$iterations" "$path"
390             echo "File '$path' has been shredded for $iterations iterations."
391         fi
392     done
393 else
394     echo "Shredding aborted."
395 fi
396 }
397
398 # shortcut for clearing terminal output
399 c() {
400     clear
401 }
402
403 # shortcuts for exiting terminal
404 q() {
405     exit
406 }
407
408 e() {
409     q
410 }
411
412 # tailscale
413 ts() {
414     tailscale status "$@"
415 }
416

```

A. .bashrc

```
417 # xournalpp (https://github.com/xournalpp/xournalpp)
418 xopp() {
419     xournalpp "$@"
420 }
421
422 # strings comparison
423 # usage (e.g.): `str_diff "blub1" "blub1"` or `str_diff blub1 blub1`
424 # or `str_diff $(echo "hey") $(echo "hey")`
425 # NOTE: exactly two arguments need to be provided
426 str_diff() {
427
428     # check number of passed arguments via `$#`
429     if [[ $# -ne 2 ]]; then
430         echo "NOTE: Exactly two arguments need to be provided"
431         return 1 # return non-zero exit code to indicate error
432     else
433
434         # compare strings
435         if [[ $1 == $2 ]]; then
436             echo -e "Strings '$1' and '$2' \033[92mmatch\033[0m"
437         else
438             echo -e "Strings '$1' and '$2' do \033[91mNOT\033[0m match"
439         fi
440     fi
441 }
442
443
444 # ----- DOCKER -----
445 d() {
446     docker "$@"
447 }
448
449 # ----- CHATGPT -----
450
451 # https://github.com/kardolus/chatgpt-cli/tree/main
452 gpt(){
453     chatgpt -i
454 }
455
456 export OPENAI_KEY=[...]
457
458 # ----- ALWAYS EXECUTE -----
459
460
461 add_bit
```


B. Amazing Programs, Extensions, Plugins & Packages

- <https://etherpad.org/>
- <https://github.com/charmbracelet/glow>
- <https://github.com/0xacx/chatGPT-shell-cli>
- <https://github.com/kardolus/chatgpt-cli/tree/main>

– For setting the right model (cf. here for all available models),

```
1 chatgpt --set-model gpt-4-1106-preview --set-max-tokens 128000
```

– Usage:

```
1 chatgpt -i
```

- <https://tailscale.com/download/>

– Once installation is complete, the command

```
1 sudo tailscale up
```

should be run to login, though this command will also display after installation in the CLI. The signing in should happen via GitHub. To be able to use Tailscale from a new device, it must be added as a device under <https://login.tailscale.com/admin/machines>. Once this is done, open a CLI and type

```
1 ssh name@ip_address # find out <name> and <ip_address> via  
tailscale console  
2 # ssh ellie@100.xx.xxx.xx
```

NOTE that if the file already exists locally, it will be overwritten.

– For file copying (e.g. from the host machine to the currently used machine), do this

```
1 scp name@ip_address:/path/to/remote_file.ext /local/path # find  
out <name> and <ip_address> via tailscale console  
2 # ssh ellie@100.xx.xxx.xx
```

For directory copying,

```
1 scp -r name@ip_address:/path/to/remote_dir /local/path # find  
out <name> and <ip_address> via tailscale console  
2 # ssh ellie@100.xx.xxx.xx
```

B. Amazing Programs, Extensions, Plugins & Packages

- <https://tailscale.com/kb/1080/cli/> (no separate installation necessary, only tailscale needs to be installed)

– Finding out the IPv4 address of the currently active machine,

```
1 tailscale ip -4
```

– Finding out the IPv4 address of another machine connected via the Tailscale network,

```
1 tailscale ip -4 custom-name
2 # tailscale ip -4 ellie
```

- <https://github.com/aws/aws-cli>
- <https://github.com/termcolor/termcolor>
- **LibreOffice dark theme,**

Tools → Options → LibreOffice → Application Colors → Custom Colors → General → Document Background, choose a dark color.

C. Opening Programs from the CLI in Linux

- Opening the settings from CLI,

```
1  gnome-control-center
```

- Opening VSCode from CLI:

```
1  code path_to_file/file_name.ext
```

If a VSCode editor is already open, use the *-n* flag to open the file in a new editor:

```
1  code -n path_to_file/file_name.ext
```

A folder can also be opened directly:

```
1  code path_to_dir
```

Listing C.1: Opening VSCode dir from CLI

- Opening LibreOffice from CLI:

```
1  libreoffice --writer path_to_dir/filename.odt
```

- Opening an image via the CLI:

```
1  eog /path/to/your/image.jpg
```


D. VSCode

D.1. Recommended Extensions

- <https://marketplace.visualstudio.com/items?itemName=ms-vscode-remote.vscode-remote>
- <https://marketplace.visualstudio.com/items?itemName=Gruntfuggly.todo-tree>

D.2. Debugging

- Stepping into external code with Python debugger, tutorial [here](#)
- Creating a JSON file, [here](#) some instructions

D.3. settings.json

Opening the file,

1. press `Ctrl + Shift + P` to the Command Palette,
2. type `Open User Settings (JSON)` and select it to open the `settings.json` file.

D.4. Fix Unresolved Python Imports

- If you run a docker container where a conda environment is installed (with packages that you do not have locally), then VSCode will show those imports as unresolved. To fix this, open the `settings.json` file, cf. App. D.3, and add the following setting:

```
1  "python.analysis.diagnosticSeverityOverrides": {  
2    "reportMissingImports": "none"  
3  }
```

Incorporating this into the `settings.json` file is shown in App. D.6.

- Note that if you have an SSH connection to another machine going on, e.g. in the Remote Development extension, putting the above lines into the `settings.json` file will not have an immediate effect, for this the SSH connection needs to be restarted.

D.5. Opening a Duplicate Workspace

1. press `Ctrl + Shift + P` to open the Command Palette,
2. then type `Workspaces: Duplicate As Workspace in New Window`

D.6. settings.json

Contents of settings.json,

```
1  {
2    "workbench.colorTheme": "Default Dark Modern",
3    "telemetry.telemetryLevel": "off",
4    "editor.wordWrap": "wordWrapColumn",
5    "editor.wordWrapColumn": 79,
6    "workbench.editor.enablePreview": false,
7    "gitlens.telemetry.enabled": false,
8    "notebook.lineNumbers": "on",
9    "explorer.confirmDragAndDrop": false,
10   "window.zoomLevel": 1,
11   "python.analysis.diagnosticSeverityOverrides": {
12     "reportMissingImports": "none"
13   },
14   "todo-tree.general.tags": [
15     "BUG",
16     "HACK",
17     "FIXME",
18     "TODO",
19     "NOTE",
20     "XXX",
21     "[ ]",
22     "[x]"
23   ],
24
25   "files.associations": {"*.log": "plaintext"},
26   "[plaintext]": {"editor.wordWrap": "off"},
27   "[shellscript]": {"editor.wordWrap": "off"},
28   "workbench.editor.tabSizing": "shrink"
29 }
```