

# Infra

Imahn Shekhzadeh  
imahn.shekhzadeh@unige.ch

December 9, 2023

## Contents

<b>1</b>	<b>Baobab/Yggdrasil</b>	<b>3</b>
<b>2</b>	<b>Bash</b>	<b>4</b>
<b>3</b>	<b>Linux</b>	<b>6</b>
3.1	Opening Programs from CLI . . . . .	6
<b>4</b>	<b>Anaconda</b>	<b>8</b>
4.1	Installation of Environments . . . . .	8
4.2	Export . . . . .	8
4.3	Installation & Removal of Packages . . . . .	8
4.4	Usage in VSCode . . . . .	8
4.5	PyTorch . . . . .	9
<b>5</b>	<b>CUDA</b>	<b>10</b>
<b>6</b>	<b>Docker</b>	<b>11</b>
6.1	Installation . . . . .	11
6.2	Basics . . . . .	11
6.3	Dockerfile . . . . .	11
6.4	Docker images . . . . .	12
6.5	Docker containers . . . . .	13
6.5.1	Basics . . . . .	13
6.5.2	Passing Arguments . . . . .	14
6.5.3	Listing & Stopping . . . . .	15
6.6	Pushing to DockerHub & HPC . . . . .	15
6.7	Git . . . . .	15
<b>7</b>	<b>Python</b>	<b>16</b>
7.1	Config File & JSON Files . . . . .	16
7.2	Jupyter Notebooks . . . . .	16
7.3	Map (Built-In Function) . . . . .	16
<b>8</b>	<b>AWS S3</b>	<b>18</b>
8.1	Installation & Configuration . . . . .	18
8.2	AWS Credentials (Profiles) . . . . .	18
8.3	Buckets . . . . .	19
8.3.1	Creation . . . . .	19
8.3.2	Listings . . . . .	19

8.3.3	File Copying . . . . .	19
8.3.4	Directory Copying . . . . .	19
8.3.5	Folder/File Deletion . . . . .	20
8.4	Cloudpathlib . . . . .	20
<b>9</b>	<b>Git</b>	<b>21</b>
9.1	Cloning . . . . .	21
9.2	Merging . . . . .	21
9.3	Checking History . . . . .	21
9.4	Removing a File/Folder . . . . .	22
9.5	Renaming a Repository . . . . .	22
9.6	Restore File . . . . .	22
9.7	Delete Branches . . . . .	22
<b>10</b>	<b>Remote Development</b>	<b>23</b>
10.1	Connection . . . . .	23
10.2	Troubleshooting . . . . .	23
<b>11</b>	<b>Jax</b>	<b>24</b>
<b>A</b>	<b><i>.bashrc</i></b>	<b>25</b>
<b>B</b>	<b>Amazing Programs, Extensions, Plugins &amp; Packages</b>	<b>32</b>
<b>C</b>	<b>VSCoDe</b>	<b>33</b>
C.1	Recommended Extensions . . . . .	33
C.2	Open the <i>settings.json</i> File . . . . .	33
C.3	Fix Unresolved Python Imports . . . . .	33
C.4	Opening a Duplicate Workspace . . . . .	33
C.5	<i>settings.json</i> . . . . .	33
<b>D</b>	<b>LibreOffice</b>	<b>35</b>
D.1	Dark Theme . . . . .	35
<b>E</b>	<b>UNIGE-specific</b>	<b>36</b>

## Note

The commands in this document might only run through if you use the *.bashrc* file provided in App. A

# 1 Baobab/Yggdrasil

- To connect to Baobab from your local machine, just type into a terminal:

```
1 eval $(ssh-agent)
2 ssh-add /home/imahn/.ssh/id_ed25519_unige_hpc
3 ssh shekhza2@login2.baobab.hpc.unige.ch
4 # ssh shekhza2@login1.yggdrasil.hpc.unige.ch
```

- Scp into yggdrasil:

```
1 scp file shekhza2@login1.yggdrasil.hpc.unige.ch:/home/users/s/shekhza2/
2 # scp -r folder_name shekhza2@login1.yggdrasil.hpc.unige.ch:/home/users/s/
   shekhza2/
```

- To see all the machines that are occupied, just type

```
1 squeue
2 squeue -p cms-uhh # partition
3 squeue -u shekhza2 # user
```

Listing 1: Squeue commands

- To find out about your conda environment, just type (e.g. whether you use Anaconda2 or Anaconda3)

```
1 conda info
```

- 

```
1 pip install ipykernel
2 python -m ipykernel install --user --name <environment_name> --display-name
   "customStuff"
```

## 2 Bash

- Downloading file from URL and allowing for redirects,

```
1 curl -Lo output.out https://url.com
```

- For this directory structure,

```
1 infra_upd.tex
2 infra_upd.log
3 infra_upd.aux
4 infra_upd.out
5 infra_upd.pdf
```

rename *all* of them via

```
1 for file in infra_upd.*; do mv "$file" "${file/infra_upd/infra}"; done
```

What happens is called a [substring replacement](#).

- Appending line to file,

```
1 echo "this is a line" | tee -a output.out # -a: appending, important
```

- Checking whether provided string (e.g. via an argument) is empty or not (typically used within conditional statements):

```
1 test_sth() {
2     local env_name="$1" # bash starts counting indices from 1
3
4     if [ -z "$env_name" ]; then # spacing after '[' and before ']' needed
5         echo "The string is empty."
6         return 1 # return value of 1 indicates error
7     fi
8 }
```

Listing 2: Check (e.g. in if-clause) whether string is empty or not

- For retrieving all but the first argument,

```
1 test_sth(){
2     shift
3
4     echo "all provided args (except the first): $@"
5 }
```

- And of course there is nothing stopping us from doing this  $N \geq 1$ -times ... Pseudocode:

```
1 test_sth(){
2     shift
3     ...
4     shift
5
6     echo "all provided args (except the first N): $@"
7 }
```

If  $N$  arguments are not provided, this is **not** a problem, the code will still run through.

- Example for an alias:

```
1  # forward output
2  ts(){
3      test_sth "$@"
4  }
```

- Finding out the size of a file or directory,

```
1  du -hs <path_to_file_or_dir> # du -hs file.ext
2
3  # for shorter summary (single quotation strings required)
4  du -hs <path_to_file_or_dir> | awk '{print $1}'
```

- When you want to create a new directory and you want all parent directories to be created as well (assuming they don't already exist), do

```
1  mkdir -p <dir>
```

The `-p` option is safe, since if the directory is already existent, no error will be outputted

- Searching for all files with a specific extension, e.g. `.ext`:

```
1  find . -name "*.ext"
2  # find . -name "*.png"
```

Note that this can be nicely combined with `grep`.

- In Bash, using `[[ ]]` instead of `[ ]` is preferred, since `[[ ]]` is safer and more capable within Bash scripts. Also, within `[ ]` (where word splitting and filename expansion do occur), it's good practice to double-quote your variables. But it's safe to omit the double-quotes for e.g. `##` within `[[ ]]`.
- Unzipping a file via the CLI,

```
1  unzip /path/to/file.zip -d /path/to/destination
```

- Opening a file and automatically scrolling to the bottom,

```
1  less +G /path/to/file.ext
```

- Comparing the contents of two directories,

```
1  diff -r --color directory1 directory2 # '-r' for recursive comparison
2  diff -rq --color directory1 directory2 # '-q' suppresses the output of
    differences and only shows which files differ
```

Ignoring files only existent in one of the directories (which treats absent files as empty),

```
1  diff -rq --color --unidirectional-new-file directory1 directory2
```

## 3 Linux

- Under Ubuntu, listing *all* available kernels,

```
1 dpkg --get-architecture | grep linux-image
```

Listing 3: Find kernel versions in Ubuntu

Finding the currently *active* kernel version,

```
1 uname -a
```

Listing 4: Current kernel versions in Ubuntu

The *-a* option stands for *appending*, otherwise *tee* overwrites *output.out* (if existent).

- Better colors in CLI:
  1. Use monokai color scheme, i.e. dark gray background (#272822) with light peach color for the text (#F8F8F2)
  2. File paths are still displayed in blue, which is suboptimal, to change the color to the better readable cyan-blue color, click on the three horizontal lines in the CLI, then on **Preferences**, then choose the currently active color, switch to the **Colors** tab, then go to **Palette**, click on the blue color & instead use the color #66D9EF

where *-h* stands for human readability and *-s* for summarizing.

- Retrieving the number of available CPU resources,

```
1 echo "$(nproc)"
```

- It is possible to use colored outputs in Bash. Check the bash function *str\_diff* in App. A. (Note that the *-e* option is mandatory to enable interpretation of the backslash escapes).
- Print day and time from CLI,

```
1 echo "$(date +%d_%m_%y-%H_%M_%S)"  
2 # echo "$(date +%dp%mp%y-%Hp%Mp%S)"
```

- Seeing the resource consumption,

```
1 htop
```

- If you did an *sshfs* and the connection hung up, kill the connection via

```
1 fusermount -zu /path/to/dir
```

### 3.1 Opening Programs from CLI

- Opening the settings from CLI,

```
1 gnome-control-center
```

- Opening VSCode from CLI:

```
1 code path_to_file/file_name.ext
```

If a VSCode editor is already open, use the *-n* flag to open the file in a new editor:

```
1 code -n path_to_file/file_name.ext
```

A folder can also be opened directly:

```
1 code path_to_dir
```

Listing 5: Opening VSCode dir from CLI

- Opening LibreOffice from CLI:

```
1 libreoffice --writer path_to_dir/filename.odt
```

- Opening an image via the CLI:

```
1 eog /path/to/your/image.jpg
```

## 4 Anaconda

### 4.1 Installation of Environments

- Installing conda with specific python version,

```
1 # only 'myenv' needs to be specified (quotation marks necessary)
2 env_name="myenv" && conda create -n "$env_name" python=3.11.3 -y && conda
   activate "$env_name"
```

As of Oct 16, I wouldn't recommend installing python 3.12.0 yet (I got a lot of unmet dependency problems when trying to install torch 2.1 with NVIDIA Cuda version 11.8 afterwards).

- Installation of conda environment from bash file:

```
1 conda deactivate # go into base environment
2 source conda/filename.sh
3 touch .env
```

- Completely remove conda environment,

```
1 conda deactivate && conda remove -n custom-env-name --all -y
```

### 4.2 Export

- Exporting an yml-file to share with others for reproducibility,

```
1 conda env export > environment.yml
```

At the end of the file, there will be a line starting with "Prefix:", you can safely delete it, for details see [here](#)

### 4.3 Installation & Removal of Packages

- Installation of packages from *pyproject.toml* file,

```
1 pip install -e .
```

- Installing specific conda package version:

```
1 conda install -c conda-forge custom-pkg-name -y
2 # conda install -c conda-forge cloudpathlib=0.15.1 -y
```

- Removing list of packages from conda environment:

```
1 conda remove -n custom-env-name pkg1 pkg2 ... pkgN -y
2 # conda remove -n google_jax matplotlib -y
```

### 4.4 Usage in VSCode

- Selecting a conda environment in VSCode, do Ctrl + Shift + P and type *Python: select interpreter*.
- Stepping into external code with Python debugger: <https://stackoverflow.com/questions/53594900/visual-studio-code-python-debugging-step-into-the-code-of-external-function>



- Creating a JSON file, here some instructions: <https://code.visualstudio.com/docs/python/debugging>
- Listing all installed environments,

```
1  conda env list
```

## 4.5 PyTorch

- Checking whether gpu version of PyTorch is installed, from python shell (**for this, activate the right conda env first!**):

```
1  import os
2
3  import torch
4
5  if __name__ == "__main__":
6      os.path.dirname(torch.__file__)
```

Afterwards, do

```
1  ls -larht <path_from_prev_alg> | grep -E "cuda"
```

- If you had installed PyTorch via conda instead of pip, then this is easier, where the *-E* means we are searching for extended regular expressions (**again activate the right conda env first!**):

```
1  conda list | grep -E "torch|pytorch"
2  # or 'conda list | grep -E "torch|pytorch"'
```

## 5 CUDA

- When you need to find out the CUDA version installed, install *nvidia-cuda-toolkit*, but do NOT reboot. After its use, immediately remove this package and any package installed alongside with it!
- In case NVIDIA drivers do not allow for boot into Ubuntu (e.g. because you did not uninstall the *nvidia-cuda-toolkit* package):
  1. Boot into an older kernel version of Linux (in order to get there, do a "hard" reboot, and then go into "Advanced options for Ubuntu", and choose an older kernel version).
  2. Once booted into the older kernel version, I removed 'nvidia-cuda-toolkit' and rebooted.
  3. After a few more hard reboots and booting into the older kernel version, at some point, the newer kernel version was picked up and worked again.
  4. Now to fix the monitors (because dual-monitor setup didn't work), I had to open the program "Additional Drivers" and change the driver from the open-source version to an NVIDIA proprietary one.
  5. Then I had to install CUDA according to <https://docs.nvidia.com/cuda/cuda-installation-guide/index.html> again.
  6. For PyTorch to recognize the GPU, I had to reboot.

## 6 Docker

### 6.1 Installation

- Follow this great tutorial by DigitalOcean.
- To use NVIDIA GPUs (both in PyTorch & Jax), install the NVIDIA Container Toolkit
- Once done with the installation of the NVIDIA Container Toolkit, proceed with the configuration. During the configuration, it will be necessary to restart the docker daemon, which you can achieve as follows:

```
1 sudo systemctl restart docker
```

### 6.2 Basics

- Interactive start of containers:

```
1 d ps -a # find out ID (also docker container name)
2 d start -i ID
```

- Copying files from local system to docker container and vice versa; **run both commands from local CLI**

```
1 d cp file_name container_ID:/target_dir # local -> docker
2 d cp container_ID:/file_name dir_name # docker -> local
```

### 6.3 Dockerfile

- When you find the command for pulling a docker image on <https://hub.docker.com>, e.g.

```
1 d pull ubuntu:jammy-20231004
```

then in the Dockerfile, just write

```
1 FROM ubuntu:jammy-20231004
```

When no tag is specified, by default the *latest* one will be taken. However, using the *latest* tag can potentially cause issues with reproducibility and consistency, because you might pull a different version of the image at different times without knowing it if the latest tag gets updated. **For more predictable builds, it is advised to use a specific version tag.**

- Note that the structure of the *docker pull* command is

```
1 d pull [OPTIONS] NAME[:TAG|@DIGEST]
```

In general, the *NAME* is in the format *repository/image*. If *repository* is not specified, Docker assumes the image is located in the default DockerHub library repository. However, many images (like PyTorch) are hosted under a specific user or organization's namespace on DockerHub, rather than the top-level library. That's why the command for the docker pull (for the latest tag) reads

```
1 d pull pytorch/pytorch
```

- If using a Docker image like *pytorch/pytorch:latest*, conda is already installed. In this case, the default environment is named *base*, which is a common practice in Docker images with conda – unless otherwise stated.
- Copying local scripts into docker container,

```
1 COPY relative/path/to/script.py .
```

From the documentation:

Multiple `<src>` resources may be specified but the paths of files and directories will be interpreted as relative to the source of the context of the build.

It is also important to put the `.` at the end, since it represents the destination in the Docker image where the file should be copied. The dot `.` refers to the current working directory inside the Docker image, which is determined by the `WORKDIR` command in the Dockerfile. If `WORKDIR` is not set, it defaults to the root directory (`/`) of the image.

Also, each time the script *relative/path/to/script.py* changes, the Dockerfile needs to be rebuilt – **however, a cached version will be used, which speeds things up.**

- Copying local dirs into docker container,

```
1 COPY relative/path/to/dir/ .
```

- Running a Dockerfile:

```
1 d build -f file_name -t img_name .
2 d build -f file_name -t img_name:tag_name . # tag name optional, but
      recommended, e.g. 1.0 (no quotes required)
3 # d build -f file_name --no-cache -t [...] # forcing to rebuild from
      scratch, no cached version is used (only do if really required)
```

where *Image\_name* will be the name of the newly created image, *Tag\_name* the tag name and *file\_name* the name of the docker file.

- Via

```
1 EXPOSE custom-port-number
2 # EXPOSE 80
```

it is possible to expose a port. Note that port exposure is related to network access. Note that even though network access might not be needed, there is still no harm in exposing a port (since an exposure of the port does not make the docker container more vulnerable).

## 6.4 Docker images

- A Dockerfile does not necessarily need to have the name *Dockerfile*. To pass another name when building the img, do

```
1 d build -f custom_docker_file .
```

The `.` specifies the context of the build, which is the current directory in this case. **I would recommend running this command from the same dir in which *custom\_docker\_file* is located.**

- Check all available Docker images via

```
1 d images
```

- Cleaning up dangling docker images (these are the entries with *<none>* in the repository or tag name in the output of the previous algo):

```
1 d image prune -f
```

- Removing a Docker image – **only do this when finished with using the image**

```
1 d image rm Image_name:Tag
2 # d container rm <container_id> # in case some containers are using the
   image
```

## 6.5 Docker containers

### 6.5.1 Basics

- Running Docker images – without being able to utilize NVIDIA GPUs:

```
1 d run -it img_name # if 'tag_name' was not provided
2 d run -it img_name:tag_name # if 'tag_name' was provided during build (
   recommended)
```

- Running Docker images & utilizing GPUs:

```
1 d run --gpus all -it img_name
2 d run --gpus all -it img_name:tag_name # recommended
```

- To mount a local file to the container at runtime, do

```
1 d run -v /absolute/path/to/script.py:/path/to/workdir/script.py --gpus all
   -it img_name
2 d run -v /absolute/path/to/script.py:/path/to/workdir/script.py --gpus all
   -it img_name:tag_name # recommended, provide 'img_name' & 'tag_name'
```

The mounting expects **absolute** file paths on the side of the host machine.

- Note that you can include the bash command **pwd** to avoid having to manually pass absolute paths for the mounting

```
1 d run -v $(pwd)/script.py:/path/to/workdir/script.py --gpus all -it
   img_name:tag_name # recommended, provide 'img_name' & 'tag_name'
```

If you need the container to reflect changes made to the scripts on the host without rebuilding the image every time, you would use the *-v* flag to mount the directory. If the scripts won't change, or you don't need to reflect changes in real-time, you don't need to mount the directory, as the necessary scripts have already been copied into the image during the build process.

- It is also possible to directly mount directories:

```
1 d run -v $(pwd)/dir_path:/path/to/workdir --gpus all -it img_name:tag_name
```

Note that the specified directory from the host is mounted into the container at the specified mount point. If there are any existing files or directories in the container at the mount point, they become obscured by the mount.

- In several cases it can be useful to remove the docker container right after execution: When you...
  - ...are running many short-lived containers, like during development or testing,
  - ...want to avoid manual cleanup of stopped containers later on,
  - ...are running containers for one-off tasks that do not need to persist any state after they are finished.

In this case,

```
1 d run --rm -v $(pwd)/dir_path:/path/to/workdir --gpus all -it img_name:
    tag_name
```

- It is also possible to mount two separate host directories to two separate directories within the container,

```
1 d run --rm -v $(pwd)/dir_path1:/path/to/workdir1 -v $(pwd)/dir_path2:/path
    /to/workdir2 --gpus all -it img_name:tag_name
```

This will not cause any overwriting as each `-v` flag creates a unique mount point inside the container.

- Finding out the python version of the Docker image

```
1 d run -it --rm img_name:tag_name python3 --version
```

This command will immediately remove the container after execution.

### 6.5.2 Passing Arguments

It is possible to pass arguments when running a docker container.

1. Assuming you have a bash script *run\_scripts.sh*, in which a Python script, e.g.

```
1  #!/bin/sh
2  isort /app/scripts/*.py
3  black /app/scripts/*.py
4
5  python3 -B /app/scripts/test_script.py
6  python3 -B /app/scripts/test_anil.py
```

Modify this bash script s.t. any arguments passed to the CLI when running the docker container are picked up,

```
1  python3 -B /app/scripts/test_anil.py "$@"
2  # python3 -B /app/scripts/test_script.py "$@" # alternative
```

2. Rebuild (!) the docker image.
3. Now run the docker container as follows:

```
1  d run --rm -v $(pwd)/dir_path:/path/to/workdir --gpus all -it img_name:
    tag_name arg1 arg2
2  # d run --rm -v $(pwd)/dir_path:/path/to/workdir --gpus all -it img_name:
    tag_name --n_ways 1 --k_shots 1 # example
```

### 6.5.3 Listing & Stopping

- Listing all running containers,

```
1 d ps
```

Listing only the container ID (of all running containers),

```
1 d ps -q
```

- Stopping a running container,

```
1 d stop container-ID
```

- Stopping a running container and removing it,

```
1 d stop container-ID && d rm container-ID
```

## 6.6 Pushing to DockerHub & HPC

1. First login to Docker via

```
1 d login -u user_name -p password
```

2. Then follow the instructions from this tutorial (from minute 17:05 on)
3. And then follow the HPC tutorial from UNIGE

## 6.7 Git

- This SO post provides an excellent way of using git in docker. And here an example of using my personal git ssh keys:

```
1 d build -t "ubuntu_octave:latest" -f Dockerfile_git --build-arg ssh_prv_key  
    ="$(cat ~/.ssh/id_ed25519_github)" --build-arg ssh_pub_key="$(cat ~/.  
    ssh/id_ed25519_github.pub)" --squash .
```

- Actual cloning of repo should be done inside docker container instead of docker image

## 7 Python

### 7.1 Config File & JSON Files

- When using `argparse` in combination with a JSON configuration file, the JSON keys need to match the long option names specified in `parser.add_argument` method calls. The `argparse` module itself does not automatically recognize abbreviated forms from a JSON file.

### 7.2 Jupyter Notebooks

- Converting jupyter notebooks into PDFs:

```
1 for nb in /path/one/Notebook1.ipynb /path/two/Notebook2.ipynb [...]
2 do
3     jupyter nbconvert --to pdf "$nb"
4 done
```

If you have several notebooks in the same directory,

```
1 for nb in *.ipynb
2 do
3     jupyter nbconvert --to pdf "$nb"
4 done
```

### 7.3 Map (Built-In Function)

- Function signature:

```
1 map(function, iterable, *iterables)
```

Description provided in the documentation:

Return an iterator that applies function to every item of iterable, yielding the results. If additional iterables arguments are passed, function must take that many arguments and is applied to the items from all iterables in parallel. With multiple iterables, the iterator stops when the shortest iterable is exhausted. For cases where the function inputs are already arranged into argument tuples, see `itertools.starmap()`.

- Example usage: Natively multiplying Python lists elementwise,

```
1 from typing import List
2
3 def multiply(x: List, y: List):
4     return x * y
5
6 list_one = [i for i in range(1000)]
7 list_two = [j for j in range(1000, 2000)]
8 result = list(map(multiply, list_one, list_two)) # 'map' is a built-in
           function, do not use '(list_one, list_two)' in this case
```

- Example usage: Converting NumPy arrays into PyTorch tensors,

```
1 a = np.array([1, 2, 3, 4])
2 tensor_list = list(map(torch.from_numpy, (a,))) # list containing tensor,
           use of additional brackets necessary
```



- Example usage: Converting NumPy arrays into PyTorch tensors,

```
1 a = np.array([1, 2, 3, 4])  
2 b = np.array([5, 6, 7, 8])  
3 a, b = map(torch.from_numpy, (a, b)) # tuple unpacking
```

## 8 AWS S3

### 8.1 Installation & Configuration

1. Installation instructions: <https://docs.aws.amazon.com/cli/latest/userguide/getting-started-html#getting-started-install-instructions>
2. The CLI will display the path under which the *aws* package was installed, but it might be sufficient to simply run

```
1 aws
```

Double check by running

```
1 which aws
```

3. After installation, configuration is necessary. For this run

```
1 aws configure
```

You can leave these fields empty:

```
1 Default region name [None]:  
2 Default output format [None]:
```

A configuration file will be saved under

```
1 ~/.aws/credentials
```

4. In the case you are a member of UNIGE, you can obtain the AWS access key ID and the secret access key as follows:

```
1 echo -n "$user_name" | base64 # the '-n' is important in this context  
2 echo -n "$passwd" | md5sum
```

where `$user_name` and `$passwd` need to be provided

Otherwise, you need login to the AWS Management Console.

5. **To test the configuration was successful, do this:**

```
1 aws s3 ls --endpoint-url https://your-custom-s3-endpoint.com
```

where you replace the endpoint-url `https://your-custom-s3-endpoint.com` with yours.

### 8.2 AWS Credentials (Profiles)

- It is possible to use several profiles in the file `~/.aws/credentials`.
- For example:

```
1 [default]  
2 aws_access_key_id = YOUR_DEFAULT_ACCESS_KEY  
3 aws_secret_access_key = YOUR_DEFAULT_SECRET_KEY  
4  
5 [profile1]  
6 aws_access_key_id = ANOTHER_ACCESS_KEY_ID  
7 aws_secret_access_key = ANOTHER_SECRET_ACCESS_KEY
```

```

8
9 [profile2]
10 aws_access_key_id = YET_ANOTHER_ACCESS_KEY_ID
11 aws_secret_access_key = YET_ANOTHER_SECRET_ACCESS_KEY

```

To use a specific profile when running *aws cli* commands, you can use the *-profile* option in the command:

```

1 aws s3 --profile profile1 [...]
2 # aws s3 --profile default [...]

```

## 8.3 Buckets

One can have several buckets.

### 8.3.1 Creation

- To create a new bucket:

```

1 aws s3api create-bucket --bucket custom-bucket-name --endpoint-url https://
  custom-s3-endpoint.com --profile default

```

### 8.3.2 Listings

- Directly showing the file contents of an s3 bucket,

```

1 aws s3 ls s3://custom-bucket-name --recursive --endpoint-url https://custom
  -s3-endpoint.com --profile default # '--recursive' optional

```

### 8.3.3 File Copying

- Local machine → S3:

```

1 aws s3 cp path/to/custom_file.ext s3://custom-bucket-name/path/to/
  custom_file.ext --endpoint-url https://custom-s3-endpoint.com --profile
  default

```

- S3 → local machine:

```

1 aws s3 cp s3://custom-bucket-name/path/to/s3_file.ext custom/destination --
  endpoint-url https://custom-s3-endpoint.com --profile default

```

### 8.3.4 Directory Copying

- Local machine → S3:

```

1 aws s3 sync path/to/dir s3://custom-bucket-name/path/to --endpoint-url
2 https://custom-s3-endpoint.com --profile default

```

### 8.3.5 Folder/File Deletion

- Deleting a folder (which is essentially a prefix in S3) and its contents in an S3 bucket,

```
1  aws s3 rm s3://your-bucket-name/path-to-your-folder --recursive --endpoint-  
    url https://custom-s3-endpoint.com --profile default
```

- Deleting a file,

```
1  aws s3 rm s3://your-bucket-name/path-to-your-file.out --recursive --  
    endpoint-url https://custom-s3-endpoint.com --profile default
```

## 8.4 Cloudpathlib

- When you use the cloudpathlib module, and you want to specify a profile, do this:

```
1  from cloudpathlib import S3Path, S3Client  
2  
3  # Create an S3 client with a specific AWS profile  
4  s3_client = S3Client(  
5      aws_access_key_id=aws_access_key_id,  
6      aws_secret_access_key=aws_secret_access_key,  
7      endpoint_url=endpoint_url,  
8      profile_name="profile1", # specify profile here  
9  )  
10  
11 # Make 'client' default:  
12 client.set_as_default_client()
```

## 9 Git

### 9.1 Cloning

- Cloning a repository via *sshfs* and adjusting the folder name,


```
1 git clone <ssh_url> <folder_name>
2 # git clone <https_path> <folder_name>
```

- After moving into the `|folder_name|` via `cd`, do

```
1 git switch <desired_branch>
```


### 9.2 Merging

- Assuming the following commit-history is given,



when merging `main` and `new_branch`, the two branches will be either auto-merged or there will be a merge conflict.

- Assuming the following commit history is given,



- After merging `main` with `new_feature`, which happens via a fast-forward, you can delete it. New commit structure:
- A – B – C – D – E – F – G – H branch `|main|`
- Merging `new_feature` into `master`, do

```
1 git switch main
2 git merge <new_feature>
```

### 9.3 Checking History

- Viewing the history of commits,

```
1 git log
```

- Viewing a specific file,

```
1 git show <commit-hash>:<file-name>
2 # git show 123abc:example.txt
```

## 9.4 Removing a File/Folder

- To remove a file/folder that is already tracked, adding it to `.gitignore` won't remove it (though this also needs to happen). For this, do:

```
1 git rm --cached <file>
2 git rm -r --cached <folder>
```

- Adding the file/folder to `.gitignore` is still a good idea, though, since the file/dir won't be removed locally with the commands.

## 9.5 Renaming a Repository

1. Rename the repository remotely first (by going to your repository's URL),
2. then go to the locally cloned version of the repository and do

```
1 git remote set-url origin <new-url>
2 # git remote set-url origin https://github.com/username/new-repo-name.git
```

3. and finally

```
1 git remote -v
```

which lists the remote names and their URLs.

## 9.6 Restore File

Resetting specific file to state of previous commit,

```
1 git restore --source=<commit-hash> <file-path>
2 # git restore --source=HEAD <file_path>
```

Replace `<commit-hash>` with the commit SHA and `<file-path>` with the path to the file. This change is local and you would need to commit it if you want it to be reflected in the repository history.

## 9.7 Delete Branches

- Local git branch,

```
1 git branch -d <branch_name>
2 # git branch -d testing
```

- Regardless of merge status,

```
1 git branch -D <branch_name>
2 # git branch -D testing
```

- Remote branch,

```
1 git push origin --delete <branch_name>
2 # git push origin --delete testing
```

## 10 Remote Development

### 10.1 Connection

1. When connecting two machines remotely, install this extension on local machine (also directly in VSCode possible),
2. open VSCode on local machine,
3. press F1-button, choose “Remote-SSH: Connect to Host...” and type for the SSH host (optionally save it in the SSH config file) the same as in Algo. (B),
4. enter the passwd for the remote SSH host.

### 10.2 Troubleshooting

- If you find you are getting a permission error for saving a file on the remote machine (in VSCode when doing the local coding), try

```
1  sudo chown custom-username path/to/custom/script.ext
```

The *custom-username* here refers to the username on the remote machine.

# 11 Jax

Try to install via pip first. Only if this doesn't work use conda!

- To put a Jax array onto a specific device, use this:

```
1 import jax
2 from jax import devices, device_put, numpy as jnp
3
4 x = device_put(jnp.arange(10), device=devices("cpu")[0]) # NOTE: put '[0]'
5 # x = device_put(jnp.arange(10), device=devices("gpu")[0]) # NOTE: put
6   '[0]'
7 print(f"Device: {x.device_buffer.device()}")
```

Listing 6: Device specification in Jax

- Specifying the dtype of an array:

```
1 x = jnp.array([1, 2, 3], dtype=jnp.float32)
2 print(f"Dtype: {x.dtype}")
```

Listing 7: Jax device retrieval

- To find out the device of a Jax array, use this:

```
1 x.device_buffer.device() # x: Jay array
```

Listing 8: Jax device retrieval

- To make a Jax array out of a Python list or a NUMPY array (do not use for PYTORCH tensors):

```
1 from jax import numpy as jnp
2
3 a = jnp.array([1., 2., 3.])
4 b = jnp.array(np.array([1., 2., 3.]))
```

Listing 9: Jax array creation

- jit (just-in-time compilation): sets up a function with XLA (extended linear algebra): check out the NB *test\_jit-compil.ipynb*. To use jit, do this:

```
1 import jax
2 from jax import numpy as jnp
3
4 @jax.jit
5 def selu(x: jnp.array, lamb: float = 1., alpha: float = 0.):
6     return lamb * jnp.where(x > 0, x, alpha * (jnp.exp(x) - 1.0))
```

Listing 10: Jax array



## A *.bashrc*

```
1 ca() {
2     local conda_out="$(conda env list | grep -E "$env_name" | head -n 1 | awk '{
3         print $1}')"
4
5     # check non-emptiness
6     if [ -z "$1" ]; then
7         echo "Usage: ca <env_name>"
8         return 1
9     fi
10
11    # check env existence
12    if [ ! -z "$conda_out" ]; then
13        conda activate "$1"
14    else
15        echo "Conda environment '$env_name' does not exist." # single quotes (')
16        only for display
17        return 1
18    fi
19
20 }
21
22 # ----- CONDA -----
23
24 # activate conda environment
25 # usage: 'ca custom-env-name'
26 ca() {
27     conda activate "$@"
28 }
29
30 # deactivate currently activated conda environment
31 cod() {
32     conda deactivate
33 }
34
35 # List all available conda envs:
36 cel() {
37     conda env list
38 }
39
40 # remove conda environment
41 # usage: 'crme ant-migrate-dev'
42 crme() {
43
44     # check number of passed arguments via '$#'
45     if [[ $# -ne 1 ]]; then
46         echo "NOTE: Exactly one argument needs to be provided"
47     else
48         conda deactivate && conda remove -n "$1" --all -y
49     fi
50 }
```

```

49 }
50
51 # alias for 'conda__remove_packages'
52 # usage (e.g.): 'crm myenv pkg1 pkg2'
53 crm() {
54     conda__remove_packages "$@"
55 }
56
57 # remove conda packages from environment
58 # usage (e.g.): 'conda__remove_packages myenv pkg1 pkg2'
59 conda__remove_packages() {
60
61     # define local variables first
62     local env_name="$1"
63     local conda_out="$(conda env list | grep -E "$env_name" | head -n 1 | awk '{
64         print $1}')"
65
66     # forget first argument (which is saved in 'env_name')
67     shift
68
69     # check non-emptiness
70     if [ -z "$env_name" ]; then
71         echo "Usage: conda__remove_packages <env_name> [package1] [package2] ... [
72             packageN]"
73         return 1
74     fi
75
76     # check env existence
77     if [ ! -z "$conda_out" ]; then
78         conda remove -n "$env_name" "$@" -y
79         echo "Package(s) '$@' removed from environment '$env_name'"
80     else
81         echo "Conda environment '$env_name' does not exist." # single quotes (')
82             only for display
83         return 1
84     fi
85 }
86
87 # ----- GIT -----
88
89 # example usage: 'lsta 2' or 'lsta'
90 lsta() {
91     local stash_index=${1:-0} # Default to 0 if no argument provided
92
93     # Check if the provided argument is an integer
94     if ! [[ $stash_index =~ ^[0-9]+$ ]]; then
95         echo "The provided index is not a valid integer."
96         return 1
97     fi
98
99     # Check if the stash index exists

```

```

98  if ! git rev-parse --verify stash@{$stash_index} >/dev/null 2>&1; then
99      echo "No stash found at index $stash_index"
100     return 1
101 fi
102
103 # If all checks pass, apply the stash
104 git stash apply "stash@{$stash_index}" --index
105 }
106
107 # Forward commands to 'git stash'
108 lst() {
109     git stash "$@"
110 }
111
112 # Stash files, if arguments are provided, they are ignored
113 lstf() {
114     git stash --include-untracked
115 }
116
117 # https://stackoverflow.com/questions/19595067/git-add-commit-and-push-commands-in-one
118 # https://stackoverflow.com/questions/14763608/use-conditional-in-bash-script-to-check-string-argument
119 # if-else statements in bash: https://linuxhandbook.com/if-else-bash/
120 # example usage: lgit "bit" "add ..."
121 lpush() {
122     git add . && git commit -a -m "$1" && git push origin $(bname) && llog
123 }
124
125 # https://stackoverflow.com/questions/3236871/how-to-return-a-string-value-from-a-bash-function
126 bname() {
127     branch=$(git branch --show-current)
128     echo $branch
129 }
130
131 lupd() {
132     git fetch origin $(bname) && git log HEAD..origin/$(bname) --oneline
133 }
134
135 lpull() {
136     git pull origin $(bname)
137 }
138
139 ldiff() {
140     git status "$@" && git diff --color "$@"
141 }
142
143 lforce() {
144     git push origin $(bname) --force
145 }
146

```

```

147 llog() {
148     git log
149 }
150
151 lrm() {
152     git rm -r "$@"
153 }
154
155 lreb() {
156     # Set default value to 5:
157     num1=${1:-5}
158     git rebase -i HEAD~$num1
159 }
160
161 # Reset entire repo to state of 'HEAD', or reset specific file to a specific
    commit hash.
162 lres() {
163     if [ $# -eq 0 ]; then
164         git reset --hard HEAD
165     elif [ $# -eq 2 ]; then
166         local commit_hash="$1"
167         local file_path="$2"
168         git restore --source="$commit_hash" "$file_path"
169     else
170         echo "Usage: lres [commit_hash file_path]"
171     fi
172 }
173
174 lsh(){
175     git show "$@"
176 }
177
178 # Usage: lmv /path/to/directory file1 file2 file3 ...
179 lmv() {
180     local target_dir=$1 # The first argument is the directory path
181     if [[ ! -d "$target_dir" ]]; then
182         echo "Target directory does not exist: $target_dir" >&2
183         return 1
184     fi
185
186     # Shift the arguments so that $@ contains only the files to move
187     shift
188
189     # Now, loop through all the remaining arguments
190     for file in "$@"; do
191         if [[ -e $file ]]; then
192             git mv "$file" "$target_dir"
193         else
194             echo "File does not exist: $file" >&2
195         fi
196     done
197 }

```

```

198
199 # ----- PROTONVPN -----
200
201 p() {
202     protonvpn-cli "$@"
203 }
204
205 # ----- MISCELLANEOUS -----
206
207 # convert input notebook to PDF
208 jconv() {
209     jupyter nbconvert --to pdf "$1"
210 }
211
212 # 'less' with ANSI escape characters
213 less() {
214     /usr/bin/less -R "$@"
215 }
216
217 diff() {
218     /usr/bin/diff --color "$@"
219 }
220
221 # overload 'shred' func, allow (recursive) shredding of dirs/files
222 # multiple files/dirs can be provided, mixing allowed
223 # usage (e.g.): 'shred 10 <file_name>'
224 # shred <file_name>
225 # shred <dir_path>
226 # shred <file_name> <dir_path>
227 shred() {
228
229     # check whether first argument is a number
230     if [[ "$1" =~ ^[0-9]+$ ]]; then
231         local iterations="$1"
232         shift
233     else
234         iterations=5 # default
235     fi
236
237     # check file/dir existences
238     for path in "$@"; do
239         if check_existence "$path"; then
240             # check whether passed input is directory or not
241             if [[ -d "$path" ]]; then
242                 echo "Files to be shredded in $path:"
243                 find "$path" -type f -print0 | xargs -0 ls -ld
244             fi
245             else
246                 echo "Error occurred in check_existence for file/dir: $path"
247                 return 1
248             fi
249         done

```

```

250
251 # prompt user for confirmation
252 read -rp "Do you wish to proceed with shredding all files in $@ for
    $iterations iterations? (yes/no): " confirmation
253
254 if [[ $confirmation = [yY] || $confirmation = [yY][eE][sS] ]]; then
255     for path in "$@"; do
256         if [[ -d "$path" ]]; then
257             # shred all files within the directory
258             find "$path" -type f -exec /usr/bin/shred -uz -n "$iterations" {} \;
259             echo "All files in $path have been shredded for $iterations iterations."
260         elif [[ -f "$path" ]]; then
261             # shred the individual file
262             /usr/bin/shred -uz -n "$iterations" "$path"
263             echo "File '$path' has been shredded for $iterations iterations."
264         fi
265     done
266 else
267     echo "Shredding aborted."
268 fi
269 }
270
271 # shortcut for clearing terminal output
272 c() {
273     clear
274 }
275
276 # shortcuts for exiting terminal
277 q() {
278     exit
279 }
280
281 e() {
282     q
283 }
284
285 # tailscale
286 ts() {
287     tailscale status "$@"
288 }
289
290 # xournalpp (https://github.com/xournalpp/xournalpp)
291 xopp() {
292     xournalpp "$@"
293 }
294
295 # strings comparison
296 # usage (e.g.): 'str_diff "blub1" "blub1"' or 'str_diff blub1 blub1'
297 # or 'str_diff $(echo "hey") $(echo "hey")'
298 # NOTE: exactly two arguments need to be provided
299 str_diff() {
300

```

```

301 # check number of passed arguments via '$#'
302 if [[ $# -ne 2 ]]; then
303     echo "NOTE: Exactly two arguments need to be provided"
304     return 1 # return non-zero exit code to indicate error
305 else
306
307     # compare strings
308     if [[ $1 == $2 ]]; then
309         echo -e "Strings '$1' and '$2' \033[92mmatch\033[0m"
310     else
311         echo -e "Strings '$1' and '$2' do \033[91mNOT\033[0m match"
312     fi
313 fi
314
315 }
316
317
318 # ----- DOCKER -----
319 d() {
320     docker "$@"
321 }
322
323 # ----- CHATGPT -----
324
325 # https://github.com/Oxaxx/chatGPT-shell-cli
326 gpt(){
327     chatgpt --model gpt-4
328 }
329
330 export OPENAI_KEY=[...]
331
332 # ----- ALWAYS EXECUTE -----
333
334 add_bit

```

Listing 11: Contents of .bashrc file

## B Amazing Programs, Extensions, Plugins & Packages

- <https://github.com/charmbracelet/gh>
- <https://github.com/0xacx/chatGPT-shell-cli>
  - Prerequisite: <https://jqlang.github.io/jq/> (for download cf. <https://jqlang.github.io/jq/download/>)
- <https://tailscale.com/download/>

- Once installation is complete, the command

```
1 sudo tailscale up
```

should be run to login, though this command will also display after installation in the CLI. The signing in should happen via GitHub. To be able to use Tailscale from a new device, it must be added as a device under <https://login.tailscale.com/admin/machines>. Once this is done, open a CLI and type

```
1 ssh name@ip_address # find out <name> and <ip_address> via tailscale
  console
2 # ssh ellie@100.xx.xxx.xx
```

NOTE that if the file already exists locally, it will be overwritten.

- For file copying (e.g. from the host machine to the currently used machine), do this

```
1 scp name@ip_address:/path/to/remote_file.ext /local/path # find out <
  name> and <ip_address> via tailscale console
2 # ssh ellie@100.xx.xxx.xx
```

For directory copying,

```
1 scp -r name@ip_address:/path/to/remote_dir /local/path # find out <
  name> and <ip_address> via tailscale console
2 # ssh ellie@100.xx.xxx.xx
```

- <https://tailscale.com/kb/1080/cli/> (no separate installation necessary, only tailscale needs to be installed)
  - Finding out the IPv4 address of the currently active machine,

```
1 tailscale ip -4
```
  - Finding out the IPv4 address of another machine connected via the Tailscale network,

```
1 tailscale ip -4 custom-name
2 # tailscale ip -4 ellie
```
- <https://github.com/aws/aws-cli>
- <https://github.com/termcolor/termcolor>



## C VSCode

### C.1 Recommended Extensions

- <https://marketplace.visualstudio.com/items?itemName=ms-vscode-remote.vscode-remote-ex>
- <https://marketplace.visualstudio.com/items?itemName=Gruntfuggly.todo-tree>

### C.2 Open the *settings.json* File

1. press Ctrl + Shift + P to the Command Palette,
2. type **Open User Settings (JSON)** and select it to open the **settings.json** file.

### C.3 Fix Unresolved Python Imports

- If you run a docker container where a conda environment is installed (with packages that you do not have locally), then VSCode will show those imports as unresolved. To fix this, open the **settings.json**, cf. App. C.2, and add the following setting:

```
1  "python.analysis.diagnosticSeverityOverrides": {  
2    "reportMissingImports": "none"  
3  }
```

How to incorporate this into the **settings.json** file is shown in App. C.5.

- Note that if you have an SSH connection to another machine going on (e.g. in the Remote Development extension), then putting the above lines into the *settings.json* file will not have an immediate effect, for this the SSH connection needs to be restarted.

### C.4 Opening a Duplicate Workspace

1. press Ctrl + Shift + P to the Command Palette,
2. then type **Workspaces: Duplicate As Workspace in New Window**

### C.5 *settings.json*

```
1  {  
2    "workbench.colorTheme": "Default Dark Modern",  
3    "telemetry.telemetryLevel": "off",  
4    "editor.wordWrap": "wordWrapColumn",  
5    "editor.wordWrapColumn": 79,  
6    "workbench.editor.enablePreview": false,  
7    "gitlens.telemetry.enabled": false,  
8    "notebook.lineNumbers": "on",  
9    "explorer.confirmDragAndDrop": false,  
10   "window.zoomLevel": 1,  
11   "python.analysis.diagnosticSeverityOverrides": {  
12     "reportMissingImports": "none"  
13   },  
14   "todo-tree.general.tags": [  
15     "BUG",  
16     "HACK",
```

```
17     "FIXME",
18     "TODO",
19     "NOTE",
20     "XXX",
21     "[ ]",
22     "[x]"
23 ],
24
25 "files.associations": {"*.log": "plaintext"},
26 "[plaintext]": {"editor.wordWrap": "off"},
27 "workbench.editor.tabSizing": "shrink"
28 }
```

Listing 12: Contents of settings.json file

## D LibreOffice

### D.1 Dark Theme

Go to *Tools* → *Options* → *LibreOffice* → *Application Colors* → *Custom Colors* → *General* → *Document Background* and choose a dark color.

## E UNIGE-specific

- Setting up UNIGE e-mail in TB:

<https://plone.unige.ch/distic/pub/messagerie/configuration/comment-configurer-compte->