SE3001 – Software Const. & Dev. | Fall 2024

Time Allowed: 15 mins | Date: Sep 10, 2024

Section: _____ | Marks Obtained:

Roll no: _____ | Total Marks: 12

Quiz# 1

Q.1) You have the following code. Remove compile time errors from it. (1 mark)

```
abstract class Animal {
    protected double strength;
    abstract public void speak();
    public Animal() {
        strength = 0;
    }
    public double getStrength() {
        return this.strength;
    }
    public Animal(double strength) {
        this.strength = strength   ;
    }

    @Override
    public String toString() {
        return strength + ""; // a trick to convert into string
    }
}
```

Q.2) The following class wants to inherit from the `Animal` class.

```
class Dog {
    protected int breed; // not a good idea but anyways
    public Dog(double strength, int breed) {
      ……
    }
}
```

a. Modify the class. Remove all compile time errors and write the missing code in the constructor. (3 marks)

```
class Dog extends Animal {
    protected int breed; // not a good idea but anyways
    public Dog(double strength, int breed) {
      super(strength)
      this.breed = breed;
    }
    @override
    public void speak() {
      System.out.println("woof!");
    }
}
```

b. class `Animal` is overriding which class's `toString()` method? (2 marks)

class Object's

Q.3) You have the following interface:

```
interface Fightable {
    public boolean fights(Fightable other);
}
```

a) class Dog wants to be `Fightable`. Mention the code changes that you'll do in Dog. The function returns true if the caller object's strength is greater than the parameter object. Otherwise, it returns false. (3 marks)

```
class Dog extends Animal implements Fightable {
  protected int breed; // not a good idea but anyways
  public Dog(double strength, int breed) {
    super(strength);
    this.breed = breed;
  }

  @Override
  public void speak() {
    System.out.println("Woof!");
  }
  @Override
  public boolean fights(Fightable other) {
    Animal an = (Animal) other;
    return this.strength > an.getStrength();
  }
}
```

b) How can we allow the fight of a Dog with a `Cat`? You may mention code additions in English but do write the calling/driver code. (3 marks)

Make a subclass `Cat` that implements `Fightable` interface.

```
public static void main(String[] args) {

Fightable aDog = new Dog(4, 8);
      Fightable aCat = new Cat(5, 8);
      boolean result = aDog.fights(aCat);
      System.out.println(result);
    }
```