

ENCCA

Enterprise Network Configuration Compliance Auditor

PROFESSIONAL SECURITY AUDIT REPORT

Configuration	BRANCH-SW-SECURE-VIVA.txt
Hostname	BRANCH-SW-SECURE
Audit Time	23 Aug 2026, 20:58
Compliance Engine	v2.1
Risk Assessment Engine	v1.0
Audit ID	b3c6aa5698c4

Executive Security Summary

COMPLIANCE 100.0%	SECURITY SCORE 100.0/100	FAILED CONTROLS 0	RISK EXPOSURE 0.0%
-----------------------------	------------------------------------	--------------------------	------------------------------

Overall risk level: **Low**. Compliance decisions are deterministic and authoritative; the Risk Engine interprets failed findings using severity weights.

Compliance & Risk Statistics

Statistic	Value	Statistic	Value
Applicable Controls	37	Critical Findings	0
Passed Controls	37	High Findings	0
Failed Controls	0	Medium Findings	0
Not Applicable	0	Low Findings	0
Total Interfaces	5	Access / Trunk / Unused	2 / 1 / 1

Prioritized Risk Findings

No failed risk findings were identified. All applicable controls passed.

Compliance Findings & Remediation

All applicable compliance controls passed.

Control Results Appendix

The following table contains the complete set of Compliance Engine v2.1 decisions for this audit.

Rule	Category	Check	Target	Status	Severity	Evidence
SSH-001	SSH	SSH configured	Global	PASS	-	SSH configured = True
SSH-002	SSH	SSH Version 2	Global	PASS	-	SSH version = 2
SSH-003	SSH	SSH authentication retries limited	Global	PASS	-	SSH authentication retries = 3
SSH-004	SSH	SSH idle timeout configured	Global	PASS	-	SSH timeout = 60
TEL-001	Remote Access	Telnet disabled	Global	PASS	-	Telnet allowed = False
AAA-001	AAA	AAA enabled	Global	PASS	-	aaa new-model = True
AAA-002	AAA	Privileged local administrator exists	Global	PASS	-	Local users = [{ 'username': 'encca-admin', 'privilege': 15}]
PWD-001	Password Security	Enable secret configured	Global	PASS	-	enable secret present = True
MGMT-001	Management Access	VTY management ACL	Global	PASS	-	VTY access classes = ['MGMT-ACL']
MGMT-002	Management Access	HTTP management disabled	Global	PASS	-	HTTP server enabled = False
MGMT-003	Management Interface	Management SVI has an IP address	Global	PASS	-	Management SVIs = [{ 'interface': 'Vlan99', 'ip_address': '10.99.10.10 255.255.255.0', 'shutdown': False}]
SNMP-001	SNMP	Secure SNMP version	Global	PASS	-	SNMP configured = True; version = v3
SNMP-002	SNMP	No default SNMP community	Global	PASS	-	Insecure community detected = False
LOG-001	Logging	Remote logging configured	Global	PASS	-	Logging servers = ['10.10.10.10']
NTP-001	NTP	NTP server configured	Global	PASS	-	NTP servers = ['10.10.10.20']
DHCP-001	DHCP Snooping	DHCP Snooping enabled	Global	PASS	-	enabled = True; VLANs = 10,20,30,40,99
DAI-001	Dynamic ARP Inspection	DAI enabled for protected VLANs	Global	PASS	-	DAI VLANs = 10,20,30,40,99
VTY-001	Remote Access	VTY session timeout	VTY block 1	PASS	-	exec-timeout = 10 0
L2-001	Layer 2	Port security on active access ports	GigabitEthernet1/0/1	PASS	-	port_security = True
L2-002	Layer 2	Port-security maximum MAC limit	GigabitEthernet1/0/1	PASS	-	port-security maximum = 2
L2-003	Layer 2	Secure port-security violation mode	GigabitEthernet1/0/1	PASS	-	violation mode = restrict
STP-001	STP	PortFast on active access ports	GigabitEthernet1/0/1	PASS	-	PortFast = True
STP-002	STP	BPDU Guard on active access ports	GigabitEthernet1/0/1	PASS	-	BPDU Guard = True
STORM-001	Layer 2	Broadcast storm control on active access ports	GigabitEthernet1/0/1	PASS	-	broadcast storm control = True
STORM-002	Layer 2	Multicast storm control on active access ports	GigabitEthernet1/0/1	PASS	-	multicast storm control = True
L2-001	Layer 2	Port security on active access ports	GigabitEthernet1/0/2	PASS	-	port_security = True
L2-002	Layer 2	Port-security maximum MAC limit	GigabitEthernet1/0/2	PASS	-	port-security maximum = 2
L2-003	Layer 2	Secure port-security violation mode	GigabitEthernet1/0/2	PASS	-	violation mode = restrict
STP-001	STP	PortFast on active access ports	GigabitEthernet1/0/2	PASS	-	PortFast = True
STP-002	STP	BPDU Guard on active access ports	GigabitEthernet1/0/2	PASS	-	BPDU Guard = True

Rule	Category	Check	Target	Status	Severity	Evidence
STORM-001	Layer 2	Broadcast storm control on active access ports	GigabitEthernet1/0/2	PASS	-	broadcast storm control = True
STORM-002	Layer 2	Multicast storm control on active access ports	GigabitEthernet1/0/2	PASS	-	multicast storm control = True
TRK-001	Trunk Security	Restricted trunk VLAN list	GigabitEthernet1/1/1	PASS	-	allowed VLANs = 10,20,30,40,99,999
TRK-002	Trunk Security	Non-default native VLAN	GigabitEthernet1/1/1	PASS	-	native VLAN = 999
TRK-003	Trunk Security	DHCP Snooping trust on approved uplink	GigabitEthernet1/1/1	PASS	-	DHCP Snooping trust = True
TRK-004	Trunk Security	DAI trust on approved uplink	GigabitEthernet1/1/1	PASS	-	DAI trust = True
INT-001	Interface Security	Unused interfaces disabled	GigabitEthernet1/0/23	PASS	-	description = UNUSED; shutdown = True