

ENCCA

Enterprise Network Configuration Compliance Auditor

PROFESSIONAL SECURITY AUDIT REPORT

Configuration	parser_v2_sample.txt
Hostname	BRANCH-SW01
Audit Time	23 Aug 2026, 14:51
Compliance Engine	v2.1
Risk Assessment Engine	v1.0
Audit ID	eb41c988832d

Executive Security Summary

COMPLIANCE 94.87%	SECURITY SCORE 96.55/100	FAILED CONTROLS 2	RISK EXPOSURE 3.45%
-----------------------------	------------------------------------	--------------------------	-------------------------------

Overall risk level: **Low**. Compliance decisions are deterministic and authoritative; the Risk Engine interprets failed findings using severity weights.

Compliance & Risk Statistics

Statistic	Value	Statistic	Value
Applicable Controls	39	Critical Findings	0
Passed Controls	37	High Findings	0
Failed Controls	2	Medium Findings	1
Not Applicable	0	Low Findings	1
Total Interfaces	6	Access / Trunk / Unused	2 / 1 / 2

Risk Contribution by Category

Category	Findings	Weight	Contribution
Layer 2	2	3	100.0%

Prioritized Risk Findings

Rule	Risk	Category	Target	Evidence	Contribution	Recommendation
STORM-001	Medium	Layer 2	GigabitEthernet1/0/2	broadcast storm control = False	2.3%	Configure broadcast storm control.
STORM-002	Low	Layer 2	GigabitEthernet1/0/2	multicast storm control = False	1.15%	Configure multicast storm control.

Compliance Findings & Remediation

STORM-001 · Medium · GigabitEthernet1/0/2

Category	Layer 2
Check	Broadcast storm control on active access ports
Evidence	broadcast storm control = False
Expected	Broadcast storm control configured.
Recommendation	Configure broadcast storm control.
Remediation	storm-control broadcast level 1.00 0.50
Reference	Project Layer-2 Security Baseline

STORM-002 · Low · GigabitEthernet1/0/2

Category	Layer 2
Check	Multicast storm control on active access ports
Evidence	multicast storm control = False
Expected	Multicast storm control configured.
Recommendation	Configure multicast storm control.
Remediation	storm-control multicast level 1.00 0.50
Reference	Project Layer-2 Security Baseline

Control Results Appendix

The following table contains the complete set of Compliance Engine v2.1 decisions for this audit.

Rule	Category	Check	Target	Status	Severity	Evidence
SSH-001	SSH	SSH configured	Global	PASS	-	SSH configured = True
SSH-002	SSH	SSH Version 2	Global	PASS	-	SSH version = 2
SSH-003	SSH	SSH authentication retries limited	Global	PASS	-	SSH authentication retries = 3
SSH-004	SSH	SSH idle timeout configured	Global	PASS	-	SSH timeout = 60
TEL-001	Remote Access	Telnet disabled	Global	PASS	-	Telnet allowed = False
AAA-001	AAA	AAA enabled	Global	PASS	-	aaa new-model = True
AAA-002	AAA	Privileged local administrator exists	Global	PASS	-	Local users = [{ 'username': 'netadmin', 'privilege': 15}]
PWD-001	Password Security	Enable secret configured	Global	PASS	-	enable secret present = True
MGMT-001	Management Access	VTY management ACL	Global	PASS	-	VTY access classes = ['MGMT-ACCESS']
MGMT-002	Management Access	HTTP management disabled	Global	PASS	-	HTTP server enabled = False
MGMT-003	Management Interface	Management SVI has an IP address	Global	PASS	-	Management SVIs = [{ 'interface': 'Vlan99', 'ip_address': '192.168.99.10 255.255.255.0', 'shutdown': False}]
SNMP-001	SNMP	Secure SNMP version	Global	PASS	-	SNMP configured = True; version = v3
SNMP-002	SNMP	No default SNMP community	Global	PASS	-	Insecure community detected = False
LOG-001	Logging	Remote logging configured	Global	PASS	-	Logging servers = ['192.168.99.50']
NTP-001	NTP	NTP server configured	Global	PASS	-	NTP servers = ['192.168.99.20']
DHCP-001	DHCP Snooping	DHCP Snooping enabled	Global	PASS	-	enabled = True; VLANs = 10,20,30,40
DAI-001	Dynamic ARP Inspection	DAI enabled for protected VLANs	Global	PASS	-	DAI VLANs = 10,20,30,40
VTY-001	Remote Access	VTY session timeout	VTY block 1	PASS	-	exec-timeout = 10 0
L2-001	Layer 2	Port security on active access ports	GigabitEthernet1/0/1	PASS	-	port_security = True
L2-002	Layer 2	Port-security maximum MAC limit	GigabitEthernet1/0/1	PASS	-	port-security maximum = 1
L2-003	Layer 2	Secure port-security violation mode	GigabitEthernet1/0/1	PASS	-	violation mode = restrict
STP-001	STP	PortFast on active access ports	GigabitEthernet1/0/1	PASS	-	PortFast = True
STP-002	STP	BPDU Guard on active access ports	GigabitEthernet1/0/1	PASS	-	BPDU Guard = True
STORM-001	Layer 2	Broadcast storm control on active access ports	GigabitEthernet1/0/1	PASS	-	broadcast storm control = True
STORM-002	Layer 2	Multicast storm control on active access ports	GigabitEthernet1/0/1	PASS	-	multicast storm control = True
IPSG-001	IP Source Guard	IP Source Guard on DHCP access ports	GigabitEthernet1/0/1	PASS	-	IP Source Guard = True; DHCP rate limit = 15
L2-001	Layer 2	Port security on active access ports	GigabitEthernet1/0/2	PASS	-	port_security = True
L2-002	Layer 2	Port-security maximum MAC limit	GigabitEthernet1/0/2	PASS	-	port-security maximum = 2
L2-003	Layer 2	Secure port-security violation mode	GigabitEthernet1/0/2	PASS	-	violation mode = restrict

Rule	Category	Check	Target	Status	Severity	Evidence
STP-001	STP	PortFast on active access ports	GigabitEthernet1/0/2	PASS	-	PortFast = True
STP-002	STP	BPDU Guard on active access ports	GigabitEthernet1/0/2	PASS	-	BPDU Guard = True
STORM-001	Layer 2	Broadcast storm control on active access ports	GigabitEthernet1/0/2	FAIL	Medium	broadcast storm control = False
STORM-002	Layer 2	Multicast storm control on active access ports	GigabitEthernet1/0/2	FAIL	Low	multicast storm control = False
TRK-001	Trunk Security	Restricted trunk VLAN list	GigabitEthernet1/1/1	PASS	-	allowed VLANs = 10,20,30,40,99
TRK-002	Trunk Security	Non-default native VLAN	GigabitEthernet1/1/1	PASS	-	native VLAN = 999
TRK-003	Trunk Security	DHCP Snooping trust on approved uplink	GigabitEthernet1/1/1	PASS	-	DHCP Snooping trust = True
TRK-004	Trunk Security	DAI trust on approved uplink	GigabitEthernet1/1/1	PASS	-	DAI trust = True
INT-001	Interface Security	Unused interfaces disabled	GigabitEthernet1/0/23	PASS	-	description = UNUSED; shutdown = True
INT-001	Interface Security	Unused interfaces disabled	GigabitEthernet1/0/24	PASS	-	description = UNUSED; shutdown = True