

Validating FF-Replan vs. a state-of-the-art probabilistic planner in a real world domain

I.C.T.M Speek, A.C. Stolwijk

Seminar Algorithms, Embedded Software, Msc Embedded Systems,
Delft University of Technology
`{i.c.t.m.speek,a.c.stolwijk}@student.tudelft.nl`

Abstract. This paper argues that for many real life domains dead-ends are the end of the world, and by for example human interaction the goal can still be reached. By relaxing the definition of a dead-end, we argue that for many real life domains a simpler planning algorithm, like FF-Replan, can be sufficient, and that it's not needed to have newer and sophisticated probabilistic planners.

1 Introduction

- Describe probabilistic planning problem
- Introduce planning for uncertainty
- Describe how deterministic classical planners can be used in probabilistic domains and motivate why this is interesting
- Introduce the qualities of replanning and the second planning algorithm
- Describe the need for a new domain for real world applications
- Describe the goal and tools used to reach this goal

2 Problem formulation

- Summarize shortcomings of the previous solutions
- Describe the planning problem
- Argument the choice for 2 current papers to analyze
- Define how we would like to test the planning algorithms in a domain by our choice

3 Domain description

- Describe domains from IPPC
- Explain shortcomings
- Evaluate a valuable real-world domain in which we can test 2 papers
- Show PPDDL or RDDDL of domain (probabilistic extension of PDDL)

4 Theoretical approach

- Describe how we are using the created domain
- show pseudo code for the 2 papers
- Introduce the improvements (or combination) of the approaches of the papers fitted for the domain

5 Empirical evaluation

- Describe the experiment setup
- Show results for the experiment
- Critically analyze the results
- Compare with results from the original papers

6 Related Work

- Discuss the related work and how their approaches are different
- Discuss the other domains and why our domain adds anything to the community
- Introduce the current state of the art papers that use deterministic approaches for probabilistic domains dealing with uncertainty

Probabilistic Planning via Determinization in Hindsight (2008) [12] Hindsight optimization is an online technique that evaluates one-step-reachable states by sampling future outcomes to generate multiple non-stationary planning problems which are deterministic and can be used using search. It reinterprets FF-Replan's [6] strategy randomly generating a set of non-stationary determinized problems and combining their solutions.

Improving Determinization in Hindsight for Online Probabilistic Planning (2010) [13] Hindsight optimization has enjoyed some success for online probabilistic planning. Although it has proven to be effective for many domains, it is computationally expensive. This paper presents significant improvements. 1) a method for detecting potential useful actions, 2) exploit determinism in the domain by reusing relevant plans, 2) improves action evaluation by increasing the chance that at least one deterministic plan reaches a goal.

Probabilistic Planning in the Graphplan Framework (1999) [1] Graphplan is a successful planning algorithm for classical STRIPS domains. This paper explores the extend it can be used in *probabilistic* domains. The paper discusses two variations of Graphplan: PGraphplan and TGraphplan. PGraphplan produces an optimal plan, while TGraphplan produces a sub-optimal plan but it has increased speed. By comparing the speed and quality of the two planners the authors are able to estimate how far they are from the ideal.

Compiling Conformant Probabilistic Planning Problems into Classical Planning (2013) [7]

How Much Does a Household Robot Need To Know In Order To Tidy Up? (2013) [4] For household robot planning, it appears easy, but actually involves uncertainty. For tidying things up objects might not be there, or sensing operations might tell things wrong. This paper looks into conditions for classical planning in a replanning loop in order to solve nondeterministic partially observable open domains. This paper looks into conditions for classical planning in a replanning loop in order to solve nondeterministic partially observable open domains.

Progressive heuristic search for probabilistic planning based on interaction estimates (2013) [11] In this paper a probabilistic plan graph heuristic is described which computes information about the interaction between actions and between propositions. This information is used to find better relaxed plans to compute the probability of success. This information guides a forward state space search for high probability, non-branching seed plans. These plans are then used in a planning and scheduling system that handles unexpected outcomes by runtime replanning.

Translation based approaches to probabilistic planning (2013) [8]

7 Conclusion

- Conclude on the success of the 2 approaches
- Conclude the work done in the paper
- Hint to some future work developments

8 Some papers

- [3]
- [6]
- [10]
- [12]
- [9]
- [2]
- [8]
- [11]
- [7]
- [5]
- [4]
- [?]
- [?]
- [?]

References

1. Avrim Blum and John C. Langford. Probabilistic planning in the graphplan framework. In *IN PROCEEDINGS OF THE FIFTH EUROPEAN CONFERENCE ON PLANNING*, pages 8–12, 1999.
2. Blai Bonet and Hector Geffner. Planning under partial observability by classical replanning: Theory and experiments. In *Proceedings of the Twenty-Second international joint conference on Artificial Intelligence-Volume Volume Three*, pages 1936–1941. AAAI Press, 2011.
3. Jörg Hoffmann and Bernhard Nebel. The ff planning system: Fast plan generation through heuristic search. *Journal of Artificial Intelligence Research*, 14:2001, 2001.
4. Bernhard Nebel, Christian Dornhege, and Andreas Hertle. How much does a household robot need to know in order to tidy up? In *Proceedings of the AAAI Workshop on Intelligent Robotic Systems, Bellevue, WA*, 2013.
5. S. Russel S. Srivastava, L. Riano and P. Abbeel. Using classical planners for tasks with continuous operators in robotics. In *Intelligent Robotic Systems: Papers from the AAAI 2013 Workshop*. AAAI Press, 2013.
6. A. Fern S. Yoon and R. Givan. Ff-replan: A baseline for probabilistic planning. 2007.
7. R. Taig and R.I. Brafman. Compiling conformant probabilistic planning problems into classical planning. In *Proceedings of the Twenty-Third international conference on Automated Planning and Scheduling*. AAAI Press, 2013.
8. Ran Taig. Translation based approaches to probabilistic planning. AAAI Press, 2013.
9. Florent Teichteil-Königsbuch. Fast incremental policy compilation from plans in hybrid probabilistic domains. 2012.
10. Florent Teichteil-Königsbuch, Ugur Kuter, and Guillaume Infantes. Incremental plan aggregation for generating policies in mdps. In *Proceedings of the 9th International Conference on Autonomous Agents and Multiagent Systems: volume 1-Volume 1*, pages 1231–1238. International Foundation for Autonomous Agents and Multiagent Systems, 2010.
11. M.D. R-Moreno Y. E-Martin and D.E. Smith. Progressive heuristic search for probabilistic planning based on interaction estimates. 2013.
12. Sung Wook Yoon, Alan Fern, Robert Givan, and Subbarao Kambhampati. Probabilistic planning via determinization in hindsight. In *AAAI*, pages 1010–1016, 2008.
13. Sungwook Yoon, Wheeler Ruml, J Benton, and Minh B Do. Improving determinization in hindsight for online probabilistic planning. In *Proc. of the 20th Int. Conf. on Automated Planning and Scheduling (ICAPS)*, 2010.